

Effective July 2020

IOSA Standards Manual (ISM)

Edition 13

Remote Audit

Revision 1



NOTICE

DISCLAIMER. The information contained in this publication is subject to constant review in the light of changing government requirements and regulations. No subscriber or other reader should act on the basis of any such information without referring to applicable laws and regulations and/or without taking appropriate professional advice. Although every effort has been made to ensure accuracy, the International Air Transport Association shall not be held responsible for any loss or damage caused by errors, omissions, misprints or misinterpretation of the contents hereof. Furthermore, the International Air Transport Association expressly disclaims any and all liability to any person or entity, whether a purchaser of this publication or not, in respect of anything done or omitted, and the consequences of anything done or omitted, by any such person or entity in reliance on the contents of this publication.

© International Air Transport Association. All Rights Reserved. No part of this publication may be reproduced, recast, reformatted or transmitted in any form by any means, electronic or mechanical, including photocopying, recording or any information storage and retrieval system, without the prior written permission from:

Senior Vice President
Safety and Flight Operations
International Air Transport Association
800 Place Victoria
P.O. Box 113
Montreal, Quebec
CANADA H4Z 1M1

Table of Contents

ISM Thirteenth Edition	DOC 1
Introduction	INT 1
1 Purpose	INT 1
2 Structure	INT 1
3 Sources for IOSA Standards and Recommended Practices (ISARPs)	INT 1
4 Applicability of ISARPs	INT 1
5 Explanation of ISARPs.....	INT 2
6 Guidance Material.....	INT 4
7 Operational Audit	INT 5
8 Safety Management System (SMS).....	INT 6
9 IOSA Documentation System	INT 7
10 English Language	INT 7
11 Manual Revisions	INT 7
12 Modification Status	INT 7
13 Conflicting Information	INT 8
14 Definitions and Abbreviations	INT 8
15 IOSA Documents and Forms	INT 8
16 Authority.....	INT 8
Section 1 — Organization and Management System (ORG)	ORG 1
1 Management and Control	ORG 1
1.1 Management System Overview.....	ORG 1
1.2 Management Commitment	ORG 3
1.3 Accountability, Authorities and Responsibilities	ORG 3
1.4 Communication	ORG 3

1.5	Management Review	ORG 4
1.6	Provision of Resources	ORG 4
1.7	Effectiveness Implementation	ORG 5
1.8	Operational Planning	ORG 5
2	Documentation and Records	ORG 5
2.1	Documentation System	ORG 5
2.2	Records System	ORG 5
3	Safety Management	ORG 5
3.1	Safety Risk Management	ORG 5
3.2	Safety Assurance	ORG 8
3.3	Flight Safety Analysis Program	ORG 9
3.4	Quality Assurance Program	ORG 12
3.5	Quality Control of Outsourced Operations	ORG 15
3.6	Product Quality Control	ORG 18
3.7	Flight Data Analysis (FDA) Program	ORG 18
4	Emergency Response	ORG 18
4.1	Emergency Response Plan	ORG 18
Table 1.1—Documentation System Specifications		ORG 20
Table 1.2—Required Internal Audit Information		ORG 21

Section 2 — Flight Operations (FLT) FLT 1

1	Management and Control	FLT 1
1.1	Management System Overview	FLT 1
1.2	State Requirements	FLT 1
1.3	Accountability, Authorities and Responsibilities	FLT 3
1.4	Communication and Coordination	FLT 3
1.5	Provision of Resources	FLT 5

1.6	Documentation System	FLT 5
1.7	Operations Manual	FLT 6
1.8	Records System	FLT 6
1.9	(Intentionally open).....	FLT 6
1.10	Quality Assurance Program	FLT 6
1.11	Quality Control of Outsourced Operations and Products.....	FLT 6
1.12	Safety Management	FLT 7
2	Training and Qualification.....	FLT 10
2.1	Training and Evaluation Program	FLT 10
2.2	Training Elements	FLT 16
2.3	Line Qualification.....	FLT 31
2.4	Special Qualification.....	FLT 35
2.5	SMS Training	FLT 38
3	Line Operations	FLT 38
3.1	Common Language.....	FLT 38
3.2	Flight Crew Responsibilities	FLT 38
3.3	Flight Crew Qualifications.....	FLT 38
3.4	Flight Crew Scheduling	FLT 41
3.5	Flight Preparation.....	FLT 45
3.6	Route and Airport Planning	FLT 46
3.7	Fuel, Weight/Mass and Balance, Flight Plans	FLT 46
3.8	Aircraft Preflight and Airworthiness	FLT 48
3.9	Ground Handling	FLT 49
3.10	Airspace Rules	FLT 50
3.11	In-Flight Operations.....	FLT 50
3.12	Flight Deck Policy and Procedures.....	FLT 61

3.13	Flight Deck, Passenger Cabin, Supernumerary Compartment Coordination	FLT 63
3.14	Non-Normal/Abnormal and Emergency Operations	FLT 67
3.15	Flight Crew Reporting Requirements	FLT 70
4	Operations Engineering Specifications	FLT 70
4.1	Aircraft Performance	FLT 70
4.2	Navigation and Facilities	FLT 72
4.3	Aircraft Systems and Equipment Specifications	FLT 73
	Table 2.1—Onboard Library Specifications	FLT 74
	Table 2.2—Operations Manual (OM) Content Specifications	FLT 75
	Table 2.3—Flight Crew Qualification Requirements	FLT 77
	Table 2.4—(Intentionally open)	FLT 78
	Table 2.5—Route and Airport Knowledge Requirements	FLT 79
	Table 2.6—Elements Common to an Advanced Qualification Program (AQP), an Alternative Training and Qualification Program (ATQP) or an Evidence-based Training (EBT) Program	FLT 80
	Table 2.7—Requirements Specific to an Advanced Qualification Program (AQP) or an Alternative Training and Qualification Program (ATQP)	FLT 82
	Table 2.8—Requirements Specific to an Evidence-based Training (EBT) Program	FLT 84

Section 3 — Operational Control and Flight Dispatch (DSP)DSP 1

1	Management and Control	DSP 4
1.1	Management System Overview	DSP 4
1.2	(Intentionally open)	DSP 4
1.3	Accountability, Authorities and Responsibilities	DSP 4
1.4	Communication and Coordination	DSP 5
1.5	Provision of Resources	DSP 5
1.6	Documentation System	DSP 5
1.7	Operations Manual	DSP 5

1.8	Records System.....	DSP 5
1.9	(Intentionally open).....	DSP 5
1.10	Quality Assurance Program	DSP 5
1.11	Quality Control of Outsourced Operations and Products.....	DSP 5
1.12	Safety Management	DSP 5
2	Training and Qualification.....	DSP 8
2.1	Training and Evaluation Program	DSP 8
2.2	Training Elements	DSP 9
2.3	Line Qualification.....	DSP 9
2.4	Special Qualification.....	DSP 9
2.5	SMS Training	DSP 9
3	Line Operations.....	DSP 10
3.1	General	DSP 10
3.2	Flight Preparation and Planning	DSP 10
3.3	Aircraft Performance and Load Planning.....	DSP 10
3.4	Icing Conditions.....	DSP 12
3.5	Aircraft Tracking	DSP 12
3.6	Flight Monitoring and In-Flight Management	DSP 12
3.7	Emergency Response	DSP 13
4	Operational Control Requirements and Specifications	DSP 13
4.1	Alternate and Isolated Airports	DSP 16
4.2	Minimum Flight Altitudes and En Route Performance	DSP 19
4.3	Fuel Planning	DSP 19
4.4	Oxygen.....	DSP 27
4.5	Operations Beyond 60 Minutes from an En Route Alternate Airport and Extended Diversion Time Operations (EDTO)	DSP 27
4.6	Performance-based Methods of Compliance/Conformance	DSP 30

Table 3.1—Operational Control Personnel	DSP 33
Table 3.2—Operations Manual (OM) Content Specifications	DSP 35
Table 3.3—Operational Flight Plan (OFP) Specifications	DSP 37
Table 3.4—Flight Information	DSP 38
Table 3.5—Competencies of Operational Control	DSP 39

Section 4 — Aircraft Engineering and Maintenance (MNT) MNT 1

1	Management and Control	MNT 1
1.1	Management System Overview	MNT 1
1.2	Accountability, Authorities and Responsibilities	MNT 1
1.3	Maintenance Program	MNT 1
1.4	Provision of Resources	MNT 3
1.5	Communication	MNT 3
1.6	Documentation System	MNT 3
1.7	Maintenance Management Manual (MMM)	MNT 3
1.8	Maintenance Records System	MNT 3
1.9	Aircraft Systems/Equipment	MNT 3
1.10	Quality Assurance Program	MNT 4
1.11	Quality Control of Outsourced Operations and Products	MNT 4
1.12	Safety Management	MNT 5
2	Maintenance Control	MNT 7
2.1	Control System	MNT 7
2.2	Maintenance Planning	MNT 8
2.3	Parts Installation	MNT 8
2.4	Deferred Maintenance	MNT 10
2.5	Continuing Airworthiness Information	MNT 11
2.6	Repairs and Modifications	MNT 12

2.7	Defect Recording and Control.....	MNT 12
2.8	Extended Diversion Time Operations (EDTO).....	MNT 13
2.9	Aircraft Recorders.....	MNT 13
2.10	Electronic Navigation Data Management.....	MNT 13
2.11	Reduced Vertical Separation Minima (RVSM).....	MNT 14
2.12	Reporting to the Authority	MNT 14
3	Technical Records	MNT 14
3.1	Aircraft Maintenance Records.....	MNT 14
3.2	Aircraft Technical Log (ATL)	MNT 14
3.3	(Intentionally open)	MNT 14
3.4	Airworthiness Directives	MNT 14
4	Maintenance Organizations	MNT 14
4.1	Approval.....	MNT 14
4.2	Management.....	MNT 14
4.3	Quality Assurance.....	MNT 14
4.4	Personnel.....	MNT 15
4.5	Training Program	MNT 16
4.6	Facilities and Physical Resources	MNT 17
4.7	Material Handling.....	MNT 19
4.8	(Intentionally open)	MNT 20
4.9	Procedures Manual.....	MNT 20
4.10	Maintenance Release	MNT 20
4.11	Tooling and Calibration	MNT 22
	Table 4.1–Maintenance Program Specifications	MNT 23
	Table 4.2–Maintenance Management and Control Functions	MNT 24
	Table 4.3–Maintenance Management Manual Content Specifications.....	MNT 25
	Table 4.4–Defect Reporting Specifications.....	MNT 26

Table 4.5–ETOPS/EDTO Maintenance Requirements for Twin Turbine Engine Aircraft.....	MNT 27
Table 4.6–Aircraft Technical Log (ATL) Specifications	MNT 28
Table 4.7–Quality Assurance Program Specifications and Control Processes.....	MNT 29
Table 4.8–ESD Program Specifications	MNT 30
Table 4.9–Maintenance Procedures Manual Content Specifications	MNT 31
Table 4.10–Tooling and Calibration Program Specifications	MNT 32
Table 4.11–Required Aircraft Systems and Equipment	MNT 33
Table 4.12–Guidance Material: Required Aircraft Systems and Equipment	MNT 42
Table 4.13–Guidance Material: First Aid Kits.....	MNT 45
Table 4.14–Recommended Aircraft Systems and Equipment	MNT 46
Table 4.15–Guidance Material: Recommended Aircraft Systems and Equipment	MNT 47

Section 5 — Cabin Operations (CAB) CAB 1

1	Management and Control.....	CAB 1
1.1	Management System Overview	CAB 1
1.2	Accountability, Authorities and Responsibilities	CAB 1
1.3	Communication	CAB 2
1.4	Provision of Resources	CAB 2
1.5	Documentation System	CAB 2
1.6	Operations Manual.....	CAB 2
1.7	Records System.....	CAB 3
1.8	(Intentionally open).....	CAB 3
1.9	Quality Assurance Program	CAB 3
1.10	Quality Control of Outsourced Operations and Products.....	CAB 3
1.11	Safety Management	CAB 3
2	Training and Qualification.....	CAB 6
2.1	Training Program	CAB 6
2.2	Program Elements	CAB 7

2.3	Line Qualification.....	CAB 13
2.4	SMS Training	CAB 13
3	Line Operations.....	CAB 13
3.1	Cabin Crew Requirements	CAB 13
3.2	Cabin Crew Policies and Procedures.....	CAB 17
3.3	Flight Deck Coordination	CAB 20
3.4	Cabin Operations Policies and Procedures.....	CAB 21
4	Cabin Systems and Equipment	CAB 22
4.1	Preflight Inspection/Non-serviceable Equipment Reporting	CAB 22
4.2	Safety Equipment Requirements.....	CAB 23
	Table 5.1—Operations Manual Content Specifications	CAB 24
	Table 5.2—Elements of an Advanced Qualification Program (AQP)	CAB 25
	Table 5.3—Requirements of an Advanced Qualification Program (AQP)	CAB 27
	Table 5.3—Requirements of an Advanced Qualification Program (AQP)	CAB 28
	Tables 5.4–5.7 (Intentionally open)	CAB 29
	Table 5.8—Guidance Material: Medical Kit Contents	CAB 30
	Table 5.9—Guidance Material: Universal Precaution Kit Contents	CAB 32
	Section 6 — Ground Handling Operations (GRH)	GRH 1
1	Management and Control	GRH 2
1.1	Management System Overview.....	GRH 2
1.2	Accountability, Authorities and Responsibilities.....	GRH 2
1.3	Communication.....	GRH 2
1.4	Provision of Resources.....	GRH 2
1.5	Documentation System	GRH 2
1.6	Operational Manuals	GRH 2
1.7	Records System	GRH 3
1.8	(Intentionally open)	GRH 3

1.9	Quality Assurance Program	GRH 3
1.10	Quality Control of Outsourced Operations and Products	GRH 3
1.11	Safety Management	GRH 3
2	Training and Qualification	GRH 6
2.1	Training Program	GRH 6
2.2	Program Elements	GRH 7
2.3	SMS Training	GRH 7
3	Ground Handling Operations	GRH 7
3.1	Passenger and Baggage Handling	GRH 7
3.2	Airside Operations	GRH 8
3.3	Load Control	GRH 8
3.4	Aircraft Loading	GRH 10
3.5	Ground Support Equipment	GRH 13
3.6	Airside Event Response and Reporting	GRH 13
3.7	Security	GRH 13
4	Special Aircraft Ground Handling Operations	GRH 13
4.1	Aircraft Fueling	GRH 13
4.2	Aircraft De-/Anti-icing	GRH 13
Table 6.1—Passenger Services, Ramp Services, Load Control Training Elements		GRH 14

Section 7 — Cargo Operations (CGO) CGO 1

1	Management and Control	CGO 2
1.1	Management System Overview	CGO 2
1.2	Accountability, Authorities and Responsibilities	CGO 2
1.3	Communication	CGO 2
1.4	Provision of Resources	CGO 2
1.5	Documentation System	CGO 2

1.6	Operational Manuals	CGO 2
1.7	Records System	CGO 2
1.8	(Intentionally open).....	CGO 2
1.9	Quality Assurance Program.....	CGO 2
1.10	Quality Control of Outsourced Operations and Products.....	CGO 2
1.11	Safety Management	CGO 2
2	Training and Qualification.....	CGO 5
2.1	Training Program.....	CGO 5
2.2	Program Elements.....	CGO 5
2.3	SMS Training.....	CGO 7
3	Acceptance and Handling.....	CGO 7
3.1	General Cargo	CGO 7
3.2	Dangerous Goods	CGO 8
3.3	Live Animals and Perishables	CGO 10
3.4	Other Special Cargo	CGO 11
3.5	Unit Load Device (ULD).....	CGO 11
3.6	Combi Aircraft Operations	CGO 11
3.7	Security	CGO 12
Table 7.1—Operations Manual Content Specifications.....		CGO 14

Section 8 — Security Management (SEC)SEC 1

1	Management and Control.....	SEC 1
1.1	Management System Overview	SEC 1
1.2	Air Operator Security Program (AOSP).....	SEC 1
1.3	Authorities and Responsibilities	SEC 2
1.4	Communication	SEC 2
1.5	Provision of Resources	SEC 2

1.6	Documentation System	SEC 2
1.7	(Intentionally open).....	SEC 3
1.8	Records System.....	SEC 3
1.9	Management Review	SEC 3
1.10	Quality Assurance/Quality Control Programs	SEC 3
1.11	Quality Control of Outsourced Operations and Products.....	SEC 3
1.12	Operational Reporting	SEC 3
2	Training and Qualification.....	SEC 4
2.1	Training Program	SEC 4
3	Security Operations.....	SEC 5
3.1	Access Control	SEC 5
3.2	(Intentionally open).....	SEC 6
3.3	Carriage of Weapons	SEC 6
3.4	Passengers, Supernumeraries and Cabin Baggage	SEC 6
3.5	Special Category Passengers	SEC 8
3.6	Hold Baggage	SEC 9
3.7	Cargo Shipments	SEC 10
3.8	In-Flight, Catering and Other Supplies	SEC 10
3.9	General Protection	SEC 10
4	Security Threat and Contingency Management	SEC 10
4.1	Threat Management.....	SEC 10
4.2	Contingency Planning	SEC 11
4.3	Investigation and Notification	SEC 11

List of Effective Pages

	Page Number	Issue Date
Title Page	N/A	N/A
Disclaimer	N/A	N/A
Change/Revision History	N/A	April 2019
Table of Contents	TOC 1 to TOC 12	April 2019
List of Effective Pages	LEP 1 to LEP 2	April 2019
Description of Changes	DOC 1 to DOC 22	April 2019
Introduction	INT 1 to INT 8	April 2019

IOSA Standards and Recommended Practices

Section 1

Organization and Management System (ORG)	ORG 1 to ORG 22	April 2019
--	-----------------	------------

Section 2

Flight Operations (FLT)	FLT 1 to FLT 86	April 2019
-------------------------	-----------------	------------

Section 3

Operational Control and Flight Dispatch (DSP)	DSP 1 to DSP 40	April 2019
---	-----------------	------------

Section 4

Aircraft Engineering and Maintenance (MNT)	MNT 1 to MNT 48	April 2019
--	-----------------	------------

Section 5

Cabin Operations (CAB)	CAB 1 to CAB 32	April 2019
------------------------	-----------------	------------

Section 6

Ground Handling Operations (GRH)	GRH 1 to GRH 16	April 2019
----------------------------------	-----------------	------------

Section 7

Cargo Operations (CGO)	CGO 1 to CGO 14	April 2019
------------------------	-----------------	------------

Section 8

Security Management (SEC)	SEC 1 to SEC 12	April 2019
---------------------------	-----------------	------------

Record of Revisions

Edition Number	Revision Number	Issue Date	Effective Date
1	N/A	Apr 2003	Apr 2003
2	0	Aug 2006	Mar 2007
2	1	May 2007	Jan 2008
2	2	Feb 2009	Jul 2009
3	0	Jun 2010	Oct 2010
4	N/A	Jul 2011	Dec 2011
5	N/A	Nov 2011	Apr 2012
6	N/A	Apr 2012	Sep 2012
7	N/A	Apr 2013	Sep 2013
8	N/A	Apr 2014	Sep 2014
9	N/A	Apr 2015	Sep 2015
10	N/A	Apr 2016	Sep 2016
10	1	Apr 2016	Sep 2016
11	N/A	Apr 2017	Sep 2017
11	1	Sep 2017	Oct 2017
12	N/A	Apr 2018	Sep 2018
12	1	Sep 2018	Oct 2018
12	2	Oct 2018	Nov 2018
13	N/A	Apr 2019	Sep 2019

ISM Thirteenth Edition

The following tables describe changes contained in the Edition 13 of the IOSA Standards Manual (ISM 13). The first table, titled ISM 13 Revision Highlights, describes significant changes in ISM 13. Subsequent tables describe all changes in each of the ISM sections in relation to the current ISM Edition 12.

The second table, titled Summary–ISARPs Added/Eliminated (All Sections), displays the number of standards, recommended practices and tables added and/or eliminated in ISM 13. The added/eliminated provisions specific to each discipline are again identified with more detail at the beginning of the table for each of the respective ISM sections.

ISM 13 Revision Highlights	
Description of Significant Changes	
•	ORG section: ORG 1.3.2 revised to address telecommuting technology as a means for a manager to meet responsibilities and perform work duties.
•	ORG section: ORG 2.2.1 revised to address new Annex 19 standard for control of SMS operational records.
•	ORG section: ORG 3.4.6 revised to incorporate a new specification for the retention of information associated with the internal auditing of the ISARPs (formerly specified in ORG 3.4.8); provides reference to new Table 1.2.
•	ORG section: ORG 3.4.7 eliminated; submission of a conformance report (CR) is no longer required; all ISM references to the CR deleted.
•	ORG section: ORG 3.4.8 eliminated; specifications for retention of information associated with the internal auditing of the ISARPs incorporated in ORG 3.4.6 and new Table 1.2.
•	ORG section: new Table 1.2 specifies the information associated with the internal auditing of the ISARPs that must be retained by the operator as specified in ORG 3.4.6.
•	ORG section: ORG 3.5.4A and ORG 3.5.4B; existing ORG 3.5.4A specifies the monitoring of other operators that transport the operator's passengers under a commercial aviation agreement; effective 1 September 2020, ORG 3.5.4A will be eliminated and replaced by ORG 3.5.4B, which specifies initial and continuing auditing of other operators to ensure ICAO safety standards are being met.
•	DSP section: TR 2018-2 incorporated; DSP 3.5.1, 3.5.2, 3.5.3 revised to provide updated specifications that address aircraft tracking; DSP 3.5.4 eliminated.
•	DSP section: DSP 4.3.16 expanded to address increased fuel state awareness by providing options for determining and expressing a final reserve fuel value.
•	MNT section: New MNT 2.9.2 (standard) to provide specifications for maintenance associated with the data link recorder (DLR); requirement for a DLR is a new standard in Annex 6.
•	CAB section: CAB 3.1.1 revised with new sub-specification to address a reduction of minimum cabin crew complement during a case of incapacitation or unforeseen circumstances where a replacement cannot be obtained.
•	CAB section: CAB 4.1.1 and guidance revised to expand specifications and information related to preflight of cabin emergency systems and equipment.
•	GRH section: GRH 1.6.9 (recommended practice) revised to specify that processes and procedures for ground handling operations contained in the OM are verified against the IATA Ground Operations Manual (IGOM).
•	GRH section: GRH 2.2.4 (recommended practice) revised to specify training for ground handling personnel assigned to perform passenger services, ramp services and load control; includes reference to Table 6.1 for specified training elements.
•	GRH section: new GRH 2.2.5 (recommended practice) to specify training for ground handling personnel assigned to perform aircraft fueling.
•	GRH section: new GRH 2.2.6 (recommended practice) to specify training for ground handling personnel assigned to perform aircraft de-/anti-icing.

• GRH section: new GRH 3.1.3 (standard) to specify procedures for acceptance and handling of battery-powered mobility aids; addresses new ICAO TI and DGR requirements.
• GRH section: GRH 3.2.2 (standard) revised to specify aircraft arrival procedures to be completed prior to aircraft approaching the assigned parking gate or stand specifications (identified as existing safety-critical gap in GRH ISARPs).
• GRH section: GRH 3.2.3 (standard) revised to specify aircraft arrival procedures to be completed once aircraft has arrived and is stopped at the assigned parking gate or stand (identified as existing safety-critical gap in GRH ISARPs).
• GRH section: new GRH 3.2.7 (standard) to specify aircraft departure procedures to be completed prior to aircraft departing the parking gate or stand (identified as existing safety-critical gap in GRH ISARPs).
• GRH section: new GRH 3.2.8 (standard) to specify aircraft departure procedure for aircraft walkaround check to be completed prior to aircraft movement from the parking gate or stand (identified as existing safety-critical gap in GRH ISARPs).
• GRH section: new GRH 3.2.9 (standard) to specify procedures for aircraft pushback and towing (identified as existing safety-critical gap in GRH ISARPs).
• GRH section: GRH 3.5.1 (recommended practice) revised to specify practices and procedures for the operation of GSE in aircraft ground handling operations (identified as existing safety-critical gap in GRH ISARPs).
• GRH section: GRH 3.5.2 (recommended practice) revised to specify procedures for operation of passenger boarding bridges (identified as existing safety-critical gap in GRH ISARPs).
• GRH section: new GRH 3.7.4 (standard) to specify processes for the protection of cargo from unauthorized interference when in custody of personnel performing ground handling operational functions; harmonized with CGO provision; addresses Annex 17 standard.
• GRH section: Tables 6.2–6.11 eliminated.
• SEC section: new SEC 4.1.3 (recommended practice) to specify sharing with the State and other external entities relevant information that will to assist in the implementation of an effective security risk assessment process; addresses Annex 17 standard.
• SEC section: new SEC 4.3.3 (recommended practice effective 1 September 2020) to specify participation in the IATA Incident Data Exchange (IDX) through submission of reports of acts and preparatory acts of unlawful interference.
• Appendix A–Mandatory Observations moved to different document.

Summary—Additions/Eliminations (All Sections)	
Standards Eliminated	<ul style="list-style-type: none"> Total five (5). <ul style="list-style-type: none"> ORG (2) DSP (1) GRH (2)
Standards/Specifications Suspended	<ul style="list-style-type: none"> None.
Standards Added (Net increase 8)	<ul style="list-style-type: none"> Total twelve (12). <ul style="list-style-type: none"> FLT (4) DSP (2) (both repeated ORG provisions) MNT (1) GRH (5)
Recommended Practices Upgraded to Standard	<ul style="list-style-type: none"> Total one (1) <ul style="list-style-type: none"> FLT (1)
Recommended Practices Eliminated	<ul style="list-style-type: none"> None.

Summary—Additions/Eliminations (All Sections)	
Recommended Practices Added (Net increase 6)	<ul style="list-style-type: none"> Total six (6) <ul style="list-style-type: none"> FLT (2) GRH (2) SEC (2) ORG (1) (standard with future effective date that will replace an existing standard; no net addition of standards, not included in above total)
Tables Eliminated (Net decrease 9)	<ul style="list-style-type: none"> Total ten (10) <ul style="list-style-type: none"> GRH (10)
Tables Added	<ul style="list-style-type: none"> Total one (1) <ul style="list-style-type: none"> ORG (1)

Introduction	
Area Changed	Description of Change(s)
7 Operational Audit	<ul style="list-style-type: none"> Editorial change: under 'Implemented' header, wording revised in first paragraph to eliminate reference to 'effective.' Technical change: under 'Active Implementation (AI)' header, applicability wording revised in first paragraph to "Certain ISARPs may be designated..."
8 Safety Management System (SMS)	<ul style="list-style-type: none"> Editorial change: Title revised (word 'system' made singular) for consistency with ICAO terminology. Editorial change: wording added for consistency with note in ORG 1.1.10 regarding conformity with SMS standards.
11. Manual Revisions	<ul style="list-style-type: none"> Technical change: deletion of section under the header 'Usable Edition'.
Section 1 (ORG)	
Summary of Revisions	
General (changes that are applied multiple times)	<ul style="list-style-type: none"> Editorial changes: grammar/punctuation clean-up; commas, periods, hyphens, apostrophes, semicolons, spaces either deleted or added as applicable. Editorial changes: instances of the word 'back-up' revised to 'backup' for correct and consistent spelling. Editorial changes: all references to Conformance Report (CR) eliminated.
Standards Eliminated	<ul style="list-style-type: none"> Two (2): ORG 3.4.7, ORG 3.4.8.
Standards/Specifications Suspended	<ul style="list-style-type: none"> None.
Standards Added	<ul style="list-style-type: none"> One (1): ORG 3.5.4B (conditional addition; not effective until 01 September 2020; will replace ORG 3.5.4A, which will then be eliminated).
Recommended Practices Eliminated	<ul style="list-style-type: none"> None.

Recommended Practices Added	<ul style="list-style-type: none"> None.
Tables Eliminated	<ul style="list-style-type: none"> None.
Tables Added	<ul style="list-style-type: none"> One (1): Table 1.2.
Individual Revisions	
Area Changed	Description of Change(s)
Applicability Box	<ul style="list-style-type: none"> Technical change: references revised to reflect eliminations/ revisions associated with ORG 3.4.7, 3.4.8, 3.4.14 (last paragraph).
General Guidance	<ul style="list-style-type: none"> None.
ORG 1.1.10	<ul style="list-style-type: none"> Editorial change: wording added in note to emphasize that conformity with ORG 1.1.10 is not contingent on conformity with SMS recommended practices (only standards).
ORG 1.3.1	<ul style="list-style-type: none"> Technical change: fourth bullet point deleted as repetitive, does not appear in repeats of this provision in other sections.
ORG 1.3.2	<ul style="list-style-type: none"> Technical changes: wording revised to 'process or procedure' and 'unable to perform work duties' from 'absent from the workplace' to better express intent. Editorial change: wording revised to be consistent with repeats in other sections.
ORG 1.3.2 Auditor Actions	<ul style="list-style-type: none"> Editorial changes: wording revised to reflect changes in standard (first, fourth AA steps).
ORG 1.3.2 Guidance	<ul style="list-style-type: none"> Editorial changes: wording revised to reflect changes in standard (first paragraph). Technical change: wording added to address the use of telecommuting technology as a means of performing work duties (second paragraph).
ORG 1.6.5	<ul style="list-style-type: none"> Editorial change: wording revised to improve expression of intent.
ORG 1.6.5 Auditor Actions.	<ul style="list-style-type: none"> Editorial change: wording revised to reflect changes in standard (third AA step)
ORG 1.6.5 Guidance	<ul style="list-style-type: none"> Technical changes: wording deleted/added to define the intent of SMS training (second paragraph); training subject matter bullet points revised to reflect changes in ICAO SMM (third paragraph); wording added to address optional SMS recurrent training (fourth paragraph).
ORG 1.6.6	<ul style="list-style-type: none"> Editorial change: wording revised to improve expression of intent.
ORG 1.6.6 Guidance	<ul style="list-style-type: none"> Editorial changes: wording added to address optional SMS recurrent training (fourth paragraph); wording revised in bullet points to reflect changes in ICAO SMM (sixth paragraph).
ORG 2.1.5	<ul style="list-style-type: none"> Technical changes: wording revised to reflect requirement for SMS manual in Annex 19 standard; note added to address option for SMS manual to be either standalone or integrated in existing manuals.
ORG 2.2.1	<ul style="list-style-type: none"> Technical changes: note added to reflect requirement for control of SMS operational records in Annex 19 standard.
ORG 2.2.1 Guidance	<ul style="list-style-type: none"> Technical change: wording added to provide examples of SMS operational records (second paragraph).
ORG 3.4.6	<ul style="list-style-type: none"> Editorial change: word deleted as unnecessary. Technical change: sub-specification added (third bullet point) to address retention of information associated with the internal auditing of individual ISARPs (previously in ORG 3.4.8); provides reference to new Table 1.2.

ORG 3.4.6 Auditor Actions	<ul style="list-style-type: none"> Editorial change: wording revised to reflect changes in standard (fifth AA step).
ORG 3.4.6 Guidance	<ul style="list-style-type: none"> Technical change: wording added (previously in guidance associated with ORG 3.4.8) to address accomplishment of AAs in internal auditing of ISARPs (third paragraph). Technical change: wording added (previously in guidance associated with ORG 3.4.8) to address procedural documents (as referenced in Table 1.2) as means for retaining audit information (fourth paragraph). Technical change: wording added to confirm that IATA will provide the template to record all required information
ORG 3.4.7–3.4.9 (Intentionally open)	<ul style="list-style-type: none"> New placeholder.
ORG 3.4.7	<ul style="list-style-type: none"> Standard eliminated: elimination of requirement for submission of a CR.
ORG 3.4.8	<ul style="list-style-type: none"> Standard eliminated: specifications and guidance that address retention of information associated with internal auditing of ISARPs incorporated in ORG 3.4.6 and Table 1.2.
ORG 3.4.9 (Intentionally open)	<ul style="list-style-type: none"> Placeholder deleted.
ORG 3.4.13 Guidance	<ul style="list-style-type: none"> Editorial change: reference to IAH revised (last paragraph).
ORG 3.4.14	<ul style="list-style-type: none"> Technical changes: sub-specification revised (second bullet point); reference to ORG 3.4.8 revised to ORG 3.4.6; reference to new Table 1.2 added.
ORG 3.4.14 Guidance	<ul style="list-style-type: none"> Technical changes: wording deleted to reflect elimination of requirement for submission of a CR.
ORG 3.5.1 Auditor Actions	<ul style="list-style-type: none"> Technical change: wording added to state that contract/agreement may include 'reference to' measurable specifications (third AA step); same change made to AA step in repeats of ORG 3.5.1 in other sections.
ORG 3.5.4A	<ul style="list-style-type: none"> Editorial change: suffix 'A' added to identifier. Editorial changes: wording revised to better express intent; types of commercial aviation agreements expressed in bullet points (i)–(iii). Editorial change: wording in note revised to refer to 'other' operators rather than 'external' operators. Technical change: note added to provide notification that standard will be eliminated and replaced by ORG 3.5.4B effective 1 September 2020.
ORG 3.5.4A Auditor Actions	<ul style="list-style-type: none"> Editorial change: wording revised to reflect changes in standard (third and fourth AA steps).
ORG 3.5.4A Guidance	<ul style="list-style-type: none"> Technical change: wording added to provide examples of factors to be considered in performance monitoring of another operator (fifth paragraph). Technical change: wording added to provide possible methods of monitoring performance of another operator (sixth paragraph).
ORG 3.5.4B	<ul style="list-style-type: none"> New standard and guidance to replace ORG 3.5.4A effective 1 September 2020; specifies requirement for auditing of other operators for passenger transport operations under commercial aviation agreements; first note expresses conditions of applicability; second note addresses use of IOSA to conform to standard.
ORG 3.7.4	<ul style="list-style-type: none"> Technical change: wording in sub-specification (v) revised to broaden applicability to 'corrective or remedial actions.'

ORG 3.7.9 Guidance	<ul style="list-style-type: none"> Editorial change: reference to FDA program corrected (last paragraph).
ORG 4.1.1	<ul style="list-style-type: none"> Editorial change: inappropriate wording deleted.
ORG 4.1.4 Guidance	<ul style="list-style-type: none"> Editorial change: wording revised for consistency with terminology in the ICAO SMS framework (first paragraph).
Table 1.1	<ul style="list-style-type: none"> Editorial change: wording revised to provide link to controlling standard ORG 2.1.1 (lead paragraph).
Table 1.2	<ul style="list-style-type: none"> New table: contains specifications for information associated with the internal audit of individual ISARPs that is to be recorded and retained; previously specified in ORG 3.4.8.
Section 2 (FLT)	
Summary of Revisions	
General (changes that are applied multiple times)	<ul style="list-style-type: none"> Editorial changes: grammar/punctuation clean-up; commas, periods, hyphens, apostrophes, semicolons, spaces either deleted or added as applicable.
	<ul style="list-style-type: none"> Editorial changes: instances of the word 'back-up' revised to 'backup' for correct and consistent spelling.
Standards Eliminated	<ul style="list-style-type: none"> None.
Standards/Specifications Suspended	<ul style="list-style-type: none"> None.
Standards Added	<ul style="list-style-type: none"> Four (4): FLT 2.1.20, FLT 3.1.2, FLT 3.11.8B, FLT 3.11.8C
Recommended Practices Upgraded to Standard	<ul style="list-style-type: none"> None.
Recommended Practices Eliminated	<ul style="list-style-type: none"> None.
Recommended Practices Added	<ul style="list-style-type: none"> Two (2): FLT 3.7.10, FLT 3.11.50B
Tables Eliminated	<ul style="list-style-type: none"> None.
Tables Added	<ul style="list-style-type: none"> None.
Individual Revisions	
Area Changed	Description of Change(s)
Applicability Box	<ul style="list-style-type: none"> No changes.
FLT 1.3.3	<ul style="list-style-type: none"> Technical change: repeat ORG provision; wording revised to reflect changes to ORG 1.3.2.
FLT 1.3.3 Guidance	<ul style="list-style-type: none"> Editorial change: wording added to repeat some guidance information associated with ORG 1.3.2.
FLT 1.3.9 Auditor Actions	<ul style="list-style-type: none"> Editorial change: wording in third AA step revised to clarify intent.
FLT 1.3.10 Guidance	<ul style="list-style-type: none"> Editorial change: reference to FLT 2.2.44 deleted.
FLT 1.4.2 Guidance	<ul style="list-style-type: none"> Editorial changes: wording added to provide full name of abbreviations NOTAMS and FMS.
FLT 1.6.1 Guidance	<ul style="list-style-type: none"> Technical change: IRM reference added.
FLT 1.6.7–1.6.8 (Intentionally open)	<ul style="list-style-type: none"> Placeholder eliminated.
FLT 1.11.1 Auditor Actions	<ul style="list-style-type: none"> Technical change: wording added to state that contract/agreement may include 'reference to' measurable specifications (third AA step).

FLT 1.11.3	<ul style="list-style-type: none"> Editorial change: This is a repeated ORG provision; wording revised to be consistent with ORG 3.6.1; reference to FLT 1.11.4B added. Technical change: word 'navigation' deleted; not compatible with specifications in FLT 1.11.4B.
FLT 1.11.3 Guidance	<ul style="list-style-type: none"> Technical changes: wording added/revised to provide consistency with specifications in the provision.
FLT 1.11.4B	<ul style="list-style-type: none"> Technical/editorial changes: wording revised to more accurately state intent; structure revised to show sub-specifications.
FLT 1.11.4B Guidance	<ul style="list-style-type: none"> Editorial change: IRM reference revised for accuracy.
FLT 2.1.14	<ul style="list-style-type: none"> Technical change: wording added to provide greater specificity.
FLT 2.1.19	<ul style="list-style-type: none"> Technical change: provision wording completely replaced to address training facilities, devices, equipment and course materials.
FLT 2.1.19 Auditor Actions	<ul style="list-style-type: none"> Technical change: wording revised to reflect new specifications in the standard (multiple AA steps).
FLT 2.1.20 (Intentionally open)	<ul style="list-style-type: none"> Placeholder eliminated.
FLT 2.1.20	<ul style="list-style-type: none"> New standard: addresses qualification/performance standardization of flight instructors, evaluators, line check airmen.
FLT 2.1.36 Guidance	<ul style="list-style-type: none"> Technical change: conditional phrase deleted (last paragraph).
FLT 2.2.12	<ul style="list-style-type: none"> Editorial change: (GM) symbol added.
FLT 2.2.12 Guidance	<ul style="list-style-type: none"> Editorial changes: IRM reference added; reference to DGR revised for accuracy (last paragraph).
FLT 2.2.13	<ul style="list-style-type: none"> Editorial change: (GM) symbol added.
FLT 2.2.13 Guidance	<ul style="list-style-type: none"> Editorial change: Reference to DGR revised for accuracy (last paragraph).
FLT 2.2.26 Guidance	<ul style="list-style-type: none"> Editorial change: wording revised for consistency with wording in FLT 3.11.18 (fourth paragraph).
FLT 3.1.2	<ul style="list-style-type: none"> New standard and guidance: addresses communication among crew members when an operator has designated multiple common languages.
FLT 3.5.3	<ul style="list-style-type: none"> Editorial change: reference in sub-spec (ii) revised to FLT 1.12.2 for accuracy.
FLT 3.5.3 Guidance	<ul style="list-style-type: none"> Editorial change: spelling revised for ISM consistency (second paragraph).
FLT 3.7.10	<ul style="list-style-type: none"> New recommended practice and guidance to address flight crew fuel state awareness; specifications relocated from DSP 4.3.17.
FLT 3.8.7B	<ul style="list-style-type: none"> Editorial change: wording "interior" added to provide specificity to the type of preflight inspection.
FLT 3.8.7B Guidance	<ul style="list-style-type: none"> Technical change: new paragraph added to provide information regarding the assessment of serviceability of flight deck systems/emergency equipment.
FLT 3.8.8	<ul style="list-style-type: none"> Technical change: wording added to enhance the intent of sub-spec (ii) regarding availability/serviceability of cabin emergency systems/equipment.
FLT 3.8.8 Auditor Actions	<ul style="list-style-type: none"> Technical change: wording revised to reflect addition to specifications in the standard (first AA step).
FLT 3.8.8 Guidance	<ul style="list-style-type: none"> Technical changes: wording deleted as no longer consistent with changes to sub-spec (ii) in the standard; new paragraph added to provide information regarding the assessment of serviceability of cabin emergency systems/equipment.

FLT 3.11.2	<ul style="list-style-type: none"> Technical change: wording revised to provide an improved and more accurate expression of the specifications that address the nav accuracy check; greater detail provided.
FLT 3.11.2 Auditor Actions	<ul style="list-style-type: none"> Technical change: wording revised to reflect changes in the standard (first AA step).
FLT 3.11.8A	<ul style="list-style-type: none"> Editorial change: suffix letter 'A' added to identifier. Technical changes: wording revised/deleted to provide specifications that address only RVSM operations; reference to RNP/RNAV operations deleted.
FLT 3.11.8A Auditor Actions	<ul style="list-style-type: none"> Technical change: wording revised to reflect changes to specifications in the standard (first, second, fourth AA steps).
FLT 3.11.8A Guidance	<ul style="list-style-type: none"> Technical change: wording deleted to reflect changes to specifications in the standard.
FLT 3.11.8B	<ul style="list-style-type: none"> New standard and guidance to address RNP operations; specifications derived from RNP standards in Annex 6.
FLT 3.11.8C	<ul style="list-style-type: none"> New standard and guidance to address PBCS operations; specifications derived from standards in Annex 6.
FLT 3.11.18	<ul style="list-style-type: none"> Editorial changes: wording in body of provision revised to state 'policies and guidance'; wording in sub-spec (i) revised to state 'a requirement and procedures.' Technical change: wording in sub-spec (i) that specifies compliance with procedures in OM and certificate of airworthiness deleted as inaccurate.
FLT 3.11.48 Guidance	<ul style="list-style-type: none"> Editorial change: comma deleted.
FLT 3.11.49	<ul style="list-style-type: none"> Technical changes: wording revised, simplified; references to cabin atmospheric pressure in hPa deleted.
FLT 3.11.50A	<ul style="list-style-type: none"> Editorial change: suffix letter 'A' added to identifier.
FLT 3.11.50B	<ul style="list-style-type: none"> New recommended practice and guidance: provides specifications for limiting aircraft vertical speed when approaching an assigned altitude/flight level; specifications address standards in Annex 6.
FLT 3.12.1	<ul style="list-style-type: none"> Technical change: wording revised to provide an improved and more accurate expression of the specifications that address corrective lenses for flight crew members.
FLT 3.13.13	<ul style="list-style-type: none"> Editorial change: (GM) symbol added.
FLT 3.13.16	<ul style="list-style-type: none"> Editorial change: wording revised in sub-spec (ii) to provide an improved statement of intent.
FLT 3.13.17	<ul style="list-style-type: none"> Technical change: references revised to accurately reflect that fortified flight deck door specifications are contained in MNT Tables 4.11 and 4.14.
FLT 3.13.17 Guidance	<ul style="list-style-type: none"> Technical change: references revised to reflect fortified flight deck door specifications in MNT Tables 4.11 and 4.14.
FLT 3.13.18	<ul style="list-style-type: none"> Technical change: references revised to accurately reflect that fortified flight deck door specifications are contained in MNT Tables 4.11 and 4.14; wording in bullet point (ii) revised to more accurately state requirement for monitoring outside the flight deck door.
FLT 4.2.3	<ul style="list-style-type: none"> Technical change: conditional phrase added to provide improved clarity in the statement of the specifications.
FLT 4.2.3 Guidance	<ul style="list-style-type: none"> Technical change: wording revised for consistency with specifications in the provision (second paragraph).

FLT 4.3.1	<ul style="list-style-type: none"> Technical change: wording revised to expand specifications for satisfying operational requirements for routes/airspace of intended operations, to include, as applicable, PBN, MNPS, RVSM and PBCS.
FLT 4.3.1 Auditor Actions	<ul style="list-style-type: none"> Technical changes: wording revised to reflect changes to specifications in the standard (first, third, fourth AA steps).
FLT 4.3.5	<ul style="list-style-type: none"> Technical changes: wording revised, simplified; references to cabin atmospheric pressure in hPa deleted.
Table 2.3	<ul style="list-style-type: none"> Technical change: PBN, PBCS added to sub-spec (iii).
Table 2.9–2.13 (Intentionally open)	<ul style="list-style-type: none"> Table placeholder eliminated.
Section 3 (DSP)	
Summary of Revisions	
General (changes that are applied multiple times)	<ul style="list-style-type: none"> Editorial changes: grammar/punctuation clean-up; commas, periods, hyphens, apostrophes, semicolons, spaces either deleted or added as applicable. Editorial changes: cases of the word 'back-up' revised to 'backup' for correct and consistent spelling. Editorial changes: all AA steps that call for coordination with "flight operations" revised to "FLT Auditor" to provide proper intent.
Standards Eliminated	<ul style="list-style-type: none"> One (1): DSP 3.5.4.
Standards/Specifications Suspended	<ul style="list-style-type: none"> None.
Standards Added	<ul style="list-style-type: none"> Two (2): DSP 1.3.1A, DSP 1.3.2A (both repeated ORG provision).
Recommended Practices Eliminated	<ul style="list-style-type: none"> None.
Recommended Practices Added	<ul style="list-style-type: none"> None.
Tables Eliminated	<ul style="list-style-type: none"> None.
Tables Added	<ul style="list-style-type: none"> None.
Individual Revisions	
Area Changed	Description of Change(s)
Applicability Box	<ul style="list-style-type: none"> None.
DSP 1.3.1A	<ul style="list-style-type: none"> Editorial change: suffix letter 'A' added to identifier. New standard and guidance: repeat of ORG 1.3.1; specifications applicable to general operational control personnel.
DSP 1.3.1B	<ul style="list-style-type: none"> Editorial changes: suffix letter 'B' added to identifier; word in bullet point (ii) revised to singular.
DSP 1.3.1B Guidance	<ul style="list-style-type: none"> Editorial change: paragraph deleted, relocated as guidance for new DSP 1.3.1A.
DSP 1.3.2A	<ul style="list-style-type: none"> Editorial change: suffix letter 'A' added to identifier. New standard and guidance: repeat of ORG 1.3.2; specifications applicable to general operational control personnel.
DSP 1.3.2B	<ul style="list-style-type: none"> Editorial changes: suffix letter 'B' added to identifier. Technical changes: wording revised to focus applicability to frontline operational control personnel.
DSP 1.3.2B Auditor Actions	<ul style="list-style-type: none"> Editorial change: wording revised to reflect changes to specifications in the standard (first, third AA steps).

DSP 1.3.2B Guidance	<ul style="list-style-type: none"> Editorial changes: wording revised to address frontline operational control personnel.
DSP 1.3.5	<ul style="list-style-type: none"> Technical change: wording added to factor in the type of operational control system.
DSP 1.3.6	<ul style="list-style-type: none"> TR 2018-2 incorporated. Technical change: effective date deleted in sub-spec (vi).
DSP 1.3.6 Guidance	<ul style="list-style-type: none"> Technical change: reference to effective date in sub-spec (vi) deleted (second paragraph).
DSP 1.8.3 Auditor Actions	<ul style="list-style-type: none"> Editorial changes: wording revised to be more consistent with specifications in standard (first and third AA steps).
DSP 1.11.1 Auditor Actions	<ul style="list-style-type: none"> Technical change: wording added to state contract/agreement may include reference to measurable specifications (third AA step).
DSP 1.11.3	<ul style="list-style-type: none"> Technical change: wording revised to be consistent with ORG 3.6.1.
DSP 3.2.5 Guidance	<ul style="list-style-type: none"> Editorial change: Table number corrected (last paragraph).
DSP 3.2.6	<ul style="list-style-type: none"> Technical change: word added in conditional phrase to limit applicability to full shared operational control system.
DSP 3.2.6 Guidance	<ul style="list-style-type: none"> Editorial change: reference to guidance with DSP 1.3.4 added (first paragraph).
DSP 3.2.9C Guidance	<ul style="list-style-type: none"> Technical change: paragraph added to address the possibility of using variable time margins (based on monitoring specific flight parameters) for establishing the estimated time of use of an alternate airport. Technical change: FAR reference added (last paragraph, fourth bullet point). Editorial changes: dates deleted from regulatory references (last paragraph, second and third bullet points).
DSP 3.4.1 Auditor Actions	<ul style="list-style-type: none"> Technical change: revised to state coordination with MNT auditor (fourth AA step).
DSP 3.4.1 Guidance	<ul style="list-style-type: none"> Technical change: wording added to include consideration of the MEL to determine whether applicable equipment might be inoperative.
DSP 3.5.1	<ul style="list-style-type: none"> TR 2018-2 incorporated. Technical changes: conditional phrase deleted; note added to state that the standard does not define a specific tracking interval or reporting method.
DSP 3.5.1 Guidance	<ul style="list-style-type: none"> Technical changes: wording replaced to provide explanatory information related to intent of the specifications in the standard.
DSP 3.5.2	<ul style="list-style-type: none"> TR 2018-2 incorporated. Technical changes: conditional phrase deleted; wording revised to refine intent of specifications; one note deleted; two notes added to address risk assessment factors and the possibility of parallel conformity with DSP 3.5.3.
DSP 3.5.2 Guidance	<ul style="list-style-type: none"> Editorial change: IRM reference added. Technical changes: wording replaced to provide explanatory information related to intent of the specifications in the standard.

DSP 3.5.3	<ul style="list-style-type: none"> • TR 2018-2 incorporated. • Technical changes: effective date deleted; conditional phrase added; wording revised to refine intent of specifications; one note deleted; two notes added to address risk assessment factors and to complement the note in DSP 3.5.2 regarding the possibility of parallel conformity.
DSP 3.5.3 Guidance	<ul style="list-style-type: none"> • Technical changes: wording replaced to provide explanatory information related to intent of the specifications in the standard.
DSP 3.5.4	<ul style="list-style-type: none"> • TR 2018-2 incorporated. • Standard eliminated.
DSP 3.6.6 Guidance	<ul style="list-style-type: none"> • TR 2018-2 incorporated. • Technical change: paragraph added to address flight completion and the retention of aircraft tracking data obtained in accordance with DSP 3.5.2 and 3.5.3.
Subsection 4 General Guidance	<ul style="list-style-type: none"> • Editorial change: inappropriate wording deleted (should) (Specific Operational Capabilities, last paragraph).
DSP 4.1.3 (Intentionally open)	<ul style="list-style-type: none"> • New placeholder.
DSP 4.1.3	<ul style="list-style-type: none"> • Editorial change: recommended practice and guidance deleted and re-located; now DSP 4.5.5.
DSP 4.1.4	<ul style="list-style-type: none"> • Editorial change: word 'or' inserted after sub-sub-specs (a)–(c) in sub-spec (ii).
DSP 4.3.7	<ul style="list-style-type: none"> • Editorial change: wording "in any case not" in sub-spec (i) replace by "never."
DSP 4.3.10 Guidance	<ul style="list-style-type: none"> • Editorial change: wording deleted as obsolete (second paragraph).
DSP 4.3.13 Guidance	<ul style="list-style-type: none"> • Technical change: parenthetical example wording deleted (third paragraph).
DSP 4.3.16	<ul style="list-style-type: none"> • Technical changes: conditional phrase added; wording revised/added to include list of sub-specs that provide options for providing/expressing a final reserve fuel value.
DSP 4.3.16 Guidance	<ul style="list-style-type: none"> • Technical changes: wording revised to provide an intent statement (first paragraph), eliminate references to the flight crew (second paragraph), provide harmonization with the corresponding FLT provision (third paragraph).
DSP 4.4.1	<ul style="list-style-type: none"> • Editorial change: reference to FLT 4.3.4 deleted; FLT provision no longer exists. • Technical change: reference to pressurized/unpressurized aircraft deleted; no longer applicable
DSP 4.4.1 Auditor Actions	<ul style="list-style-type: none"> • Editorial change: coordination with "maintenance operations" revised to "MNT Auditor" to provide proper intent (fourth AA step); deleted reference to unpressurized aircraft
DSP 4.5.1 Guidance	<ul style="list-style-type: none"> • Technical changes: source references in bullet points added/revised; effective dates deleted.
DSP 4.5.2 Guidance	<ul style="list-style-type: none"> • Technical change: ICAO references revised/updated (last paragraph).
DSP 4.5.5	<ul style="list-style-type: none"> • Editorial change: recommended practice and guidance deleted and re-located; was DSP 4.1.3. • Technical change: wording added in conditional phrase to provide more specificity in the statement of applicability.

Table 3.4	<ul style="list-style-type: none"> • TR 2018-2 incorporated. • Technical changes: effective date deleted in item (xix); note added to address flight completion and the retention of aircraft tracking data.
Section 4 (MNT)	
Summary of Revisions	
General (changes that are applied multiple times)	<ul style="list-style-type: none"> • Editorial changes: grammar/punctuation clean-up; commas, periods, hyphens, apostrophes, semicolons, spaces either deleted or added as applicable. • Editorial changes: cases of the word 'back-up' revised to 'backup' for correct and consistent spelling.
Standards Eliminated	<ul style="list-style-type: none"> • None.
Standards/Specifications Suspended	<ul style="list-style-type: none"> • None.
Standards Added	<ul style="list-style-type: none"> • One (1): MNT 2.9.2.
Recommended Practices Eliminated	<ul style="list-style-type: none"> • None.
Recommended Practices Added	<ul style="list-style-type: none"> • None.
Tables Eliminated	<ul style="list-style-type: none"> • None.
Tables Added	<ul style="list-style-type: none"> • None.
Individual Revisions	
Area Changed	Description of Change(s)
Applicability Box	<ul style="list-style-type: none"> • None.
MNT 1.2.1	<ul style="list-style-type: none"> • Editorial change: repeat ORG provision; wording revised to 'safety accountability' for consistency with ORG 1.3.1.
MNT 1.2.1 Auditor Actions	<ul style="list-style-type: none"> • Editorial change: word added for consistency with revised wording in standard (first AA step).
MNT 1.2.2	<ul style="list-style-type: none"> • Technical change: repeat ORG provision; wording revised to reflect changes to ORG 1.3.2.
MNT 1.2.2 Guidance	<ul style="list-style-type: none"> • Editorial change: wording added to repeat some guidance information associated with ORG 1.3.2.
MNT 1.3.1 Guidance	<ul style="list-style-type: none"> • Technical change: unnecessary wording deleted (eighth paragraph (last two bullet points)).
MNT 1.3.2 Guidance	<ul style="list-style-type: none"> • Editorial change: inaccurate wording deleted (fourth paragraph (fourth bullet point)).
MNT 1.7.1 Guidance	<ul style="list-style-type: none"> • Technical changes: wording that addresses a list of AMO certifying personnel deleted (sixth paragraph), wording added to address MMM statements regarding instructions for continuing airworthiness and deviations from TCH maintenance instructions (twelfth paragraph, tenth, eleventh bullet points).
MNT 1.11.1 Auditor Actions	<ul style="list-style-type: none"> • Technical change: wording revised to be consistent with specifications in standard (third AA step).
MNT 1.11.2 Auditor Actions	<ul style="list-style-type: none"> • Technical change: wording revised to state maintenance agreement may include reference to measurable specifications (third AA step).
MNT 1.11.5	<ul style="list-style-type: none"> • Technical change: wording added to sub-spec (ii) to indicate applicability is limited to parts/components supplied directly to the operator. • Editorial change: (GM) symbol added.

MNT 1.11.5 Guidance	<ul style="list-style-type: none"> • New guidance.
MNT 2.1.2	<ul style="list-style-type: none"> • Technical change: wording of specifications revised to improve statement of intent.
MNT 2.5.1	<ul style="list-style-type: none"> • Technical change: wording of specifications revised to improve statement of intent. • Editorial changes: structure of provision revised to break up a very long sentence and clarify the specifications clear; (GM) symbol added.
MNT 2.5.1 Guidance	<ul style="list-style-type: none"> • New guidance.
MNT 2.9.2	<ul style="list-style-type: none"> • New standard and guidance; specification for maintenance of the data link recorder (DLR); addresses Annex 6 standard.
MNT 2.12.2	<ul style="list-style-type: none"> • Editorial change: (GM) symbol added.
MNT 2.12.2 Guidance	<ul style="list-style-type: none"> • New guidance.
MNT 4.4.2	<ul style="list-style-type: none"> • Editorial change: (GM) symbol added.
MNT 4.5.1	<ul style="list-style-type: none"> • Editorial change: (GM) symbol added.
MNT 4.9.1 Guidance	<ul style="list-style-type: none"> • Editorial change: wording that addresses list of AMO certifying personnel put into standalone paragraph (sixth paragraph).
Table 4.3	<ul style="list-style-type: none"> • Technical change: wording added in sub-spec (ii) to permit names or titles of persons responsible for ensuring maintenance is carried out in accordance with MMM.
Table 4.9	<ul style="list-style-type: none"> • Editorial changes: word 'aircraft' added for greater specificity in sub-spec (xi); first letters of term 'Type Design Organization' revised to upper case for consistency with other similar terms.
Table 4.11	<ul style="list-style-type: none"> • Editorial changes: numerous table specifications revised for simplification and consistency. • Editorial changes: table format and structure of specifications revised to improve usability of the table. • Editorial changes: specification identifiers in Table 4.11 harmonized with associated identifiers for guidance material in Table 4.12. • Technical changes: wording revised in multiple specifications to be more consistent with ICAO standard. • Technical change: item (viii) and (ix) added to address ICAO requirements for underwater locator beacons; revision closes existing suspension of these specifications. • Technical change: item (xv) is a new specification for a data link recorder (DLR); addresses new ICAO standard. • Technical change: item (xxvi) revised to address conditions of applicability for a fortified flight deck entry door; addresses revised ICAO standard.
Table 4.12	<ul style="list-style-type: none"> • Technical changes: guidance for multiple specifications eliminated; replaced with table placeholders.
Table 4.13	<ul style="list-style-type: none"> • Editorial change: wording revised in note to better reflect intent.
Table 4.14	<ul style="list-style-type: none"> • Technical change: item (i) eliminated for consistency with ICAO standard; replaced with table placeholder.
Table 4.15	<ul style="list-style-type: none"> • Technical change: item (1) eliminated to coincide with elimination of item (i) in Table 4.14; replaced with table placeholder.

Section 5 (CAB)	
Summary of Revisions	
General (changes that are applied multiple times)	<ul style="list-style-type: none"> Editorial changes: grammar/punctuation clean-up; commas, periods, hyphens, apostrophes, semicolons, spaces either deleted or added as applicable. Editorial changes: cases of the word 'back-up' revised to 'backup' for correct and consistent spelling. Technical changes: instances of 'approved by the Authority' revised to "approved or accepted by the Authority" to account for regulatory differences.
Standards Eliminated	<ul style="list-style-type: none"> None.
Standards/Specifications Suspended	<ul style="list-style-type: none"> None.
Standards Added	<ul style="list-style-type: none"> None.
Recommended Practices Eliminated	<ul style="list-style-type: none"> None.
Recommended Practices Added	<ul style="list-style-type: none"> None.
Tables Eliminated	<ul style="list-style-type: none"> None.
Tables Added	<ul style="list-style-type: none"> None.
Individual Revisions	
Area Changed	Description of Change(s)
Applicability Box	<ul style="list-style-type: none"> None.
General Guidance	<ul style="list-style-type: none"> None.
CAB 1.2.1	<ul style="list-style-type: none"> Editorial change: repeat ORG provision; wording revised to 'safety accountability' for consistency with ORG 1.3.1.
CAB 1.2.2	<ul style="list-style-type: none"> Technical change: repeat ORG provision; wording revised to reflect changes to ORG 1.3.2.
CAB 1.2.2 Guidance	<ul style="list-style-type: none"> Editorial change: wording added to repeat some guidance information associated with ORG 1.3.2.
CAB 1.5.3	<ul style="list-style-type: none"> Editorial change: wording order revised to 'approved or accepted' for consistency.
CAB 1.6.1 Guidance	<ul style="list-style-type: none"> Editorial change: wording revised to eliminate run-on sentence (first paragraph).
CAB 1.6.5	<ul style="list-style-type: none"> Editorial change: word revised ('used') in sub-spec (ii) for consistency with wording in sub-spec (i).
CAB 1.10.1 Auditor Actions	<ul style="list-style-type: none"> Technical change: wording added to state that contract/agreement may include 'reference to' measurable specifications (third AA step).
CAB 2.2.5 Guidance	<ul style="list-style-type: none"> Editorial changes: wording revised to improve grammar (fourth, sixth paragraphs).
CAB 2.2.7 Guidance	<ul style="list-style-type: none"> Editorial change: Reference to DGR revised for accuracy (last paragraph).

CAB 3.1.1	<ul style="list-style-type: none"> Technical changes: wording revised to be consistent with Annex 6 standard. TR 2018-2 incorporated. Technical changes: sub-specification (iii) added to address reduction of minimum cabin crew complement during a case of incapacitation or unforeseen circumstances where a replacement cannot be obtained. Editorial change: GM symbol added.
CAB 3.1.1 Auditor Actions	<ul style="list-style-type: none"> Technical changes: wording revised to reflect new specification in standard (multiple AA steps).
CAB 3.1.1 Guidance	<ul style="list-style-type: none"> New guidance: provides IRM and ICAO references.
CAB 3.1.3 Guidance	<ul style="list-style-type: none"> Editorial change: word 'a' deleted to improve sentence structure (third paragraph).
CAB 3.3.2	<ul style="list-style-type: none"> Editorial changes: wording and structure of sub-specs revised for consistency with FLT 3.13.16.
CAB 3.4.2	<ul style="list-style-type: none"> Editorial change: word 'also' added to improve sentence structure.
CAB 4.1.1	<ul style="list-style-type: none"> Technical changes; wording added to sub-specifications to expand technical intent as applicable to cabin operations.
CAB 4.1.1 Guidance	<ul style="list-style-type: none"> Technical changes: wording revised to provide greater specificity regarding intent and conditions associated with cabin preflight inspection procedures.
CAB 4.2.4–4.2.5 (Intentionally open)	<ul style="list-style-type: none"> Placeholder deleted.
Table 5.8	<ul style="list-style-type: none"> Editorial change: hyphen deleted for consistency with M-W dictionary spelling (nitroglycerine).
Section 6 (GRH)	
Summary of Revisions	
General (changes that are applied multiple times)	<ul style="list-style-type: none"> Editorial changes: grammar/punctuation clean-up; commas, periods, hyphens, apostrophes, semicolons, spaces either deleted or added as applicable. Editorial changes: cases of the word 'back-up' revised to 'backup' for correct and consistent spelling.
Standards Eliminated	<ul style="list-style-type: none"> Two (2): GRH 3.2.4, GRH 3.2.5.
Standards/Specifications Suspended	<ul style="list-style-type: none"> None.
Standards Added	<ul style="list-style-type: none"> Five (5): GRH 3.1.3, GRH 3.2.7, GRH 3.2.8, GRH 3.2.9, GRH 3.7.4.
Recommended Practices Eliminated	<ul style="list-style-type: none"> None.
Recommended Practices Added	<ul style="list-style-type: none"> Two (2) GRH 2.2.5, GRH 2.2.6.
Tables Eliminated	<ul style="list-style-type: none"> Ten (10): Tables 6.2–6.11.
Tables Added	<ul style="list-style-type: none"> None.

Individual Revisions	
Area Changed	Description of Change(s)
Applicability Box	<ul style="list-style-type: none"> None.
General Guidance	<ul style="list-style-type: none"> None.
GRH 1.2.1	<ul style="list-style-type: none"> Editorial change: repeat ORG provision; wording revised to 'safety accountability' for consistency with ORG 1.3.1.
GRH 1.2.1 Auditor Actions	<ul style="list-style-type: none"> Editorial change: reference to security deleted; not compatible in an SMS provision.
GRH 1.2.2	<ul style="list-style-type: none"> Technical change: repeat ORG provision; wording revised to reflect changes to ORG 1.3.2. Editorial change: wording added (in reference to post holders) to be consistent with ORG 1.3.2.
GRH 1.2.2 Guidance	<ul style="list-style-type: none"> Editorial change: wording added to repeat some guidance information associated with ORG 1.3.2.
GRH 1.6.9	<ul style="list-style-type: none"> Technical changes: wording revised to include verification against IGOM; sub-specifications added to express verification steps.
GRH 1.6.9 Auditor Actions	<ul style="list-style-type: none"> Technical changes: wording revised to be consistent with specifications in standard (multiple AA steps).
GRH 1.6.9 Guidance	<ul style="list-style-type: none"> Technical changes: wording revised to provide information relevant to the changed specifications in the provision.
GRH 1.10.1 Auditor Actions	<ul style="list-style-type: none"> Technical change: wording added to state that contract/agreement may include 'reference to' measurable specifications (third AA step).
GRH 1.11.2 Guidance	<ul style="list-style-type: none"> Technical change: IRM reference added (GSE). Editorial change: GSE abbreviation added (third paragraph, last bullet point).
GRH 1.11.6	<ul style="list-style-type: none"> Technical changes: Effective date added to address future implementation of the IATA Incident Data Exchange (IDX), which will replace the Ground Damage Database (GDDB); wording in provision revised to address IDX
GRH 1.11.6 Auditor Actions	<ul style="list-style-type: none"> Editorial change: wording revised to address IDX rather than GDDB (first and third AA steps).
GRH 1.11.6 Guidance	<ul style="list-style-type: none"> Technical changes: wording revised to address IDX in place of GDDB.
GRH 2.1.1	<ul style="list-style-type: none"> Technical change: new sub-specification (iii) added to address re-qualification training.
GRH 2.1.1 Auditor Actions	<ul style="list-style-type: none"> Technical changes: wording revised to reflect new specification in standard (first, third AA steps).
GRH 2.1.2 Guidance	<ul style="list-style-type: none"> Technical changes: wording added/deleted to provide subject areas typically included in safety and human factors training.
GRH 2.2.1	<ul style="list-style-type: none"> Editorial changes: wording revised for accuracy and consistency with CGO 2.2.1.
GRH 2.2.1 Auditor Actions	<ul style="list-style-type: none"> Editorial change: wording revised to better express intent (first AA step).
GRH 2.2.1 Guidance	<ul style="list-style-type: none"> Editorial change: Reference to DGR revised for accuracy (last paragraph).
GRH 2.2.2	<ul style="list-style-type: none"> Editorial changes: wording revised for accuracy and consistency with CGO 2.2.2.
GRH 2.2.2 Guidance	<ul style="list-style-type: none"> Editorial change: Reference to DGR revised for accuracy (last paragraph).

GRH 2.2.3	<ul style="list-style-type: none"> Technical changes: wording revised in sub-specs to state ground handling duties or functions accurately and consistent with Table 6.1.
GRH 2.2.4	<ul style="list-style-type: none"> Technical change: wording revised to specify training for ground handling personnel assigned to perform passenger services, ramp services and load control; includes reference to Table 6.1 for training elements.
GRH 2.2.4 Auditor Actions	<ul style="list-style-type: none"> Technical changes: wording revised to be consistent with specifications in standard (multiple AA steps).
GRH 2.2.5	<ul style="list-style-type: none"> New recommended practice and guidance to specify training for ground handling personnel assigned to perform aircraft fueling; training elements expressed in list of sub-specifications.
GRH 2.2.6	<ul style="list-style-type: none"> New recommended practice and guidance to specify training for ground handling personnel assigned to perform aircraft de-/anti-icing; includes conditional phrase; training elements expressed in list of sub-specifications.
GRH 3.1.3	<ul style="list-style-type: none"> New standard and guidance to specify procedures for acceptance and handling of battery-powered mobility aids; includes conditional phrase; requirements expressed in list of sub-specifications; addresses ICAO TI and DGR requirements.
GRH 3.1.4 (Intentionally open)	<ul style="list-style-type: none"> Placeholder revised.
GRH 3.2.2	<ul style="list-style-type: none"> Technical change: wording in standard and guidance revised to specify aircraft arrival procedures to be completed prior to aircraft approaching the assigned parking gate or stand (addresses GRH gap identified as safety-critical).
GRH 3.2.3	<ul style="list-style-type: none"> Technical change: wording in standard and guidance revised to specify aircraft arrival procedures to be completed once aircraft has arrived and is stopped at the assigned parking gate or stand (addresses GRH gap identified as safety-critical).
GRH 3.2.4-3.2.5 (Intentionally open)	<ul style="list-style-type: none"> New placeholder.
GRH 3.2.4	<ul style="list-style-type: none"> Standard eliminated.
GRH 3.2.5	<ul style="list-style-type: none"> Standard eliminated.
GRH 3.2.7	<ul style="list-style-type: none"> New standard and guidance to specify aircraft departure procedures to be completed prior to aircraft departing the parking gate or stand (addresses GRH gap identified as safety-critical).
GRH 3.2.8	<ul style="list-style-type: none"> New standard and guidance to specify aircraft departure procedure for aircraft walkaround check to be completed prior to aircraft movement (addresses GRH gap identified as safety-critical).
GRH 3.2.9	<ul style="list-style-type: none"> New standard and guidance to specify procedures for aircraft pushback and towing (addresses GRH gap identified as safety-critical).
GRH 3.4.3	<ul style="list-style-type: none"> Technical changes: wording revised to include transportation of dangerous goods to/from an aircraft (in addition to loading/securing).
GRH 3.4.3 Auditor Actions	<ul style="list-style-type: none"> Technical changes: wording revised to include transportation of dangerous goods to/from aircraft (AA steps three and five).
GRH 3.4.3 Guidance	<ul style="list-style-type: none"> Technical change: reference to DGR revised to include transportation of dangerous goods.
GRH 3.4.14	<ul style="list-style-type: none"> Editorial change: conditional phrase added. Technical change: wording revised to better express intent.

GRH 3.5.1	<ul style="list-style-type: none"> Technical changes: wording revised, sub-specifications added to specify practices and procedures for the operation of GSE (addresses GRH gap identified as safety-critical).
GRH 3.5.1 Auditor Actions	<ul style="list-style-type: none"> Technical changes: wording revised to be consistent with specifications in standard (multiple AA steps).
GRH 3.5.1 Guidance	<ul style="list-style-type: none"> Editorial change: IGOM reference revised.
GRH 3.5.2	<ul style="list-style-type: none"> Technical change: wording in standard and guidance revised to specify procedures for operation of passenger boarding bridges; includes conditional phrase (addresses GRH gap identified as safety-critical).
GRH 3.5.2 Auditor Actions	<ul style="list-style-type: none"> Technical changes: wording revised to be consistent with specifications in standard (multiple AA steps).
GRH 3.7.4	<ul style="list-style-type: none"> New standard and guidance to specify processes for the protection of cargo from unauthorized interference when in custody of personnel performing ground handling operational functions; addresses Annex 17 standard.
GRH 4.1.2	<ul style="list-style-type: none"> Technical change: wording deleted for consistency with Annex 6 standard.
GRH 4.1.3	<ul style="list-style-type: none"> Technical change: wording deleted to expand scope of the provision.
GRH 4.1.4	<ul style="list-style-type: none"> Technical change: wording revised/deleted to expand scope of the provision.
GRH 4.1.5	<ul style="list-style-type: none"> Technical change: wording deleted for consistency with Annex 6 standard.
GRH 4.1.6	<ul style="list-style-type: none"> Technical change: wording revised/deleted to expand scope of the provision.
Table 6.1	<ul style="list-style-type: none"> Technical change: content of table revised to specify training elements for ground handling personnel assigned to perform passenger services, ramp services and load control.
Table 6.2–6.11	<ul style="list-style-type: none"> Tables eliminated.
Section 7 (CGO)	
Summary of Revisions	
General (changes that are applied multiple times)	<ul style="list-style-type: none"> Editorial changes: grammar/punctuation clean-up; commas, periods, hyphens, apostrophes, semicolons, spaces either deleted or added as applicable. Editorial changes: cases of the word 'back-up' revised to 'backup' for correct and consistent spelling.
Standards Eliminated	<ul style="list-style-type: none"> None.
Standards/Specifications Suspended	<ul style="list-style-type: none"> None.
Standards Added	<ul style="list-style-type: none"> None.
Recommended Practices Eliminated	<ul style="list-style-type: none"> None.
Recommended Practices Added	<ul style="list-style-type: none"> None.
Tables Eliminated	<ul style="list-style-type: none"> None.
Tables Added	<ul style="list-style-type: none"> None.

Individual Revisions	
Area Changed	Description of Change(s)
Applicability Box	<ul style="list-style-type: none"> None.
CGO 1.2.1	<ul style="list-style-type: none"> Editorial change: repeat ORG provision; wording revised to 'safety accountability' for consistency with ORG 1.3.1.
CGO 1.2.2	<ul style="list-style-type: none"> Technical change: repeat ORG provision; wording revised to reflect changes to ORG 1.3.2. Editorial change: wording added (in reference to post holders) to be consistent with ORG 1.3.2.
CGO 1.2.2 Guidance	<ul style="list-style-type: none"> Editorial change: wording added to repeat some guidance information associated with ORG 1.3.2.
CGO 1.10.1 Auditor Actions	<ul style="list-style-type: none"> Technical change: wording added to state that contract/agreement may include 'reference to' measurable specifications (third AA step).
CGO 2.1.2 Guidance	<ul style="list-style-type: none"> Editorial change: Reference to DGR revised for accuracy (last paragraph).
CGO 2.2.1	<ul style="list-style-type: none"> Technical changes: wording deleted for accuracy of intent; core specification applies only to personnel that accept dangerous goods cargo.
CGO 2.2.1 Guidance	<ul style="list-style-type: none"> Editorial change: Reference to DGR revised for accuracy (last paragraph).
CGO 2.2.2	<ul style="list-style-type: none"> Editorial change: wording revised to specify recurrent training interval for consistency with CGO 2.2.1.
CGO 2.2.2 Guidance	<ul style="list-style-type: none"> Technical change: wording deleted; not compatible with wording in provision (first paragraph, fourth bullet point) Editorial change: Reference to DGR revised for accuracy (last paragraph).
CGO 2.2.3	<ul style="list-style-type: none"> Editorial change: wording added/revised for consistency with previous provisions.
CGO 2.2.3 Guidance	<ul style="list-style-type: none"> Editorial change: Reference to DGR revised for accuracy (last paragraph).
CGO 3.2.10	<ul style="list-style-type: none"> Technical change: note deleted; specifications for separation of dangerous goods associated with aircraft loading are found in GRH 3.4.3.
CGO 3.2.10 Guidance	<ul style="list-style-type: none"> Technical change: wording deleted/added for consistency with elimination of the note in the provision; reference to GRH 3.4.3 added.
CGO 3.7.6	<ul style="list-style-type: none"> Editorial change: (GM) symbol added.
CGO 3.7.6 Guidance	<ul style="list-style-type: none"> New guidance to complement guidance associated with GRH 3.7.4; addresses the protection of cargo from unauthorized interference when in custody of personnel performing cargo operational functions; addresses Annex 17 standard.

Section 8 (SEC)	
Summary of Revisions	
General (changes that are applied multiple times)	<ul style="list-style-type: none"> Editorial changes: grammar/punctuation clean-up; commas, periods, hyphens, apostrophes, semicolons, spaces either deleted or added as applicable. Editorial changes: cases of the word 'back-up' revised to 'backup' for correct and consistent spelling.
Standards Eliminated	<ul style="list-style-type: none"> None.
Standards/Specifications Suspended	<ul style="list-style-type: none"> None.
Standards Added	<ul style="list-style-type: none"> None.
Recommended Practices Eliminated	<ul style="list-style-type: none"> None.
Recommended Practices Added	<ul style="list-style-type: none"> Two (2): SEC 4.1.3, SEC 4.3.3. (effective 1 September 2020).
Tables Eliminated	<ul style="list-style-type: none"> None.
Tables Added	<ul style="list-style-type: none"> None.
Individual Revisions	
Area Changed	Description of Change(s)
Applicability Box	<ul style="list-style-type: none"> None.
SEC 1.3.2	<ul style="list-style-type: none"> Technical change: wording revised to reflect changes to ORG 1.3.2.
SEC 1.3.2 Guidance	<ul style="list-style-type: none"> Editorial change: wording added to repeat some guidance information associated with ORG 1.3.2.
SEC 1.5.3 Guidance	<ul style="list-style-type: none"> Technical change: wording added to address escorted and unescorted access to security restricted areas as associated with the specification for background checks.
SEC 1.8.1	<ul style="list-style-type: none"> Editorial change: identifiers of listed sub-specifications converted to lower-case Roman numerals.
SEC 1.10.4 Guidance	<ul style="list-style-type: none"> Technical change: wording added to provide information regarding the focus of security surveys.
SEC 1.11.2	<ul style="list-style-type: none"> Editorial change: wording revised to better align with ORG 3.5.2.
SEC 1.12.1 Guidance	<ul style="list-style-type: none"> Technical change: wording added to provide expanded information regarding an operational security reporting system (sixth, seventh, eighth paragraphs). Editorial changes; IRM reference added; paragraphs reorganized, wording added/revised to address reporting system database taxonomy and future implementation of IDX.
SEC 3.4.1 Guidance	<ul style="list-style-type: none"> Technical change: wording added to address the non-continuous use of explosive detection screening equipment.
SEC 3.4.2	<ul style="list-style-type: none"> Technical change: wording revised to be consistent with SEC 3.4.1 (international flights).
SEC 3.4.6	<ul style="list-style-type: none"> Technical change: word added for correct expression of intent ('operational security personnel').
SEC 3.4.6 Guidance	<ul style="list-style-type: none"> Technical change: wording added to provide information that describes the conditions when behaviour detection methods are typically implemented.
SEC 3.9.2	<ul style="list-style-type: none"> Technical change: wording added to include a supply chain security process as a means of ensuring merchandise and supplies used in security areas are subjected to appropriate security controls.

SEC 4.1.3	<ul style="list-style-type: none">• New recommended practice and guidance to specify sharing with the State and other external entities relevant information that will to assist in the implementation of an effective security risk assessment process.
SEC 4.3.2	<ul style="list-style-type: none">• Technical change: wording added to include preparatory acts of unlawful interference in core specification; provides consistency with wording in Annex 17 standard.
SEC 4.3.3	<ul style="list-style-type: none">• New recommended practice and guidance to specify/address reporting of acts and preparatory acts of unlawful interference to IATA for inclusion in the Incident Data Exchange (IDX).

INTENTIONALLY LEFT BLANK

Introduction

1 Purpose

The IOSA Standards Manual (ISM) is published in order to provide the IOSA standards, recommended practices (ISARPs), associated guidance material and other supporting information necessary for an operator to successfully prepare for an audit.

The ISM is the sole source of assessment criteria to be utilized by auditors when conducting an audit against the ISARPs.

The ISM may also be used as a guide for any operator desiring to structure its operational management and control systems in conformity with the latest industry operational practices.

2 Structure

The ISM is organized as follows:

- [Section 1](#) → Organization and Management System (ORG);
- [Section 2](#) → Flight Operations (FLT);
- [Section 3](#) → Operational Control and Flight Dispatch (DSP);
- [Section 4](#) → Aircraft Engineering and Maintenance (MNT);
- [Section 5](#) → Cabin Operations (CAB);
- [Section 6](#) → Ground Handling Operations (GRH);
- [Section 7](#) → Cargo Operations (CGO);
- [Section 8](#) → Security Management (SEC).

Each section in this Manual is assigned an associated 3-letter identifier (in parentheses above). The reference number for every standard or recommended practice within a section includes the specific 3-letter identifier for that section (e.g. [ORG 1.1.1](#)).

3 Sources for IOSA Standards and Recommended Practices (ISARPs)

The safety and security requirements published in the Annexes to the Convention on International Civil Aviation (ICAO Annexes) are the primary source for specifications contained in the ISARPs. Safety and security requirements in the ICAO Annexes used as the basis for ISARPs are those that are applicable either directly or indirectly to the air operator.

4 Applicability of ISARPs

Applicability Guidance

To provide guidance to operators, an Applicability box is found at the beginning of each section of this manual. Within the box is a general description of the applicability of the ISARPs contained in the section.

The applicability of individual standards or recommended practices is always determined by the auditor. As a means to assist with the interpretation of individual application, many ISARPs begin with a *conditional phrase* as described below.

Systemic Applicability

When making a determination as to the applicability of individual ISARPs, it is important to take into account operations (relevant to the individual standard or recommended practice) that are conducted within stations and locations throughout the operator's network.

Aircraft Applicability

The ISARPs as published in this version of the ISM are applicable only for the audit of an operator that *operates* a minimum of one (i.e. one or more) multi-engine, two-pilot aircraft with a maximum certificated takeoff mass in excess of 5,700 kg (12,566 lb) to conduct:

- Passenger flights with or without cabin crew.
- Cargo flights with or without the carriage of passengers or supernumeraries.

ISARPs may not be applied or used for the Audit of an operator that **either**:

- Does not *operate* a minimum of one aircraft as specified above, **or**
- Has *all* aircraft operations conducted by another operator.

ISARPs may not be applied or used for the Audit of operations that are conducted with:

- Aircraft that have a maximum certificated takeoff mass of 5,700 kg (12,566 lb) or less;
- Single engine aircraft;
- Piston engine aircraft;
- Single pilot aircraft;
- Helicopters;
- Seaplanes.

During an audit, ISARPs are applied only to those aircraft that are of the type authorized in the Air Operator Certificate (AOC) and utilized in commercial passenger and/or cargo operations. Certain ISARPs are also applicable to non-commercial operations, and such application is indicated in a note that is part of the standard or recommended practice.

Other owned or leased aircraft that are *not* of the type authorized in the AOC and/or not utilized in commercial air transport operations will not be evaluated during an audit. However, the existence of such aircraft will be referenced with an explanation in the IOSA Audit Report (IAR).

Systems and Equipment Applicability

Aircraft that meet the above-specified aircraft applicability criteria are assessed for conformity with the applicable aircraft and cabin systems and equipment specifications contained in ISM Section 4 (MNT), [Table 4.11](#) to [Table 4.14](#).

5 Explanation of ISARPs

ISARPs contained in this manual have been developed for use under the IOSA program and contain the operational criteria upon which the audits are based. ISARPs are *not* regulations.

ISARPs Identifiers

All ISM provisions (i.e. the ISARPs) are preceded by an identifier that consists of the three-letter section abbreviation and a string of three numbers separated by two decimal points (e.g. [ORG 1.1.1](#)).

Stabilization of the ISARPs identifiers is an important goal, primarily for facilitating use of the ISARPs by operators, auditors and others, but also for the purpose of ensuring an accurate statistical basis. Therefore, when revising the ISM, every effort is made to minimize any re-numbering of the ISARPs.

In certain instances, new provisions must be inserted into an existing series of ISARPs. Normally this is done when it is important that the new provision has a logical locational relationship with another existing provision. When this occurs, an additional upper-case letter is attached to the identifier of the applicable provisions as the means of avoiding the re-numbering of other ISARPs that follow in the series.

For example, when a new FLT provision was developed to address AQP/ATQP, its logical location was immediately following the existing FLT 2.1.1, which contains the core flight crew training program specifications. The new provision was inserted immediately under FLT 2.1.1, and the two provisions became [FLT 2.1.1A](#) and [FLT 2.1.1B](#). The addition of upper-case letters to the identifiers of those two provisions precluded the need to renumber all of the other ISARPs that follow in that series.

Standards

IOSA Standards are specified systems, policies, programs, processes, procedures, plans, sets of measures, facilities, components, types of equipment or any other aspect of operations under the scope of IOSA that have been determined to be an operational necessity, and with which an operator will be expected to be in conformity at the conclusion of an audit.

Standards always contain the word “shall” (e.g. “The Operator shall have a process...”) in order to denote that conformance by an operator being audited is a requirement for IOSA registration.

During an audit, determination of nonconformity with specifications contained in an IOSA Standard results in a Finding, which in turn results in the generation of a Corrective Action Report (CAR).

To close a Finding, an operator will develop a Corrective Action Plan (CAP), and then implement corrective action in accordance with the CAP.

Recommended Practices

IOSA Recommended Practices are specified systems, policies, programs, processes, procedures, plans, sets of measures, facilities, components, types of equipment or any other aspects of operations under the audit scope of IOSA that have been determined to be operationally desirable, but conformance is optional by an operator. Recommended Practices always contain the italicized word “*should*” (e.g. “The Operator *should* have a policy...”) to denote conformance is optional.

During an audit, a determination of nonconformity with specifications contained in an IOSA Recommended Practice results in an Observation, which in turn results in the generation of a CAR.

An operator is not obliged to close an observation with corrective action but, as a minimum, must provide the root cause analysis (RCA) portion of the CAP. However, if an operator chooses to close an Observation, it will require subsequent implementation of corrective action in the same manner as is required to close a Finding.

Conditional Phrase

Certain provisions (i.e. standards or recommended practices, or sub-specifications within certain provisions), begin with a conditional phrase. The conditional phrase states the conditions (one or more) that serve to define the applicability of the provision or sub-specification to the individual operator being audited. A conditional phrase begins with the words “If the Operator...”

When assessing an operator against a provision or sub-specification that begins with a conditional phrase, the Auditor will first determine if an operator meets the condition(s) stated in the conditional phrase. If the operator meets the stated condition(s), the provision or sub-specification is applicable to the operator and must be assessed for conformance. If the operator does not meet the condition(s), the provision or sub-specification is not applicable to that operator, and such non-applicability will then be recorded as N/A.

Parallel Conformity Option (PCO)

A Parallel Conformity Option (PCO) may be included in a limited number of provisions in this ISM. A PCO provides an optional means for an operator to be in conformity with an IOSA provision that contains a basic operational specification (typically derived from ICAO standards), which, due to technical, logistical regulatory or other relevant factors, cannot be implemented by a large segment of the industry.

Where a PCO is included in an IOSA provision, it will be clearly identified by a **[PCO]** symbol and described in an informational note (see Notes and Symbols below). If the PCO has an expiration date, the note will also include the expiration date.

Within a provision, the basic operational specification(s) will always be stated first and the identifiable PCO specification(s) will immediately follow thereafter.

Each PCO is subject to approval under the IOSA Standards Change Management Process. If a PCO includes an expiration date, such date will be reviewed on a regular basis to determine if an extension is required. Such review will include an investigation of industry capability to meet the basic operational specification. At the point it can be determined the industry will have the capability to meet the basic operational specification, a PCO will be allowed to expire.

Notes and Symbols

An italicized note (*Note:*) immediately following a provision contains information relevant to the specification(s) in the provision and is to be considered as part of the provision.

An <AC> symbol in the reference number of an IOSA provision indicates that the provision is applicable to an operator that conducts flights with cargo aircraft.

An [SMS] symbol in bold text following the last sentence of an IOSA provision indicates the provision specifies one or more of the elements of a safety management system (SMS). (SMS is addressed in [subsection 8](#) below.)

A [PCO] symbol in bold text following a sub-specification within or the last sentence of an IOSA provision identifies a parallel conformity option (PCO).

A (GM) symbol in bold text following the last sentence of an IOSA provision indicates the existence of associated guidance material. (Guidance Material is addressed in [subsection 6](#) below.)

A ► symbol at the end of an individual standard or recommended practice in [Section 1 \(ORG\)](#) indicates the specific provision is repeated almost verbatim in one or more of the other seven sections of the ISM.

A ◀ symbol at the end of a provision in [Sections 2–8](#) indicates the specific provision is also contained in [Section 1 \(ORG\)](#) and has been repeated almost verbatim.

A ▲ symbol is the identifier for a paragraph that immediately follows a provision and designates the provision as eligible for the application of Active Implementation. (Active Implementation is addressed in [subsection 7](#) below.)

Special Review Suspension

IATA, upon request from an appropriate industry source, may subject the technical specifications within an IOSA standard to a special review in accordance with the IOSA Standards Special Review Process. Such process is defined in Section 1 of the IOSA Program Manual (IPM).

When a special review is conducted, the IOSA standard or certain sub-specifications within the IOSA standard are put under suspension until the special review has been completed.

When a new edition of the ISM is published while a special review is in progress, the suspended IOSA standard or sub-specification(s) within the IOSA standard will be identified with either of the following, as appropriate:

- ***(This standard is currently suspended in accordance with the IOSA Standards Special Review Process),*** or
- ***(This sub-specification is currently suspended in accordance with the IOSA Standards Special Review Process).***

6 Guidance Material

Guidance material is informational in nature and supplements or clarifies the meaning or intent of certain ISARPs. ISARPs that are self-explanatory do not have associated guidance material.

Guidance material is designed to ensure a common interpretation of specifications in ISARPs and provide additional detail that assists an operator to understand what is required in order to achieve conformity. Where applicable, guidance material also presents examples of acceptable alternative means of achieving conformity.

Guidance material associated with an individual standard or recommended practice is co-located with the relevant provision and is preceded by the bold sub-heading **Guidance**.

Additionally, some guidance material relates to an entire ISM section or to a specific grouping of provisions within a section. Such guidance stands alone in an appropriate location and is preceded by the bold heading **General Guidance**.

Audit specifications are contained only in the ISARPs, and never in the guidance material.

7 Operational Audit

During an audit, an operator is assessed against the ISARPs contained in this manual. To determine conformity with any standard or recommended practice, an auditor will gather evidence to assess the degree to which specifications are *documented* and *implemented* by the operator. In making such an assessment, the following information is applicable.

Documented

Documented shall mean the specifications in the ISARPs are published and accurately represented by an operator in a controlled document. A controlled document is subject to processes that provide for positive control of content, revision, publication, distribution, availability and retention.

Documentation is necessary for an operator to ensure systems, programs, policies, processes, procedures and plans are implemented in a standardized manner, and to further ensure such standardized implementation is sustained on an on-going basis. Documentation provides the standards that govern the way personnel perform tasks within the management system and in operations. Such documented standards are necessary for an operator to:

- Provide continuity in the flow of information to personnel;
- Ensure personnel are properly trained;
- Conduct evaluations (e.g. audits, inspections, performance assessments).

Implemented

△ *Implemented* shall mean the specification(s) in the ISARPs are established, activated, integrated, incorporated, deployed, installed, maintained and/or made available, as part of the operational system, and is (are) monitored and evaluated, as necessary, to ensure the desired outcome is being achieved.

The continuity of implementation is directly linked to documentation. To ensure standardization within the management system and in the conduct of operations, an operator must ensure specified systems, programs, policies, processes, procedures and plans are implemented as published in its controlled documents.

The requirement for specifications to be documented and implemented by an operator is inherent in ISARPs unless indicated otherwise.

Mandatory Observations

Mandatory Observations are conducted during an Audit as a means for collecting evidence that may, or may not, complement factual evidence that has already been (or will be) collected during the course of the Audit. These observations are normally conducted using checklists supplied by IATA, which are attached to the ISM as an Appendix. The applicability and use of the MO checklists is described in the IPM and the IAH.

Inactive Approved Operations

It is not unusual for an operator to elect not to conduct certain types of operations for which it has regulatory approval (e.g. transport of dangerous goods). In such cases, IOSA provisions with specifications that address such inactive operations would not be applicable to the operator during an Audit *if it is stated clearly in a controlled document (e.g. Operations Manual) that the specified operations are not conducted by the operator.*

Outsourced Operational Functions

Where an operator has chosen to outsource operational functions specified in IOSA provisions to external service providers, conformity with those provisions will be based on evidence provided by the operator that demonstrates acceptable processes are in place (i.e. processes that are documented and implemented) for monitoring such external service providers to ensure fulfillment of applicable operator and regulatory requirements affecting the safety and security of operations. Auditing is recommended as an effective method for an operator to monitor external service providers.

Active Implementation (AI)

- △ Certain ISARPs may be designated as eligible for the application of Active Implementation (AI), which is a concept that permits an operator to be in conformity with a standard based on a demonstration of active and real progress toward completion of an acceptable Implementation Action Plan (IAP). Provisions eligible for AI are identified by a ▲ symbol (see **Notes and Symbols** above).

An acceptable IAP defines and maps out the satisfaction of all requirements for an operator to achieve conformity with the designated IOSA Standard. As a minimum, an acceptable IAP shall specify:

- A detailed schedule of all work or activities necessary to complete the IAP;
- The equipment, components, material or other physical resources necessary to complete the IAP;
- A series of milestone dates against which progress toward completion of the plan can be measured;
- A date when the plan is projected to be completed.

Designation of any IOSA Standard for the application of AI will always be predicated on an up-front risk analysis that indicates application of AI would not pose an unacceptable safety risk. Additionally, such designation may include prerequisite conditions that must be satisfied by an operator in order to be eligible for AI.

An IOSA Standard that has been designated for application of AI will be clearly identified in this manual, along with prerequisite conditions, if any.

To conform to a standard based on AI, an operator must be able to provide evidence that execution of an acceptable IAP is underway and material or physical progress toward completion of the plan is consistent with the planned schedule, as measured against published milestones. If applicable, an operator must also demonstrate satisfaction of any associated prerequisite conditions.

An operator that provides only an IAP without other demonstrable evidence of having materially or physically begun execution of the plan does not meet the criteria for conformance based on AI.

8 Safety Management System (SMS)

The components and elements of an SMS for air operators are published in the ICAO Framework for Safety Management Systems (SMS) as published in ICAO in Annex 19. Guidance supporting the Framework may be found in the ICAO Safety Management Manual (SMM), Doc 9859. All SMS components and elements contained in the ICAO Framework are addressed in the ISARPs.

Specific SMS requirements for an operator will always be mandated by the State in accordance with its individual State Safety Plan (SSP).

- △ SMS standards and recommended practices are identified by a bold **[SMS]** symbol immediately following the last sentence of the provision. An operator that is audited and found to be in conformity with all *standards* (not recommended practices) identified by the [SMS] symbol is considered to have a *baseline SMS* in place.

Such baseline SMS might not meet the SMS requirements of all states because certain states, in accordance with their individual SSP, could add requirements above those contained in the ICAO framework.

Additionally, some states might mandate operators to implement SMS using a multi-phase approach. In either case, having the basic SMS elements implemented in accordance with the IOSA standards should facilitate compliance with individual state SMS requirements.

Note: The term *safety* as used in the ISM includes the management of both safety and/or security risks that have the potential to affect aircraft operations.

9 IOSA Documentation System

The ISM is used in association with the following related manuals:

- [IOSA Program Manual \(IPM\)](#);
- [IATA Reference Manual for Audit Programs \(IRM\)](#);
- [IOSA Audit Handbook \(IAH\)](#).

The IPM, ISM, IRM and IAH comprise the IOSA documentation system.

10 English Language

English is the official language of the IOSA Program; documents comprising the IOSA Documentation System are written in International English* in accordance with IATA policy.

The IPM requires auditors to ensure the English language version of this ISM and/or IOSA Checklists is always used as the basis for a final determination of conformity or nonconformity with ISARPs during the conduct of an audit. Versions of the ISM or IOSA Checklists that have been translated into another language are subject to misinterpretation; therefore, any translated IOSA document is considered an unofficial reference.

* Refer to the IRM for the definition of *International English*.

* The official reference for International English in accordance with IATA policy is the online Merriam-Webster Dictionary (<http://www.merriam-webster.com>).

11 Manual Revisions

Revisions to the ISM are developed and issued in accordance with the IOSA Standards Change Management process, which is published in the IOSA Program Manual (IPM).

The ISM is normally revised annually. In accordance with IATA policy, a revision to the ISM (other than a temporary revision) will always result in a new *edition* of the ISM.

The time period between the issuance of a new edition of the ISM and the effective date of such new edition is typically four full months.

Should critical issues arise that affect the content of the ISM, a temporary revision (TR) will be issued.

⊗

12 Modification Status

All changes in this document are listed in the revision highlights table. For easier orientation, the following symbols identify any changes made within each section:

- Addition of a new item.
- △ Change to an item.
- ⊗ Deletion of an item.

13 Conflicting Information

IOSA Documentation System

Manuals within the IOSA documentation system are not revised concurrently, thus creating the potential for conflicting information in different IOSA manuals. If there are inconsistencies between the IOSA documentation, namely the ISM, IPM and IAH, IATA should be contacted for clarification and correction.

IATA Dangerous Goods Regulations (DGR)

The DGR is a manual that is published annually and is effective on 1 January of each calendar year. The ISM is published in April of each calendar year, which creates the potential for conflicting DGR-ISM requirements. In the case of a DGR-ISM conflict, the requirement contained in the current effective version of the DGR shall be considered valid.

14 Definitions and Abbreviations

The IATA Reference Manual for Audit Programs (IRM) contains the Glossary of Terms and the List of Abbreviations that are associated with the IOSA program.

15 IOSA Documents and Forms

IOSA documents and forms that are referenced in this manual are available for download on the IOSA website (<http://www.iata.org/iosa>).

16 Authority

The IOSA Program operates under the authority of the IATA Operations Committee (OPC) with reference to the IATA Board of Governors (BoG).

Section 1 — Organization and Management System (ORG)

Applicability

[Section 1](#) addresses the organization and management system of an operator for the purpose of ensuring the safety and security of aircraft operations.

Individual ORG provisions or sub-specifications within an ORG provision that:

- Do not begin with a conditional phrase are applicable to all operators unless determined otherwise by the Auditor.
- Begin with a conditional phrase (“If the Operator...”) are applicable if the operator meets the condition(s) stated in the phrase.

Many IOSA standards and recommended practices in this [Section 1](#) (ORG ISARPs) are repeated in one or more other sections of the ISM (as indicated by the ► symbol). Refer to the IOSA Audit Handbook for information relevant to the proper internal auditing of repeated ORG ISARPs.

[ORG 3.4.6](#) in this section is applicable only to an operator that is currently on the IOSA Registry and is being audited for the purpose of registration renewal.

General Guidance

Definitions of technical terms used in this ISM [Section 1](#), as well as the meaning of abbreviations and acronyms, are found in the IATA Reference Manual for Audit Programs (IRM).

1 Management and Control

1.1 Management System Overview

ORG 1.1.1

The Operator shall have a management system that has continuity throughout the organization and ensures control of operations and management of safety and security outcomes. (GM) ►

Auditor Actions

- ☐ **Identified/Assessed** organizational management system structure.
- ☐ **Assessed** status of conformity with all other ORG management system ISARPs.
- ☐ **Coordinated** to verify status of conformity with management system ISARPs in all operational areas.
- ☐ **Other Actions** (Specify)

Guidance

Refer to the IRM for the definitions of [Operations](#), [Operator](#), [Safety \(Operational\)](#), [Security \(Aviation\)](#) and [State](#).

A management system is documented in controlled company media at both the corporate and operational levels. Manuals or controlled electronic media are acceptable means of documenting the management system.

Documentation provides a comprehensive description of the scope, structure and functionality of the management system and depicts lines of accountability throughout the organization, as well as authorities, duties, responsibilities and the interrelation of functions and activities within the system for ensuring safe and secure operations.

Acceptable means of documentation include, but are not limited to, organograms (organization charts), job descriptions and other descriptive written material that define and clearly delineate the management system.

Documentation also reflects a functional continuity within the management system that ensures the entire organization works as a system and not as a group of independent or fragmented units (i.e., silo effect).

An effective management system is fully implemented and functional with a clear consistency and unity of purpose between corporate management and management in the operational areas.

The management system ensures compliance with all applicable standards and regulatory requirements. In addition to internal standards and regulations of the State, an operator may also be required to comply with authorities that have jurisdiction over operations that are conducted over the high seas or within a foreign country.

ORG 1.1.3

The Operator shall identify one senior management official as the accountable executive (AE) who is accountable for performance of the management system as specified in [ORG 1.1.1](#) and:

- (i) Irrespective of other functions, is accountable on behalf of the Operator for the implementation and maintenance of the safety management system (SMS) throughout the organization;
- (ii) Has the authority to ensure the planning and allocation of resources necessary to manage safety and security risks to aircraft operations;
- (iii) Has overall accountability for ensuring operations are conducted in accordance with conditions and restrictions of the Air Operator Certificate (AOC), and in compliance with applicable regulations and standards of the Operator. **[SMS] (GM)**

Auditor Actions

- ☐ **Identified** senior management official designated as the AE for the conduct of operations.
- ☐ **Examined** management system structure and organizational lines of accountability.
- ☐ **Examined** job description of designated AE (focus: accountability/responsibilities are as specified in the standard).
- ☐ **Interviewed** AE and/or designated management representative(s).
- ☐ **Other Actions** (Specify)

Guidance

Refer to the IRM for the definitions of [Accountability](#), [Accountable Executive \(AE\)](#), [Authority](#), [Aircraft Operations](#), [Responsibility](#), [Safety Risk Management](#) and [Senior Management](#).

The requirement for an AE is an element of the Safety Policy and Objectives component of the SMS framework.

The designation of an AE means the accountability for operational quality, safety and security performance is placed at a level in the organization having the authority to take action to ensure the management system is effective. Therefore, the AE is typically the chief executive officer (CEO), although, depending on the type and structure of the organization, it could be a different senior official (e.g. chairperson/member of the board of directors, company owner).

The AE has the authority, which includes financial control, to make policy decisions, provide adequate human and physical resources, resolve operational quality, safety and security issues and, in general, ensure necessary system components are in place and functioning properly.

In terms of resources, the AE would have the overall responsibility for ensuring, not only adequate numbers of personnel, but also that positions within the SMS are filled by personnel in accordance with [ORG 1.6.2](#). Additionally, the AE would be responsible for ensuring the SMS is provided with adequate facilities, workspace equipment and supporting services as specified in [ORG 1.6.1](#).

In an SMS, the AE would typically have:

- Ultimate responsibility and accountability for the safety of the entire operation together with the implementation and maintenance of the SMS;
- Responsibility for ensuring the SMS is properly implemented in all areas of the organization and performing in accordance with specified requirements.

The AE also is responsible for ensuring the organization is in compliance with requirements of applicable authorities (i.e. regulations), as well as its own policies and procedures, which may exceed existing regulations or address areas that are not regulated (e.g. ground handling operations). An operator's policies and procedures are typically published in its Operations Manual (OM).

To ensure that the operator continues to meet applicable requirements, the AE might designate a manager with the responsibility for monitoring compliance. The role of such manager would be to ensure that the activities of the operator are monitored for compliance with the applicable regulatory requirements, as well as any additional requirements as established by the operator, and that these activities are being carried out properly under the supervision of the relevant head of functional area. Expanded guidance may be found in the ICAO SMM, Document 9859.

Safety Management System

1.2 Management Commitment

1.3 Accountability, Authorities and Responsibilities



ORG 1.3.2

The Operator shall have a process or procedure for the delegation of duties within the management system that ensures managerial continuity is maintained when operational managers including, if applicable, post holders are unable to carry out work duties. **(GM) ►**

Auditor Actions



- ☐ **Identified/Assessed** processes for management system delegation of duties (focus: processes maintain managerial continuity during periods when corporate/operational managers are unable to perform work duties).
- ☐ **Interviewed** AE and/or designated management representative(s).
- ☐ **Coordinated** to verify processes for management system delegation of duties in all operational areas.
- ☐ **Examined** example(s) of delegation of duties when managers have been unable to perform work duties.
- ☐ **Other Actions** (Specify)



Guidance



The intent of this provision is for an operator to have a process or procedure that ensures a specific person (or perhaps more than one person) is identified to assume the duties of any operational manager that is or is expected to be, unable to accomplish assigned work duties. An operator may have nominated deputies in place or a process for ensuring the appointment of a temporary replacement.



For the purpose of this provision, the use of telecommuting technology and/or being on call and continually contactable are acceptable means for operational managers to remain available and capable of carrying out assigned work duties.

A notification of such delegation of duties may be communicated throughout the management system using email or other suitable communication medium.

1.4 Communication

ORG 1.4.2

The Operator shall have processes for the communication of safety information throughout the organization to ensure personnel maintain an awareness of operational safety management. **[SMS] (GM)**

Auditor Actions

- ❑ **Identified/Assessed** corporate communication system (focus: organizational capability for communicating safety information to personnel; information stresses SMS awareness/operational safety issues).
- ❑ **Interviewed** AE and/or designated management representative(s).
- ❑ **Interviewed** selected management system personnel.
- ❑ **Observed** examples of safety information communication.
- ❑ **Coordinated** to verify communication of safety information in all operational areas.
- ❑ **Other Actions** (Specify)

Guidance

Safety communication is an element of the Safety Promotion component of the SMS framework.

The general intent of safety communication is to foster a positive safety culture in which all employees receive ongoing information on safety issues, safety metrics, specific hazards existing in the workplace, and initiatives to address known safety issues. Such communication typically conveys safety-critical information, explains why particular actions are taken to improve safety, and why safety procedures are introduced or changed.

Information and issues relevant to safety performance are typically derived from various sources such as, but not limited to, the quality assurance/flight safety analysis programs, operational safety reporting and accident/incident investigations.

Expanded guidance may be found in the ICAO SMM, Document 9859.

1.5 Management Review**1.6 Provision of Resources****ORG 1.6.3**

The Operator shall ensure personnel who perform functions relevant to the safety or security of aircraft operations are required to maintain competence on the basis of continued education and training and, if applicable for a specified position, continue to satisfy any mandatory technical competency requirements. **(GM)**

Auditor Actions

- ❑ **Identified/Assessed** standards/processes for maintaining competency of personnel in functions relevant to safety/security of aircraft operations (focus: standards specify continuing education/training, meeting technical requirements).
- ❑ **Interviewed** AE and/or designated management representative(s).
- ❑ **Coordinated** to verify application of competency standards.
- ❑ **Other Actions** (Specify)

Guidance

Positions or functions within an airline organization considered “operationally critical” are those that have the potential to affect operational safety or security. This definition includes management positions and any positions or functions that may affect the airworthiness of aircraft.

Typically, training programs are implemented to ensure personnel throughout the organization are qualified and competent to perform individual duties.

Some management positions within airline operations may require an individual to maintain a technical competency as a requirement for being assigned to the position. For example, it may be specified that certain management positions within Flight Operations may only be filled by individuals who are qualified flight crew members. Similar situations could exist within Cabin Operations, Engineering and Maintenance or other operational disciplines.

In such cases, the job description specifies the requirement for maintaining technical competency, and adequate opportunity is provided to fulfill the requirement.

1.7 Effectiveness Implementation



ORG 1.7.1

The Operator *should* demonstrate that systems, processes and procedures specified by the ISARPs identified with the **[Eff]** symbol are achieving the designated Desired Outcome.

Note: *Conformity with this ORG recommended practice is possible only when the Operator demonstrates effectiveness of implementation for all ISARPs designated with the **[Eff]** symbol.*

1.8 Operational Planning

2 Documentation and Records

2.1 Documentation System

2.2 Records System

3 Safety Management

3.1 Safety Risk Management

ORG 3.1.1

The Operator shall have a hazard identification program that is implemented and integrated throughout the organization, to include:

- (i) A combination of reactive and proactive methods of hazard identification;
- (ii) Processes for safety data analysis that identify existing hazards, and may predict future hazards, to aircraft operations. **[SMS] (GM) ►**

Note: *Conformity with this ORG standard is possible only when the Operator is in conformity with all repeats of this ORG standard in other ISM sections. Refer to the IAH for information that identifies such repeats.*

Auditor Actions

- ☐ **Identified/Assessed** organizational safety hazard identification program (focus: program identifies hazards to aircraft operations; describes/defines method(s) of safety data collection/analysis).
- ☐ **Identified/Assessed** cross-discipline process for safety hazard identification (focus: all operational disciplines participate in process).
- ☐ **Interviewed** SMS manager and/or designated management representative(s).
- ☐ **Examined** selected records/documents that illustrate organizational integration (focus: coordinated involvement of all operational disciplines in hazard identification process).
- ☐ **Examined** selected examples of hazards identified through data collection/analysis.
- ☐ **Coordinated** to verify implementation of safety hazard identification program in all operational areas.
- ☐ **Other Actions** (Specify)

Guidance

Refer to the IRM for the definitions of [Hazard \(Aircraft Operations\)](#) and [Safety Risk](#).

Hazard identification is an element of the Safety Risk Management component of the SMS framework.

The methods used to identify hazards will typically depend on the resources and constraints of each particular organization. Some organizations might deploy comprehensive, technology-intensive hazard identification processes, while organizations with smaller, less complex operations might implement more modest hazard identification processes. Regardless of organizational size or

complexity, to ensure all hazards are identified to the extent possible, hazard identification processes are necessarily formalized, coordinated and consistently applied on an on-going basis in all areas of the organization where there is a potential for hazards that could affect aircraft operations.

To be effective, reactive and proactive processes are used to acquire information and data, which are then analyzed to identify existing or predict future (i.e. potential) hazards to aircraft operations.

Examples of processes that typically yield information or data for hazard identification include:

- Confidential or other reporting by personnel;
- Investigation of accidents, incidents, irregularities and other non-normal events;
- Flight data analysis;
- Observation of flight crew performance in line operations and training;
- Quality assurance and/or safety auditing;
- Safety information gathering or exchange (external sources).

Processes would be designed to identify hazards that might be associated with organizational business changes (e.g. addition of new routes or destinations, acquisition of new aircraft type(s), the introduction of significant outsourcing of operational functions).

Typically, hazards are assigned a tracking number and recorded in a log or database. Each log or database entry would normally include a description of the hazard, as well as other information necessary to track associated risk assessment and mitigation activities.

Expanded guidance may be found in the ICAO SMM, Document 9859.



ORG 3.1.2

The Operator shall have a safety risk assessment and mitigation program that includes processes implemented and integrated throughout the organization to ensure:

- (i) Hazards are analyzed to determine corresponding safety risks to aircraft operations;
- (ii) Safety risks are assessed to determine the requirement for risk mitigation action(s);
- (iii) When required, risk mitigation actions are developed and implemented in operations.

[SMS] [Eff] (GM) ►

Note: *Conformity with this ORG standard is possible only when the Operator is in conformity with all repeats of this ORG standard in other ISM sections. Refer to the IAH for information that identifies such repeats.*

Assessment Tool

Desired Outcome

The Operator maintains an overview of its operational risks and through implementation of mitigation actions, as applicable, ensures risks are at an acceptable level.

Suitability Criteria (Suitable to the size, complexity and nature of operations)

Number and type of analyzed hazards and corresponding risks.

Means used for recording risks and mitigation (control) actions.

Safety data used for the identification of hazards.

Effectiveness Criteria

(i) All relevant hazards are analyzed for corresponding safety risks.

(ii) Safety risks are expressed in at least the following components:

- Likelihood of an occurrence.
- Severity of the consequence of an occurrence.
- Likelihood and severity have clear criteria assigned.

(iii) A matrix quantifies safety risk tolerability to ensure standardization and consistency in the risk assessment process which is based on clear criteria.

- (iv) Risk register(s) across the organization capture risk assessment information, risk mitigation (control) and monitoring actions.
- (v) The risk mitigation (control) actions include time lines, allocation of responsibilities and risk control strategies such as hazard elimination, risk avoidance, risk acceptance, risk mitigation.
- (vi) Mitigation (control) actions are implemented to reduce the risk to a level of - as low as reasonably practical.
- (vii) Identified risks and mitigation actions are regularly reviewed for accuracy and relevance.
- (viii) Effectiveness of risk mitigation (control) actions are monitored at least yearly to include auditing in accordance with [ORG 3.4.1](#).
- (ix) Personnel performing risk assessments are appropriately trained in accordance with [ORG 1.6.5](#).
- (x) The program takes into consideration any area of the organization where there is a potential for hazards that could affect aircraft operations.
- (xi) The program has some form of central coordination to ensure all existing or potential hazards that have been identified as relevant are subjected to risk assessment and, if applicable, mitigation.

Auditor Actions

- ☐ **Identified/Assessed** organizational safety risk assessment/mitigation program (focus: hazards analyzed to identify/define risk; risk assessed to determine appropriate action; action implemented/monitored to mitigate risk).
- ☐ **Identified/Assessed** cross-discipline process for risk assessment/mitigation (focus: all operational disciplines participate in process).
- ☐ **Interviewed** SMS manager and/or designated management representative(s).
- ☐ **Examined** selected records/documents that illustrate organizational integration (focus: coordinated involvement of all operational disciplines in risk assessment/mitigation program).
- ☐ **Examined** selected examples of risk assessment/risk mitigation action(s).
- ☐ **Coordinated** to verify implementation of safety risk assessment/mitigation in all operational areas.
- ☐ **Other Actions** (Specify)

Guidance

Refer to the IRM for the definition of [Safety Risk Assessment \(SRA\)](#).

Risk assessment and mitigation is an element of the Safety Risk Management component of the SMS framework.

To be completely effective, a risk assessment and mitigation program would typically be implemented in a manner that:

- Is active in all areas of the organization where there is a potential for hazards that could affect aircraft operations;
- Has some form of central coordination to ensure all existing or potential hazards that have been identified are subjected to risk assessment and, if applicable, mitigation.

The safety risks associated with an identified existing or potential hazard are assessed in the context of the potentially damaging consequences related to the hazard. Safety risks are generally expressed in two components:

- Likelihood of an occurrence;
- Severity of the consequence of an occurrence.

Typically, matrices that quantify safety risk acceptance levels are developed to ensure standardization and consistency in the risk assessment process. Separate matrices with different risk acceptance criteria are sometimes utilized to address long-term versus short-term operations.

A risk register is often employed for the purpose of documenting risk assessment information and monitoring risk mitigation (control) actions.

Expanded guidance may be found in the ICAO SMM, Document 9859.

Operational Reporting

ORG 3.1.3

The Operator shall have an operational safety reporting system that is implemented throughout the organization in a manner that:

- (i) Encourages and facilitates personnel to submit reports that identify safety hazards, expose safety deficiencies and raise safety concerns;
- (ii) Ensures mandatory reporting in accordance with applicable regulations;
- (iii) Includes analysis and management action as necessary to address safety issues identified through the reporting system. **[SMS] (GM) ►**

Note: *Conformity with this ORG standard is possible only when the Operator is in conformity with all repeats of this ORG standard in other ISM sections. Refer to the IAH for information that identifies such repeats.*

Auditor Actions

- ☐ **Identified/Assessed** organizational operational safety reporting system (focus: system urges/facilitates reporting of hazards/safety concerns; includes analysis/action to validate/address reported hazards/safety concerns).
- ☐ **Interviewed** SMS manager and/or designated management representative(s).
- ☐ **Examined** records of selected operational/safety reports (focus: analysis/follow-up to identify/address reported hazards/safety concerns).
- ☐ **Coordinated** to verify implementation of operational safety reporting system in all operational areas.
- ☐ **Other Actions** (Specify)

Guidance

Safety reporting is a key aspect of SMS hazard identification and risk management.

Frontline personnel, such as flight or cabin crew members and maintenance technicians, are exposed to hazards and face challenging situations as part of their everyday activities. An operational reporting system provides such personnel with a means to report these hazards or any other safety concerns so they may be brought to the attention of relevant managers.

To build confidence in the reporting process and encourage more reporting, an acknowledgement of receipt is typically provided to each person that submits a report.

An effective system provides for a review and analysis of each report to determine whether a real safety issue exists, and if so, ensure development and implementation of appropriate action by responsible management to correct the situation.

Expanded guidance may be found in the ICAO SMM, Document 9859.

3.2 Safety Assurance

ORG 3.2.2

The Operator shall have a process to identify changes within or external to the organization that have the potential to affect the level of safety risks associated with aircraft operations, and to manage risks that may arise from or are affected by such changes in accordance with [ORG 3.1.1](#) and [ORG 3.1.2](#). **[SMS] (GM)**

Auditor Actions

- ☐ **Identified/Assessed** organizational change management process (focus: process identifies/assesses internal/external changes to determine operational safety risk).
- ☐ **Interviewed** SMS manager and/or designated management representative(s).
- ☐ **Examined** selected records/documents that show processing of internal/external changes (focus: assessment of changes to determine safety risk; actions taken to implement/revise new/existing risk controls).

- ☐ **Coordinated** to verify implementation of change management process in all operational areas.
- ☐ **Other Actions** (Specify)

Guidance

Refer to the IRM for the definition of [Change Management](#).

Change management is an element of the Safety Assurance component of the SMS framework and is considered a proactive hazard identification activity in an SMS.

Safety risk management requires an operator to have a formal process to identify hazards that may affect aircraft operations. Hazards may exist in ongoing aircraft operations or be inadvertently introduced whenever internal or external changes occur that could affect aircraft operations. In such cases, hazard identification as specified in [ORG 3.1.1](#) and safety risk assessment and mitigation as specified in [ORG 3.1.2](#) (both are repeated in other ISM sections) are integral elements of an operator's change management process.

A change management process is normally designed to ensure risk management is applied to any internal or external change that has the potential to affect an operator's established operational processes, procedures, products, equipment and services. The change management process typically takes into account the following three considerations:

- **Criticality.** Criticality assessments determine the systems, equipment or activities that are essential to the safe operation of aircraft. While criticality is normally assessed during the system design process, it is also relevant during a situation of change. Systems, equipment and activities that have higher safety criticality are reviewed following change to make sure that corrective actions can be taken to control potentially emerging safety risks.
- **Stability of systems and operational environments.** Changes might be planned and under the direct control of the operator. Examples of such changes include organizational growth or contraction, the expansion of products or services delivered, or the introduction of new technologies. Changes might also be unplanned and external to the operator, such as changing economic cycles, labor unrest and changes to the political, regulatory or operating environments.
- **Past performance.** Past performance of critical systems and trend analyses in the safety assurance process is typically employed to anticipate and monitor safety performance under situations of change. The monitoring of past performance will also assure the effectiveness of corrective actions taken to address safety deficiencies identified as a result of audits, evaluations, investigations or reports.

Expanded guidance may be found in the ICAO SMM, Document 9859.

3.3 Flight Safety Analysis Program

Program Elements

ORG 3.3.11

The Operator shall have a process for identifying and investigating irregularities and other non-routine operational occurrences that might be precursors to an aircraft accident or incident.

[SMS] (GM)

Auditor Actions

- ☐ **Identified/Assessed** process for identification/investigation of irregularities/non-routine occurrences (focus: process output includes final report with recommendations).
- ☐ **Interviewed** responsible manager(s).
- ☐ **Examined** selected irregularity/non-routine occurrence reports (focus: process identifies operational safety hazards, produces recommendations to mitigate risk).
- ☐ **Other Actions** (Specify)

Guidance

Investigation of operational irregularities is considered a *reactive* hazard identification activity in an SMS.

A primary purpose of investigating non-routine operational occurrences is hazard identification, which is an element of the Safety Risk Management component of the SMS framework.

The investigation of irregularities or non-routine occurrences is a hazard identification activity. Minor events, irregularities and occurrences occur often during normal operations, many times without noticeable consequences. Identifying and investigating certain irregular operational occurrences can reveal system weaknesses or deficiencies that, if left un-checked, could eventually lead to an accident or serious incident. These types of events are referred to as accident *precursors*.

A process to monitor operations on a regular basis permits the identification and capture of information associated with internal activities and events that could be considered precursors. Such events are then investigated to identify undesirable trends and determine contributory factors.

The monitoring process is typically not limited to occurrences, but also includes a regular review of operational threats and errors that have manifested during normal operations. Monitoring of normal operations can produce data that further serve to identify operational weaknesses and, in turn, assist the organization in developing system solutions.

As with the investigation of accidents and serious incidents, the investigation of minor internal occurrences results in a report that is communicated to relevant operational managers for analysis and the possible development of corrective or preventive action.

Expanded guidance may be found in the ICAO SMM, Document 9859.



ORG 3.3.13

If the Operator conducts flights with aircraft of a maximum certified takeoff mass in excess of 27,000 kg (59,525 lb), the Operator shall have a flight data analysis (FDA) program applicable to such aircraft that is non-punitive and contains adequate safeguards to protect data sources. The FDA program shall include either:

- (i) A systematic download and analysis of electronically recorded aircraft flight data, or
- (ii) A systematic acquisition, correlation and analysis of flight information derived from a combination of some or all of the following sources:
 - (a) Aircraft flight data recorder (FDR) readouts;
 - (b) Confidential flight and cabin crew operational safety reports;
 - (c) Flight and cabin crew interviews;
 - (d) Quality assurance findings;
 - (e) Flight and cabin crew evaluation reports;
 - (f) Aircraft engineering and maintenance reports. **[PCO] [SMS] [Eff] (GM)**

Note: Item ii) is a Parallel Conformity Option (PCO) for item i); in effect until 31 August 2022.

Note: Effective 1 September 2022, **ORG 3.3.13** will be eliminated and replaced by the standards located in **ORG sub-section 3.7**.

Assessment Tool

Desired Outcome

Hazards arising from aircraft operations are systematically identified for all aircraft types based on the analysis of electronically recorded flight data which results in a statistical reliability level of at least 90%. Identified hazards are analyzed for corresponding risks and actions are taken in a timely manner to address any issues resulting from the FDA program.

Suitability Criteria (Suitable to the size, complexity and nature of operations)

Means for collecting data.

Type and completeness of data.

Safety data used for the identification of hazards.

Effectiveness Criteria

- (i) FDA program is based on electronically downloaded flight data.
- (ii) All aircraft above 27t within the operator's fleet are analyzed.
- (iii) FDA staff are specifically trained and qualified for their duties.
- (iv) Analysis of data is performed without undue delay and on a regular basis.
- (v) Relevant hazards and risks are acted upon with actions/measures.
- (vi) Relevant hazards are fed into the overall hazard identification and risk assessment program.
- (vii) All relevant data is summarized and provided to crews on a regular basis.
- (viii) Corrective or remedial actions are taken in a constructive and non-punitive manner.
- (ix) Corrective or remedial actions are continuously monitored for effectiveness.

Auditor Actions

- ☐ **Option 1:** Applicable to ([ORG 3.3.13 i](#))
- ☐ **Identified/Assessed** flight data analysis (FDA) program (focus: download/analysis of recorded flight data; defined criteria for non-discipline; identification of existing/potential flight safety hazards; production of recommendations to mitigate risk).
- ☐ **Interviewed** responsible manager(s).
- ☐ **Interviewed** FDA analyst(s).
- ☐ **Observed** FDA resources and activities.
- ☐ **Examined** selected FDA program data/reports (focus: analysis of data; identification of flight safety hazards; recommendations to mitigate risk).
- ☐ **Other Actions** (Specify)
- ☐ **Option 2:** Applicable to ([ORG 3.3.13 ii](#))
- ☐ **Identified/Assessed** flight data analysis (FDA) program (focus: acquisition/correlation/analysis of flight information; defined criteria for non-discipline; identification of existing/potential flight safety hazards; production of recommendations to mitigate risk).
- ☐ **Interviewed** responsible manager(s).
- ☐ **Interviewed** FDA analyst(s).
- ☐ **Observed** FDA resources and activities.
- ☐ **Examined** selected FDA program data and reports (focus: analysis of information; identification of flight safety hazards; recommendations to mitigate risk).
- ☐ **Crosschecked** to verify sources of FDA information in applicable operational areas.
- ☐ **Other Actions** (Specify)

Guidance

Refer to the IRM for the definitions of [Flight Data Analysis \(FDA\) Program](#) and [Parallel Conformity Option \(PCO\)](#).

Refer to the ISM Introduction for an expanded description of Parallel Conformity Option.

Flight data analysis is considered a *reactive* and *proactive* hazard identification activity in an SMS.

A primary purpose of an FDA program is hazard identification, which is an element of the Safety Risk Management component of the SMS framework.

The systematic download and analysis of recorded flight data has been used by international airlines for many years to identify hazards, evaluate the operational environment, validate operating criteria and establish training effectiveness.

Refer to the guidance associated with [ORG 3.7.1](#) for information that addresses a non-punitive environment (Just Culture).

As a minimum, an acceptable program for the analysis of recorded aircraft flight data includes the following elements:

- A manager and staff of flight operations experts, commensurate with the size of the operation, to provide verification and analysis of the data collected from the aircraft fleet under the operator's program;
- Aircraft designated within the operator's fleet that provide downloadable flight data from onboard recording systems, such as the flight data recorder (FDR) or quick access recorder (QAR);
- A system for downloading and transferring recorded data from the aircraft to a data analysis system;
- A data analysis system that transforms raw digital data into a usable form of information that can then be verified, processed, categorized and analyzed by flight operations experts for flight safety purposes;
- A process for applying the output from flight data analysis to the management of risk and assessment of flight operations performance;
- A process for management of the data, to include security and retention.

All or certain of the elements could be outsourced to an external party; however, the operator would retain overall responsibility for the maintenance of the program.

The most comprehensive approach to flight data analysis would be a program that includes not only systematic download and analysis of electronically recorded aircraft flight data (as described above), but also acquisition, correlation and analysis of flight information derived from other sources (as described below).

Where appropriate, there might be a formal agreement with applicable labor organizations to ensure a mutually acceptable and structured approach to the investigation of significant safety events identified through the FDA program.

Further guidance may be found in the ICAO Safety Management Manual (Doc 9859).

Parallel Conformity Option

If an operator does not have a process for the regular download and analysis of recorded flight data, then as an alternative the operator may have a systematic process for acquiring and correlating flight information from other sources that can be analyzed to identify hazards or potential hazards to flight.

Useful information can be derived from external sources to supplement flight data derived internally. Other such sources include:

- Regulatory authorities;
- Investigative bodies;
- Safety organizations;
- Manufacturers;
- Other operators.

Flight information is analyzed collectively to identify hazards, system weaknesses, process breakdowns, regulatory violations and other trends or conditions that could potentially lead to accidents or serious incidents. The process includes a method of risk analysis and prioritization to enable the development and implementation of effective corrective or preventive action.

3.4 Quality Assurance Program

ORG 3.4.1

The Operator shall have a quality assurance program that provides for the auditing of the management system of operations, and maintenance functions, to ensure the organization is:

- (i) Complying with applicable regulations and standards;
- (ii) Satisfying stated operational needs;
- (iii) Identifying areas requiring improvement;
- (iv) Identifying hazards to operations;
- (v) Assessing the effectiveness of safety risk controls. **[SMS] (GM) ►**

Note: If the quality assurance audit function is performed by an external organization, the Operator, as the AOC holder, shall be responsible for ensuring the quality assurance program is in conformity with the specifications of this provision.

Note: Conformity with this ORG standard is possible only when the Operator is in conformity with all repeats of this ORG standard in other ISM sections. Refer to the IAH for information that identifies such repeats.

Auditor Actions

- ☐ **Identified/Assessed** quality assurance program (focus: role/purpose within organization/SMS; definition of audit program scope/objectives; description of program elements/procedures for ongoing auditing of management system/operational areas).
- ☐ **Interviewed** SMS manager and/or designated management representative(s).
- ☐ **Interviewed** quality assurance program manager.
- ☐ **Interviewed** selected operational managers (focus: interface with quality assurance program).
- ☐ **Examined** selected audit reports (focus: audit scope/process/organizational interface).
- ☐ **Coordinated** to verify implementation of quality assurance audit program in all operational areas.
- ☐ **Other Actions** (Specify)

Guidance

Refer to the IRM for the definitions of [Audit](#), [Group Company](#) and [Quality Assurance](#).

The quality assurance program comprises two complementary functions: To monitor an operator's compliance with relevant regulations and standards, as well as to evaluate and continually improve operational safety performance. Such functions are elements of the Safety Assurance component of the SMS framework.

In some organizations the quality assurance program may have a different name (e.g. internal audit program, internal evaluation program).

In certain circumstances, an operator may have the quality assurance audit function performed by an external organization. This typically occurs when the operator is affiliated with one or more other organizations in a Group Company. However, an operator might also choose to simply outsource the quality assurance audit function to a qualified external service provider that is not part of or associated with a Group Company. In both cases, the operator, as the AOC holder, has the ultimate responsibility for ensuring the quality assurance program meets the needs of its organization in accordance with the specifications of this standard.

A robust quality assurance program ensures a scope of auditing that encompasses all areas of the organization that impact operational quality in terms of safety and/or security. Operational functions include flight operations, operational control/flight dispatch, maintenance operations, cabin operations, ground handling and cargo operations.

This provision is designed to permit flexibility in the implementation of the quality assurance program. The structure and organization of the program within an operator's management system, whether centralized, non-centralized or a combination thereof, is at the discretion of the operator in accordance with its corporate culture and regulatory environment.

An effective audit program includes:

- Audit initiation, including scope and objectives;
- Planning and preparation, including audit plan and checklist development;
- Observation and gathering of evidence to assess documentation and implementation;
- Analysis, findings, actions;
- Reporting and audit summary;
- Follow-up and close out.

To ensure auditors gather sufficient evidence to produce realistic assessments during an audit, the program typically includes guidance that defines the various sampling techniques that are expected to be used by auditors in the evidence collection phase of the audit.

The audit process typically includes a means whereby the auditor and responsible personnel from the audited area have a comprehensive discussion and reach agreement on the findings and corresponding corrective actions. Clear procedures are established to resolve any disagreement between the auditor and audited area.

All action items require follow-up to ensure closeout within an appropriate period of time.

ORG 3.4.3

The Operator shall have a process for addressing findings that result from audits conducted under the quality assurance program, which ensures:

- (i) Identification of root cause(s);
- (ii) Development of corrective action as appropriate to address findings;
- (iii) Implementation of corrective action in appropriate operational area(s);
- (iv) Evaluation of corrective action to determine effectiveness. **(GM) ►**

Auditor Actions

- ☐ **Identified/Assessed** process for addressing quality assurance audit findings.
- ☐ **Interviewed** quality assurance program manager.
- ☐ **Examined** selected audit reports/records (focus: identification of root cause, development/implementation of corrective action, follow-up to ensure effectiveness).
- ☐ **Coordinated** to verify implementation of audit findings process in all operational areas.
- ☐ **Other Actions** (Specify)

Guidance

Certain audit findings might fall under the category of hazards to operations. In such cases, the hazard would be subject to the risk assessment and mitigation process in the development of corrective action.

Refer to the IAH for information relevant to auditing under the quality assurance program.

△

ORG 3.4.6

If the Operator is on the IOSA Registry, the Operator shall ensure the quality assurance program as specified in [ORG 3.4.1](#) provides for the auditing of the IOSA Standards and Recommended Practices (ISARPs) a minimum of once during the IOSA registration period. For internal audits of the ISARPs, the Operator shall have processes that ensure:

- (i) The effective edition of the IOSA Standards Manual (ISM) is utilized;
- (ii) Auditor Actions are accomplished by auditors;
- (iii) Recording and retention of information associated with the internal audit of individual ISARPs as specified in [Table 1.2](#). **(GM)**

☐

Note: If a new edition of the ISM becomes effective during the first 19 months of the Operator's 24-month IOSA registration period, the Operator shall take into account all changes that might require additional auditing (e.g. new or significantly revised ISARPs).

Auditor Actions

- ☐ **Identified/Assessed** processes that ensure auditing of all ISARPs during the IOSA registration period.
- ☐ **Identified/Assessed** internal audit processes/procedures (focus: use of effective ISM edition; auditors accomplish Auditor Actions).
- ☐ **Interviewed** quality assurance program manager.
- ☐ **Interviewed** selected internal auditors.
- ☐ **Examined** selected records (database, procedural documents) of audits performed against ISARPs (focus: effective ISM edition used, all specified information included, Auditor Actions accomplished).
- ☐ **Other Actions** (Specify)

△

Guidance

Refer to the IRM for the definitions of [Auditor Actions](#), [IOSA Operator](#), [IOSA Registration Period](#) and [Registration Renewal Audit](#).

The currently effective edition of the ISM is used for auditing of the ISARPs during the first 19 months of the IOSA registration period. Use of an ISM edition that becomes effective in the final five (5) months of the operator's registration period is optional.

- ☐ The accomplishment of Auditor Actions as specified in item (ii) is necessary to ensure internal auditors gather the necessary evidence to determine whether (or not) a standard or recommended practice is documented and implemented by the operator.
 - ☐ [Table 1.2](#), as specified in item (iii), includes a note that refers to procedural documents. An example of a procedural document is an audit checklist in which all specified audit information associated with the audit of the individual ISARPs is recorded, including accomplishment of the Auditor Action steps.
 - ☐ IATA continues to provide a template in the form of a spreadsheet to record all required information as per [ORG 3.4.6](#) and [Table 1.2](#).
- To the extent possible, auditing of the ISARPs should be spread out over the full registration period rather than waiting to conduct all auditing just prior to the registration renewal audit.
- Refer to the IAH for information relevant to auditing of the ISARPs under the quality assurance program.

Program Elements

3.5 Quality Control of Outsourced Operations

ORG 3.5.2

The Operator shall have processes to monitor external service providers that conduct outsourced operational functions for the Operator to ensure requirements that affect the safety and/or security of operations are being fulfilled. **(GM)** ►

Note: *IOSA or ISAGO registration is acceptable as part of the Operator's monitoring process when such registration is included in or combined with a risk assessment of the provider.*

Auditor Actions

- ☐ **Identified/Assessed** processes for monitoring external service providers that conduct outsourced operational functions.
- ☐ **Interviewed** responsible manager(s).
- ☐ **Examined** selected records/reports resulting from monitoring of service providers (focus: monitoring process ensures provider is fulfilling applicable safety/security requirements).
- ☐ **Coordinated** to verify implementation of service provider monitoring in applicable operational areas.
- ☐ **Other Actions** (Specify)

Guidance

An operator has a responsibility to ensure outsourced operational functions are conducted in a manner that meets its own operational safety and security requirements. A monitoring process is necessary to satisfy that responsibility, and such process would be applicable to any external service provider that conducts outsourced operational functions, including the parent organization or a separate affiliate of the operator.

In some regulatory jurisdictions, there may be a regulatory control process that permits certain organizations to meet rigorous standards and become approved to conduct outsourced operations or maintenance for an operator. Such regulatory control process would be an acceptable means for meeting the specification of this provision if it can be demonstrated by the operator that the regulatory control process:

- Includes ongoing monitoring of the approved service providers;
- Such monitoring is sufficiently robust to ensure the approved service providers fulfill the operational requirements of the operator on a continuing basis.

Achieving and maintaining IOSA and/or ISAGO registration is a way for an external service provider to demonstrate fulfillment of requirements that affect the safety and/or security of operations. Thus, an operator's process that requires such service providers to maintain IOSA and/or ISAGO registration would be acceptable as a method of monitoring when such registration(s) is/are used in conjunction with a risk assessment of the provider.

To ensure effective monitoring, consideration is given to a range of internal and external methods for use in the oversight of external service providers. Methods might include auditing, systematic review and risk assessment of reported hazards and/or occurrences, monitoring of performance output (KPIs), reporting and governance processes; monitoring and analysis of targeted risk areas, as well as the establishment of an effective two-way communication link with the service provider.

Under certain circumstances, operational functions may be involuntarily removed from an operator and conducted by a governmental or quasi-governmental authority that is not under the control of the operator (e.g. passenger or baggage security screening at some airports). Under such circumstances, the operator would have a process to monitor output of the function being conducted by the authority to ascertain desired results are being achieved.

If an operator is part of a Group Company and has management and/or operational functions performed by an affiliate organization that is part of the same Group Company, an operator may demonstrate monitoring of the external organization by processes that ensure functions performed by the affiliate organization for the operator are:

- Subjected to auditing under the quality assurance program of the affiliate organization;
- Continually satisfying the needs of the operator.

△

ORG 3.5.4A

The Operator shall have a process to monitor the performance of other operators that transport its passengers under a commercial aviation agreement. Such monitoring process shall ensure the operational safety and security needs of the Operator are being fulfilled and be applicable to other operators under the following commercial aviation agreements:

- (i) Wet lease, ACMI lease and damp lease agreements;
- (ii) Code share agreements;
- (iii) Capacity purchase agreements. **[Eff] (GM)**

□

Note: The specifications of this standard shall be applicable to the Operator if it has transported its passengers on another operator under any of the specified commercial aviation agreements during the most recent IOSA registration period.

△

Note: IOSA registration is acceptable as part of the Operator's monitoring process when such registration is included in or combined with a risk assessment of the other operator(s).

□

Note: Effective 1 September 2021, **ORG 3.5.4A** will be eliminated and replaced by **ORG 3.5.4B**.

Assessment Tool

Desired Outcome

The Operator actively monitors the safety performance of other operators. The monitoring is commensurate to the scope of operations to be monitored. It is continuous and based on accurate and up-to-date information to ensure its requirements are fulfilled.

Suitability Criteria (Suitable to the size, complexity and nature of operations)

Type and length of contract/operation, routes, destinations.

Monitoring elements such as audits, surveys, occurrence reporting, investigations and studies.

Frequency of monitoring intervals.

Infrastructure, software and resources used to manage and record monitoring process.

Effectiveness Criteria

(i) Procurement standards are defined with specific requirements for wet lease, code share and CPA operators.

(ii) An assessment of an operator is made prior to first utilization.

(iii) Specific procedures and standards for active monitoring/assessment are in place.

(iv) Substandard performance of an operator is addressed and actions are taken.

Auditor Actions

- ☐ **Identified/Assessed** process for monitoring safety/security performance of external operators that transport passengers of the Operator.
- ☐ **Interviewed** responsible managers.
- ☐ **Examined** plan/methods for monitoring applicable other operators (focus: includes all operators that transport the operator's passengers under a commercial aviation agreement).
- ☐ **Examined** selected monitoring reports of other operators (focus: monitoring process ensures the other operator is fulfilling applicable safety/security requirements).
- ☐ **Other Actions** (Specify)

Guidance

Refer to the IRM for the definitions of [ACMI Lease Agreement](#), [Capacity Purchase Agreement \(CPA\)](#), [Code Share Agreement](#), [Damp Lease Agreement](#), [IOSA Registration Period](#) and [Wet Lease Agreement](#).

The intent of this standard is that monitoring is required by an operator when it has entered into an agreement to transport its passengers on flights conducted by an external operator.

Aircraft lease agreements typically cover ACMI lease, wet lease and damp lease.

For aircraft lease, code share, capacity purchase or another type of agreement in excess of three months, it is recommended for operators that conduct passenger flights to have such agreement(s) with IOSA-registered operators.

Performance monitoring of an operator typically includes an assessment of the following factors:

- Accident/incident rate;
- Financial condition, company ownership, relevant economic environment;
- Management, company stability, turnover of key personnel, labor action, other potentially disruptive aspects;
- Age of fleet, aircraft on order, aircraft being returned/retired;
- Operational capabilities (i.e. international operations compared to domestic operations only, indicators of established infrastructure, approved maintenance organizations, flight simulators, other key operational capabilities);
- Company history, level of sophistication;
- Interface and/or cooperation with the other operator (i.e. familiarity with its personnel, sharing of data, regular meetings/conferences, other forms of communication or cooperation).

Methods of monitoring the performance of another operator might include any of the following:

- Requesting relevant certifications;
- Conducting inspections and/or audits;
- Accepting third-party audits;

- Flight monitoring;
- Assessing other relevant safety indicators.

⊗

IOSA registration indicates that an operator has undergone a third-party operational audit and is in conformity with internationally recognized standards.

3.6 Product Quality Control

3.7 Flight Data Analysis (FDA) Program

4 Emergency Response

4.1 Emergency Response Plan

△

ORG 4.1.1

The Operator shall have a corporate emergency response plan (ERP) for the central management and coordination of all activities necessary to respond to a major aircraft accident or other type of adverse event that results in fatalities, serious injuries, considerable damage and/or a significant disruption of aircraft operations. **[SMS] (GM)**

Auditor Actions

- ☐ **Identified/Assessed** corporate emergency response plan (ERP) (focus: plan suitable for organizational response to major aircraft accident/other adverse event).
- ☐ **Interviewed** designated ERP manager.
- ☐ **Coordinated** to verify implementation of ERP in all operational areas.
- ☐ **Other Actions** (Specify)

Guidance

Refer to the IRM for the definitions of [Emergency Response Plan \(ERP\)](#) and [Public Health Emergency](#).

Emergency response planning is an element of the Safety Policy and Objectives component of the SMS framework.

An emergency (or crisis) response plan is based upon an assessment of risk appropriate to the size and type of operations, and includes consideration of a major aircraft accident and other potential, aircraft and/or non-aircraft events that would require a full corporate emergency response.

In some states, emergency or crisis response is assumed by a governmental authority rather than by the operator. In such case, an emergency response plan focuses on and addresses interaction with and/or participation in the governmental response to an emergency or crisis.

As a best practice, an operator might consider defining in its ERP an appropriately coordinated response to a public health emergency.

An effective ERP includes industry best practices and ensure community expectations are addressed. Additionally, an ERP:

- Specifies general conditions for implementation;
- Provides a framework for an orderly implementation;
- Ensures proper coordination with external entities at all potential locations (refer to [ORG 4.1.4](#));
- Addresses all potential aspects of an event, including casualties;
- Ensures regulatory requirements associated with specific events are satisfied;
- Provides a scenario for the transition back to normal operations;
- Ensures regular practice exercises as a means to achieve continual improvement (refer to [ORG 4.1.14](#) and [ORG 4.1.15](#)).

IATA provides a guide for use by operators in addressing a public health emergency. Such document, titled Emergency Response Plan and Action Checklist, may be found at <http://www.iata.org/whatwedo/safety/health/Pages/diseases.aspx>.

Plan Elements

Table 1.1–Documentation System Specifications

△ **As specified in ORG 2.1.1**, the Operator shall have a system for the management and control of documentation and/or data used directly in the conduct or support of operations. Such system shall comprise the elements specified below.

Note: Refer to the IRM for the definitions of [Documentation](#), [Electronic Documentation](#) and [Paper Documentation](#).

Elements		Documentation Types		
		Type 1	Type 2	Type 3
(i)	Identification of the version and effective date of relevant documents and/or data.	Recommended	Recommended	Required ^{Note}
(ii)	Identification of the title and, if applicable, sub-titles of relevant documents and/or data.	Recommended	Recommended	Required ^{Note}
(iii)	Distribution and/or dissemination that ensures all users are provided relevant documents and/or data on or before the effective date: (a) Throughout appropriate areas of the organization; (b) To external service providers that conduct outsourced operational functions.	Required ^{Note}	Required ^{Note}	Required ^{Note}
(iv)	Definition of the specific media type(s) designated for presentation or display of the controlled version of relevant documents and/or data.	Required ^{Note}	Required ^{Note}	Required ^{Note}
(v)	Definition of documentation and/or data that is considered to be reproduced and/or obsolete.	Required ^{Note}	Required ^{Note}	Required ^{Note}
(vi)	Review and revision to maintain the currency of relevant documents and/or data.	Required ^{Note}	Required ^{Note}	Required ^{Note}
(vii)	Retention that ensures access to the content of relevant documents and/or data for a minimum period as defined by the Operator.	Required ^{Note}	Required ^{Note}	Required ^{Note}
(viii)	Provision for a scheduled backup by copying and archiving relevant documents and/or data, to include validation of the documents or data being backed up.	Required ^{Note}	Required ^{Note}	Required ^{Note}
(ix)	Identification and allocation of documentation access/user and modification rights.	Required ^{Note}	Required ^{Note}	Required ^{Note}
(x)	Dissemination and/or accessibility of documentation received from external sources such as regulatory authorities and original equipment manufacturers.	Required ^{Note}	Required ^{Note}	Required ^{Note}

Note: Required for conformity with [ORG 2.1.1](#).



Table 1.2–Required Internal Audit Information

As specified in [ORG 3.4.6](#), the Operator shall ensure the following information associated with the internal audit of individual ISARPs is recorded and retained:

- (i) The alpha-numeric identifier;
- (ii) Appropriate documentation reference(s) (from the Operator's documentation system);
- (iii) Auditor name(s);
- (iv) Audit date(s);
- (v) Auditor Actions accomplished by auditor(s) to provide evidence of implementation;
- (vi) If applicable, a description of non-conformance(s) and:
 - (a) The root cause(s) of non-conformance(s);
 - (b) The corrective action(s) implemented to address non-conformance(s).
- (vii) If applicable, a description of non-applicability (N/A);
- (viii) The current status of conformance (documented and implemented). **GM**

Note: The above-specified audit information may be retained in the Operator's electronic database as specified in [ORG 3.4.14](#) or in controlled procedural documents.

INTENTIONALLY LEFT BLANK

Section 2 — Flight Operations (FLT)

Applicability

[Section 2](#) addresses safety and security requirements for flight operations, and is applicable to an operator that utilizes two-pilot, multi-engine aircraft with a maximum certificated takeoff mass in excess of 5,700 kg (12,566 lbs.) to conduct:

- Passenger flights with or without cabin crew;
- Cargo flights with or without the carriage of passengers or supernumeraries.

Additionally, the IOSA standards and recommended practices (ISARPs) in [Section 2](#) are applicable only to those aircraft that are of the type authorized in the Air Operator Certificate (AOC) and utilized in commercial passenger and/or cargo operations unless applicability is extended to encompass non-commercial operations as stated in a note immediately under the body of the provision.

Individual FLT provisions or sub-specifications within a FLT provision that:

- Do not begin with a conditional phrase are applicable unless determined otherwise by the Auditor.
- Begin with a conditional phrase (“If the Operator...”) are applicable if the operator meets the condition(s) stated in the phrase.

Individual provisions that contain the **<AC>** symbol in the reference number are applicable to an operator that conducts flights with cargo aircraft.

Where an operator outsources flight operations functions to external service providers, an operator retains responsibility for ensuring the management of safety in the conduct of such operations and must demonstrate processes for monitoring applicable external service providers in accordance with [FLT 1.11.2](#).

Some cabin safety specifications applicable to functions or equipment within the scope of flight operations are located in [Section 5 \(CAB\)](#) of this manual.

General Guidance

The definitions of technical terms used in this ISM [Section 2](#), as well as the list of abbreviations and acronyms, are found in the IATA Reference Manual for Audit Programs (IRM).

1 Management and Control

1.1 Management System Overview

1.2 State Requirements

FLT 1.2.1

The Operator shall have a valid Air Operator Certificate (AOC) or equivalent document issued by the State of the Operator (hereinafter, the State) that authorizes the Operator to conduct commercial air transport operations in accordance with specified conditions and limitations. The AOC and/or associated documents shall include:

- (i) Operator identification (name and location);
- (ii) Date of issue and period of validity;
- (iii) Description of types of operations authorized;
- (iv) Type(s) of aircraft authorized for use;
- (v) Authorized areas of operation or routes;
- (vi) Exemptions, deviations and waivers (listed by name);
- (vii) Special authorizations, to include, as applicable:
 - (a) Low visibility takeoff (LVTO);
 - (b) CAT II and/or III approaches;

- (c) Head-up displays (HUD) and enhanced vision systems (EVS) operations (if such systems are used to gain operational benefit);
- (d) GPS approaches;
- (e) EDTO;
- (f) RVSM operations;
- (g) MNPS operations;
- (h) AR navigation specifications for PBN operations;
- (i) Transport of dangerous goods as cargo (if AOC authorization is required for the transport of dangerous goods);
- (j) Electronic Flight Bag (EFB) operations (if approval for such operations is required by the Authority). **(GM)**

Note: An ETOPS approval is equivalent to an EDTO approval.

Auditor Actions

- ☐ **Identified** the documents that authorize the Operator to conduct commercial air transport operations in accordance with conditions and limitations specified by the State.
- ☐ **Interviewed** responsible manager(s) in flight operations.
- ☐ **Examined** AOC (focus: information is current and relevant to the Operator).
- ☐ **Crosschecked** AOC against OM (focus: authorizations/limitations consistent with operations conducted by Operator).
- ☐ **Other Actions** (Specify)

Guidance

Refer to the IRM for the definitions of [Electronic Flight Bag \(EFB\)](#), [EDTO \(Extended Diversion Time Operations\)](#), [Enhanced Visual System \(EVS\)](#), [Head-up Display \(HUD\)](#), [Minimum Navigation Performance Specifications \(MNPS\)](#), [PBN Navigation Specification AR \(Authorization Required\)](#), [Reduced Vertical Separation Minima \(RVSM\)](#), [Required Navigation Performance \(RNP\)](#) and [State](#).

The specifications of this provision require the conditions and limitations of any State-approved or State-accepted air transport operations, conducted by the operator, to be described in the AOC, AOC equivalents and/or associated documents.

The AOC is produced (by the State) in a manner consistent with local conditions for State approval or acceptance. This should not preclude the operator from describing authorized operations, including conditions and limitations for such operations, in associated documents and in a manner consistent with the specifications of this provision. Such documents typically include the OM or any operational document that describes the conditions and limitations of authorized operations.

The exemptions, deviations, waivers and special authorizations in specifications vi) and vii) may be described in State-approved or State-accepted documents other than the AOC.

Operators subject to laws or regulations of the State that prevent the issuance of an AOC consistent with the specifications of this provision and/or prohibit the description of authorized operations in a manner consistent with the specifications of this provision may demonstrate an equivalent method of ensuring the specifications of this provision are satisfied.

The period of validity is designated on the AOC or determined by reference to the dates of issuance and expiration.

The specification in item vii) e) refers to aircraft operated on routes where the diversion time from any point on the route to an en route alternate airport exceeds the threshold time but is within the maximum diversion time as established by the State.

1.3 Accountability, Authorities and Responsibilities

FLT 1.3.2

The Operator shall delegate authority and assign responsibility for the management and supervision of specific areas of the organization relevant to the flight operations management system, to include, as a minimum:

- (i) Fleet operations;
- (ii) Line operations;
- (iii) Documentation control;
- (iv) Flight crew training;
- (v) Operations engineering;
- (vi) Flight crew scheduling;
- (vii) Accident prevention and flight safety;
- (viii) Human resources;
- (ix) Quality assurance;
- (x) Security. **(GM)**

Auditor Actions

- ☐ **Identified** positions with authority/responsibility for management/supervision of the specified areas of flight operations.
- ☐ **Interviewed** responsible manager(s) in flight operations.
- ☐ **Examined** job description for selected management positions (focus: authority/responsibility for management of the specified areas of flight operations).
- ☐ **Other Actions** (Specify)

Guidance

Refer to the IRM for the definition of [Flight Crew](#) and [Operations Engineering](#).

The specification in:

- Item i) refers to the management of policies, rules, procedures and instructions governing specific aircraft.
- Item ii) refers to the management of policies, rules, procedures and instructions governing flight crew.
- Item vii) could also be referred to as the flight safety program.
- Item viii) refers to the provision of Human Resources including management staff, support staff, administrative staff and flight crew.

1.4 Communication and Coordination

FLT 1.4.2

The Operator shall have a process to ensure issues that affect operational safety and security are coordinated among personnel with expertise in the appropriate areas within the flight operations organization and relevant areas outside of flight operations, to include, as appropriate:

- (i) Accident prevention and flight safety;
- (ii) Cabin operations;
- (iii) Engineering and maintenance;
- (iv) Operations engineering;
- (v) Operational control/flight dispatch;
- (vi) Human resources;
- (vii) Ground handling, cargo operations and dangerous goods;

- (viii) Manufacturers, (AFM/AOM, operational and safety communication);
- (ix) Regulatory agencies or authorities. **(GM)**

Auditor Actions

- ☐ **Identified/Assessed** operational safety and security coordination process(es).
- ☐ **Interviewed** responsible manager(s) in flight operations.
- ☐ **Examined** selected evidence of internal/external coordination.
- ☐ **Other Actions** (Specify)

Guidance

Refer to the IRM for the definitions of [Aircraft Operating Manual \(AOM\)](#) and [Approved Flight Manual](#).

Some examples of issues that could affect operational safety and security include aircraft modifications, new equipment, new destinations/routes, or regulatory changes.

The specifications of this provision are satisfied if an operator can demonstrate that a process exists within the flight operations organization that ensures necessary internal and external coordination.

The coordination processes specified in this provision may occur during meetings or other means of liaison (e.g. email, memos, conference call).

The specification in item iv) refers to coordination with the following or other appropriate categories of personnel:

- The operations engineering manager or other person responsible for defining, producing, customizing and distributing aircraft performance data;
- The manager responsible for defining, producing, customizing and/or distributing route and airport instructions or information, Notices to Airmen (NOTAMs) and Flight Management System (FMS) databases, if applicable;
- The operations engineering manager or other person in charge of aircraft equipment specification.

The specification in item iv) typically includes coordination on the following operational safety issues:

- Fleet and cross-fleet standardization;
- Flight deck layout;
- Aircraft avionics, instrumentation, equipment and/or components in accordance with the provisions of [FLT 4.3.1](#).

The specification in item vi) refers to coordination with respect to staffing necessary to meet operator requirements.

FLT 1.4.3

The Operator shall have a process to ensure the dissemination of safety-critical operational information to appropriate personnel within and external to the flight operations organization, to include:

- (i) Airworthiness Directives (ADs);
- (ii) Manufacturer bulletins;
- (iii) Flight crew bulletins or directives;
- (iv) NOTAMs. **(GM)**

Auditor Actions

- ☐ **Identified/Assessed** process that ensures the dissemination of safety-critical operational information.
- ☐ **Interviewed** responsible manager(s) in flight operations.
- ☐ **Interviewed** frontline personnel.
- ☐ **Examined** selected evidence of information dissemination.
- ☐ **Other Actions** (Specify)

Guidance

Refer to the IRM for the definitions of [Airworthiness Directive](#), [Flight Crew Bulletin](#) and [NOTAM](#).

The intent of this provision is to ensure a process is in place to disseminate safety critical information to personnel that require it.

1.5 Provision of Resources

1.6 Documentation System

FLT 1.6.3

The Operator shall ensure the system for the management and control of flight operations documentation as specified in [ORG 2.1.1](#) and [Table 1.1](#) addresses, as a minimum, the following documents from external sources:

- (i) As applicable, regulations of the State and of the other states or authorities relevant to operations;
- (ii) As applicable, relevant ICAO Standards and Recommended Practices (SARPS), manuals, regional supplementary procedures and/or circulars;
- (iii) Airworthiness Directives (ADs);
- (iv) As applicable, Aeronautical Information Publications (AIP) and NOTAMS;
- (v) State-approved or State-accepted Aircraft Flight Manuals (AFM);
- (vi) Manufacturer's Aircraft Operating Manuals (AOMs), including performance data, weight and balance data/manuals, checklists and MEL/CDL;
- (vii) As applicable, other manufacturer's operational communications. **(GM)**

Auditor Actions

- ☐ **Identified/Assessed** system(s) for management and control of documentation and data used in flight operations (focus: system includes management/control of specified documents from external sources).
- ☐ **Interviewed** responsible manager(s) in flight operations.
- ☐ **Examined** selected documents from external sources (focus: application of management/control elements).
- ☐ **Other Actions** (Specify)

Guidance

Refer to the IRM for the definitions of [Aeronautical Information Publication \(AIP\)](#), [Aircraft Operating Manual \(AOM\)](#), [Approved Flight Manual \(AFM\)](#), [Airworthiness Directive \(AD\)](#), [Configuration Deviation List \(CDL\)](#), [Master Minimum Equipment List \(MMEL\)](#), [Minimum Equipment List \(MEL\)](#), [State Acceptance](#) and [State Approval](#).

The specification in item i) refers to applicable regulations imposed on an operator by the State, which issues the Air Operator Certificate (AOC), and other states and/or authorities that actively regulate foreign operators or have jurisdiction over international operations conducted by the operator. This may be done through the issuing of an Operational Specification (OPS SPEC) or specific state legislation.

The specification in item ii) refers to applicable ICAO standards, recommended practices, supplemental procedures and/or guidance material made applicable to the operations of the operator by any states or authority with jurisdiction over the operations of the operator. Applicable authorities typically include those authorities that have jurisdiction over international operations conducted by an operator over the high seas or over the territory of a state that is other than the State of the Operator.

The specification in item ii) also refers to applicable ICAO standards and/or recommended practices that are referenced in the operator's documentation.

The specification for the manufacturer's AFM in item v) may be replaced by an Aircraft Operating Manual (AOM) customized by the manufacturer for the specific use in flight operations by an operator.

The specification in item vi) refers to bulletins or directives distributed by the manufacturer for the purposes of amending aircraft technical specifications and/or operating procedures.

The specification in item vii) refers to operational communications received from the manufacturer of equipment that is installed on the airplane, typically from the manufacturers of the engines, components and safety equipment.

1.7 Operations Manual

1.8 Records System

1.9 (Intentionally open)

1.10 Quality Assurance Program

1.11 Quality Control of Outsourced Operations and Products

FLT 1.11.4A

If the Operator utilizes aircraft with electronic navigation data capabilities, the Operator shall have processes, approved or accepted by the State, if required, which ensure electronic navigation data products acquired from suppliers, prior to being used as a means for navigation in operations:

- (i) Are assessed for a level of data integrity commensurate with the intended application;
- (ii) Are compatible with the intended function of equipment in which it is installed;
- (iii) Are distributed in a manner to allow insertion of current and unaltered electronic navigation data into all aircraft that require it. **(GM)**

Auditor Actions

- ☐ **Identified/Assessed** processes for acceptance/internal distribution of electronic navigation data products.
- ☐ **Identified** suppliers of electronic navigation data products (focus: suppliers accredited in accordance with approved/accepted standards of data integrity/quality).
- ☐ **Interviewed** responsible manager(s) in flight operations.
- ☐ **Examined** selected product acceptance records (focus: products assessed for data integrity, currency and compatibility with intended function).
- ☐ **Examined** selected aircraft data insertion records (focus: current/unaltered data inserted on all applicable aircraft).
- ☐ **Coordinated** with MNT auditor (focus: verification of currency of aircraft navigation databases).
- ☐ **Other Actions** (Specify)

Guidance

Refer to the IRM for the definition of [Navigation Data Integrity](#).

The responsibility of ensuring that electronic navigation data is assessed for integrity and is compatible with its intended application rests with the operator.

Navigation database integrity can be assured by obtaining data from a supplier accredited in accordance with approved or accepted standards of data integrity and quality. Such standards include:

- RTCA/DO-200A, Standards for Processing Aeronautical Data, issued 09/28/98;
- RTCA/DO-201A, Standards for Aeronautical Information, issued 04/19/00;
- Advisory Circular (AC) 20-153A, Acceptance of Data Processes and Associated Navigation Databases, issued 09/20/10;
- Any other State-approved or State-accepted standards of data integrity and quality that assure navigation database integrity.

The specifications in items i) and ii) may be satisfied by the operator, in accordance with State-approved or State-accepted methods for assuring data integrity and compatibility, such as:

- Obtaining a letter of acceptance from an applicable authority stating the data supplier conforms to a recognized standard for data integrity and compatibility that provides an assurance level of navigation data integrity and quality sufficient to support the intended application; **or**
- The existence of operator and flight crew validation processes to determine navigation data compatibility and accuracy that provide an assurance level of navigation data integrity and quality sufficient to support the intended application.

Letters of acceptance are approved by the applicable authority (the state where data is sourced or supplied) *and* approved or accepted by the State (state in which the data is applied). For example, the FAA, via a letter of acceptance, attests to the integrity of data from a U.S. supplier. The State would subsequently approve or accept the FAA letter as the operator's means to assure data integrity.

The specification in item iii) refers to processes that ensure timely insertion of data and mitigate the introduction of aeronautical information errors related to the content of navigation databases. The physical insertion of navigation data into applicable aircraft is addressed in ISM Section 4 (MNT), [Subsection 2, Maintenance Control](#).

Monitoring and control of electronic navigation data products acquired from suppliers would also be in accordance with [FLT 1.11.3](#).

1.12 Safety Management

Risk Management

FLT 1.12.1

The Operator shall have a hazard identification program in the flight operations organization that includes:

- (i) A combination of reactive and proactive methods for hazard identification;
- (ii) Processes for safety data analysis that identify existing hazards, and may predict future hazards, to aircraft operations. **[SMS] (GM) ◀**

Auditor Actions

- ☐ **Identified/Assessed** safety hazard identification program in flight operations (focus: program identifies hazards to aircraft operations; describes/defines method(s) of safety data collection/analysis).
- ☐ **Identified/Assessed** role of flight operations in cross-discipline safety hazard identification program (focus: participation with other operational disciplines).
- ☐ **Interviewed** responsible manager(s) in flight operations.
- ☐ **Interviewed** person(s) that perform flight operations data collection/analysis to identify hazards to aircraft operations.
- ☐ **Examined** selected examples of hazards identified through flight operations data collection/analysis.
- ☐ **Other Actions** (Specify)

Guidance

Refer to the IRM for the definitions of [Hazard \(Aircraft Operations\)](#) and [Safety Risk](#).

Hazard identification is an element of the Safety Risk Management component of the SMS framework.

Refer to Guidance associated with [ORG 3.1.1](#) located in ISM Section 1.



FLT 1.12.2

The Operator shall have a safety risk assessment and mitigation program in the flight operations organization that specifies processes to ensure:

- (i) Hazards are analyzed to determine the corresponding safety risks to aircraft operations;
- (ii) Safety risks are assessed to determine the requirement for risk mitigation action(s);
- (iii) When required, risk mitigation actions are developed and implemented in flight operations. **[SMS] [Eff] (GM) ◀**

Assessment Tool

Desired Outcome

The Operator maintains an overview of its flight operational risks and through implementation of mitigation actions, as applicable, ensures risks are at an acceptable level.

Suitability Criteria (Suitable to the size, complexity and nature of operations)

Number and type of analyzed hazards and corresponding risks.

Means used for recording risks and mitigation (control) actions.

Safety data used for the identification of hazards.

Effectiveness Criteria

- (i) All relevant flight operations hazards are analyzed for corresponding safety risks.
- (ii) Safety risks are expressed in at least the following components:
 - Likelihood of an occurrence.
 - Severity of the consequence of an occurrence.
 - Likelihood and severity have clear criteria assigned.
- (iii) A matrix quantifies safety risk tolerability to ensure standardization and consistency in the risk assessment process which is based on clear criteria.
- (iv) Risk register(s) within the flight operations organization capture risk assessment information, risk mitigation (control) and monitoring actions.
- (v) The risk mitigation (control) actions include time lines, allocation of responsibilities and risk control strategies such as hazard elimination, risk avoidance, risk acceptance, risk mitigation.
- (vi) Mitigation (control) actions are implemented to reduce the risk to a level of - as low as reasonably practical.
- (vii) Identified risks and mitigation actions are regularly reviewed for accuracy and relevance.
- (viii) Effectiveness of risk mitigation (control) actions are monitored at least yearly to include auditing in accordance with [ORG 3.4.1](#).
- (ix) Personnel performing risk assessments are appropriately trained in accordance with [ORG 1.6.5](#).

Auditor Actions

- ☐ **Identified/Assessed** safety risk assessment and mitigation program in flight operations (focus: hazards analyzed to identify/define risk; risk assessed to determine appropriate action; action implemented/monitored to mitigate risk).
- ☐ **Identified/Assessed** role of flight operations in cross-discipline safety risk assessment/mitigation program (focus: participation with other operational disciplines).
- ☐ **Interviewed** responsible manager(s) in flight operations.
- ☐ **Interviewed** person(s) that perform flight operations risk assessment/mitigation.
- ☐ **Examined** selected records/documents that illustrate risk assessment/mitigation action.
- ☐ **Other Actions** (Specify)

Guidance

Refer to the IRM for the definition of [Rescue](#) and [Fire Fighting Services \(RFFS\)](#).

Risk assessment and mitigation is an element of the Safety Risk Management component of the SMS framework.

Hazards relevant to the conduct of aircraft operations are potentially associated with:

- Weather (e.g. adverse, extreme and space);
- Geophysical events (e.g. volcanic ash, earthquakes, tsunamis);
- Operations in airspace affected by armed conflict;
- ATM congestion;
- Mechanical failure;
- Geography (e.g. adverse terrain, large bodies of water, polar);
- Airport constraints (e.g. isolated, runway closure, RFFS capability);
- Alternate airport selection, specification and availability at the estimated time of use;
- Preflight fuel planning and in-flight fuel management;
- Critical fuel scenarios;
- EDTO;
- Performance-based compliance to prescriptive regulations;
- The capabilities of an individual aircraft (e.g. cargo smoke detection and fire suppression systems, open MEL items);
- Criminal, dangerous, and/or unauthorized activities directed at manned aircraft or in the vicinity of manned aircraft operations (e.g. laser pointing, unauthorized UAS/RPAS operations);
- Any other condition(s) that would pose a safety risk to aircraft operations (e.g. radiation).

Refer to Guidance associated with [ORG 3.1.2](#) located in ISM Section 1.

Operational Reporting

FLT 1.12.3

The Operator shall have an operational safety reporting system in the flight operations organization that:

- (i) Encourages and facilitates flight crew members and other flight operations personnel to submit reports that identify safety hazards, expose safety deficiencies and raise safety concerns;
- (ii) Ensures mandatory reporting in accordance with applicable regulations;
- (iii) Includes analysis and flight operations management action as necessary to address safety issues identified through the reporting system. **[SMS] (GM) ◀**

Auditor Actions

- ☐ **Identified/Assessed** operational safety reporting system in flight operations (focus: system urges/facilitates reporting of hazards/safety concerns; includes analysis/action to validate/address reported hazards/safety concerns).
- ☐ **Interviewed** responsible manager(s) in flight operations.
- ☐ **Interviewed** person(s) that perform operational safety report review/analysis/follow-up in flight operations.
- ☐ **Interviewed** selected flight crew members.
- ☐ **Examined** selected data that confirm an effective flight operations safety reporting system (focus: quantity of reports submitted/hazards identified).
- ☐ **Examined** records of selected flight operations safety reports (focus: analysis/follow-up to identify and address reported hazards/safety concerns).
- ☐ **Other Actions** (Specify)

Guidance

Safety reporting is a key aspect of SMS hazard identification and risk management.

Refer to Guidance associated with [ORG 3.1.3](#) located in ISM Section 1.

Safety Performance Monitoring and Management**2 Training and Qualification****General Guidance**

Certain provisions in this sub-section specify traditional training program requirements that may be replaced by an equivalent requirement as part of an Advanced Qualification Program (AQP), Alternative Training and Qualification Program (ATQP) or Evidence-based Training (EBT) program in accordance with [FLT 2.1.1A](#) and [FLT 2.1.1B](#). AQP, ATQP and EBT are contemporary data-driven training programs that allow for variations in the manner and method by which training and, when applicable, an evaluation are conducted. Additionally, traditional recurrent training intervals may be replaced in accordance with intervals specified in the continuing qualification curriculum that is defined in an operator's AQP, ATQP or EBT (as applicable).

Many provisions in this subsection contain specifications related to the recurring frequency of training and evaluation events for flight crew members. Such provisions, with a few exceptions, define cycles or intervals for the completion of recurrent training and/or evaluation expressed in months since training was first completed or qualification was first established. It is important to note, however, that for the purpose of conformance with these provisions, such intervals are nominal and that the actual interval may vary slightly. For example, an operator may adjust the frequency of evaluations to minimize overlap, provide scheduling flexibility, preserve the original qualification date, and/or ensure evaluations are consistently completed in accordance with the nominal cycle set forth by the State and/or applicable authorities. Accommodations of this nature are commonplace and vary widely by regulatory jurisdiction. In all cases, however, the auditor will make the determination of whether or not such accommodations fit within the nominal cycles established in each provision.

2.1 Training and Evaluation Program**General****FLT 2.1.1A**

The Operator shall have a training and evaluation program, approved or accepted by the Authority, that consists of ground and flight training and, when applicable, evaluations to ensure flight crew members are competent to perform assigned duties. The program shall address traditional and, if applicable, advanced, alternative or evidence-based training and qualification, and ensure training and evaluation is conducted for each type of aircraft in the fleet. Such program shall also, as a minimum, address:

- (i) Initial qualification;
- (ii) Continuing qualification;
- (iii) Re-qualification;
- (iv) As applicable, aircraft transition or conversion;
- (v) Upgrade to PIC;
- (vi) As applicable, other specialized training requirements, including those associated with operations authorized in the AOC;
- (vii) As applicable, each traditional training program requirement that is replaced by a requirement under an Advanced Qualification Program (AQP), Alternative Training and Qualification Program (ATQP) or Evidence-based Training (EBT) program. **(GM)**

Auditor Actions

- ☐ **Identified/Assessed** flight crew training/qualification program (focus: program includes each type of aircraft in the fleet).
- ☐ **Identified/Assessed** AQP/ATQP/EBT elements/regulatory approval (as applicable).
- ☐ **Interviewed** responsible manager(s) in flight operations.
- ☐ **Examined** training/qualification course curriculum for selected aircraft types (focus: inclusion of applicable training/qualification courses for each aircraft type).
- ☐ **Examined** training/qualification records of selected flight crew members (focus: completion of applicable training/qualification courses).
- ☐ **Other Actions** (Specify)

Guidance

Refer to the IRM for the definitions of [Advanced Qualification Program \(AQP\)](#), [Alternative Training and Qualification Program \(ATQP\)](#) and [Evidence-based Training \(EBT\)](#).

The intent of this provision is to ensure an operator's training program contains the elements necessary to ensure flight crew members are continuously competent to perform assigned duties.

The initial qualification process provided to newly hired crew members typically includes company indoctrination and initial endorsement on company aircraft types. This presupposes that the newly hired crew member already holds a commercial flying license.

Initial endorsement training may not be required as part of initial qualification if a newly hired crew member already holds a type endorsement acceptable to both the State and the Operator. Company indoctrination training, however, is considered a part of initial qualification.

Continuing qualification includes recurrent or refresher training and also includes any training necessary to meet recency-of-experience requirements.

Transition (conversion) training refers to an aircraft type qualification training and evaluation program for each type of aircraft in the fleet and is not required when an operator only utilizes one type of aircraft.

Specialized training could also include training on a specific type of new equipment (e.g., ACAS).

AQP/ATQP incorporate the elements and specifications contained in [FLT 2.1.1B](#), [Table 2.6](#) and [Table 2.7](#).

EBT incorporates the elements and specifications contained in [FLT 2.1.1B](#), [Table 2.6](#) and [Table 2.8](#).

Training could be outsourced, in which case services typically range from simple dry lease of a training device to delegation of all training to an external organization (e.g., Authorized Flight Training School).

FLT 2.1.3

The Operator shall ensure flight crew members receive training that supports the introduction of:

- (i) New policies, rules, instructions and procedures;
- (ii) New aircraft types, systems and fleet modifications/upgrades. **(GM)**

Auditor Actions

- ☐ **Identified/Assessed** methodology for introduction of specified new elements into flight crew training/evaluation program.
- ☐ **Interviewed** responsible manager(s) in flight operations.
- ☐ **Examined** selected training/qualification course curricula/syllabi (focus: examples of new elements as specified).
- ☐ **Observed** flight simulator operations (focus: training/evaluation reflects current policies/procedures/equipment/aircraft modifications).
- ☐ **Other Actions** (Specify)

Guidance

This provision is satisfied if a process exists for the introduction into the training program of each specification that results from the coordination processes required by [FLT 1.4.2](#). Such coordination processes typically occur:

- Within the training program;
- Between those responsible for the training program and the relevant areas of the organization in accordance with [FLT 1.4.2](#).

Training Manual**FLT 2.1.12**

The Operator shall ensure the Training Manual contains standards for flight crew training and evaluation that have been approved or accepted by the State and include, as a minimum:

- (i) Standardized procedures for training and the conduct of evaluations;
- (ii) Standards that ensure piloting technique and the ability to execute normal and non-normal procedures are checked in a way that demonstrates each pilot's competence;
- (iii) A requirement that simulated aircraft, weather and environmental conditions are standardized and appropriate for the training/evaluation being administered;
- (iv) If the Operator conducts training flights, a definition of the conditions and/or maneuvers that can be safely simulated in the aircraft, as well as the minimum weather and environmental conditions required to ensure the training/evaluation being administered can be safely and effectively conducted;
- (v) Limits for the number of times maneuvers may be repeated and the evaluation still be considered acceptable;
- (vi) Procedures for remedial training and subsequent evaluation of a flight crew unable to achieve or maintain required standards. **(GM)**

Auditor Actions

- ☐ **Identified/Assessed** flight crew training manual, regulatory approval of standards.
- ☐ **Interviewed** the responsible manager(s) in flight operations.
- ☐ **Examined** selected parts of training manual (focus: content includes specified standards/requirements).
- ☐ **Examined** training/qualification records of selected flight crew members (focus: application of training manual standards/requirements in flight crew training).
- ☐ **Other Actions** (Specify)

Guidance

Refer to the IRM for the definitions of [Maneuver Tolerances](#) and [Training Flights](#).

The intent of this provision is to ensure that the standards for flight crew training and evaluation are published or referenced in the Training Manual.

The specifications in item ii) of this provision are normally satisfied by the application of tolerances to normal and non-normal maneuvers during training and evaluations for the following flight parameters:

- Heading
- Airspeed
- Height/altitude
- Course tracking

With respect to item iv), operators that conduct training flights and cannot safely train/evaluate a non-normal maneuver or procedure in an aircraft or in a representative flight simulator as specified in [FLT 2.2.38](#) may demonstrate an alternative means of conformance in accordance with [FLT 2.2.41](#).

For training and/or evaluations conducted in an aircraft during line operations, maneuver tolerances normally include allowances for turbulence, aircraft characteristics and passenger comfort.

Remedial training and subsequent evaluation of flight crew unable to achieve or maintain required standards can be tailored to the needs of the individual concerned.

The terms “normal” and “non-normal/emergency” typically refer to AOM checklists, procedures and/or maneuvers. The term “non-normal” includes AOM emergency checklists and/or procedures (i.e. an emergency procedure is a subset of non-normal).

The terms can also be used to describe an event, situation or operation that would be addressed by normal or non-normal/emergency procedures or checklists. When used in this manner, the terms may be separated by forward slash marks (e.g. normal/non-normal/emergency).

Resources



FLT 2.1.20

The Operator shall have processes that ensure instructors, evaluators, and line check airmen (whether employed or contracted) are standardized and:

- (i) As applicable, have the required certification(s)/approval(s) from the State;
- (ii) As applicable, meet the required qualification and performance standards of the Operator or the State;
- (iii) Are periodically evaluated to ensure compliance with required qualification and performance standards.

Auditor Actions

- ☐ **Identified/Assessed** flight crew training/evaluation program (focus: includes qualification and performance standards that ensure standardization and appropriate certification/acceptance/approval/evaluation of instructors/evaluators/line check airmen).
- ☐ **Identified/Assessed** processes for the standardization of instructors/evaluators/line check airmen in the flight crew training/qualification program.
- ☐ **Interviewed** the responsible manager(s) in flight operations.
- ☐ **Examined** selected qualification records for training/evaluator/line check personnel (focus: certification/approval in accordance with applicable regulations/standards; periodically evaluated against qualification/performance standards).
- ☐ **Observed** flight simulator operations (focus: Instructors/evaluators/ meet required standards).
- ☐ **Other Actions** (Specify)

FLT 2.1.21

The Operator shall have sufficient instructors, evaluators, line check airmen and support personnel to administer the training and evaluation programs in accordance with requirements of the Operator and/or the State, as applicable.

Auditor Actions

- ☐ **Identified/Assessed** staffing requirements for instructor/evaluator/line check airman/support personnel in flight crew training/evaluation program.
- ☐ **Interviewed** the responsible manager(s) in flight operations.
- ☐ **Examined** selected personnel staffing records (focus: staffing in accordance with required levels).
- ☐ **Other Actions** (Specify)

Program Improvement

FLT 2.1.27

The Operator shall ensure formal and regular communication occurs between and among flight operations management, instructors, evaluators, line check airmen and flight crew members to achieve continual improvement of ground, simulator and aircraft training and line operations. **(GM)**

Auditor Actions

- ☐ **Identified/Assessed** requirements for communication among management/training personnel/flight crew members for continual improvement in flight crew training/evaluation program.
- ☐ **Interviewed** the responsible manager(s) in flight operations.
- ☐ **Interviewed** selected flight training personnel/flight crew members.
- ☐ **Examined** selected communication media: (focus: communication for purpose of program continual improvement).
- ☐ **Other Actions** (Specify)

Guidance

The intent of this provision is for the operator to ensure a mandate exists, as well the means and opportunity, for the conduct of regular communications between and among the operational personnel for the purpose of achieving continual program improvement.

Instructors, Evaluators, and Line Check Airmen**FLT 2.1.35**

The Operator shall have an initial training program for instructors, evaluators and line check airmen, to include:

- (i) An instructor course that addresses as a minimum:
 - (a) The fundamentals of teaching and evaluation;
 - (b) Lesson plan management;
 - (c) Briefing and debriefing;
 - (d) Human performance issues;
 - (e) Company policies and procedures;
 - (f) Simulator serviceability and training in simulator operation;
 - (g) If the Operator conducts training flights, dangers associated with simulating system failures in flight;
 - (h) As applicable, the simulated or actual weather and environmental conditions necessary to conduct each simulator or aircraft training/evaluation session to be administered.
- (ii) A formal observation program consisting of:
 - (a) The observation by the candidate of experienced instructors administering the course and syllabus lessons;
 - (b) The observation of the candidate during supervised practical instruction.
- (iii) A seat-specific (right or left seat, as applicable) qualification program for instructors, evaluators, line check airmen and any other pilots, so designated by management, who perform duties from either seat;
- (iv) If non-line qualified instructors are utilized, a jump seat observation program or equivalent for non-line qualified instructors to provide familiarity with current and type-related line operations. **(GM)**

Auditor Actions

- ☐ **Identified/Assessed** requirement for initial training program for instructors/evaluators/line check airmen in flight crew training/evaluation program.
- ☐ **Interviewed** the responsible manager(s) in flight operations.
- ☐ **Examined** selected initial training course curricula/syllabi for instructors/evaluators/line check airmen (focus: specified elements are addressed in initial training for instructors/evaluators/line check airmen).
- ☐ **Other Actions** (Specify)

- ❑ **Observed** flight simulator operations (focus: Instructor/evaluator demonstrates competence to administer flight training).

Guidance

The specification in item iv) of this provision may be satisfied by an equivalent program that includes line-oriented simulator sessions and/or completion of the company recurrent training program administered to line pilots.

The specification in item i), sub-item g), is applicable to operators that conduct training flights.

The specification in item i), sub-item h), would typically require operators that conduct training flights to specify the actual conditions that will permit such training to be accomplished safely and effectively in accordance with [FLT 2.1.12](#).

FLT 2.1.36

The Operator shall have a recurrent qualification program for instructors, evaluators, and line check airmen that, as a minimum, requires participation in:

- (i) Standardization meetings as defined by the Operator or the State;
- (ii) Training or evaluation sessions (simulator or aircraft) conducted while supervised by an individual approved by the Operator;
- (iii) A State-approved or State-accepted minimum number of training events and/or evaluations per 12-month period or required participation in a supplementary re-qualification/recertification program if the minimum number of events are not completed;
- (iv) A seat-specific (right or left seat, as applicable) recurrent program for instructors, evaluators, Line Check Airmen, who perform duties from either pilot station;
- (v) If non-line qualified instructors are utilized, a jump seat observation program or equivalent approved or accepted by the State for non-line qualified instructors to provide familiarity with current and type-related line operations. **(GM)**

Auditor Actions

- ❑ **Identified/Assessed** requirement for recurrent training program for instructors/evaluators/line check airmen in flight crew training/evaluation program.
- ❑ **Interviewed** the responsible manager(s) in flight operations.
- ❑ **Interviewed** selected instructors/evaluators/line check airmen.
- ❑ **Examined** selected recurrent training course curricula/syllabi for instructors/evaluators/line check airmen (focus: specified observations/events/seat-specific training are included in recurrent training).
- ❑ **Examined** selected instructor/evaluator/line check airman training/qualification records (focus: completion of applicable formal observations/required events/seat-specific training).
- ❑ **Other Actions** (Specify)

Guidance

The operator could have different recurrent qualification programs for line check airmen authorized to conduct line flying under supervision and those who conduct simulator and/or aircraft evaluations.

Instructors, evaluators and line check airmen typically attend a standardization meeting at least once within the preceding 12 months. Minutes of standardization meetings are normally distributed to instructors, evaluators and line check airmen.

The observations required in conjunction with item ii) are typically conducted at least within the preceding 12 months for each instructor, evaluator and line check airman, unless a longer interval is approved or accepted by the Authority.

Simulator observations in conjunction with item ii) typically entail an assessment of the individual while carrying out the duties for which highest qualified (e.g., instructor or evaluator).

The specification in item v) of this provision may be satisfied by an equivalent program that includes line-oriented simulator sessions and/or completion of the company recurrent training program administered to line pilots.



Facilities, Training Aids and Equipment

FLT 2.1.46

The Operator shall have published guidance for instructors and evaluators, approved or accepted by the State, if applicable, that specifies minimum serviceability levels of training devices and/or training aircraft to ensure serviceability does not adversely affect training, evaluation and/or safety, as applicable. **(GM)**

Auditor Actions

- ☐ **Identified/Assessed** guidance for instructors/evaluators that specifies minimum required serviceability levels for training devices in flight crew training/evaluation program.
- ☐ **Interviewed** responsible manager(s) in flight operations.
- ☐ **Interviewed** selected instructors/evaluators.
- ☐ **Observed** flight simulator operations (focus: documentation that specifies minimum simulator serviceability levels for type of training/evaluation to be conducted).
- ☐ **Other Actions** (Specify)

Guidance

Minimum serviceability guidance for training devices typically takes into account, among other things, simulator motion, visual systems, or instrumentation.

Minimum serviceability guidance for aircraft utilized for Training Flights would typically take into account MEL allowances that are permissible under passenger operations, but unsuitable for the conduct of the training/evaluation to be conducted.

The specification of this provision is satisfied if an operator provides guidance to instructors and evaluators when critical components of a training device are fully or partially inoperative. For example, simulator minimum serviceability requirements typically refer instructors or evaluators to published company guidance to determine if a certain type of training (such as LOFT/LOS) can be conducted with simulator components inoperative.

2.2 Training Elements

FLT 2.2.8

The Operator shall ensure flight crew members complete practical training exercises:

- (i) In the use of emergency and safety equipment required to be on board the aircraft, and such training shall be completed during initial ground training and subsequently during recurrent training either once every 12 months or, if applicable, in accordance with the continuing qualification schedule as defined in the Operator's AQP/ATQP/EBT that conforms to the specifications of [FLT 2.1.1B](#);
- (ii) That address emergency evacuation and coordination among flight crew members and, as applicable, cabin crew members and/or supernumeraries, and such training shall be completed during initial ground training and subsequently during recurrent training either once every 36 months or, if applicable, in accordance with the continuing qualification schedule as defined in the Operator's AQP/ATQP/EBT that conforms to the specifications of [FLT 2.1.1B](#). **(GM)**

Auditor Actions

- ☐ **Identified/Assessed** requirement for practical training exercises in flight crew training/evaluation program.
- ☐ **Identified/Assessed** flight crew AQP/ATQP/EBT, (focus continuing qualification recurrent schedule for practical training exercises).
- ☐ **Interviewed** responsible manager(s) in flight operations.
- ☐ **Examined** selected initial/recurrent training/qualification course curricula/syllabi (focus: inclusion of initial/recurrent practical training exercises as specified).

- ❑ **Examined** selected flight crew member training/qualification records (focus: completion of practical training exercises in initial/recurrent training).
- ❑ **Other Actions** (Specify)

Guidance

The principal intent of the specifications of this provision is to ensure flight crew members have a working knowledge of the emergency and safety equipment required to be on board an aircraft. Training exercises typically address the operation of safety and emergency equipment carried on the flight deck, emergency exits and slides, flotation devices (e.g. life rafts, life vests) and locating equipment (e.g. ELT).

The extent to which training exercises must include the actual use or manipulation of such equipment is typically determined by the operator in conjunction with requirements of the Authority. Additionally, since the routine manipulation or use of certain required items may pose an occupational health hazard, such training is typically accomplished using mock-ups or non-functioning replicas.

Training is applicable to all flight crew members.

Supernumeraries as specified in item ii) are those that are required for the safety of operations in accordance with [FLT 2.2.44](#).

[FLT 2.1.1B](#) addresses overall AQP/ATQP/EBT elements and specifications, as well as Authority approval/acceptance requirements.

FLT 2.2.11

The Operator shall ensure flight crew members complete training and an evaluation in aircraft systems and limitations, to include a demonstration of competence in the operation of aircraft systems. Such training and evaluation shall be completed during initial ground training and subsequently during recurrent training either once every 36 months or, if applicable, in accordance with the continuing qualification schedule as defined in the Operator's AQP/ATQP/EBT that conforms to the specifications of [FLT 2.1.1B](#). **(GM)**

Auditor Actions

- ❑ **Identified/Assessed** requirement for training/evaluation in aircraft systems/limitations in flight crew training/evaluation program.
- ❑ **Identified/Assessed** flight crew AQP/ATQP/EBT (if applicable): (focus continuing qualification recurrent schedule for training/evaluation in aircraft systems/limitations).
- ❑ **Interviewed** responsible manager(s) in flight operations.
- ❑ **Examined** selected initial/recurrent training/qualification course curricula/syllabi (focus: training/evaluation in aircraft systems limitations/operation).
- ❑ **Examined** selected flight crew member training/qualification records (focus: completion of training/evaluation in aircraft systems limitations/operation).
- ❑ **Observed** flight simulator operations (focus: training/evaluation in flight crew operation of aircraft systems/limitations).
- ❑ **Other Actions** (Specify)

Guidance

Training and evaluation is applicable to all flight crew members.

[FLT 2.1.1B](#) addresses overall AQP/ATQP/EBT elements and specifications, as well as Authority approval/acceptance requirements.

FLT 2.2.12

If the Operator transports dangerous goods as cargo, the Operator shall ensure flight crew members complete training and an evaluation in dangerous goods during initial ground training and subsequently once during recurrent training either within the 24-month period from the previous training in dangerous goods or, if applicable, in accordance with the continuing qualification schedule as defined in the Operator's AQP/ATQP/EBT that conforms to the specifications of [FLT 2.1.1B](#). **(GM)**.

Auditor Actions

- ❑ **Identified/Assessed** requirement for training/evaluation in dangerous goods in flight crew training/evaluation program.
- ❑ **Identified/Assessed** flight crew AQP/ATQP/EBT (if applicable): (focus continuing qualification recurrent schedule for training/evaluation in dangerous goods).
- ❑ **Interviewed** responsible manager(s) in flight operations.
- ❑ **Examined** selected initial/recurrent training/qualification course curricula/syllabi (focus: dangerous goods training/evaluation; definition of specific aspects/subjects addressed).
- ❑ **Examined** selected flight crew member training/qualification records (focus: completion of training/evaluation in dangerous goods in initial/recurrent training).
- ❑ **Other Actions** (Specify)

Guidance

❑

Refer to the IRM for the definition of [Dangerous Goods Regulations \(DGR\)](#).

Training and evaluation is applicable to all flight crew members.

Recurrent training in dangerous goods is typically completed within a validity period that expires 24 months from the previous training to ensure knowledge is current, unless a shorter period is defined by a competent authority. However, when such recurrent training is completed within the final 3 months of the 24-month validity period, the new validity period may extend from the month on which the recurrent training was completed until 24 months from the expiry month of the current validity period. If such recurrent training is completed *prior* to the final three months (or 90 days) of the validity period, the new validity period would extend 24 months from the month the recurrent training was completed.

[FLT 2.1.1B](#) addresses overall AQP/ATQP/EBT elements and specifications, as well as Authority approval/acceptance requirements.

The curriculum for dangerous goods training for flight crew members will typically address the following subject areas:

- General philosophy;
- Limitations;
- List of dangerous goods;
- Labeling and marking;
- Recognition of undeclared dangerous goods;
- Storage and loading procedures;
- Pilot's notification;
- Provisions for passengers and crew;
- Emergency procedures.

△

Refer to [DGR 1.5.2](#) and [Table 1.5.A](#) for guidance that addresses dangerous goods training for crew members.

FLT 2.2.13

If the Operator does not transport dangerous goods as cargo, the Operator shall ensure flight crew members complete training and an evaluation in dangerous goods during initial ground training and subsequently once during recurrent training either within the 24-month period from the previous training in dangerous goods or, if applicable, in accordance with the continuing qualification schedule as defined in the Operator's AQP/ATQP/EBT that conforms to the specifications of [FLT 2.1.1B](#). **(GM)**.

Auditor Actions

- ❑ **Identified/Assessed** requirement for training/evaluation in dangerous goods in flight crew training/evaluation program.
- ❑ **Identified/Assessed** flight crew AQP/ATQP/EBT (if applicable): (focus continuing qualification recurrent schedule for training/evaluation in dangerous goods).

- ❑ **Interviewed** responsible manager(s) in flight operations.
- ❑ **Examined** selected initial/recurrent training/qualification course curricula/syllabi (focus: dangerous goods training/evaluation; definition of aspects/subjects addressed).
- ❑ **Examined** selected flight crew member training/qualification records (focus: completion of training/evaluation in dangerous goods in initial/recurrent training).
- ❑ **Other Actions** (Specify)

Guidance

Training and evaluation is applicable to all flight crew members.

Recurrent training in dangerous goods is typically completed within a validity period that expires 24 months from the previous training to ensure knowledge is current, unless a shorter period is defined by a competent authority. However, when such recurrent training is completed within the final 3 months of the 24-month validity period, the new validity period may extend from the month on which the recurrent training was completed until 24 months from the expiry month of the current validity period. If such recurrent training is completed prior to the final three months (or 90 days) of the validity period, the new validity period would extend 24 months from the month the recurrent training was completed.

[FLT 2.1.1B](#) addresses overall AQP/ATQP/EBT elements and specifications, as well as Authority approval/acceptance requirements.

The curriculum for dangerous goods training for flight crew members is commensurate with responsibilities and will typically address:

- (i) General philosophy;
- (ii) Limitations;
- (iii) Labeling and marking;
- (iv) Recognition of undeclared dangerous goods;
- (v) Provisions for passengers and crew;
- (vi) Emergency procedures.

△ Refer to [DGR 1.5.2](#) and [Table 1.5.B](#) for guidance that addresses dangerous goods training for crew members.

FLT 2.2.14

The Operator shall ensure flight crew members complete training and, when applicable, an evaluation in crew resource management (CRM), including Threat and Error Management, using facilitators that have been trained in human performance and human factors principles. Such training and evaluation shall be completed during initial ground training and subsequently during recurrent training either once every 36 months or, if applicable, in accordance with the continuing qualification schedule as defined in the Operator's AQP/ATQP/EBT that conforms to the specifications of [FLT 2.1.1B](#). (GM)

Auditor Actions

- ❑ **Identified/Assessed** flight requirements for training/evaluation in CRM, use of CRM facilitators trained in human performance/factors principles in crew training/evaluation program.
- ❑ **Identified/Assessed** flight crew AQP/ATQP/EBT (if applicable): (focus continuing qualification recurrent schedule for training/evaluation in CRM, use of CRM facilitators).
- ❑ **Interviewed** responsible manager(s) in flight operations.
- ❑ **Examined** selected initial/recurrent training/qualification course curricula/syllabi (focus: training/evaluation in CRM, threat/error management).
- ❑ **Examined** selected flight crew member training/qualification records (focus: completion of training/evaluation in CRM in initial/recurrent training).
- ❑ **Observed** line flight operations (focus: application of CRM/TEM principles/skills to flight management).
- ❑ **Other Actions** (Specify)

Guidance

Refer to the IRM for the definitions of [CRM](#), [Facilitator](#), [Human Performance](#), [Human Factors Principles](#) and [Threat and Error Management](#).

CRM training is applicable to all flight crew members.

[FLT 2.1.1B](#) addresses overall AQP/ATQP elements and specifications, as well as Authority approval/acceptance requirement.

FLT 2.2.16A

The Operator shall ensure flight crew members complete training and an evaluation in subjects associated with adverse weather and/or environmental conditions during initial ground training and subsequently during recurrent training either once every 36 months or, if applicable, in accordance with the continuing qualification schedule as defined in the Operator's AQP/ATQP/EBT that conforms to the specifications of [FLT 2.1.1B](#). Such training and evaluation shall address, as applicable:

- (i) Cold weather operations;
- (ii) De-/anti-icing policies and procedures as specified in [FLT 3.9.6](#);
- (iii) Contaminated runway operations;
- (iv) Thunderstorm avoidance. **(GM)**

Note: Item ii) is applicable if the Operator conducts flights from any airport when conditions are conducive to ground aircraft icing.

Auditor Actions

- ☐ **Identified/Assessed** requirement for training/evaluation in adverse weather/environmental conditions in flight crew training/evaluation program.
- ☐ **Identified/Assessed** flight crew AQP/ATQP/EBT (if applicable): (focus continuing qualification recurrent schedule for training/evaluation in adverse weather/environmental conditions).
- ☐ **Interviewed** responsible manager(s) in flight operations.
- ☐ **Examined** selected initial/recurrent training/qualification course curricula/syllabi (focus: training/evaluation in adverse weather/environmental conditions; definition of aspects/subjects addressed).
- ☐ **Examined** selected flight crew member training/qualification records (focus: completion of training/evaluation in adverse weather/environmental conditions in initial/recurrent training).
- ☐ **Observed** flight simulator operations (focus: training/evaluation in operations in adverse weather/environmental conditions).
- ☐ **Other Actions** (Specify)

Guidance

Training and evaluation is applicable to all flight crew members.

The intent of this provision is to ensure flight crew members receive recurrent training and an evaluation in the subjects associated with the adverse weather or environmental conditions they may encounter in operations.

[FLT 2.1.1B](#) addresses overall AQP/ATQP/EBT elements and specifications, as well as Authority approval/acceptance requirements.

FLT 2.2.17

The Operator shall ensure flight crew members complete upset prevention and recovery training (UPRT) during initial ground training and subsequently during recurrent training either once every 36 months or, if applicable, in accordance with the continuing qualification schedule as defined in the Operator's AQP/ATQP/EBT that conforms to the specifications of [FLT 2.1.1B](#). **(GM)**

Auditor Actions

- ❑ **Identified/Assessed** requirement for training in procedures for aircraft upset recovery in flight crew training/evaluation program.
- ❑ **Identified/Assessed** flight crew AQP/ATQP/EBT (if applicable): (focus continuing qualification recurrent schedule for training in procedures for aircraft upset recovery).
- ❑ **Interviewed** responsible manager(s) in flight operations.
- ❑ **Examined** selected initial/recurrent training/qualification course curricula/syllabi (focus: training in procedures for aircraft upset recovery).
- ❑ **Examined** selected flight crew member training/qualification records (focus: completion of upset recovery training/evaluation in initial/recurrent training).
- ❑ **Observed** flight simulator operations (focus: training in upset recovery).
- ❑ **Other Actions** (Specify)

Guidance

Training is applicable to all *pilot* crew members and typically addresses pilot flying (PF) and pilot monitoring (PM) duties.

Aircraft upset recovery training typically includes:

- Upset prevention;
- Factors leading to an upset or loss of control situation;
- Upset situation identification;
- Recovery techniques;
- Emphasis on aerodynamic factors present during the upset and the recovery.

Acceptable means of ground training may include video presentation(s), verbal instruction and/or group discussion.

[FLT 2.1.1B](#) addresses overall AQP/ATQP/EBT elements and specifications, as well as Authority approval/acceptance requirements.

FLT 2.2.26

The Operator shall ensure flight crew members complete training in normal and non-normal procedures and maneuvers during initial training and subsequently during recurrent training either once every 12 months or, if applicable, in accordance with the continuing qualification schedule as defined in the Operator's AQP/ATQP/EBT that conforms to the specifications of [FLT 2.1.1B](#). Such training shall address, as a minimum:

- (i) Pilot Monitoring (PM) Pilot Flying (PF) and other flight crew division of duties (task sharing);
- (ii) Positive transfer of aircraft control;
- (iii) Consistent checklist philosophy;
- (iv) Emphasis on a prioritization of tasks (e.g. "aviate, navigate, communicate");
- (v) Proper use of all levels of flight automation. **(GM)**

Auditor Actions

- ❑ **Identified/Assessed** requirement for training in normal/non-normal procedures/maneuvers in flight crew training/evaluation program.
- ❑ **Identified/Assessed** in flight crew AQP/ATQP/EBT (if applicable): (focus continuing qualification recurrent schedule for training in normal/non-normal procedures/maneuvers).
- ❑ **Interviewed** responsible manager(s) in flight operations.
- ❑ **Examined** selected initial/recurrent training/qualification course curricula/syllabi (focus: training in normal/non-normal procedures/maneuvers; definition of specific elements/subjects addressed).
- ❑ **Examined** selected flight crew member training/qualification records (focus: completion of initial/recurrent training in the specified normal/non-normal procedures/maneuvers).

- ☐ **Observed** flight simulator operations (focus: training in normal/non-normal procedure/maneuvers).
- ☐ **Other Actions** (Specify)

Guidance

Refer to the IRM for the definitions of [Pilot Flying \(PF\)](#) and [Pilot Monitoring \(PM\)](#).

Training is applicable to all flight crew members.

The intent of this provision is to set a training interval for normal and non-normal procedures, and additionally to ensure the training manual, curricula, lesson plans, or other guidance associated with such training addresses the specifications in items i) through v).

Division of flight crew duties, transfer of aircraft control, checklist use and prioritization of tasks are in accordance with the operator's policies for task sharing and as specified in [FLT 3.11.18](#).

Proper use of automation levels is in accordance with the operator's automation policy and as specified in [FLT 3.11.22](#).

[FLT 2.1.1B](#) addresses overall AQP/ATQP/EBT elements and specifications, as well as Authority approval/acceptance requirements.

Elements of training may be accomplished as part of ground, simulator, aircraft or line training.

The term *Pilot Monitoring (PM)* has the same meaning as the term *Pilot Not Flying (PNF)* for the purpose of applying the specifications of this provision.

The specification in item iv) refers to the following prioritization of tasks during any normal or abnormal situation or maneuver:

- Aviate: fly the aircraft in accordance with restrictions and limitations set forth in the OM;
- Navigate: guide the aircraft along the intended or appropriate route;
- Communicate: verbalize intentions to other crew members and ATC, as applicable.

The term "abnormal" is used to describe a condition or situation (e.g. abnormal airframe vibration, abnormal landing configuration).

The terms "normal" and "non-normal/emergency" typically refer to AOM checklists, procedures and/or maneuvers. The term "non-normal" includes AOM emergency checklists and/or procedures (i.e. an emergency procedure is a subset of non-normal).

The terms can also be used to describe an event, situation or operation that would be addressed by normal or non-normal/emergency procedures or checklists. When used in this manner, the terms may be separated by forward slash marks (e.g. normal/non-normal/emergency).

The term "emergency" used alone refers to declarations and non-AOM procedures.

FLT 2.2.27

The Operator shall ensure flight crew members complete training and, when applicable, an evaluation, that includes a demonstration of competence in normal and non-normal procedures and maneuvers, to include, as a minimum, rejected takeoff, emergency evacuation, engine failure and/or those procedures and maneuvers specified in the Operator's AQP/ATQP/EBT as approved or accepted by the Authority. Such training and, when applicable, evaluation shall be accomplished *either*:

- (i) During initial training and subsequently during recurrent training once every 12 months, *or*
- (ii) If applicable, in accordance with an AQP, an ATQP or EBT approved by the Authority that requires evaluations to be satisfactorily completed within the maximum evaluation period delineated in, as applicable, [Table 2.7](#) or [Table 2.8](#), and includes a demonstration of competence in normal and non-normal procedures and maneuvers. **(GM)**

Auditor Actions

- ☐ **Identified/Assessed** requirement for training/evaluation including a demonstration of competence in normal/non-normal procedures/maneuvers in flight crew training/evaluation program.

- ☐ **Identified/Assessed** flight crew AQP/ATQP/EBT (if applicable): (focus continuing qualification recurrent schedule for training/evaluation in normal/non-normal procedures/maneuvers).
- ☐ **Interviewed** responsible manager(s) in flight operations.
- ☐ **Examined** selected initial/recurrent training/qualification course curricula/syllabi (focus: training/evaluation in specified normal/non-normal procedures/maneuvers).
- ☐ **Examined** selected flight crew member training/qualification records (focus: completion of initial/recurrent training/evaluation in the specified normal/non-normal procedures/maneuvers).
- ☐ **Observed** flight simulator operations (focus: training/evaluation in performance of normal/non-normal procedures/maneuvers).
- ☐ **Other Actions** (Specify)

Guidance

The intent of this provision is to define the basic initial and subsequent recurrent training and evaluation cycles that ensure flight crew members are competent to perform normal and non-normal procedures and maneuvers. It is understood that competence in all potential normal and non-normal procedures may not be demonstrated annually but in accordance with a schedule that is acceptable to the Authority.

The modification of qualification intervals in accordance with an AQP, ATQP or EBT program requires conformity with [FLT 2.1.1B](#).

Training and, when applicable, a demonstration of competence in specified normal and non-normal procedures and maneuvers is applicable to all *pilot* crew members.

Training and, when applicable, evaluation is accomplished as part of ground, simulator/aircraft and line training;

Line training is in normal procedures/maneuvers only.

An evaluation of competence in the normal and non-normal procedures and maneuvers specified is applicable when such procedures and/or maneuvers are stipulated by the operator and/or State in conjunction with State-approved or State-accepted training courses that require a method of evaluation. Such courses typically include:

- Type qualification;
- Transition (conversion);
- Upgrade to PIC;
- Re-qualification;
- Recurrent training.

Operators that conduct training flights and cannot safely train/evaluate a non-normal procedure or maneuver in an aircraft or in a representative flight simulator as specified in [FLT 2.2.38](#) may demonstrate an alternative means of conformance in accordance with [FLT 2.2.41](#).

All pilot flight crew members who receive training in the normal and non-normal procedures and maneuvers specified in this provision also demonstrate competence in such procedures and maneuvers in accordance with the applicable specifications of [FLT 2.3.2](#).

FLT 2.2.29

The Operator shall ensure flight crew members, before starting line training, have successfully completed an Operator proficiency evaluation administered by an Evaluator of the Operator or a representative of the Authority, and have demonstrated the skill and knowledge level adequate for operating the aircraft at or above the standards stipulated in the training syllabus. **(GM)**

Auditor Actions

- ☐ **Identified/Assessed** requirement for a final evaluation prior to a flight crew member commencing line flight training.
- ☐ **Interviewed** responsible manager(s) in flight operations.

- ❑ **Examined** syllabus for final evaluations of flight crew members prior to line flight training (focus: demonstration of skill/knowledge adequate to operate the aircraft at or above the standards stipulated in the training syllabus; definition of evaluation criteria).
- ❑ **Examined** selected flight crew member training/qualification records (focus: successful completion of final evaluation conducted by an evaluator prior to commencing line flight training).
- ❑ **Other Actions** (Specify)

Guidance

An evaluation in conjunction with Initial Type Qualification satisfies the specifications in this provision.

FLT 2.2.31

The Operator shall ensure flight crew members complete a Line Operational Simulation (LOS) profile during initial simulator or aircraft training, and subsequently during recurrent training either once every 12 months or, if applicable, in accordance with the continuing qualification schedule as defined in the Operator's AQP/ATQP/EBT that conforms to the specifications of [FLT 2.1.1B](#). Such training shall be:

- (i) Approved or accepted by the State;
- (ii) Administered real-time in a line environment setting;
- (iii) An uninterrupted planned scenario with specific CRM objectives where such skills are observed and debriefed upon completion. **(GM)**

Auditor Actions

- ❑ **Identified/Assessed** requirement for approved LOS in flight crew training/evaluation program.
- ❑ **Identified/Assessed** flight crew AQP/ATQP/EBT (if applicable): (focus continuing qualification recurrent schedule for LOS).
- ❑ **Interviewed** responsible manager(s) in flight operations.
- ❑ **Examined** criteria for administration of LOS (focus: conducted as uninterrupted scenario in real-time line environment with planned CRM objectives, CRM skills observed/briefed at completion).
- ❑ **Examined** selected initial/recurrent training/qualification course curricula/syllabi (focus: inclusion of LOS in simulator/aircraft or during line flight training).
- ❑ **Examined** selected flight crew member training/qualification records (focus: completion of LOS in initial/recurrent training).
- ❑ **Observed** flight simulator operations (focus: training using LOS profile).
- ❑ **Other Actions** (Specify)

Guidance

Refer to the IRM for the definition of [Line Operational Simulation \(LOS\)](#).

Training and/or evaluation is applicable to flight crew members.

[FLT 2.1.1B](#) addresses overall AQP/ATQP/EBT elements and specifications, as well as Authority approval/acceptance requirements.

SPOT, LOE, and/or LOFT scenarios incorporated into the training program satisfy the specifications of this provision.

LOS scenarios are as standardized and scripted as possible. A simple menu of expected weather conditions and/or normal/non-normal procedures/maneuvers would not be acceptable as this would increase the subjectivity of the presentation.

In the absence of a representative flight simulator, such alternatives typically employ:

- LOS profiles conducted in a generic simulation device or representative flight training device;
- An uninterrupted planned scenario in the aircraft with specific CRM objectives that include behavioral observation and assessment of crew performance, where such skills are observed and debriefed upon completion. This requires an operator to specify how the CRM objectives are set, evaluated and debriefed in a line environment.

The term “abnormal” is used to describe a condition or situation (e.g. abnormal airframe vibration, abnormal landing configuration).

The terms “normal” and “non-normal/emergency” typically refer to AOM checklists, procedures and/or maneuvers. The term “non-normal” includes AOM emergency checklists and/or procedures (i.e. an emergency procedure is a subset of non-normal).

The terms can also be used to describe an event, situation or operation that would be addressed by normal or non-normal/emergency procedures or checklists. When used in this manner, the terms may be separated by forward slash marks (e.g. normal/non-normal/emergency).

The term “emergency” used alone refers to declarations and non-AOM procedures.

FLT 2.2.32

The Operator shall ensure flight crew members complete training and, when applicable, an evaluation, that includes a demonstration of competence, in wind shear avoidance and recovery from predictive and actual wind shear. Such training shall be completed during initial ground and simulator training, and subsequently during recurrent simulator training either once every 36 months or, if applicable, in accordance with the continuing qualification schedule as defined in the Operator's AQP/ATQP/EBT that conforms to the specifications of [FLT 2.1.1B](#). **(GM)**

Auditor Actions

- ☐ **Identified/Assessed** requirement for training/evaluation/demonstration of competence in wind shear avoidance/recovery from predictive/actual wind shear in flight crew training/evaluation program.
- ☐ **Identified/Assessed** flight crew AQP/ATQP/EBT (if applicable): (focus continuing qualification recurrent schedule for wind shear training/evaluation).
- ☐ **Interviewed** responsible manager(s) in flight operations.
- ☐ **Examined** selected initial/recurrent training/qualification course curricula/syllabi (focus: wind shear training/evaluation/demonstration of competence).
- ☐ **Examined** selected flight crew member training/qualification records (focus: completion of initial/recurrent wind shear training/evaluation).
- ☐ **Observed** flight simulator operations (focus: training/evaluation in wind shear avoidance/recovery from predictive/actual wind shear).
- ☐ **Other Actions** (Specify)

Guidance

Refer to the IRM for the definition of [Wind Shear](#).

The intent of this provision is to ensure training and evaluation occurs, as applicable, in the maneuvers specified within the intervals specified. Such training and evaluation can occur in conjunction with any State-approved or State-accepted training course.

[FLT 2.1.1B](#) addresses overall AQP/ATQP/EBT elements and specifications, as well as Authority approval/acceptance requirements.

Training and, when applicable, an evaluation in the specified normal and non-normal procedures and maneuvers is applicable to all *pilot* crew members.

Training is accomplished in a representative flight simulator approved for the purpose by the State.

Such evaluation of competence in the normal and non-normal procedures and maneuvers specified is applicable when such procedures and/or maneuvers are stipulated by the operator and/or State in conjunction with State-approved or State-accepted training courses that require a method of evaluation. Such courses typically include:

- Type qualification;
- Transition (conversion);
- Upgrade to PIC;
- Re-qualification;
- Recurrent training.

Training and evaluation of the non-normal procedures and maneuvers specified in this provision cannot be safely accomplished in an aircraft on a training flight (see [FLT 2.2.38](#)).

Operators that cannot conform to the specifications of this provision due to the non-existence of a representative flight simulator may demonstrate an alternative means of conforming to these specifications in accordance with [FLT 2.2.41](#).

The additional ground and line training and evaluation used to satisfy the specifications of this provision and of [FLT 2.2.41](#) in the absence of a representative flight simulator typically include a review of:

- Conditions conducive to wind shear;
- Effects on aircraft performance;
- Indications of wind shear presence;
- Avoidance and recovery techniques;
- Wind shear case studies or scenarios.

FLT 2.2.33

The Operator shall ensure flight crew members complete training and an evaluation, which includes a demonstration of competence in terrain awareness procedures and maneuvers. Such training shall be completed during initial ground and simulator training and subsequently during recurrent simulator training either once every 36 months or, if applicable, in accordance with the continuing qualification schedule as defined in the Operator's AQP/ATQP/EBT that conforms to the specifications of [FLT 2.1.1B](#). Such training and evaluation shall include:

- (i) Knowledge and conduct of associated procedures;
- (ii) Response to GPWS alerts and warnings;
- (iii) The avoidance of Controlled Flight Into Terrain (CFIT). **(GM)**

Auditor Actions

- ☐ **Identified/Assessed** requirement for training/evaluation/demonstration of competence in terrain awareness procedures/maneuvers in flight crew training/evaluation program.
- ☐ **Identified/Assessed** flight crew AQP/ATQP/EBT (if applicable): (focus continuing qualification recurrent schedule for training/evaluation in terrain awareness procedures/maneuvers).
- ☐ **Interviewed** responsible manager(s) in flight operations.
- ☐ **Examined** selected initial/recurrent training/qualification course curricula/syllabi (focus: training/evaluation in terrain awareness procedures/maneuvers; definition of subjects addressed).
- ☐ **Examined** selected flight crew member training/qualification records (focus: completion of initial/recurrent training/evaluation in terrain awareness procedures/maneuvers).
- ☐ **Observed** line flight and flight simulator operations (focus: terrain awareness procedures/maneuvers).
- ☐ **Other Actions** (Specify)

Guidance

The intent of this provision is to ensure training and evaluation occurs, as applicable, in the maneuvers specified within the intervals specified. Such training and evaluation can occur in conjunction with any State-approved or State-accepted training course.

[FLT 2.1.1B](#) addresses overall AQP/ATQP/EBT elements and specifications, as well as Authority approval/acceptance requirements.

Training and evaluation in the specified normal and non-normal procedures and maneuvers in a representative flight simulator approved for the purpose by the State is applicable to *pilot* crew members.

Training and evaluation of the non-normal procedures and maneuvers specified in this provision cannot be safely accomplished in an aircraft on a training flight (see [FLT 2.2.38](#)).

Operators that cannot conform to the specifications of this provision due to the non-existence of a representative flight simulator may demonstrate an alternative means of conforming to these specifications in accordance with [FLT 2.2.41](#).

The additional ground and line training and evaluation used to satisfy the specifications of this provision and of [FLT 2.2.41](#) in the absence of a representative flight simulator typically includes a review of:

- CFIT avoidance techniques;
- CFIT recovery techniques and maximizing aircraft performance;
- GPWS alerts and warnings;
- CFIT case studies or scenarios.

FLT 2.2.34

If the Operator conducts low visibility operations (LVO), the Operator shall ensure flight crew members complete training and an evaluation that includes a demonstration of competence in such operations, as well as operations with inoperative ground based and/or aircraft equipment. Such training shall be completed during initial ground and simulator training and subsequently during recurrent simulator training either once every 12 months or, if applicable, in accordance with the continuing qualification schedule as defined in the Operator's AQP/ATQP/EBT that conforms to the specifications of [FLT 2.1.1B](#). (GM)

Auditor Actions

- ☐ **Identified/Assessed** requirement for training/evaluation/demonstration of competence in LVO and/or operations with inoperative ground based/aircraft equipment in flight crew training/evaluation program.
- ☐ **Identified/Assessed** flight crew AQP/ATQP/EBT (if applicable): (focus continuing qualification recurrent schedule for training/evaluation in LVO and/or operations with inoperative ground based/aircraft equipment).
- ☐ **Interviewed** responsible manager(s) in flight operations.
- ☐ **Examined** selected initial/recurrent training/qualification course curricula/syllabi (focus: training/evaluation in LVO and/or operations with inoperative ground based/aircraft equipment).
- ☐ **Examined** selected flight crew member training/qualification records (focus: completion of initial/recurrent training/evaluation in LVO and/or operations with inoperative ground based/aircraft equipment).
- ☐ **Observed** flight simulator operations (focus: training in LVO).
- ☐ **Other Actions** (Specify)

Guidance

Refer to the IRM for the definition of [Low Visibility Operations \(LVO\)](#).

[FLT 2.1.1B](#) addresses overall AQP/ATQP/EBT elements and specifications, as well as Authority approval/acceptance requirements.

Training and evaluation in low visibility operations is applicable to all *pilot* crew members.

For the purposes of this provision, low visibility operations are considered in effect when the Runway Visual Range (RVR) is below 400 m for takeoff and/or below Category I limits for landing.

Operators that conduct training flights and cannot safely train/evaluate the specified procedures in an aircraft or in a representative flight simulator as specified in [FLT 2.2.38](#) may demonstrate an alternative means of conformance in accordance with [FLT 2.2.41](#).

FLT 2.2.35

The Operator shall ensure flight crew members with duties and responsibilities related to TCAS/ACAS alerting equipment complete training and an evaluation that includes a demonstration of competence in maneuvers and procedures for the proper response to TCAS/ACAS alerts. Such training and evaluation shall be completed during initial ground and simulator training and subsequently during recurrent simulator training either once every 36 months or, if applicable, in

accordance with the continuing qualification schedule as defined in the Operator's AQP/ATQP/EBT that conforms to the specifications of [FLT 2.1.1B](#). **(GM)**

Auditor Actions

- ❑ **Identified/Assessed** requirement for training/evaluation/demonstration of competence in procedures for proper response to TCAS/ACAS alerts in flight crew training/evaluation program.
- ❑ **Identified/flight** crew AQP/ATQP/EBT (if applicable): (focus continuing qualification recurrent schedule for training/evaluation in response to TCAS/ACAS alerts).
- ❑ **Interviewed** responsible manager(s) in flight operations.
- ❑ **Examined** selected initial/recurrent training/qualification course curricula/syllabi (focus: training/evaluation in procedures for proper response to TCAS/ACAS alerts).
- ❑ **Examined** selected flight crew member training/qualification records (focus: completion of initial/recurrent training/evaluation in procedures for proper response to TCAS/ACAS alerts).
- ❑ **Observed** flight simulator operations (focus: training/evaluation in response to TCAS/ACAS alerts).
- ❑ **Other Actions** (Specify)

Guidance

The intent of this provision is to ensure training and evaluation occurs, as applicable, in the maneuvers specified within the intervals specified. Such training and evaluation can occur in conjunction with any State-approved or State-accepted training course.

[FLT 2.1.1B](#) addresses overall AQP/ATQP/EBT elements and specifications, as well as Authority approval/acceptance requirements.

Training is accomplished in a representative flight simulator approved for the purpose by the State.

TCAS training may be performed without demonstrating capability in a simulator (since many simulators do not have TCAS capability).

Training and evaluation of the non-normal procedures and maneuvers specified in this provision cannot be safely accomplished in an aircraft on a training flight (see [FLT 2.2.38](#)).

Operators that cannot conform to the specifications of this provision due to the non-existence of a representative flight simulator may demonstrate an alternative means of conforming to these specifications in accordance with [FLT 2.2.41](#).

The additional ground and line training and evaluation used to satisfy the specifications of this provision and of [FLT 2.2.41](#) in the absence of a representative flight simulator typically include a review of:

- TCAS procedures and alert responses;
- TCAS alerts;
- TCAS case studies or scenarios.

FLT 2.2.38

If the Operator conducts training flights, the Operator shall specify those required maneuvers and procedures that cannot be safely accomplished in an aircraft, and ensure such maneuvers and procedures are either trained and evaluated in a representative flight simulator or, if such a synthetic device does not exist, ensure a demonstration of pilot competence in those maneuvers and procedures using an alternative means in accordance with [FLT 2.2.41](#). Maneuvers and procedures that cannot be safely accomplished in an aircraft shall include, as a minimum:

- (i) Wind shear avoidance and recovery;
- (ii) Response to GPWS alerts and warnings and the avoidance of Controlled Flight Into Terrain (CFIT);
- (iii) Response to TCAS/ACAS alerts. **(GM)**

Note: If a representative flight simulator exists, conformity with [FLT 2.2.32](#), [FLT 2.2.33](#) and [FLT 2.2.35](#) is required for the Operator to be in conformity with this provision.

Note: If a representative flight simulator does not exist, conformity with [FLT 2.2.41](#) is required for the Operator to be in conformity with this provision.

Auditor Actions

- ❑ **Identified/Assessed** designation of required maneuvers/procedures that cannot be accomplished in an aircraft, requirement for flight crew training/evaluation in such maneuvers/procedures in an approved representative flight training device or using alternative means in accordance with [FLT 2.2.41](#).
- ❑ **Interviewed** responsible manager(s) in flight operations.
- ❑ **Examined** aircraft training/qualification curriculum/syllabus (focus: exclusion of specified maneuvers from aircraft training).
- ❑ **Examined** selected flight crew member training/qualification records (focus: completion of specified maneuvers in an approved representative training device or via alternative means).
- ❑ **Other Actions** (Specify)

Guidance

Refer to the IRM for the definition of [Flight Simulator](#).

The intent of this provision is to ensure both of the following:

- The maneuvers and procedures that cannot be safely accomplished in an aircraft are specified by the operator and include, as a minimum, those maneuvers specified in i), ii) and iii);
- A demonstration of pilot competence in the specified maneuvers and procedures using either a representative flight simulator or an alternative means (as specified in [FLT 2.2.41](#)) if such flight simulator does not exist.

Training is accomplished in a representative flight simulator approved for the purpose by the State.

Refer to [FLT 2.2.41](#) if no representative flight simulator exists for the aircraft type.

Refer to [FLT 2.2.32](#), [FLT 2.2.33](#), [FLT 2.2.35](#) and associated Guidance for additional specifications and information related to the training and evaluation on the specified maneuvers.

FLT 2.2.41

If the Operator conducts training flights and is unable to train and evaluate the required maneuvers and procedures specified in [FLT 2.2.38](#) due to the non-existence of a representative flight simulator, the Operator shall utilize an alternative means for ensuring a demonstration of pilot competence in such maneuvers and procedures. Any alternative means shall be approved or accepted by the State, and require a demonstration of competence through a combination of means, to include:

- (i) The use of generic flight simulators;
- (ii) The use of representative and/or generic flight training devices;
- (iii) Additional ground and line training and evaluation;
- (iv) As applicable, any other means that ensures a demonstration of pilot competence in the applicable maneuvers and procedures. **(GM)**

Auditor Actions

- ❑ **Identified/Assessed** requirement for flight crew demonstration of competence utilizing alternative means for required maneuvers/procedures that cannot be accomplished in an aircraft or due to the non-availability of a representative flight training device.
- ❑ **Interviewed** responsible manager(s) in flight operations.
- ❑ **Examined** applicable training/qualification curriculum/syllabus (focus: training/evaluation in designated maneuvers accomplished; definition of acceptable alternative means of training).
- ❑ **Examined** selected flight crew member training/qualification records (focus: demonstration of competence in designated maneuvers completed utilizing alternative means).
- ❑ **Other Actions** (Specify)

Guidance

Refer to the IRM for the definition of [Flight Training Device \(FTD\)](#).

The intent of this provision is for the operator to ensure, in the absence of a representative flight simulator necessary to conform to [FLT 2.2.38](#), that suitable and effective alternatives are utilized for the training and evaluation of maneuvers and procedures that cannot be safely conducted in an aircraft.

It is important to note that conformity with this provision requires a *combination* of alternative training and evaluation methods to ensure a demonstration of pilot competence (i.e. generic simulators and/or flight training devices, ground training/evaluation, line training/evaluation, other). This requirement is based on the presumption that any one method when used alone would be inadequate to ensure competence in the specified maneuvers as well as associated procedures.

Wind shear, GPWS, and TCAS training maneuvers and procedures, as specified in [FLT 2.2.38](#), cannot be safely accomplished in an aircraft during a training flight or line training.

Refer to [FLT 2.2.32](#), [FLT 2.2.33](#), [FLT 2.2.35](#) and associated Guidance for additional specifications and information related to the required training and evaluation associated with:

- Wind shear avoidance and recovery;
- Response to GPWS alerts and warnings and the avoidance of Controlled Flight Into Terrain (CFIT);
- Response to TCAS/ACAS alerts.

FLT 2.2.42

If the Operator transports passengers or supernumeraries, the Operator shall ensure flight crew members complete security training as approved or accepted by the State, and in accordance with the Operator's security training program as specified in [SEC 2.1.1](#). Such training shall be completed during initial ground training and subsequently during recurrent training either a minimum of once every 36 months or, if applicable, in accordance with the continuing qualification schedule as defined in the Operator's AQP/ATQP/EBT that conforms to the specifications of [FLT 2.1.1B](#). Flight crew security training shall address the following subject areas:

- (i) Determination of the seriousness of the occurrence;
- (ii) Crew communication and coordination;
- (iii) Appropriate self-defense responses;
- (iv) Use of non-lethal protective devices assigned to crew members for use as authorized by the State;
- (v) Understanding the behavior of terrorists so as to facilitate the ability to cope with hijacker behavior and passenger responses;
- (vi) Situational training exercises regarding various threat conditions;
- (vii) Flight deck procedures to protect the aircraft;
- (viii) Aircraft search procedures;
- (ix) As practicable, guidance on least-risk bomb locations. **(GM)**

Note: *Flight crew members shall complete initial security training prior to being assigned to operational duties.*

Note: *The specifications of this provision are applicable to flight crew members utilized on board an aircraft during commercial and/or non-commercial operations.*

Auditor Actions

- ☐ **Identified/Assessed** flight crew security training program (focus: approval/acceptance by the State; meets applicable requirements of other states).
- ☐ **Identified/Assessed** flight crew AQP/ATQP/EBT (if applicable): (focus continuing qualification recurrent schedule for flight crew security training).
- ☐ **Interviewed** responsible manager(s) in flight operations.

- ☐ **Examined** selected initial/recurrent training/qualification course curricula/syllabi (focus: security training is included; required subjects are addressed).
- ☐ **Examined** selected flight crew member training/qualification records (focus: completion of security training).
- ☐ **Other Actions** (Specify)

Guidance

Refer to the IRM for the definitions of [Air Operator Security Program \(AOSP\)](#) and [Non-Lethal Protective Device](#).

Flight crew members are directly involved in the implementation of security measures and thereby require an awareness of obligations to the Security Program of the operator.

Crew security training would normally be in accordance with applicable regulations and/or the civil aviation security program of the State, and where no regulatory guidance exists, in accordance with the policy of the operator.

Security training for flight crew members typically focuses on the need for the flight crew to maintain control of the flight deck.

Specific subject areas included in recurrent security training are typically identified and derived from an analysis of actual or likely situations or trends experienced during line operations.

Training as specified in item v) typically addresses topics or tactics as appropriate for the operator that might be associated with or could be used to facilitate crew-passenger reaction to or interaction with hijackers (e.g. conflict management, use of passive or non-passive cooperation, understanding Stockholm Syndrome, identification of and response to hijacker types/motives).

Training exercises as specified in item vi) are typically interactive in nature, and scenarios or situations (e.g. bomb threat, hijacking, unruly passenger) may be presented using various accepted training methods (e.g. live role playing, table top, computer-based training).

Training as specified in item ix) is applicable to aircraft types that have designated least-risk bomb locations.

2.3 Line Qualification

FLT 2.3.1

The Operator shall have a line qualification program consisting of line training and, where applicable, evaluations, approved or accepted by the State, which ensures flight crew members are qualified to operate in areas, on routes or route segments and into the airports to be used in operations for the Operator. Such program shall:

- (i) Be published in the Training Manual or equivalent documents;
- (ii) Ensure each pilot flight crew member has adequate knowledge of the elements specified in [Table 2.5](#), as applicable to the areas, routes and route segments of intended operation;
- (iii) Specify qualification requirements for operations in all areas, on all routes or route segments, and into all airports of intended use;
- (iv) Ensure line training and evaluation for each pilot crew member is completed during initial qualification and, if applicable, in accordance with the continuing qualification curriculum as defined in the Operator's AQP/ATQP/EBT that conforms to the specifications of [FLT 2.1.1B](#);
- (v) Ensure line training and evaluation is completed prior to a pilot crew member being used as a PIC in operations. **(GM)**

Auditor Actions

- ☐ **Identified/Assessed** flight crew line qualification training/evaluation program, approved/accepted by the State, specifies qualification requirements for operations associated with areas/routes/route segments/airports used in operations.
- ☐ **Identified/Assessed** flight crew AQP/ATQP/EBT (if applicable): (focus continuing qualification schedule for line training/evaluation).
- ☐ **Interviewed** responsible manager(s) in flight operations.

- ❑ **Examined** flight crew line qualification initial/recurrent curricula/syllabi (focus: line training/evaluation in areas/airports of operations; program elements consistent with specifications in [Table 2.5](#)).
- ❑ **Examined** selected flight crew member training/qualification records (focus: completion of initial/recurrent line qualification training/evaluation).
- ❑ **Observed** line flight operations (focus: flight crew demonstrates knowledge of relevant operational requirements).
- ❑ **Other Actions** (Specify)

Guidance

The intent of this provision is to ensure flight crew members are qualified to conduct routine operations within each theater of operation as defined by the operator. It does not address the additional and specialized knowledge required to conform to [FLT 2.4.1](#).

Refer to [FLT 2.4.1](#) and associated Guidance for additional specifications and information that addresses special areas, routes route segments and special airports.

[FLT 2.1.1B](#) addresses overall AQP/ATQP/EBT elements and specifications, as well as approval/acceptance requirements of the Authority.

This specification in item v) applies to all candidates for the position of PIC, to include SIC upgrade candidates and pilots hired directly into PIC positions in operations for the operator.

The training and evaluation specified in this provision is accomplished by pilot flight crew members as part of; ground training, simulator/aircraft training or line training.

FLT 2.3.2

The Operator shall ensure each pilot flight crew member, in order to maintain qualification, receives training and, when applicable, successfully completes an evaluation at or above the standards stipulated in the training syllabus and administered by an Evaluator of the Operator or a representative of the Authority, and demonstrates piloting technique and competence to execute emergency procedures and comply with instrument flight rules. Such training and, when applicable, evaluation shall be conducted in accordance with the requirements of the State and applicable authorities to ensure evaluations for all pilot flight crew members are conducted utilizing one or more of the following intervals, as applicable:

- (i) For the PIC, twice within any period of one year plus or minus one calendar month from the original qualification anniversary date or base month, **and/or**
- (ii) For pilot crew members other than the PIC, in accordance with i), or once within any period of one year plus or minus one calendar month from the original qualification anniversary date or base month, **and/or**
- (iii) For any pilot crew member participating in an AQP, ETQP or EBT program, once within any period of one year, or other period approved or accepted by the State, provided such training and qualification program incorporates all elements and specifications contained in [Table 2.6](#), [Table 2.7](#) and [Table 2.8](#). **(GM)**

Auditor Actions

- ❑ **Identified/Assessed** requirement for flight crew continuing qualification that includes a demonstration of piloting technique and competence to execute emergency procedures and comply with instrument flight rules; definition of continuing training/evaluation interval(s).
- ❑ **Identified/Assessed** flight crew AQP/ATQP/EBT (if applicable): (focus continuing qualification schedule for demonstration of piloting technique and competence to execute emergency procedures and comply with instrument flight rules).
- ❑ **Interviewed** responsible manager(s) in flight operations.
- ❑ **Examined** selected recurrent training/qualification course curricula/syllabi (focus: training/evaluation in emergency procedures/compliance with instrument flight rules).

- ❑ **Examined** selected flight crew training/qualification records (focus: completion of continuing qualification training/evaluation at intervals as specified).
- ❑ **Other Actions** (Specify)

Guidance

Refer to the IRM for definitions of [Base Month](#), [Calendar Month](#), [LOE](#) and [Training to Proficiency](#).

The modification of qualification intervals in accordance with an AQP, ATQP or EBT program requires conformity with [FLT 2.1.1B](#).

The intent of this provision is to define the conditions necessary for a pilot crewmember to maintain qualification and to set a basic qualification interval, which may be slightly modified in accordance with the specifications of the provision or conditions stipulated in guidance material.

The specifications of this provision are minimum requirements and might be exceeded by requirements of the State or other applicable authorities. The applicable authorities specified in this provision typically refer to authorities that have jurisdiction over international operations conducted by an operator over the high seas or the territory of a state that is other than the State of the Operator.

An operator, in accordance with the requirements of the State and other applicable authorities, may adjust the frequency of evaluations specified in item i) of this provision to minimize overlap, preserve the original qualification date, and ensure evaluations are completed within the annual cycle set forth by the operator, State and/or applicable authorities.

Providing a minimum of two simulator training sessions within a thirteen-month period typically satisfies the requirements of item i) if the interval between training sessions is not less restrictive than what is specified by the operator, State and/or applicable authorities.

The evaluation cycles specified in items i) and ii) of this provision may be completed in 13 months in accordance with State requirements that allow such cycle to be adjusted a maximum of plus or minus one calendar month from the original qualification anniversary date or base month. Such flexibility is normally incorporated in the training and evaluation program to allow for latitude in the trainee scheduling process.

The evaluation cycles specified in items i) and ii) of this provision may also be adjusted in accordance with State requirements that ensure each flight crew member undergoes training and, when applicable, an evaluation at least every 6 or 12 calendar months, as applicable. If the training and evaluation, however, is conducted within 3 calendar months prior to the expiry of the 6-calendar month period in the case of item i) or the 12 calendar months period in the case of item ii), the next training and evaluation must be completed within 6 or 12 calendar months, respectively, of the original expiry date of the previous training and evaluation.

Accommodations made to adjust evaluation cycles or frequency may not affect the original anniversary date or base month when flight crew member qualification was *either*:

- First established, or
- Re-established following a period of extended absence, and subject to the satisfactory completion of a training program designed specifically for the re-qualification of flight crew members following an extended absence.

One of the evaluations specified in item i), in a 12-calendar month period, may be administered by an instructor, trained and authorized by the operator and the Authority, during the conduct of a simulator or aircraft training course, approved or accepted by the Authority, for the purpose of maintaining piloting technique and competence.

One of the evaluations specified in item ii), in a 24-calendar month period, may be administered by an instructor, trained and authorized by the operator and the Authority, during the conduct of a simulator or aircraft training course, approved or accepted by the Authority, for the purpose of maintaining piloting technique and competence.

Simulator or aircraft training courses approved or accepted by the Authority for the purpose of maintaining piloting technique and competence typically include one or more of the following elements:

- Training-to-proficiency at the pilot controls of an aircraft or aircraft simulator;
- Appropriate briefings before and after the training;

- LOE utilizing a complete flight crew;
- Maneuvers and procedures (abnormal and emergency) that may occur in line operations.

The term “abnormal” is used to describe a condition or situation (e.g. abnormal airframe vibration, abnormal landing configuration).

The terms “normal” and “non-normal/emergency” typically refer to AOM checklists, procedures and/or maneuvers. The term “non-normal” includes AOM emergency checklists and/or procedures (i.e. an emergency procedure is a subset of non-normal).

The terms can also be used to describe an event, situation or operation that would be addressed by normal or non-normal/emergency procedures or checklists. When used in this manner, the terms may be separated by forward slash marks (e.g. normal/non-normal/emergency).

The term “emergency” used alone refers to declarations and non-AOM procedures.

FLT 2.3.4

The Operator shall ensure pilot flight crew members complete an evaluation that includes a demonstration of knowledge of the operations approved as part of the Air Operator Certificate (AOC) during initial training and subsequently during recurrent training either once every 12 months or, if applicable, in accordance with the continuing qualification schedule as defined in the Operator's AQP/ATQP/EBT that conforms to the specifications of [FLT 2.1.1B](#). Such evaluation shall include a demonstration of knowledge of:

- Approaches authorized by the Authority;
- Ceiling and visibility requirements for takeoff, approach and landing;
- Allowance for inoperative ground components;
- Wind limitations (crosswind, tailwind and, if applicable, headwind). **(GM)**

Auditor Actions

- ☐ **Identified/Assessed** requirement for flight crew initial/continuing qualification that includes a demonstration of knowledge of operations approved as part of the AOC.
- ☐ **Identified/Assessed** flight crew AQP/ATQP/EBT (if applicable): (focus continuing qualification recurrent schedule for demonstration of knowledge of AOC operations).
- ☐ **Interviewed** responsible manager(s) in flight operations.
- ☐ **Examined** flight crew line qualification initial/recurrent curricula/syllabi (focus: evaluation of relevant operational knowledge; definition of operational areas addressed).
- ☐ **Examined** selected flight crew training/qualification records (focus: completion of initial/continuing qualification training/evaluation).
- ☐ **Other Actions** (Specify)

Guidance

[FLT 2.1.1B](#) addresses overall AQP/ATQP/EBT elements and specifications, as well as Authority approval/acceptance requirements.

The training and evaluation specified in this provision is accomplished by pilot flight crew members as part of ground, simulator/aircraft or line training.

The specifications of this provision are normally satisfied during line training but can occur elsewhere in the training program.

The wind limitations specified in item iv) refer to maximum limits that have been demonstrated for takeoff and landing, as well as limits that have been established for the type of operation being conducted (e.g., as applicable, automatic landing, HUD/EVS guided, or contaminated runway).

FLT 2.3.6

The Operator shall ensure pilot flight crew members complete a Command Training and Evaluation program during initial training and qualification and, if applicable, in accordance with the continuing qualification curriculum as defined in the Operator's AQP/ATQP/EBT that conforms to the specifications of [FLT 2.1.1B](#). Such training and evaluation shall be completed prior to a pilot flight crew member being assigned as PIC in operations. **(GM)**

Auditor Actions

- ☐ **Identified/Assessed** requirement for PIC command training/evaluation program.
- ☐ **Identified/Assessed** flight crew AQP/ATQP/EBT (if applicable): (focus continuing qualification recurrent schedule for PIC command training/evaluation).
- ☐ **Interviewed** responsible manager(s) in flight operations.
- ☐ **Examined** selected flight crew training/qualification records (focus: completion of command training/evaluation prior to assignment to PIC duties).
- ☐ **Other Actions** (Specify).

Guidance

[FLT 2.1.1B](#) addresses overall AQP/ATQP/EBT elements and specifications, as well as Authority approval/acceptance requirements.

The specifications of this provision apply to all candidates for the position of PIC, to include SIC upgrade candidates and pilots hired directly into PIC positions in operations for the operator.

Command training and evaluation is accomplished by pilot flight crew members as part of ground, simulator/aircraft or line training.

Command training and evaluation programs may be conducted in addition to, and/or in conjunction with, one or more of the training programs specified in [FLT 2.1.1](#).

The program specified in this provision addresses the technical and non-technical aspects of command relevant to the operations of the operator, and typically includes:

- Technical seat-specific aircraft training for the aircraft type;
- Basic operator familiarization training in subjects relevant to the PIC;
- Human performance and CRM skill training relevant to command, the relationship with other crew members and the operation as a whole (e.g. leadership, team building, conflict resolution, etc.);
- Training in the sections of the OM relevant to command, to include:
 - Authority and responsibilities of the PIC in operations for the operator;
 - Adherence to the limitations of the AOC;
 - Responsibilities relevant to the OFP and ATL;
 - Responsibilities relevant to the reporting of accidents and incidents.

2.4 Special Qualification

FLT 2.4.1

The Operator shall ensure each PIC completes training in the special skills and/or knowledge required to operate in areas and on routes or route segments over difficult terrain and/or into special airports, as designated by the State or by the operator. Such training shall be completed during initial training and prior to a flight crew member being used as a PIC, and subsequently during recurrent training once either every 12 months or, if applicable, in accordance with the continuing qualification schedule as defined in the Operator's AQP/ATQP/EBT that conforms to the specifications of [FLT 2.1.1B](#). The content of training shall ensure the PIC has adequate knowledge of the elements specified in [Table 2.5](#) as applicable to the areas, routes, route segments and special airports of intended operation. **(GM)**

Auditor Actions

- ☐ **Identified/Assessed** requirement for flight crew training in special skills/knowledge needed for operations associated with specific areas/routes/route segments/difficult terrain/airports as designated by State or operator.
- ☐ **Identified/Assessed** flight crew AQP/ATQP/EBT (if applicable): (focus continuing qualification recurrent schedule for training in special skills and knowledge required for designated operations).
- ☐ **Interviewed** responsible manager(s) in flight operations.

- ❑ **Examined** selected flight crew qualification initial/recurrent curricula/syllabi (focus: training in special skills/knowledge required for certain operations; program elements consistent with specifications in [Table 2.5](#)).
- ❑ **Examined** selected flight crew training/qualification records (focus: completion of special training for operations associated with designated areas/routes/route segments/terrain/airports).
- ❑ **Other Actions** (Specify)

Guidance

[FLT 2.1.1B](#) addresses overall AQP/ATQP/EBT elements and specifications, as well as Authority approval/acceptance requirements.

Specifications in this provision apply to candidates for the position of PIC, to include SIC upgrade candidates and pilots hired directly into PIC positions in operations for the operator.

The training specified in this provision is accomplished by pilot flight crew members as part of ground training, simulator/aircraft training or line training program.

Training requirements typically vary by state and class of special airport, but generally renewed once per 12-month period unless special airport training occurs in conjunction with the training required to conform to [FLT 2.3.2](#) or the interval is adjusted in accordance with an operator's AQP/ATQP/EBT as approved or accepted by the Authority.

Special airport and/or route qualification (if applicable) could include one or more of the following elements, as approved or accepted by the State:

- PIC review of an adequate pictorial representation (aerial photographic approach plate, video presentation, slideshows, etc.);
- Simulator training;
- Line check airmen briefing;
- PIC operation into the airport accompanied by a line check or other qualified airman;
- Exemptions for VFR operations.

The specifications of this provision address the training required to operate over difficult terrain and/or into special airports based on a determination, by the operator and/or State, that pilots require special skills or knowledge for such operations. Such training typically addresses routes and/or airports that are over or in areas:

- With mountainous terrain, including high terrain, rapidly rising terrain or terrain with steep gradients;
- With terrain that contributes to the existence of mountain waves, turbulence, high surface winds, sudden wind changes and/or other atmospheric phenomena that could affect the performance of the aircraft;
- Containing topographical variations such as ridgelines, valleys, ravines, fjords or other areas where downdrafts on the leeward or downwind side can make traversing the area or accomplishing a crosswind landing hazardous;
- Where the airport, runway and/or approach environment is difficult to identify at night due to surrounding lights;
- Where featureless or expansive terrain could contribute to optical illusions during the day or at night;
- That are devoid of lighting where airport, runway and/or approach area identification is difficult at night due to lack of visible landmarks;
- That are devoid of lighting and sole reference to external or visual cues is insufficient for the maintenance of proper aircraft attitude control;
- That require the application of any other specific skills or knowledge, as determined by the operator and/or State.

FLT 2.4.2

If the Operator engages in specialized navigation (MNPS, AMU), the Operator shall ensure flight crew members complete training or an evaluation in such operations during initial training and prior to being utilized in operations that require such specialized navigation. **(GM)**

Auditor Actions

- ☐ **Identified/Assessed** requirement for flight crew training/evaluation in specialized navigation operations (MNPS/AMU, as applicable).
- ☐ **Interviewed** responsible manager(s) in flight operations.
- ☐ **Examined** selected flight crew qualification initial curricula/syllabi (focus: training in relevant specialized navigation).
- ☐ **Examined** selected flight crew training/qualification records (focus: completion of training/evaluation in applicable specialized navigation operations prior to being utilized in such specialized operations).
- ☐ **Other Actions** (Specify)

Guidance

Refer to the IRM for the definitions of [Areas of Magnetic Unreliability \(AMU\)](#) and [Minimum Navigation Performance Specifications \(MNPS\)](#).

The training or evaluation specified in this provision is accomplished by flight crew members as part of the initial ground training, simulator/aircraft training or line training program.

The specifications of this provision apply to pilot flight crew members and, if utilized in conjunction with such operations, flight navigators.

FLT 2.4.3

If the Operator utilizes flight crew members to concurrently operate aircraft of different types, or operate variants within one type, the Operator shall have qualification processes that are approved or accepted by the State and ensure such flight crew members complete training and an evaluation that emphasizes the differences between aircraft types and variants. Such training and evaluation shall be completed during initial ground, simulator and line training, and subsequently during recurrent simulator training either once every 12 months or, if applicable, in accordance with the continuing qualification schedule as defined in the Operator's AQP/ATQP/EBT that conforms to the specifications of [FLT 2.1.1B](#). **(GM)**

Auditor Actions

- ☐ **Identified/Assessed** requirement for flight crew training/evaluation in differences between aircraft types/variants (as applicable).
- ☐ **Identified/Assessed** flight crew AQP/ATQP/EBT (if applicable): (focus continuing qualification recurrent schedule for training/evaluation in differences between aircraft types/variants).
- ☐ **Interviewed** responsible manager(s) in flight operations.
- ☐ **Examined** flight crew line qualification initial/recurrent curricula/syllabi (focus: training/evaluation in differences between relevant aircraft types/variants).
- ☐ **Examined** selected flight crew training/qualification records (focus: completion of training/evaluation in differences between aircraft types/variants).
- ☐ **Other Actions** (Specify)

Guidance

Refer to the IRM for the definitions of [Aircraft Type](#) and [Aircraft Variant](#) (within Type).

The intent of this specification is to ensure flight crew members are familiarized with the significant differences in equipment and/or procedures between concurrently operated types or variants.

The determination of variant within type is within the domain of the State as part of flight crew licensing.

FLT 2.1.1B addresses overall AQP/ATQP/EBT elements and specifications, as well as Authority approval/acceptance requirements.

Qualification processes are applicable to all flight crew members used in such operations and as defined in the IRM.

Aircraft differences that require emphasis typically include level of technology, ergonomics, operational differences and handling characteristics.

2.5 SMS Training

3 Line Operations

3.1 Common Language

☐ 3.2 Flight Crew Responsibilities

3.3 Flight Crew Qualifications

FLT 3.3.2

The Operator shall have guidance and criteria that address the pairing of inexperienced pilot crew members and ensure scheduling processes prevent inexperienced pilot flight crew members, as defined by the Operator or the State, from operating together. **(GM)**

Auditor Actions

- ☐ **Identified/Assessed** guidance/criteria that prohibit pairing of inexperienced pilot flight crew members.
- ☐ **Identified/Assessed** tracking/scheduling processes that prevent pairing of inexperienced pilot flight crew members.
- ☐ **Interviewed** responsible manager(s) in flight operations.
- ☐ **Examined** selected flight crew pairing records (focus: inexperienced flight crew members not paired together).
- ☐ **Observed** flight crew scheduling operations (focus: scheduling uses guidance/criteria that prevent pairing of inexperienced flight crew members).
- ☐ **Other Actions** (Specify)

Guidance

The definition of inexperienced pilot flight crew member typically varies depending on the operator or the State and generally refers to a minimum number of hours in aircraft type after the completion of initial training/qualification.

The specifications of this provision are intended to preclude two newly trained or inexperienced pilots from operating together in an aircraft type until they each achieve a level of experience defined by the operator or the State.

FLT 3.3.7

The Operator shall have a process to ensure flight crew member recency-of-experience requirements are satisfied as follows:

- (i) A pilot does not act as PIC or SIC of an aircraft unless *either*:
 - (a) On the same type or variant of aircraft within the preceding 90 days (120 days if under the supervision of an instructor or evaluator), that pilot has operated the flight controls during at least three takeoffs and landings in the aircraft type or in a flight simulator approved for the purpose by the appropriate authority, *or*
 - (b) On the same type or variant of aircraft within a time period acceptable to the State and applicable authorities, that pilot has operated the flight controls during the number of takeoffs and landings in the aircraft type or in a flight simulator approved

for the purpose by the appropriate authority, necessary to conform to a defined recency of experience schedule approved or accepted by the State and applicable authorities.

- (ii) A pilot does not act in the capacity of a cruise relief pilot unless, within the preceding 90 days, that pilot has *either*:
 - (a) Operated as PIC, SIC or cruise relief pilot on the same type or variant of aircraft, *or*
 - (b) Completed flying skill refresher training to include normal, abnormal and emergency procedures specific to cruise flight on the same type of aircraft or in a flight simulator approved for the purpose, and has practiced approach and landing procedures, where the approach and landing procedure practice may be performed as the PM.
- (iii) A flight engineer does not perform duties in an aircraft unless *either*:
 - (a) Within the preceding 6 months, that individual has had at least 50 hours of flight time as a flight engineer on that aircraft type aircraft, *or*
 - (b) Within the preceding 90 days, that individual has operated as a flight engineer on board that aircraft type or in a simulator of the aircraft type.
- (iv) A flight navigator or radio operator does not perform duties in an aircraft unless recency-of-experience requirements of the Operator and the State have been satisfied.
- (v) If a flight crew member does not satisfy recency-of-experience requirements in accordance with i), ii), iii) or iv), such flight crew member completes re-qualification in accordance with the Operator's training and evaluation program. **(GM)**

Auditor Actions

- ☐ **Identified/Assessed** tracking/scheduling processes that prevent flight crew members from flight duty assignment unless recency-of-experience qualification requirements are met.
- ☐ **Interviewed** responsible manager(s) in flight operations.
- ☐ **Examined** OM guidance/procedures (focus: definition of recency-of-experience qualification requirements).
- ☐ **Examined** selected flight crew training/qualification records (focus: satisfaction of recency-of-experience qualification requirements).
- ☐ **Observed** flight crew scheduling operations (focus: scheduling tracks/accounts for flight crew member recency-of-experience qualification requirements).
- ☐ **Other Actions** (Specify)

Guidance

Refer to the IRM for the definition of [Cruise Relief Pilot](#).

The specification in item i) requires the pilots to operate the flight controls: PM duties do not satisfy recency-of-experience requirements for this specification.

The term Pilot Monitoring (PM) has the same meaning as the term Pilot Not Flying (PNF) for the purpose of applying the specifications of this provision.

The specification in item i) b) may stipulate the number of takeoffs and landings to be performed according to a defined schedule in order to establish an equivalent level of recency experience. Such schedule would not have to adhere exactly to the specification in item i) a) of this provision if the level of recent experience is acceptable to the State and applicable authorities, and the PIC or SIC, as applicable, is required to operate the flight controls in order to satisfy recency-of-experience requirements.

Item v) specifies that a flight crew member whose recency has lapsed for any reason becomes unqualified and must be re-qualified by the operator. The requalification program for such a flight crewmember need not specify the same number of takeoffs and landings as the recency requirements.

Applicable authorities include those authorities that have jurisdiction over international operations conducted by an operator over the high seas or the territory of a state that is other than the State of the Operator.

The term “abnormal” is used to describe a condition or situation (e.g. abnormal airframe vibration, abnormal landing configuration).

The terms “normal” and “non-normal/emergency” typically refer to AOM checklists, procedures and/or maneuvers. The term “non-normal” includes AOM emergency checklists and/or procedures (i.e. an emergency procedure is a subset of non-normal).

The terms can also be used to describe an event, situation or operation that would be addressed by normal or non-normal/emergency procedures or checklists. When used in this manner, the terms may be separated by forward slash marks (e.g. normal/non-normal/emergency).

The term “emergency” used alone refers to declarations and non-AOM procedures.

FLT 3.3.9

The Operator shall have a process to ensure each pilot, prior to being used as a PIC in operations, is currently qualified for operations into airports of intended landing in areas, on routes or route segments to be used in operations for the Operator. If an instrument approach is required into an airport for which the PIC has not made an actual approach, the PIC shall be accompanied by a pilot flight crew member or pilot observer on the flight deck who is qualified for the airport unless any of the following conditions exist:

- (i) The approach to the airport is *not* over difficult terrain and the instrument approach procedures and aids available are similar to those with which the pilot is familiar, and the normal operating minima are adjusted by a process that adds a margin of safety that is approved or accepted by the State, or there is reasonable certainty that the approach and landing can be made in visual meteorological conditions, or
- (ii) Descent from the initial approach altitude to landing at the airport can be made by day in VMC, or
- (iii) The operator qualifies the PIC to land at the airport by means of a pictorial representation approved or accepted the Authority, or
- (iv) The airport is adjacent to another airport at which the PIC is currently qualified to land. **(GM)**

Auditor Actions

- ☐ **Identified/Assessed** tracking/scheduling processes for ensuring PICs will meet qualification requirements for airports/areas/routes to be used in operations.
- ☐ **Interviewed** responsible manager(s) in flight operations.
- ☐ **Examined** OM guidance/procedures (focus: definition of crew member qualification criteria for operations into airports/areas/routes used in operations).
- ☐ **Observed** flight crew scheduling operations (focus: scheduling accounts for PIC qualification on intended routes/airports).
- ☐ **Other Actions** (Specify)

Guidance

The specification in item i) may be satisfied by a process, approved or accepted by the State, that:

- Identifies instrument approach procedures that require the application of margins to operating minima;
- Specifies the operating margin to be applied.

The specification in item iii) may be satisfied by any pictorial representation approved or accepted for the purpose by the Authority, such as an instrument approach plate or chart.

Refer to [FLT 2.4.1](#) and associated Guidance for additional specifications and information that addresses special areas, routes, route segments and special airports.

FLT 3.3.10

The Operator shall have a process to ensure a pilot is not utilized as a PIC in operations that require the application of special skills or knowledge within areas, on routes over difficult terrain and/or into special airports, as designated by the State or by the Operator, unless, within the preceding 12 months, that pilot has *either*:

- (i) Made at least one trip as a pilot flight crew member, line check airman or observer on the flight deck on a route in close proximity and over similar terrain within the specified area(s), on the specified route and/or into the special airport, as applicable, *or*
- (ii) Fulfilled special line qualification requirements in accordance with [FLT 2.4.1](#). **(GM)**

Auditor Actions

- ☐ **Identified/Assessed** tracking/scheduling processes that prevent PICs from flight duty assignment into airports/areas and on routes/route segments that require special skills/knowledge, unless qualification requirements have been satisfied.
- ☐ **Interviewed** responsible manager(s) in flight operations.
- ☐ **Examined** OM guidance/procedures (focus: definition of PIC qualification criteria for operations into airports/areas/routes that require special knowledge/skills).
- ☐ **Observed** flight crew scheduling operations (focus: scheduling tracks/accounts for PIC qualification for routes/airports that require special knowledge/skills).
- ☐ **Other Actions** (Specify)

Guidance

Special airport and/or route/area re-qualification (if applicable) could take the form of pictorial review, simulator training, line check airmen briefing or operation into the airport accompanied by a line check airman.

The intent of this provision is to ensure the PIC has a level of knowledge of terrain, minimum safe altitudes, seasonal meteorological conditions, communication and air traffic facilities, services and procedures, search and rescue services and navigational facilities and procedures, including any long-range navigation procedures, required for safe operations.

Refer to [FLT 2.4.1](#) and associated Guidance for additional specifications and information that addresses special areas, routes route segments and special airports.

3.4 Flight Crew Scheduling

FLT 3.4.1

The Operator shall have a means to ensure flight crew members are qualified and current prior to accepting and/or being assigned to duty. Such means shall consist of:

- (i) A requirement that prohibits flight crew members from operating an aircraft if not qualified for duty in accordance with requirements contained in [Table 2.3](#);
- (ii) A scheduling process that ensures flight crew members, prior to being assigned to duty, are qualified and current in accordance with the applicable flight crew qualification requirements contained in [Table 2.3](#) and, if applicable, additional requirements of the State. **(GM)**

Auditor Actions

- ☐ **Identified/Assessed** tracking/scheduling processes that prevent flight crew members from flight duty assignment unless currently qualified in accordance with [Table 2.3](#) or other applicable requirements of the State.
- ☐ **Interviewed** responsible manager(s) in flight operations.
- ☐ **Examined** process for determining additional flight crew qualification requirements of the State.
- ☐ **Examined** selected flight crew duty assignment records (focus: satisfaction of applicable qualification requirements).

- ❑ **Observed** flight crew scheduling operations (focus: scheduling requires flight crew member qualification in accordance with [Table 2.3](#) and requirements of State).
- ❑ **Other Actions** (Specify)

Guidance

The intent of this provision is to ensure flight crew member requirements and related scheduling processes preclude operation of an aircraft by a flight crew member that is not qualified and current in accordance with the specifications of the provision.

FLT 3.4.3A

The Operator shall have a methodology for the purpose of managing fatigue-related safety risks to ensure fatigue occurring in one flight, successive flights or accumulated over a period of time does not impair a flight crew member's alertness and ability to safely operate an aircraft or perform safety-related duties. Such methodology shall consist of:

- (i) Flight time, flight duty period, duty period and rest period limitations that are in accordance with the applicable prescriptive fatigue management regulations of the State, and/or
- (ii) If applicable, the Operator's Fatigue Risk Management System (FRMS) approved or accepted by the State and established in accordance with [FLT 3.4.3B](#). **(GM)**

Auditor Actions

- ❑ **Identified/Assessed** requirements/methodology for flight crew fatigue management and/or FRMS in accordance with regulations of the State.
- ❑ **Identified/Assessed** FRMS (if applicable) (focus: approved/accepted by State, incorporates elements as specified in [FLT 3.4.3B](#)).
- ❑ **Identified/Assessed** tracking/scheduling processes (focus: processes take into account flight time/flight duty period/duty period/rest period limitations in the duty assignment of flight crew members).
- ❑ **Interviewed** responsible manager(s) in flight operations.
- ❑ **Interviewed** selected scheduling personnel.
- ❑ **Examined** selected flight crew duty assignment records (focus: examples of application of flight crew fatigue management limitations/mitigations).
- ❑ **Observed** flight crew scheduling operations (focus: scheduling includes management of fatigue-related safety risk).
- ❑ **Other Actions** (Specify)

Guidance

Refer to the IRM for the definitions of [Fatigue](#) and [Fatigue Risk Management System \(FRMS\)](#).

The intent of this provision is to ensure an operator establishes a methodology for the management of crew member fatigue in a manner that:

- Is based upon scientific principles and knowledge;
- Is consistent with the prescriptive fatigue management and/or FRMS regulations of the State;
- Precludes fatigue from endangering safety of the flight.

Where authorized by the State, the operator may use a Fatigue Risk Management System (FRMS) in accordance with [FLT 3.4.3B](#) alone or in combination with prescriptive flight time, flight duty period, duty period and rest period limitations as the means for managing fatigue-related risks.

Guidance for the implementation of an FRMS is contained in the IATA/ICAO/IFALPA Fatigue Management Guide for Airline Operators, and, as applicable, other reference documents approved or accepted by the State for the purpose of FRMS implementation (e.g. FAA, AC 120-103A–Fatigue Risk Management Systems for Aviation Safety).

FLT 3.4.3B

If the Operator utilizes an FRMS to manage flight crew fatigue-related safety risks, the Operator shall incorporate scientific principles and knowledge within the FRMS, comply with any applicable requirements for managing flight crew fatigue as established by the State or Authority and, as a minimum:

- (i) Define and document the FRMS policy;
- (ii) Incorporate risk management processes for fatigue hazard identification, risk assessment and risk mitigation;
- (iii) Develop and maintain effective FRMS safety assurance processes;
- (iv) Establish and implement effective FRMS promotion processes. **(GM)**

Auditor Actions

- ☐ **Identified/Assessed** FRMS policy/components/elements, compliance with fatigue risk management requirements of State/Authority.
- ☐ **Identified/Assessed** FRMS processes for flight crew fatigue risk management data collection/analysis/hazard identification, safety risk assessment, safety risk mitigation/control.
- ☐ **Interviewed** responsible manager(s) in flight operations.
- ☐ **Interviewed** selected personnel that perform flight crew fatigue-related safety risk management functions.
- ☐ **Examined** selected examples of fatigue risk management (focus: hazard identified, risk assessed, mitigation action developed and implemented).
- ☐ **Observed** flight crew scheduling operations (focus: scheduling includes management of fatigue-related safety risk in accordance with an approved FRMS).
- ☐ **Other** Action (Specify)

Guidance

The intent of this provision is to ensure fatigue occurring either in one flight, successive flights or accumulated over a period of time does not impair a crew member's alertness and ability to safely operate an aircraft or perform safety-related duties.

Where authorized by the State, the operator may use an FRMS as a means to determine that variations from prescriptive fatigue management policies demonstrate an acceptable level of safety. Guidance for the implementation of an FRMS is contained in the IATA/ICAO/IFALPA Fatigue Management Guide for Operators, and, as applicable, other reference documents approved or accepted by the State for the purpose of FRMS implementation (e.g. FAA, AC 120-103A—Fatigue Risk Management Systems for Aviation Safety).

The applicability of this provision is limited to those operations wherein fatigue is managed in accordance with the FRMS as defined in the operator's FRMS documentation. It is important to note, however, that an FRMS may be used alone or in combination with prescriptive flight time, flight duty period, duty period and rest period limitations as the means for managing fatigue related risks.

The components of an effective FRMS as specified in this provision are described in the following table.

FRMS Component	Item	Description
FRMS policy and documentation	(i)	<p>Policy:</p> <ul style="list-style-type: none"> • Defines FRMS Terms of Reference • Identifies scope of FRMS operations • Identifies FRMS elements • Reflects shared responsibility • States safety objectives • Declares management commitment • Identifies lines of accountability <p>Documentation:</p> <ul style="list-style-type: none"> • Policy and objectives • Processes and procedures • Accountabilities, responsibilities and authorities • Mechanism for involvement of all stakeholders • FRMS training records • Planned and actual times worked • Outputs (findings, recommendations, actions)
Fatigue risk management processes	(ii)	<ul style="list-style-type: none"> • Fatigue hazard identification (reactive/proactive/predictive processes) • Safety risk assessment • Safety risk mitigation
FRMS safety assurance processes	(iii)	<ul style="list-style-type: none"> • FRMS performance monitoring • Operational and organizational change management • Continual FRMS improvement
FRMS promotion processes	(iv)	<ul style="list-style-type: none"> • Training programs (for management, crew members and all other involved personnel under the FRMS) • Communication plan (explains FRMS policies, procedures and responsibilities to all relevant stakeholders and also describes communication channels)

FLT 3.4.4

The Operator shall consider the following as duty time for the purposes of determining required rest periods and calculating duty time limitations for operating flight crew members:

- (i) Entire duration of the flight;
- (ii) Pre-operating deadhead time;
- (iii) Training periods prior to a flight;
- (iv) Administrative or office time prior to a flight (for flight crew members that serve in a management function);
- (v) If required by the State, flight time accrued by flight crew members in operations other than those of the Operator. **(GM)**

Auditor Actions

- ☐ **Identified/Assessed** requirements/criteria used for determination of required rest periods/calculation of duty time limitations for operating flight crew members.
- ☐ **Identified/Assessed** processes used to track flight crew compliance with duty time/rest period limitations.
- ☐ **Interviewed** responsible manager(s) in flight operations.
- ☐ **Examined** selected flight crew duty assignment records (focus: application of duty time/rest period limitations).
- ☐ **Observed** flight crew scheduling operations (focus: scheduling uses defined criteria for determining required flight crew rest periods/calculating duty time limitations).
- ☐ **Other Actions** (Specify)

Guidance

Refer to the IRM for the definition of [Deadheading](#).

The intent of this provision is to ensure an operator considers non-flight duty time, or flight time accrued in operations other than those of the operator, that is likely to induce fatigue into the calculation of duty time limitations and the determination of required rest periods.

FLT 3.4.6

If the Operator utilizes flight crew members that are concurrently qualified to operate aircraft of different types, or operate variants within one type, and the State specifies unique training and/or recency requirements for such flight crew members to remain concurrently qualified, the Operator shall have a scheduling process that addresses such unique requirements, to include, as a minimum:

- (i) Required differences training (between type or variants);
- (ii) Recency of experience necessary to maintain currency on all types or variants. **(GM)**

Auditor Actions

- ☐ **Identified/Assessed** scheduling processes that address flight crew members concurrently qualified to operate aircraft of different types/variants within one type.
- ☐ **Interviewed** responsible manager(s) in flight operations.
- ☐ **Interviewed** flight crew scheduling personnel.
- ☐ **Examined** requirements/criteria applicable to concurrently qualified flight crew members (focus: differences training, recency of experience).
- ☐ **Other Actions** (Specify)

Guidance

The intent of this provision is to ensure scheduling processes address the unique State requirements (e.g. recency on each type or variant, or training on each type or variant), if any, that are necessary for flight crew members to remain concurrently qualified to operate multiple types or variants within type.

The determination of variant within type is within the domain of the State as part of flight crew licensing.

3.5 Flight Preparation

FLT 3.5.2

If the Operator utilizes aircraft with electronic navigation data capabilities, the Operator shall have guidance and procedures for flight crew members to ensure the validity of any electronic navigation database installed into aircraft navigation equipment. **(GM)**

Auditor Actions

- ☐ **Identified/Assessed** OM guidance/procedures for flight crew preflight of aircraft navigation equipment (focus: validation of any installed navigation databases; definition of validation criteria).
- ☐ **Interviewed** responsible manager(s) in flight operations.
- ☐ **Observed** line flight operations (focus: flight crew preflight navigation database validation).
- ☐ **Other Actions** (Specify)

Guidance

Where more than one database is available for use in the aircraft navigation system, an operator can ensure database validity by providing guidance for the flight crew to select the new database for use prior to the first flight on the effective date for the new database.

The operator may provide relief in the MEL, permitting flight crew use of a non-current database for a specified period of time due to database errors or faults.

3.6 Route and Airport Planning

3.7 Fuel, Weight/Mass and Balance, Flight Plans

FLT 3.7.1

The Operator shall have a fuel policy and guidance that enables the flight crew to determine the minimum dispatch/departure fuel for each phase of flight in accordance with [DSP 4.3.1](#). **(GM)**

Auditor Actions

- ☐ **Identified/Assessed** policy/OM guidance that requires flight crew to determine minimum dispatch/departure fuel. (focus: availability to flight crew; minimum dispatch/departure fuel includes fuel for phases of flight specified in [DSP 4.3.1](#)).
- ☐ **Interviewed** responsible manager(s) in flight operations.
- ☐ **Observed** line flight and flight simulator operations (focus: determination of minimum dispatch/departure fuel).
- ☐ **Other Actions** (Specify)

Guidance

[DSP 4.3.1](#) specifies the fuel categories that are typically used when defining regulatory and/or operational requirements during the flight planning process and on the OFP.

Individual aircraft fuel consumption, MEL/CDL adjustments, anticipated operational constraints (weather, de-icing, slots, etc.) are all factors normally to be considered in calculating minimum dispatch/departure fuel required.

Fuel calculations are typically made by a flight crew member, a Flight Operations Officer/Flight Dispatcher, or both.

FLT 3.7.2

The Operator shall delegate the authority to the PIC to ensure:

- (i) A flight is not commenced unless the usable fuel required in accordance with [DSP 4.3.1](#) is on board the aircraft and is sufficient to complete the planned flight safely;
- (ii) If fuel is consumed during a flight for purposes other than originally intended during pre-flight planning, such flight is not continued without a re-analysis and, if applicable, adjustment of the planned operation to ensure sufficient fuel remains to complete the flight safely. **(GM)**

Auditor Actions

- ☐ **Identified/Assessed** OM requirement for PIC to ensure required safe usable fuel on board prior to flight (focus: delegation of authority to PIC; instructions for determination of safe usable fuel).
- ☐ **Interviewed** responsible manager(s) in flight operations.

- ☐ **Observed** line flight operations (focus: determination of usable safe fuel prior to flight).
- ☐ **Other Actions** (Specify)

Guidance

Refer to the IRM for the definition of [Discretionary Fuel](#).

The intent of this provision is for the PIC to have the authority to ensure sufficient fuel is on board the aircraft to commence or continue the planned flight safely, and to be able to authorize the loading of *Discretionary Fuel* if such fuel is required for the safe conduct of the flight and will not cause operating limits to be exceeded.

In a shared system of operational control, the PIC and the Flight Dispatcher/Flight Operations Officer share the responsibility to ensure operating limitations are not exceeded and sufficient fuel is on board to commence or continue the planned flight safely.

The extent of the re-analysis or adjustment specified in item ii) is commensurate with the scope and complexity of the planned operation.

FLT 3.7.9

If the Operator conducts isolated airport operations, the Operator shall have guidance and instructions for the flight crew to:

- (i) Practically calculate or determine a point of safe return (PSR) for each flight into an isolated airport;
- (ii) Ensure the flight does not continue past the actual PSR unless a current assessment of meteorological conditions, traffic, and other operational conditions indicate that a safe landing can be made at the estimated time of use. **(GM)**

▲ An operator may conform to [FLT 3.7.9](#) through Active Implementation as long as the implementation Action Plan (IAP) projects conformance on or before 31 August 2021.

Auditor Actions

- ☐ **Identified** aircraft fleets used in isolated aerodrome operations.
- ☐ **Identified/Assessed** OM guidance/procedures for flight crew calculation/consideration of PSR for isolated airport operations (focus: instructions for calculation/re-calculation of PSR; definition of conditions that permit continuation beyond PSR).
- ☐ **Identified/Assessed** Active Implementation plan (if applicable).
- ☐ **Interviewed** responsible manager(s) in flight operations.
- ☐ **Observed** line flight operations (focus: calculation/use of PSR).
- ☐ **Other Action** (Specify)

Guidance

Refer to the IRM for the definitions of [Isolated Airport](#) and [Point of Safe Return \(PSR\)](#).

This provision, in combination with the fuel carriage requirements of [DSP 4.3.11](#), is intended to mitigate some of the risks associated with operations to isolated airports that preclude the selection and specification of a destination alternate.

A PSR is the point of last possible diversion to an en route alternate. While this point can be calculated and specified on the OFP during the flight planning stage in accordance with [DSP 4.1.7](#), such a calculation does not typically take into account discretionary fuel or the real-time changes in fuel consumption that will occur after departure. These factors typically result in an actual PSR that will be reached later in the flight than the point originally calculated on the OFP.

In order to conform to item i), an operator would provide practical instructions for the flight crew to re-calculate the position of the PSR while en route. These instructions usually involve using a fuel plotting chart or the calculating capabilities of the Flight Management System (FMS). Alternatively, the position of the actual PSR can be re-calculated by operational control personnel and relayed to the en route aircraft, which also satisfies the specification in item i).

A PSR may coincide with the Final Decision Point used in Decision Point Planning or the Pre-determined Point used in Pre-determined Point planning.

Guidance on flight planning methods including planning operations to isolated airports and guidance related to the determination of a PSR is contained in the ICAO Flight Planning and Fuel Management Manual (Doc 9976).

□ 3.8 Aircraft Preflight and Airworthiness

FLT 3.8.3

The Operator shall assign the PIC the authority to reject an aircraft prior to departure of a flight if dissatisfied with any aspect of the airworthiness and/or maintenance status of the aircraft. **(GM)**

Auditor Actions

- **Identified/Assessed** OM guidance/procedures for acceptance/rejection of aircraft based on airworthiness assessment (focus: delegation of authority to PIC; instructions for assessment of airworthiness).
- **Interviewed** responsible manager(s) in flight operations.
- **Observed** line flight operations (focus: use of ATL).
- **Other Actions** (Specify)

Guidance

The intent of this provision is to ensure that PIC acceptance of an aircraft is based on a review of the MEL/CDL, ATL and/or any other operator or State-approved sources of technical information attesting to the mechanical state of the aircraft.



FLT 3.8.7B

The Operator shall have a procedure to ensure the availability, accessibility and serviceability of aircraft flight deck systems and emergency equipment. Such procedure shall include an interior preflight inspection of systems and equipment, which, as a minimum, is conducted by the flight crew prior to the first flight:

- (i) Of the flight crew on an aircraft during a duty period;
- (ii) On an aircraft after it has been left unattended by the flight crew, unless the Operator has a process or a procedure that ensures flight deck systems and emergency equipment remain undisturbed. **(GM)**

Note: The specifications of this provision are applicable to commercial and/or non-commercial operations.

Auditor Actions

- **Identified/Assessed** OM guidance/procedures for flight crew preflight inspection of flight deck emergency systems/equipment (focus: instructions for conduct of inspection; definition of emergency systems/equipment to be included).
- **Interviewed** responsible manager(s) in flight operations.
- **Observed** line flight operations (focus: flight deck preflight inspection).
- **Other Actions** (Specify)

Guidance

The intent of this provision is for the flight crew to ensure the availability, accessibility and serviceability of aircraft flight deck systems and emergency equipment prior to flight.



Serviceability is typically assessed by checking fire extinguisher pressures, oxygen bottle pressures, PBE humidity indicators and/or other preflight checks specified by the aircraft or equipment manufacturers and documented in the operator's procedures.

3.9 Ground Handling

FLT 3.9.6

If the Operator conducts flights from any airport when conditions are conducive to ground aircraft icing, the Operator shall have de-/anti-icing policies and procedures published in the OM or in other documents that are available to the flight crew during flight preparation and accessible to the flight crew during flight. Such policies and procedures shall address any flight crew duties and responsibilities related to de-/anti-icing and include:

- (i) Holdover Time tables;
- (ii) A requirement for a member of the flight crew or qualified ground personnel to perform a visual check of the wings before takeoff, if any contamination is suspected;
- (iii) A requirement that takeoff will not commence unless the critical surfaces are clear of any deposits that might adversely affect the performance and/or controllability of the aircraft;
- (iv) A statement that delegates authority to the PIC to order De-/Anti-icing whenever deemed necessary. **(GM)**

Note: The specifications of this provision are applicable to commercial and/or non-commercial operations.

Auditor Actions

- ☐ **Identified/Assessed** OM policy/procedures for aircraft de-/anti-icing of aircraft (focus: availability/accessibility to flight crew prior to/during flight; description of flight crew authority/duties/responsibilities; statement that requires critical surfaces to be clear of ice prior to takeoff).
- ☐ **Interviewed** responsible manager(s) in flight operations.
- ☐ **Observed** line flight operations (focus: operations in ground icing conditions; de-/anti-icing operations).
- ☐ **Other Actions** (Specify)

Guidance

Refer to the IRM for the definitions of [De-/Anti-icing Program](#) and [Holdover Time](#).

The intent of this provision is to ensure flight crew members comply with the clean aircraft concept prior to takeoff anytime there is a potential for the accretion of ice on aircraft critical surfaces during ground operations.

Refer to [GRH 4.2.1](#) located in ISM Section 6 for specifications and associated guidance related to the establishment and maintenance of a De-/Anti-icing Program.

Qualified ground personnel specified in item ii) are typically used to perform a visual wing check in instances when the wings are not visible to the flight crew from the interior of the aircraft (e.g., cargo aircraft operations).

The surfaces specified in item iii) include wings, flight controls, engine inlets, fuselage surfaces in front of engines or other areas defined in the AOM.

FLT 3.9.8

If the Operator transports dangerous goods as cargo, the Operator shall ensure information and guidance that enable the flight crew to carry out duties and responsibilities related to the transport of dangerous goods is published or referenced in the OM and included in the onboard library. Such guidance shall include, as a minimum:

- (i) General policies and procedures;
- (ii) Duties and responsibilities;
- (iii) As applicable, preflight acceptance requirements;
- (iv) Flight crew written notification requirements;
- (v) Dangerous goods incident and/or emergency response procedures. **(GM)**

Auditor Actions

- ☐ **Identified/Assessed** OM guidance/procedures associated with transport of dangerous goods (focus: included in onboard library; description of flight crew duties/responsibilities; acceptance/notification requirements).
- ☐ **Interviewed** responsible manager(s) in flight operations.
- ☐ **Observed** line flight operations (focus: provision/receipt/acknowledgement of onboard dangerous goods).
- ☐ **Other Actions** (Specify)

Guidance

Refer to the IRM for the definitions of [Dangerous Goods Regulations \(DGR\)](#) and [NOTOC \(Notification to Captain\)](#).

An operator, in accordance with requirements of the Authority, typically develops flight crew guidance related to the transport of dangerous goods based on technical information from one or more source reference documents, to include:

- IATA Dangerous Goods Regulations (DGR);
- ICAO Doc. 9481 AN/928, Emergency Response Guidance for Aircraft Incidents Involving Dangerous Goods;
- An equivalent dangerous goods manual, dangerous goods emergency response guide or other reference document approved or accepted by the Authority for the development of flight crew guidance related to the transportation of dangerous goods by air.

The specification in item iii) refers to procedures and information formulated to assist each applicable flight crew member in performing or directly supervising the acceptance of dangerous goods for transport on an aircraft. Such information might include, but not limited to:

- Details and locations of cargo compartments;
- The maximum quantity of dry ice permitted in each compartment;
- If radioactive materials are to be carried, instructions on loading;
- Dangerous goods reporting requirements.

Item iii) is only applicable to flight crew members assigned such responsibilities by the State or the operator.

The specification in item iv) refers to PIC and/or flight crew duties and responsibilities related to the acquisition and review of the NOTOC (Notification to Captain).

3.10 Airspace Rules

3.11 In-Flight Operations

Navigation

FLT 3.11.4

The Operator shall ensure minimum flight altitude information applicable to all phases of a flight, including guidance that specifies when descent below any applicable prescribed minimum altitude is permissible, is made available to the flight crew along with instructions for the use of such information. **(GM)**

Auditor Actions

- ☐ **Identified/Assessed** OM guidance that specifies when descent below applicable prescribed minimum altitude is permissible (focus: availability of minimum altitude information to flight crew during flight; instructions/procedures for adherence to/descent below minimum altitudes all phases of flight).
- ☐ **Interviewed** responsible manager(s) in flight operations.

- ☐ **Observed** line flight and flight simulator operations (focus: adherence to minimum altitudes).
- ☐ **Other Actions** (Specify)

Guidance

Minimum prescribed safety altitudes typically include:

- Minimum Safety Altitude (MSA);
- Minimum Descent Altitude/Height (MDA/H);
- Minimum En route Altitude (MEA);
- Minimum Obstruction Clearance Altitude (MOCA);
- Minimum Off-Route Altitude (MORA);
- Minimum Vectoring Altitude (MVA);
- Any other minimum altitudes prescribed by the Authority.

FLT 3.11.5

The Operator shall have guidance that requires flight crews to monitor meteorological conditions during the en route phase of flight, to include current weather and forecasts for:

- (i) Destination airport;
- (ii) Destination alternate airport(s), if applicable;
- (iii) En route alternate airports(s), if applicable.

Auditor Actions

- ☐ **Identified/Assessed** OM requirement/guidance for monitoring meteorological conditions during the en route phase of flight (focus: instructions for flight crew monitoring of en route meteorological conditions, current/forecast weather for destination/alternate airports).
- ☐ **Interviewed** responsible manager(s) in flight operations.
- ☐ **Observed** line flight operations (focus: monitoring en route/airport weather conditions).
- ☐ **Other Actions** (Specify)

FLT 3.11.7

The Operator shall have guidance that requires the PIC to monitor fuel during flight to ensure a fuel quantity upon landing that is not less than final reserve fuel. **(GM)**

Auditor Actions

- ☐ **Identified/Assessed** OM requirement/guidance for monitoring en route fuel to ensure landing with not less than final reserve fuel (focus: instructions/procedure for flight crew fuel monitoring to ensure landing with final reserve fuel as specified in [DSP 4.3.12](#)).
- ☐ **Interviewed** responsible manager(s) in flight operations.
- ☐ **Observed** line flight operations (focus: en route fuel monitoring/tracking).
- ☐ **Other Actions** (Specify)

Guidance

Refer to [FLT 3.14.16](#) and [FLT 3.14.17](#) for actions to be taken by the PIC in the event the final reserve minimum fuel quantity specified in [DSP 4.3.12](#) cannot be protected in flight and preserved upon landing.

☐

FLT 3.11.9

If the Operator is authorized to conduct LVO, the Operator shall have guidance to ensure the proper conduct of such operations. Such guidance shall address, as a minimum:

- (i) Required ground and airborne equipment;
- (ii) Operating limitations and procedures;
- (iii) Crew qualifications;
- (iv) Operating minima (RVR). **(GM)**

Auditor Actions

- ☐ **Identified** authorization to conduct low visibility operations.
- ☐ **Identified/Assessed** OM guidance/procedures for the conduct of low visibility operations (focus: procedures/limitations for conduct of operations; requirements for ground/airborne equipment, crew qualifications, operating minima).
- ☐ **Interviewed** responsible manager(s) in flight operations.
- ☐ **Observed** line flight and flight simulator operations (focus: conduct of low visibility operations).
- ☐ **Other Actions** (Specify)

Guidance

The operating limitations specified in item 1) typically address crosswinds, runway condition and aircraft equipment capability.

FLT 3.11.10

If the operator conducts operations beyond 60 minutes from a point on a route to an alternate, the Operator shall have guidance that includes:

- (i) Procedures to ensure proper conduct of such operations;
- (ii) For all aircraft, a requirement for flight crews to monitor meteorological information for any en route alternates during the en route phase of a flight;
- (iii) Procedures to ensure, for aircraft with two-engines engaged in ETOPS/EDTO, the most up-to-date information provided to the flight crew indicates that conditions at identified en route alternate airports will be at or above the operator's established airport operating minima for the operation at the estimated time of use. **(GM)**

Auditor Actions

- ☐ **Identified** authorization to conduct ETOPS/EDTO/operations beyond 60 minutes from an alternate airport.
- ☐ **Identified/Assessed** OM guidance/procedures for the conduct of ETOPS/EDTO/operations beyond 60 minutes from alternate airport (focus: procedures/limitations for conduct of operations; requirements for monitoring en route alternate airport meteorological information; for two-engine aircraft, requirements for en route alternate airports).
- ☐ **Interviewed** responsible manager(s) in flight operations.
- ☐ **Observed** line flight and flight simulator operations (focus: conduct of ETOPS/EDTO/operations beyond 60 minutes from alternate airport).
- ☐ **Other Actions** (Specify)

Guidance

The intent of item ii) of this provision is to ensure flight crew are knowledgeable about diversion airport options and prevailing weather conditions appropriate for the type of operation conducted.

The intent of item iii) of this provision is to ensure a larger strategy exists to protect a diversion regardless of whether the diversion is for technical (airplane system- or engine-related) or non-technical reasons.

An operator, in accordance with requirements of the Authority, typically uses technical guidance for the conduct of operations beyond 60 minutes, from a point on a route to an en route alternate airport, including ETOPS/EDTO. Such guidance might be derived from one or more of the following source references, as applicable:

- ICAO Annex 6, Amendment 36, Attachment D: Guidance for Operations by Turbine Engine Aeroplanes Beyond 60 minutes to an En-route Alternate Aerodrome Including Extended Diversion Time Operations (EDTO);
- ICAO Flight Planning and Fuel Management Manual (Doc 9976);
- FAA Advisory Circular - AC No: 120-42B: Extended Operations (ETOPS and Polar Operations), Effective 6/13/08;

- EU-OPS AMC 20-6 rev. 2 Effective: 12/23/2010: Extended Range Operation with Two-Engine Aeroplanes, ETOPS Certification and Operation;
- Any equivalent reference document approved or accepted by the Authority for the purpose of providing guidance for the conduct of flight operations by turbine engine aircraft beyond 60 minutes to an en-route alternate airport including ETOPS/EDTO.

Flight Management and General Procedures

FLT 3.11.17

The Operator shall have a policy and procedures that define a sterile flight deck during critical phases of flight, to include:

- (i) A protocol for intra-flight deck communication;
- (ii) If the Operator conducts passenger flights with cabin crew, a protocol for communication between the flight crew and cabin crew;
- (iii) The mandatory use of headsets and boom microphones for communication with ATC;
- (iv) A restriction of flight crew activities to essential operational matters. **(GM)**

Auditor Actions

- ☐ **Identified/Assessed** OM policy/requirement/procedures for sterile flight deck (focus: procedures associated with sterile flight deck; definition of protocols/requirements/restrictions).
- ☐ **Interviewed** responsible manager(s) in flight operations.
- ☐ **Observed** line flight operations (focus: adherence to sterile flight deck).
- ☐ **Other Actions** (Specify)

Guidance

Refer to the IRM for the definition of [Sterile Flight Deck](#) and [Critical Phase of Flight](#).

The specifications of this provision require an operator to ensure the OM defines the specific phases of flight when the operational state of the flight deck is to be “sterile.”

FLT 3.11.20

The Operator shall have a policy and procedures that require flight crew members to crosscheck and confirm critical actions during normal, abnormal and emergency situations, to include:

- (i) Aircraft configuration changes (landing gear, wing flaps, speedbrakes);
- (ii) Altimeter bug and airspeed bug settings, as applicable;
- (iii) Altimeter subscale settings;
- (iv) Altitude (window) selections;
- (v) Transfer of control of the aircraft;
- (vi) Changes to the Automated Flight System (AFS)/Flight Management System (FMS) and radio navigation aids during the departure and or approach phases of flight;
- (vii) Weight/mass and balance calculations and associated AFS/FMS entries;
- (viii) Performance calculations or inputs, including AFS/FMS entries. **(GM)**

Auditor Actions

- ☐ **Identified/Assessed** OM policy/requirement/procedures for crosscheck/confirmation in performance of critical actions during normal/abnormal/emergency situations (focus: procedures for flight crew crosscheck/confirmation when performing critical actions; definition of critical actions in normal/abnormal/emergency situations).
- ☐ **Interviewed** responsible manager(s) in flight operations.
- ☐ **Observed** line flight and flight simulator operations (focus: flight crew crosscheck/confirmation when performing critical actions).
- ☐ **Other Actions** (Specify)

Guidance

The intent of this provision is to ensure flight crew actions, when considered critical to the safety of flight, are crosschecked and confirmed. It is important to note that the criticality of certain actions may be dependent on phase of flight (e.g. flap selection before takeoff).

The specification in item iii) refers to the barometric pressure setting to which altitude is referenced.

The term “abnormal” is used to describe a condition or situation (e.g. abnormal airframe vibration, abnormal landing configuration).

The terms “normal” and “non-normal/emergency” typically refer to AOM checklists, procedures and/or maneuvers. The term “non-normal” includes AOM emergency checklists and/or procedures (i.e. an emergency procedure is a subset of non-normal).

The terms can also be used to describe an event, situation or operation that would be addressed by normal or non-normal/emergency procedures or checklists. When used in this manner, the terms may be separated by forward slash marks (e.g. normal/non-normal/emergency).

The term “emergency” used alone refers to declarations and non-AOM procedures.

Altitude Awareness and Altimetry

FLT 3.11.28

The Operator shall have policies, procedures and guidance that address altitude awareness, to include:

- (i) Instructions for the use of automated or verbal flight crew altitude callouts and any other actions to be taken by the flight crew to maintain altitude awareness;
- (ii) Policies and/or procedures for the avoidance of altitude deviations;
- (iii) Policies and/or procedures that address call sign confusion during altitude clearance acceptance and readback;
- (iv) Instructions for the flight crew to report the cleared flight level on first contact with ATC, unless specifically requested not to do so by ATC. **(GM)**

Auditor Actions

- ☐ **Identified/Assessed** OM policies/guidance/procedures that address altitude awareness (focus: instruction/procedures for flight crew focus on altitude awareness; definition of strategies for avoidance of altitude deviations).
- ☐ **Interviewed** responsible manager(s) in flight operations.
- ☐ **Observed** line flight and flight simulator operations (focus: application of altitude awareness procedures).
- ☐ **Other Actions** (Specify)

Guidance

Refer to the IRM for the definition of [Altitude Deviation](#).

The intent of this provision is for the operator to provide policies, procedures and guidance in the OM designed to manage or mitigate potential risks related to the acceptance and maintenance of assigned altitudes.

As an example, OM guidance to address altitude awareness can include instructions for:

- A crosscheck that the assigned altitude is above the minimum safe altitude;
- “1000 to go” standard callout;
- Dual pilot response for ATC altitude clearance;
- “Double point” to altitude window (both pilots physically point to and confirm the new altitude set).

FLT 3.11.32

The Operator shall have guidance that enables the flight crew to correct for potential errors in altimetry and that addresses:

- (i) The effects of Outside Air Temperature (OAT) that is significantly lower than standard temperature;
- (ii) Maximum allowable barometric altimeter errors:
 - (a) Referenced to field elevation;
 - (b) Compared to other altimeters;
 - (c) Permissible to meet RVSM limitations. **(GM)**

Auditor Actions

- ☐ **Identified/Assessed** OM guidance that addresses avoidance of potential altimetry errors (focus: instructions/procedures for flight crew avoidance of barometric altimeter errors; definition of maximum allowable barometric altimeter errors).
- ☐ **Interviewed** responsible manager(s) in flight operations.
- ☐ **Observed** line flight operations (focus: avoidance of barometric altimeter errors).
- ☐ **Other Actions** (Specify)

Guidance

The intent of this provision is to ensure that potential errors in altimetry are identified and corrected when necessary.

The specification in item i) refers to temperature compensation corrections applied to ensure obstacle clearance in conditions of extreme cold (typically starting at -10 C). Such corrections may be applied manually by the flight crew (e.g. temperature correction charts) or automatically by onboard systems (e.g. Air Data Computer).

The operator may provide tables, charts or other means to address potential errors in altimetry.

Meteorological Conditions and Environment

FLT 3.11.38

The Operator shall have policies and procedures for operations in the proximity of adverse weather and/or environmental conditions to include:

- (i) Thunderstorms;
- (ii) Turbulence;
- (iii) Contaminated runways, including the effect of type and depth of contaminants on performance;
- (iv) Cold weather;
- (v) Volcanic ash, if the Operator conducts operations on routes that traverse large active volcanic areas or in the terminal areas of airports in the vicinity of active volcanoes. **(GM)**

Auditor Actions

- ☐ **Identified/Assessed** OM policies/procedures for operations in proximity of adverse weather/environmental conditions (focus: flight crew adverse weather/environmental conditions operating procedures; definition of adverse weather/environmental conditions).
- ☐ **Interviewed** responsible manager(s) in flight operations.
- ☐ **Observed** line flight operations (focus: operations in proximity of adverse weather/environmental conditions).
- ☐ **Other Actions** (Specify)

Guidance

The intent of this provision is to ensure flight crew members have access to policies and procedures associated with the adverse weather or environmental conditions they might encounter in operations.

Active volcanic areas specified in item v) normally include the following: Pacific Ring of Fire, the Rift Valley in Africa, North and South America, Indonesia, Japan and Iceland.

FLT 3.11.39

The Operator shall have guidance that includes policies and procedures for:

- (i) Wind shear avoidance;
- (ii) Wind shear encounter recovery;
- (iii) As applicable, response to predictive and/or reactive alerts. **(GM)**

Auditor Actions

- ☐ **Identified/Assessed** OM policy/guidance for wind shear avoidance/encounter recovery/response to predictive/reactive alerts (focus: flight crew wind shear avoidance/recovery procedures).
- ☐ **Interviewed** responsible manager(s) in flight operations.
- ☐ **Observed** line flight and flight simulator operations (focus: wind shear awareness/avoidance/recovery).
- ☐ **Other Actions** (Specify)

Guidance

Refer to the IRM for the definition of [Airborne Wind shear Warning System](#), which includes definitions for [Predictive Alert](#) and [Reactive Alert](#).

Limitations and Performance**FLT 3.11.46**

The Operator shall provide, and require compliance with, operating limitations, as defined by the original equipment manufacturer (OEM) and established by the State of Registry for each aircraft type used in operations.

Auditor Actions

- ☐ **Identified/Assessed** OM provision of/requirement for compliance with operating limitations as defined by OEM (focus: guidance/procedures for flight crew compliance with operating limitations).
- ☐ **Interviewed** responsible manager(s) in flight operations.
- ☐ **Observed** line flight and flight simulator operations (focus: compliance with operating limitations).
- ☐ **Other Actions** (Specify)

FLT 3.11.47

The Operator shall have wind component limitations for takeoff, approach and landing that do not exceed the values demonstrated or recommended by the OEM and also address operations when the:

- (i) Runway is contaminated;
- (ii) Visibility is degraded;
- (iii) Aircraft stopping capability is degraded. **(GM)**

Auditor Actions

- ☐ **Identified/Assessed** OM procedures for compliance with takeoff/approach/landing wind component limitations that do not exceed OEM limitations (focus: requirement/procedures for flight crew compliance with wind component limitations).
- ☐ **Interviewed** responsible manager(s) in flight operations.
- ☐ **Observed** line flight and flight simulator operations (focus: compliance with wind component limitations).
- ☐ **Other Actions** (Specify)

Guidance

The intent of this provision is to ensure the operator provides wind component limitations for the phases of flight specified in the body of the provision (e.g. maximum crosswind component for landing). Additionally, the provision ensures the operator provides wind component limitations under the conditions specified in the sub-specifications (e.g. maximum crosswind component for landing on a contaminated runway). In either case such values cannot exceed those demonstrated or recommended by the OEM.

Contaminated runways are typically defined by a specific contaminant type/depth or equivalent braking action report.

FLT 3.11.48

The Operator shall have guidance that specifies a minimum aircraft height above ground level (AGL) or above airport level (AAL) for commencing a turn after takeoff. **(GM)**

Auditor Actions

- ☐ **Identified/Assessed** OM guidance that specifies a minimum aircraft height above ground level (AGL)/above airport level (AAL) for commencing a turn after takeoff (focus: requirement/procedures for flight crew compliance with minimum altitude limitations for turn after takeoff).
- ☐ **Interviewed** responsible manager(s) in flight operations.
- ☐ **Observed** line flight and flight simulator operations (focus: compliance with turn-after-takeoff altitude limitations).
- ☐ **Other Actions** (Specify)

Guidance

Values typically vary depending on the operator or could include exceptions covering special airport operations.

Approach and Landing

FLT 3.11.58

The Operator shall have guidance and procedures that enable the flight crew to determine the conditions required to commence or continue an approach to a landing, to include, as a minimum:

- (i) Crew qualification requirements;
- (ii) Onboard equipment requirements;
- (iii) Ground based equipment requirements;
- (iv) Operating minima.

Auditor Actions

- ☐ **Identified/Assessed** OM requirements/information/guidance/procedures that enables flight crew to determine conditions required to commence/continue an approach to landing (focus: flight crew procedures/requirements for commencing/continuing approach to landing).
- ☐ **Interviewed** responsible manager(s) in flight operations.
- ☐ **Observed** line flight and flight simulator operations (focus: determination of conditions for approach/landing).
- ☐ **Other Actions** (Specify)

FLT 3.11.59

The Operator shall have a stabilized approach policy with associated guidance, criteria and procedures to ensure the conduct of stabilized approaches. Such policy shall specify:

- (i) A minimum height for stabilization not less than 1000 feet AAL for approaches in IMC or not less than 500 ft. AAL for approaches in IMC as designated by the operator and/or State where a lower stabilization height is operationally required;
- (ii) A minimum height for stabilization not less than 500 feet AAL for approaches in VMC;

- (iii) Aircraft configuration requirements specific to each aircraft type (landing gear, wing flaps, speedbrakes);
- (iv) Speed and thrust limitations;
- (v) Vertical speed limitations;
- (vi) Acceptable vertical and lateral displacement from the normal approach path. **(GM)**

Auditor Actions

- ☐ **Identified/Assessed** OM policy/guidance/procedures for the conduct of a stabilized approach (focus: flight crew procedures/definition of criteria for stabilized approach).
- ☐ **Interviewed** responsible manager(s) in flight operations.
- ☐ **Examined** selected output from FDA/FDM/FOQA program (if applicable) (focus: data that indicates status of fleet stabilized approach performance).
- ☐ **Observed** line flight and flight simulator operations (focus: stabilized approach).
- ☐ **Other Actions** (Specify)

Guidance

Refer to the IRM for the definition of [Flight Data Analysis \(FDA\) Program](#).

The intent of this provision is for the operator to implement a stabilized approach policy, as well as have guidance, criteria and procedures that ensure the maintenance of the intended lateral and vertical flight path during visual approaches and/or as depicted in published approach procedures without excessive maneuvering. The parameters to be considered at the 1000 ft. AAL and 500 ft. gates as well as in the definition of a stabilized approach are listed in items iii) through vi) of the provision.

The specifications in item i) permit an operator, in accordance with operational requirements approved or accepted by the Authority, to establish stabilization criteria for heights lower than 1000 ft. AAL, but no lower than 500 ft. AAL (IMC or VMC), for approaches designated by the operator and/or State where:

- Lower minimum approach stabilization heights are authorized for turbo-propeller aircraft operations (e.g., 500 feet AAL on VMC/IMC approaches), **and/or**
- Maneuvering at a lower height AAL is required to meet instrument or other charted approach constraints (e.g. RNAV/RNP approaches, circling approaches and charted visual approaches), **and/or**
- Aircraft are required to comply with ATC speed constraints on final approach, **and/or**
- Deviations from selected approach stabilization criteria at a height lower than 1000 feet AAL, but above 500 feet AAL, are operationally required, and the operator can demonstrate pilot adherence to its stabilized approach policy via a continually monitored, managed and active flight data analysis (FDA) program.

The criteria used to conform to the specifications in item vi) also typically address the maneuvering that may be required in accordance with a charted visual or instrument approach procedure.

FLT 3.11.60

The Operator shall have a policy that requires the flight crew to execute a missed approach or go-around if the aircraft is not stabilized in accordance with criteria established by the Operator. **(GM)**

Auditor Actions

- ☐ **Identified/Assessed** OM policy/requirements for execution of a missed approach/go-around when approach not stabilized in accordance with established criteria (focus: flight crew guidance/procedures for execution of a missed approach/go-around).
- ☐ **Interviewed** responsible manager(s) in flight operations.
- ☐ **Examined** selected output from FDA/FDM/FOQA program (if applicable) (focus: data that indicates fleet status of missed approach/go-around from unstabilized approach).

- ☐ **Observed** line flight and flight simulator operations (focus: missed approach/go-around from unstabilized approach).
- ☐ **Other Actions** (Specify)

Guidance

The intent of this provision is for an operator's stabilized approach policy to address the actions to be taken by the flight crew in the event of deviations from the criteria that define a stabilized approach, and to designate the minimum altitude at which a go-around must be accomplished if the aircraft is not stabilized in accordance with the operator's stabilization criteria.

FLT 3.11.61

The Operator shall have a policy and procedures to ensure the flight crew maneuvers the aircraft so as to touchdown within the touchdown zone or other defined portion of the runway, as specified by the Operator or the Authority. **(GM)**

Auditor Actions

- ☐ **Identified/Assessed** OM policy/procedures for landing aircraft in the defined touchdown zone (focus: flight crew guidance/procedures for landing aircraft in touchdown zone).
- ☐ **Interviewed** responsible manager(s) in flight operations.
- ☐ **Examined** selected output from FDA/FDM/FOQA program (if applicable) (focus: data that indicates fleet status of landings in the defined touchdown zone).
- ☐ **Observed** line flight and flight simulator operations (focus: landing in touchdown zone).
- ☐ **Other Actions** (Specify)

Guidance

The definition of the touchdown zone could vary, depending on the operator.

FLT 3.11.65

The Operator shall have guidance, criteria, and procedures for the acceptance of a clearance for a non-ILS (including non-precision) approach and the conduct of such approach, to include:

- (i) Minimum weather conditions and visibility required to continue an approach;
- (ii) Operating conditions that require a missed approach to be initiated;
- (iii) Circling approach minima;
- (iv) Approach-related duties of the PF and PM. **(GM)**

Auditor Actions

- ☐ **Identified/Assessed** OM guidance/procedures/criteria for acceptance of clearance and conduct of a non-ILS approach (focus: flight crew procedures/definition of criteria for accepting/conducting a non-ILS approach).
- ☐ **Interviewed** responsible manager(s) in flight operations.
- ☐ **Observed** line flight and flight simulator operations (focus: non-ILS approach operations).
- ☐ **Other Actions** (Specify)

Guidance

The term Pilot Monitoring (PM) has the same meaning as the term Pilot Not Flying (PNF) for the purpose of applying the specifications of this provision.

FLT 3.11.66

The Operator shall have a policy and procedures that require and ensure the proper use of a stabilized constant descent profile during the final segment of a non-ILS (including non-precision) approach. **(GM)**

Auditor Actions

- ☐ **Identified/Assessed** OM policy/procedures for conduct of stabilized constant descent profile for final segment of non-ILS approach (focus: flight crew procedures/use of descent profile for conduct of final segment of non -ILS approach).
- ☐ **Interviewed** responsible manager(s) in flight operations.
- ☐ **Observed** line flight and flight simulator operations (focus: non-ILS approach operations; final segment profile).
- ☐ **Other Actions** (Specify)

Guidance

The intent of this provision is to ensure, to the extent reasonably practicable, the use of a stabilized constant descent profile inside the Final Approach Fix (FAF). It does not, however, preclude the definition of altitude gates such as Visual Descent Point (VDP) or level segments between the FAF and the runway where such constraints are deemed necessary and reflected in approach design.

Constant descent profiles during the final segment of an approach might be accomplished by various means to include:

- Vertical Navigation (V-NAV);
- Flight Path Angle (FPA);
- Constant Path Angle (CPA);
- Constant Angle Non-Precision Approaches (CANPA);
- Other methods that provide a stabilized constant path angle for the final segment of a non-ILS approach.

FLT 3.11.69

If the Operator is authorized to conduct circling approaches, the Operator shall have guidance and procedures to ensure the proper conduct of such approaches. Such guidance and procedures shall be in accordance with [FLT 3.11.59](#) and address, as a minimum:

- (i) Operating limitations and minima;
- (ii) Stabilization criteria and go-around requirements;
- (iii) Obstacle clearance requirements. **(GM)**

Auditor Actions

- ☐ **Identified** authorization to conduct circling approaches.
- ☐ **Identified/Assessed** OM requirements/guidance/procedures for conduct of circling approaches (focus: flight crew procedures/definition of criteria for conducting a circling approach).
- ☐ **Interviewed** responsible manager(s) in flight operations.
- ☐ **Observed** line flight and flight simulator operations (focus: circling approach operations).
- ☐ **Other Actions** (Specify)

Guidance

Refer to the IRM for the definition of [Circling Approach](#), [PANS-OPS](#) and [TERPS](#).

The intent of this provision is for the operator to provide guidance and procedures in the OM or other controlled document in order to manage or mitigate potential risks related to the conduct of circling approaches. Circling approaches may require maneuvering at low airspeeds in marginal weather at or near the minimum descent altitude/height (MDA/H) as established by the state in which an airport is located.

Guidance and procedures related to circling approaches typically address the following:

- The meteorological conditions (e.g. visibility, and if applicable, ceiling) required for commencement/continuation of circling;
- Approach category to be used or the maximum speed to be attained throughout the circling maneuver;

- Aircraft configuration at various stages of a circling approach;
- The use of flight control systems and automation to assist in the positioning of the aircraft during the approach procedure;
- Required visual references with the runway or runway environment required to descend below the MDA/H;
- The prohibition of descent below MDA/H until obstacle clearance can be maintained, the landing runway threshold has been identified and the aircraft is in a position to continue with a normal rate of descent and land within the touchdown zone;
- Go-around requirements and the missed approach procedure;
- The design criteria used to define containment areas and provide obstacle clearance (e.g. PAN-OPS, TERPs).

A side-step maneuver that culminates in a straight-in instrument procedure is not considered a circling approach, and thus is not addressed by this provision.

3.12 Flight Deck Policy and Procedures

FLT 3.12.7

The Operator shall have guidance that addresses runway incursions, to include a description of the flight crew duties, responsibilities, procedures and any other flight crew actions necessary to prevent, or reduce the risk of, a runway incursion occurring during taxi, takeoff, and landing. Such guidance shall include:

- Instructions for the maintenance of situational awareness by the flight crew while operating in the airport environment, on the ground and in the air, to ensure an awareness of the aircraft position relative to the airport surface;
- Operating policies and procedures for use during periods when there is a high risk of an incursion;
- Specific instructions for the use of onboard equipment and aircraft lighting as a means to mitigate the risk of an incursion;
- The identification, in documentation available to the flight crew, of areas on the airport surface that could pose a higher risk of an incursion;
- Specific reduced visibility and relevant LVO policies and procedures that minimize the risk of an incursion. **(GM)**

Auditor Actions

- ☐ **Identified/Assessed** OM guidance for runway incursion prevention/risk reduction during taxi/takeoff/landing phases of flight (focus: definition of flight crew duties/responsibilities/procedures/actions for runway incursion prevention/risk reduction).
- ☐ **Interviewed** responsible manager(s) in flight operations.
- ☐ **Observed** line flight and flight simulator operations (focus: runway incursion prevention/risk reduction).
- ☐ **Other Actions** (Specify)

Guidance

The intent of this provision is for an operator to ensure the OM incorporates an error mitigation strategy for reducing the risk of a runway incursion occurring during taxi, takeoff, and landing. Such error mitigation strategy would address each of the elements specified in this provision.

The specification in item i) refers to instructions that typically address:

- Specific methods used by the flight crew to maintain situational awareness in order to prevent or minimize the risks of runway incursions;
- The use of all available resources (heading indicators, airport diagrams, airport signs, markings lighting and air traffic control) to keep an aircraft on its assigned flight and/or taxi route;

- Reference to the airport diagram and airport signage;
- Taxi progress monitoring and/or verbal call-outs after taxiway passage;
- The development and/or discussion of a pre-taxi plan and taxi route briefing;
- The transcription of complex ATC taxi instructions;
- Not stopping on a runway and, if possible, taxiing off an active runway and then initiating communications with ATC to regain orientation;
- Visually clearing the final approach path prior to taxiing into the takeoff position on the runway.

The specification in item ii) refers to operating policies and procedures that typically address:

- Managing flight crew workload prior to takeoff and before landing;
- Procedures for deferring administrative tasks until non-critical phases of flight;
- Identifying checklist items that must be re-accomplished in the event of a runway change;
- Maintaining a "Sterile Flight Deck";
- The use of standard R/T phraseology;
- Clearance read-back and confirmation of changes;
- Monitoring clearances given to other aircraft;
- Obtaining directions or progressive taxi instructions when taxi route in doubt;
- Takeoff and landing runway verification and crosscheck;
- Takeoff and landing clearance verification;
- Questioning clearances when holding or lined up in position for takeoff on the runway, and takeoff clearance has not been received within a specified period of time.

The specification in item iii) refers to instructions that typically address:

- Use of aircraft of lighting during taxi, runway crossing, takeoff, and landing;
- Appropriate transponder use at airports with ground surveillance radar;
- Appropriate use of TCAS when on the runway and holding in the takeoff position (e.g. center mode on Navigation Display to display traffic on final approach).

The specification in item iv) refers to areas on the airport that could be identified through:

- Delineation of potential incursion areas or points (e.g. hot spots) on airport diagrams;
- Use of operator data collection programs to identify potential incursion areas in other documentation available to the flight crew;
- The presence of Land and Hold Short Operations (LAHSO).

The specification in item v) refers to the provision of reduced visibility and relevant LVO policies and procedures, regardless of LVO authorization, such as:

- Methods for maintaining situational awareness at night and during times of reduced visibility;
- A recommendation that checklists be suspended or delayed until the aircraft is stopped;
- If authorized for LVO, methods for maintaining situational awareness during LVO;
- If authorized for LVO, CAT II/III Surface Movement Guidance System (SMGS) procedures.

An operator, in accordance with requirements of the Authority, typically develops flight crew guidance related to the prevention of runway incursions from one or more source reference documents, to include:

- ICAO Document 9870, Manual on the Prevention of Runway Incursions;
- European Action Plan for the Prevention of Runway Incursions;
- FAA Advisory Circular AC No: 120–74B;
- Runway Safety; A Pilot's Guide to Safe Surface Operations, published by FAA Air Traffic Organization (ATO), Office of Safety Services;
- Communications; A key Component of Safe Surface Operations, published by FAA Air Traffic Organization (ATO), Office of Safety Services;

- Any equivalent reference document approved or accepted by the Authority for the development of flight crew guidance related to the prevention of runway incursions.

3.13 Flight Deck, Passenger Cabin, Supernumerary Compartment Coordination

FLT 3.13.3

If the Operator conducts passenger flights with cabin crew, the Operator shall have procedures for communication and coordination between the flight crew and the cabin crew to ensure a combined and coordinated process in addressing:

- (i) Passenger safety information;
- (ii) Cabin readiness prior to first aircraft movement, takeoff and landing;
- (iii) If applicable, arming or disarming of cabin door slides;
- (iv) Preparation for an encounter with turbulence;
- (v) Flight or cabin crew member incapacitation;
- (vi) Emergency evacuation;
- (vii) Abnormal situations;
- (viii) Emergency situations. **(GM)**

Auditor Actions

- ☐ **Identified/Assessed** OM procedures for flight/cabin crew communication/coordination in addressing situations that require combined/coordinated action (focus: procedures for flight/cabin crew communication/coordination; definition of situations that require combined/coordinated action).
- ☐ **Interviewed** responsible manager(s) in flight operations.
- ☐ **Coordinated** with cabin operations (focus: complementary procedures for communication/coordination).
- ☐ **Observed** line flight operations (focus: flight/cabin crew communication/coordination).
- ☐ **Other Actions** (Specify)

Guidance

Refer to the Guidance associated with [CAB 3.3.3](#) located in ISM Section 5.

Communication and coordination may be verbal or accomplished by an alternative means (e.g. chimes, lights).

Cabin crew coordination briefings could include security issues, aircraft technical issues affecting cabin service, en route weather, use of seat-belt sign, meal service.

Procedures defining communication/coordination could be part of specific non-normal/emergency procedures.

First aircraft movement as specified in item ii) is defined as pushback, powerback and/or taxi.

The operator may specify a non-communication period during critical phases of flight (e.g. during takeoff roll or during landing).

Refer to [FLT 3.13.4](#) for operations that do not utilize cabin crew members.

The term “abnormal” is used to describe a condition or situation (e.g. abnormal airframe vibration, abnormal landing configuration).

The terms “normal” and “non-normal/emergency” typically refer to AOM checklists, procedures and/or maneuvers. The term “non-normal” includes AOM emergency checklists and/or procedures (i.e. an emergency procedure is a subset of non-normal).

The terms can also be used to describe an event, situation or operation that would be addressed by normal or non-normal/emergency procedures or checklists. When used in this manner, the terms may be separated by forward slash marks (e.g. normal/non-normal/emergency).

The term “emergency” used alone refers to declarations and non-AOM procedures.

FLT 3.13.8

If the Operator transports passengers and/or supernumeraries, the Operator shall have procedures that ensure the preparation of the cabin or supernumerary compartment prior to takeoff and landing, and provide for notification to, as applicable, passengers and/or supernumeraries by either the flight crew or cabin crew:

- (i) To prepare for takeoff;
- (ii) When in the descent phase of flight;
- (iii) To prepare for landing. **(GM)**

Note: The specifications of this provision are applicable to commercial and/or non-commercial operations.

Auditor Actions

- ☐ **Identified/Assessed** OM procedures for preparation of cabin/supernumerary compartment and notification to passengers/supernumeraries prior to takeoff/landing (focus: flight/cabin crew procedures for cabin/supernumerary compartment preparation; definition of situations that require flight/cabin crew notification).
- ☐ **Interviewed** responsible manager(s) in flight operations.
- ☐ **Coordinated** with cabin operations (focus: complementary procedures for compartment preparation/notifications).
- ☐ **Observed** line flight operations (focus: flight/cabin crew notification prior to takeoff/landing).
- ☐ **Other Actions** (Specify)

Guidance

The intent of this provision is to ensure cabin or supernumerary compartment readiness under the conditions specified. Additionally, the provision requires that all applicable personnel are notified when in the specified phases of flight.

If cabin crew members are not used, preparation of the cabin prior to takeoff and landing would normally require the flight crew to verify certain conditions are in effect. Items checked by the flight crew will vary according to aircraft type and equipment carried, but might typically include:

- Passenger seat belts fastened;
- Tray tables and seat backs in a stowed and upright position;
- Cabin baggage and other carry-on items secure in designated areas;
- As applicable, in-flight entertainment system viewing screens off and stowed;
- Galleys and associated equipment stowed or restrained.

FLT 3.13.16

If the Operator utilizes aircraft equipped with a flight deck door, the Operator shall have policies and/or procedures that are in accordance with the requirements of the Authority and, as a minimum, define:

- (i) When the flight deck door must remain locked;
- (ii) If the Operator conducts passenger flights with cabin crew, the means used and actions necessary for cabin crew members to:
 - (a) Notify the flight crew in the event of suspicious activity or security breaches in the cabin;
 - (b) Gain entry to the flight deck. **(GM)**

Auditor Actions

- ☐ **Identified/Assessed** OM policies/procedures that address flight deck security (focus: requirements for door being locked/unlocked; methods for cabin crew to provide security notifications; process for cabin crew entry to flight deck).
- ☐ **Interviewed** responsible manager(s) in flight operations.

- ☐ **Coordinated** with cabin operations (focus: complementary procedures for security communication/flight deck entry).
- ☐ **Observed** line flight operations (focus: flight deck door operation; cabin crew entry).
- ☐ **Other Actions** (Specify)

Guidance

The principal intent of this provision is to ensure the security of the flight deck by providing the flight crew and cabin crew with complementary policies and/or procedures for use when a lockable flight deck door is installed. Such policies and/or procedures define the means used and actions necessary to address the specifications of this provision.

Policies and/or procedures related to flight deck security may be considered sensitive information and provided to relevant personnel in a manner that protects the content from unnecessary disclosure.

FLT 3.13.17

If the Operator utilizes aircraft equipped with an approved flight deck door as specified in (MNT) Table 4.11 (xxvi) (c) (d) and or Table 4.14 (iv), the Operator shall provide guidance, procedures and instructions for the use of such door by the flight crew to ensure the security of the flight deck. Such guidance shall include, as a minimum, the procedural means by which the crew:

- (i) Prevents access to the flight deck by unauthorized personnel;
- (ii) Identifies authorized personnel requesting entry into the flight deck. **(GM)**

Auditor Actions

- ☐ **Identified/Assessed** OM policies/procedures that address flight deck security (focus: requirements/procedures for flight crew use of door; procedures for identification of persons requesting flight deck entry).
- ☐ **Interviewed** responsible manager(s) in flight operations.
- ☐ **Coordinated** with cabin operations (focus: complementary procedures for gaining flight deck entry).
- ☐ **Observed** line flight operations (focus: flight deck door operation; identification of persons requesting entry).
- ☐ **Other Actions** (Specify)

Guidance

The principal intent of this provision is to ensure the security of the flight deck by providing the flight crew with appropriate guidance, procedures and instructions for use when a reinforced flight deck door is installed, regardless of the aircraft configuration (passenger, cargo, combi).

Guidance, procedures and instructions related to flight deck security are considered sensitive information and are normally provided to relevant personnel in a manner that protects the content from unnecessary disclosure.

Tables 4.11 and 4.14 in ISM Section 4 (MNT) contain specifications related to requirements and recommendations for the installation of reinforced flight deck doors. This provision, however, contains specifications only related to the use of such doors when installed.

FLT 3.13.18

If the Operator conducts international passenger flights utilizing aircraft equipped with an approved flight deck door as specified in (MNT) Table 4.11 (xxvi) (c) (d) and Table 4.14 (iv), the Operator shall have procedures:

- (i) To ensure the flight deck door is:
 - (a) Closed from the time all external aircraft doors are closed following embarkation;
 - (b) Closed and locked from the time of engine start or commencement of pushback, and until any external aircraft door is subsequently opened for disembarkation, except when necessary to permit access or egress by authorized persons.



- (ii) To monitor, using visual or procedural means, the entire area outside the flight deck door to identify persons requesting entry and to detect suspicious behavior or potential threat. **(GM)**

Auditor Actions

- ☐ **Identified/Assessed** OM policies/procedures that address flight deck security (focus: requirements for door being locked/unlocked; procedures for monitoring area outside door).
- ☐ **Interviewed** responsible manager(s) in flight operations.
- ☐ **Observed** line flight operations (focus: door locked/unlocked; monitoring area outside door).
- ☐ **Other Actions** (Specify)

Guidance

The principal intent of this provision is to ensure the security of the flight deck by providing the flight crew with appropriate procedures for use when a reinforced flight deck door is installed.

Procedures related to flight deck security may be considered sensitive information and provided to relevant personnel in a manner that protects the content from unnecessary disclosure.

The specification in item i) refers to the period when the aircraft is being operated beginning when all exterior doors are closed for engine start or pushback and ending when the aircraft is parked and any exterior door is opened for disembarkation.

For monitoring the area outside the flight deck door, a closed-circuit television (CCTV) system is an acceptable method of conformance. However, a CCTV system is not required in order to conform to this provision. Implementation of other procedural methods in accordance with applicable regulations is also considered acceptable.

Any means utilized by an operator for such monitoring ensures that the cabin area outside the flight deck door, and any persons that might be in that area, would be identifiable to the extent necessary to meet the requirements of this standard.

FLT 3.13.19

If the Operator conducts passenger operations and does not utilize a flight deck door, the Operator shall have measures in place to ensure unauthorized persons are prevented from entering the flight deck. **(GM)**

Auditor Actions

- ☐ **Identified/Assessed** OM guidance/procedures that address flight deck security (focus: measures/procedures for flight deck entry control/prevention).
- ☐ **Interviewed** responsible manager(s) in flight operations.
- ☐ **Observed** line flight operations (focus: prevention of unauthorized flight deck entry).
- ☐ **Other Actions** (Specify)

Guidance

The principal intent of this provision is to ensure the security of the flight deck, and refers specifically to aircraft that:

- Do not have a flight deck door, or
- Are equipped with flight deck door that cannot be locked, or
- Are equipped with a smoke barrier.

Measures referred to in this provision are in place to address the potential for *unauthorized personnel* to gain entry to the flight deck or gain access to the control seats and/or flight controls. Such measures may include, but are not limited to:

- Defining authorized personnel (e.g. jump-seat occupants, supernumeraries);
- Authorizing personnel for flight deck access;
- Airline Security programs (as defined by the authority);
- Briefings, announcements, placards;

- Any other measure designed to ensure unauthorized personnel are not permitted access to the flight deck, control seats, or flight controls.

3.14 Non-Normal/Abnormal and Emergency Operations

FLT 3.14.3

The Operator shall have a policy and guidance that defines the execution of abnormal/non-normal and emergency procedures and that ensures a crosscheck and verbal confirmation by two flight crew members (dual response) occurs before the actuation of any critical aircraft system controls. Such guidance shall identify critical systems, as defined by the OEM, and address, as a minimum:

- (i) Engine thrust levers;
- (ii) Fuel master or control switches;
- (iii) Engine fire handles or switches;
- (iv) Engine fire extinguisher discharge switches (if not automatically armed in conjunction with the associated fire handle or switch);
- (v) IDG/CSD disconnect switch. **(GM)**

Auditor Actions

- ☐ **Identified/Assessed** OM policy/guidance that addresses execution of abnormal/non-normal/emergency procedures (focus: procedures for dual flight crew crosscheck/verbal confirmation prior to actuation of critical aircraft system controls; definition of critical aircraft systems).
- ☐ **Interviewed** responsible manager(s) in flight operations.
- ☐ **Observed** line flight and flight simulator operations (focus: execution of abnormal/non-normal/emergency procedures).
- ☐ **Other Actions** (Specify)

Guidance

The intent of this provision is to ensure the operator's policy and guidance defines how abnormal/non-normal and emergency procedures are executed, and additionally ensures that the critical actions taken during the execution of such procedures are crosschecked and verbally confirmed by at least two flight crew members. Such critical actions are defined by the OEM and typically addressed in operating policy and guidance associated with the use of abnormal/non-normal and emergency checklists. This does not preclude, however, an OEM or operator from procedurally addressing critical actions in the checklists themselves.

The specification in item iv) need only be addressed if required by the OEM when the arming of a fire extinguisher discharge switch (or button) is not linked to the actuation of the associated fire handle or switch.

The term "abnormal" is used to describe a condition or situation (e.g. abnormal airframe vibration, abnormal landing configuration).

The terms "normal" and "non-normal/emergency" typically refer to AOM checklists, procedures and/or maneuvers. The term "non-normal" includes AOM emergency checklists and/or procedures (i.e. an emergency procedure is a subset of non-normal).

The terms can also be used to describe an event, situation or operation that would be addressed by normal or non-normal/emergency procedures or checklists. When used in this manner, the terms may be separated by forward slash marks (e.g. normal/non-normal/emergency).

The term "emergency" used alone refers to declarations and non-AOM procedures.

FLT 3.14.9

The Operator shall have policies and procedures in accordance with [FLT 3.11.18](#), applicable to each aircraft type, that are applied during a GPWS or other terrain avoidance alert provided by onboard equipment. Such guidance shall, as a minimum, define a CFIT escape maneuver as an aggressive pitch up maneuver that maximizes the performance of the aircraft.

Auditor Actions

- ❑ **Identified/Assessed** OM policies/procedures that address reaction to GPWS/terrain avoidance alert/warning (focus: procedures for each aircraft type; definition of/procedure for aggressive pitch-up escape maneuver; procedures include flight crew sharing/prioritization of tasks).
- ❑ **Interviewed** responsible manager(s) in flight operations.
- ❑ **Observed** line flight and flight simulator operations (focus: GPWS/terrain alert/warning procedures).
- ❑ **Other Actions** (Specify)

FLT 3.14.15

The Operator shall have an in-flight fuel management policy that requires the PIC to request air traffic delay information from ATC when unanticipated circumstances may result in landing at the destination airport with less than *either*:

- (i) The final reserve fuel plus any fuel required to proceed to an alternate airport, *or*
- (ii) The fuel required to operate to an isolated airport. **(GM)**

Auditor Actions

- ❑ **Identified/Assessed** OM policy/procedures for in-flight fuel management (focus: flight crew procedures for monitoring en route fuel usage/identifying trends; requirement for flight crew to request airport delay information when trend indicates landing with less than final reserve plus alternate fuel, or isolated airport fuel).
- ❑ **Interviewed** responsible manager(s) in flight operations.
- ❑ **Observed** line flight and flight simulator operations (focus: in-flight fuel management procedures).
- ❑ **Other Action** (Specify)

Guidance

Refer to the IRM for the definition of [Fuel \(Flight Planning\)](#), which includes the definition of [Final Reserve Fuel](#).

The intent of this provision is to ensure an operator defines the conditions that require the PIC to request air traffic delay information from ATC. Such operator policy is typically part of the overall in-flight fuel management strategy to ensure planned reserves are used as intended or required. It also typifies the beginning of a process that could ultimately preclude a landing with less than final reserve fuel on board.

It should be noted that the request for air traffic delay information is a procedural means for the flight crew to determine an appropriate course of action when confronted with unanticipated delays. There is no specific phraseology recommended for use in this type of communication with ATC as each situation may be very different.

Guidance on in-flight fuel management and requesting delay information from ATC is contained in the ICAO Flight Planning and Fuel Management Manual (Doc 9976).

FLT 3.14.16

The Operator shall have an in-flight fuel management policy that requires the PIC to advise ATC of a minimum fuel state:

- (i) When, having committed to land at a specific airport, the PIC calculates that any change to the existing clearance to that airport may result in landing with less than planned final reserve fuel;
- (ii) By declaring "MINIMUM FUEL." **(GM)**

▲ An operator may conform to [FLT 3.14.16 ii](#)) through Active Implementation as long as the implementation Action Plan (IAP) projects conformance on or before 31 August 2021.

Auditor Actions

- ☐ **Identified/Assessed** OM policy/procedures for in-flight fuel management (focus: flight crew procedures for monitoring en route fuel usage/identifying trends; requirement for flight crew to declare minimum fuel when minimum fuel for landing at destination airport might be less than planned final reserve fuel).
- ☐ **Identified/Assessed** Active Implementation plan (if applicable).
- ☐ **Interviewed** responsible manager(s) in flight operations.
- ☐ **Observed** line flight and flight simulator operations (focus: in-flight fuel management procedures).
- ☐ **Other** Action (Specify)

Guidance

The intent of a “MINIMUM FUEL” declaration is to inform ATC that the flight has committed to land at a specific airport and any change to the existing clearance may result in landing with less than planned final reserve fuel. This is not an emergency situation, but rather an indication that an emergency situation is possible should any additional delay occur.

Active Implementation is applicable to the specification in item ii) for the sole purpose of affording states the time necessary to implement the standard ICAO phraseology related to minimum fuel states.

Guidance on in-flight fuel management, including minimum fuel declarations, is contained in the ICAO Flight Planning and Fuel Management Manual (Doc 9976).

FLT 3.14.17

The Operator shall have an in-flight fuel management policy that requires the PIC to declare a situation of fuel emergency:

- (i) When the calculated usable fuel predicted to be available upon landing at the nearest airport where a safe landing can be made is less than the planned final reserve fuel;
- (ii) By declaring “MAYDAY, MAYDAY, MAYDAY, FUEL.” **(GM)**

▲ An operator may conform to [FLT 3.14.17](#) ii) through Active Implementation as long as the implementation Action Plan (IAP) projects conformance on or before 31 August 2021.

Auditor Actions

- ☐ **Identified/Assessed** OM policy/procedures for in-flight fuel management (focus: flight crew procedures for monitoring en route fuel usage/identifying trends; requirement for flight crew to declare an emergency when minimum fuel for landing at nearest airport is calculated to be less than planned final reserve fuel).
- ☐ **Identified/Assessed** Active Implementation Plan (if applicable).
- ☐ **Interviewed** responsible manager(s) in flight operations.
- ☐ **Observed** line flight and flight simulator operations (focus: in-flight fuel management procedures).
- ☐ **Other** Action (Specify)

Guidance

The intent of this provision is to specify the last procedural step in a series of steps to ensure the safe completion of a flight. The “MAYDAY, MAYDAY, MAYDAY, FUEL” declaration provides the clearest and most urgent expression of an emergency situation brought about by insufficient usable fuel remaining to protect the planned final reserve. It communicates that immediate action must be taken by the PIC and the air traffic control authority to ensure that the aircraft can land as soon as possible. It is used when all opportunities to protect final reserve fuel have been exploited and in the judgment of the PIC, the flight will now land with less than final reserve fuel remaining in the tanks. The word fuel is used as part of the declaration simply to convey the exact nature of the emergency to ATC.

Active Implementation is applicable to the specification in item ii) for the sole purpose of affording States the time necessary to implement standard ICAO phraseology related to fuel emergencies.

Guidance on in-flight fuel management including emergency fuel declarations is contained in the ICAO Flight Planning and Fuel Management Manual (Doc 9976).

3.15 Flight Crew Reporting Requirements

FLT 3.15.2

The Operator shall have a policy that requires the PIC to report any hazardous flight condition to the appropriate ATC facility without delay. **(GM)**

Auditor Actions

- ☐ **Identified/Assessed** policy for flight crew ATC hazard reporting (focus: flight crew procedures for reporting occurrences that could potentially have adverse effect on safety of flight operations).
- ☐ **Interviewed** responsible manager(s) in flight operations.
- ☐ **Interviewed** selected flight crew members.
- ☐ **Other Actions** (Specify)

Guidance

The intent of this provision is to ensure hazards with the potential to pose safety risks to the reporting aircraft or flight operations are appropriately identified and reported to the applicable ATS unit as soon as possible. Such required reports are typically defined by the State or applicable authorities and may include types of hazards as described in the following table.

Generic Hazard	Report Description
Meteorological Conditions	Un-forecast or severe weather, icing, wind shear, severe turbulence
Geophysical Events	Volcanic ash observed or encountered
Security Breaches	Air Piracy or other hostile acts that threaten the safety of the aircraft or its passengers
Wildlife	Birds or large animals in the vicinity of the airport or runways
Facilities and infrastructure	Inadequacy of navigational facilities or undesirable navigational aid performance, Braking Action or other irregularity in navigational or ground facilities
Aircraft Performance	Unable to accept or maintain RVSM and reason (e.g. turbulence, mountain wave, wake turbulence, etc.), loss of navigational capability
Lasers	Illumination activities, events or exposure
Other	Unmanned free balloons, downed aircraft observation or ELT broadcast

4 Operations Engineering Specifications

4.1 Aircraft Performance

FLT 4.1.1

The Operator shall have a process, performed by Operations Engineering, to determine and maintain guidance, procedures and performance data in the OM, applicable to each aircraft type, for applicable departure, destination and alternate airports. Such guidance and data shall enable the flight crew to determine or compute:

- (i) Maximum structural weights (taxi, takeoff, landing);
- (ii) Takeoff performance (accelerate - stop, close-in obstacles) that also ensures charting accuracy is accounted for, when necessary, in assessing takeoff performance in the event of a critical power unit failing at any point in the takeoff;
- (iii) Maximum brake energy and minimum cooling time;

- (iv) Climb performance (distant obstacles);
- (v) Landing performance (minimum landing distance, go-around). **(GM)**

Auditor Actions

- ☐ **Identified/Assessed** OM guidance/procedures/data for flight crew calculation of aircraft performance for taxi/takeoff/climb/landing at departure/destination/alternate airports (focus: performance data provided for all aircraft types; OM contains performance data as specified in standard).
- ☐ **Interviewed** responsible manager(s) in flight operations.
- ☐ **Interviewed** selected operations engineering personnel (focus: process for development of OM performance information/data).
- ☐ **Observed** line flight operations (focus: use of taxi/takeoff/climb/landing performance information/data).
- ☐ **Other Actions** (Specify)

Guidance

The intent of this provision is to ensure the operator has a process or processes to obtain or determine the specified performance data for use by flight crew. Such process(es) also address the maintenance and publication of guidance, procedures, and performance data in the OM.

Data may be tailored for airports of intended use (e.g. runway analysis).

The specifications in items ii) and v) may necessitate the inclusion of guidance and/or patterns to be followed in case of engine failure during takeoff, approach and go-around.

Tailored data is not always available for emergency alternate airports.

FLT 4.1.2

The Operator shall have a process, performed by Operations Engineering, to determine and maintain guidance, data and procedures in the OM, applicable to each aircraft type, that enable the flight crew to determine and/or compute aircraft performance for all phases of flight. Such guidance and data shall ensure the flight crew considers all relevant factors affecting aircraft performance, to include:

- (i) Aircraft weight (mass);
- (ii) Operating procedures;
- (iii) Pressure altitude;
- (iv) Temperature;
- (v) Wind;
- (vi) Runway gradient;
- (vii) Runway contaminant/braking action;
- (viii) Obstacle data;
- (ix) NOTAMs (including airport NOTAMs);
- (x) As applicable, MEL/CDL information;
- (xi) Aircraft configuration (wing flap setting);
- (xii) Anti-ice usage and, when applicable, ice accretion;
- (xiii) As applicable, runway length used for aircraft alignment prior to takeoff;
- (xiv) As applicable, fuel freeze considerations during extended operations. **(GM)**

Auditor Actions

- ☐ **Identified/Assessed** OM guidance/procedures/data for flight crew calculation of aircraft performance for all phases of flight (focus: performance data provided for all aircraft types; OM guidance/data incorporates relevant factors/limitations as specified in standard).
- ☐ **Interviewed** responsible manager(s) in flight operations.
- ☐ **Interviewed** selected operations engineering personnel (focus: process for development of OM performance information/data).

- ☐ **Observed** line flight operations (focus: determination of relevant factors affecting aircraft performance).
- ☐ **Other Actions** (Specify)

Guidance

The intent of this provision is to ensure the operator has a process or processes to obtain or determine the specified performance data for use by flight crew. Such process(s) also address the maintenance and publication of guidance, procedures, and performance data in the OM.

The specification in item vii) could be defined by a specific contaminant type/depth or equivalent braking action report.

The specifications in xiii) refers to a determination of the length of the runway available, taking into account the loss, if any, of runway length due to alignment of the aircraft prior to takeoff.

The specifications in xiv) apply to considerations regarding the use of standard fuel freeze temperatures, fuel temperature analysis and en route fuel temperature monitoring for the specific fuels used in operations. Such considerations allow the flight crew to determine the actual fuel freeze temperature during extended operations (e.g. polar operations) in order to prevent in-flight freezing of fuel.

4.2 Navigation and Facilities

FLT 4.2.2

The Operator shall have a process, performed by Operations Engineering, to ensure completion of an analysis that addresses relevant operational factors prior to operating over any new route or into any new airport. Such analysis shall take into account:

- (i) Obstacle clearance for all phases of flight (minimum safe altitudes);
- (ii) Runway (width, length and pavement loading);
- (iii) Navigation aids and lighting;
- (iv) Weather considerations;
- (v) Emergency services;
- (vi) Fuel burn calculations;
- (vii) As applicable, fuel freeze considerations;
- (viii) As applicable, ETOPS/EDTO requirements;
- (ix) Air Traffic Services;
- (x) Critical engine inoperative operations;
- (xi) Depressurization over critical areas;
- (xii) (Special) airport classification. **(GM)**

Auditor Actions

- ☐ **Identified/Assessed** process for analysis to identify/address relevant operational factors prior to conducting operations over new routes/into new airports (focus: analysis includes/addresses factors as specified in standard).
- ☐ **Interviewed** responsible manager(s) in flight operations.
- ☐ **Interviewed** selected operations engineering personnel (focus: process for analysis of new routes/airports).
- ☐ **Examined** selected examples of new route/airport analyses.
- ☐ **Other Actions** (Specify)

Guidance

The specifications in:

- Item vii) refers to a determination if the occurrence of fuel freeze during extended operations is operationally relevant when planning a new route. If operationally relevant, the specification vii) of this provision requires the operator to determine and designate the methods used by the flight crew to determine fuel freeze points in accordance with the specifications of [FLT 4.1.2](#).
- Item xi) refers to carriage of fuel to respect oxygen requirement after depressurization.
- Item xi) may be satisfied by depressurization routes, charts and/or tables that consider oxygen requirements over high terrain and fuel burn over remote areas.
- Item xii) may be satisfied by standardized criteria for the determination and classification of special airports (e.g., EU-OPS).



4.3 Aircraft Systems and Equipment Specifications

Table 2.1—Onboard Library Specifications

The following documents shall be included in the Onboard Library:

General Operating Information

- (i) General Operations Manual (GOM).

Aircraft Operating Information

- (ii) Applicable Aircraft Operating Manual (AOM) and, as a minimum:
 - (a) Normal and Emergency Checklists for each operating flight crew member as required by the AFM;
 - (b) Performance tables or access to performance calculations via telecom systems (e.g. ACARS) is acceptable, if completed with appropriate backup procedures;
 - (c) Takeoff performance deviations (e.g. due to inoperative equipment or abnormal situations).
- (iii) Minimum Equipment List (MEL) and Configuration Deviation List (CDL);
- (iv) Aircraft-specific weight/mass and balance instructions/data (including load sheet).

Areas, Routes and Airport Information

- (v) Flight Plans (OFP and ATS) for each flight;
- (vi) The applicable departure, navigation and approach charts for use by each operating flight crew member as required by the AFM;
- (vii) Route and airport instructions and information (flight crew member route guide) for each flight to include, as a minimum:
 - (a) Departure airport;
 - (b) Destination airport;
 - (c) En route alternate airports;
 - (d) Emergency airports.
- (viii) If applicable, the escape routes used in case of decompression or engine failure in an area of high terrain.

Other Information

- (ix) Cabin safety and emergency procedures relevant to the flight crew;
- (x) Dangerous Goods manual or parts relevant to the flight crew, to include information and instructions on the carriage of dangerous goods and action to be taken in the event of an emergency;
- (xi) Security Manual or parts relevant to the flight crew, including bomb search procedures;
- (xii) Ground Handling Manual or parts relevant to the flight crew, if required for flight crew to accomplish assigned duties (recommendation only and only applicable to cargo aircraft operations).

Table 2.2—Operations Manual (OM) Content Specifications

This table contains the fundamental OM content specifications required to achieve conformance with [FLT 1.7.1](#) and [FLT 2.1.10](#). The table also specifies [Section 3 \(DSP\)](#) provisions that must be addressed in the sections of the OM relevant to flight crew.

Note: Specific flight crew policies, guidance, data and/or procedures that must also be addressed in the sections of the OM relevant to flight crew can be found in individual [Section 2](#) provisions and are not duplicated in the table.

General Information		DSP ISARP
(i)	General Operations Manual (GOM), to include:	None
(a)	Non-aircraft type related and/or standard operating procedures for each phase of flight, policies, procedures, checklists, descriptions, guidelines, emergency procedures and other relevant information;	None
(b)	Authorities, duties and responsibilities associated with the operational control of flights;	DSP 1.3.1, 1.3.4, 1.3.5, 1.3.6, 1.3.7
(c)	If applicable, guidance that identifies and defines the common flight documents used by the flight crew, the FOO, FOA and/or other personnel responsible for operational control.	DSP 3.2.2
Aircraft Operating Information		DSP ISARP
(ii)	Aircraft Operating Manual (AOM), to include:	None
(a)	Normal, abnormal/non-normal and emergency procedures, instructions, and checklists;	None
(b)	Aircraft systems descriptions, limitations and performance data.	None
(iii)	Minimum Equipment List (MEL) and Configuration Deviation List (CDL);	None
(iv)	Aircraft specific weight/mass and balance instructions/data (including load sheet);	DSP 3.3.3
(v)	Instructions for the computation of the quantities of fuel and oil (if required) to be carried.	DSP 4.3 (all)
Areas, Routes and Airport Information		DSP ISARP
(vi)	Route and airport instructions and information (departure, destination, en route and destination alternates, to include:	None
(a)	Airway manuals and charts, including information regarding communication facilities and navigation aids;	None
(b)	Airport charts, including the method for determining airport operating minima;	None
(c)	FMS databases;	None
(d)	Airport and runway analysis manual or documents;	None
(e)	If applicable, supplemental oxygen requirements;	None
(f)	If applicable, escape routes used in the event of a decompression or engine failure in an area of high terrain;	None
(g)	If applicable, procedures for loss of communication between the aircraft and the FOO;	DSP 3.6.1
(h)	Instructions for the selection, designation (on the OFP) and protection of departure, en route and destination alternate airports.	DSP 4.1 (all), 3.6.5B, 4.5.2, 4.5.3
Areas, Routes and Airport Information		DSP ISARP
(i)	Instructions to address departure if current meteorological reports and forecasts indicate that the destination airport or destination alternate will not be at or above operating minima;	DSP 3.2.9B

Table 2.2—Operations Manual (OM) Content Specifications

(j)	Instructions to address the continuation of a flight towards an airport of intended landing if the latest available information indicates a landing cannot be accomplished at that airport or at least one destination alternate;	DSP 3.2.9B, 3.6.5A
(k)	If applicable, flight monitoring requirements and instructions to ensure the PIC notifies the operator of en route flight movement or deviations from the OFP;	DSP 3.6.2, 3.6.3
(l)	If applicable, flight planning considerations that address the continuation of a flight after the failure of the critical engine on a two-engine aircraft and/or the second engine on a three or four engine aircraft;	DSP 4.2.2, 4.2.3
(m)	The essential information concerning the search and rescue services in the area over which the aircraft will be flown.	None
(n)	Information regarding RFFS capability available at airports of intended use.	None
Training Information		DSP ISARP
(vii)	Training Manual, to include:	None
(a)	Details of all relevant training programs, policies, directives and requirements, including curricula and syllabi, as applicable, for basic operator familiarization, initial qualification, continuing qualification (including recency-of-experience), re-qualification, aircraft transition or conversion, upgrade to PIC and other specialized training requirements, as applicable;	None
(b)	Curricula to include: ground training, simulator training, aircraft training, evaluation and certification, line flying under supervision, and any specialized training;	None
(c)	Comprehensive syllabi to include lesson plans, procedures for training and the conduct of evaluations;	None
(d)	The training program for the development of knowledge and skills related to human performance (Crew Resource Management/Dispatch Resource Management, CRM/DRM).	None
Other Information		DSP ISARP
(viii)	Cabin safety and emergency procedures relevant to the flight crew.	None
(ix)	Dangerous Goods manual or parts relevant to the flight crew, to include information and instructions on the carriage of dangerous goods and action to be taken in the event of an emergency.	None
(x)	Security Manual or parts relevant to the flight crew, including bomb search procedures.	None
(xi)	Ground Handling Manual or parts relevant to the flight crew, if required for flight crew to accomplish assigned duties (recommendation only and only applicable to cargo aircraft operations).	None

Table 2.3—Flight Crew Qualification Requirements

Fulfillment of the following flight crew certifications, qualifications, training and currency requirements shall be recorded and retained in accordance with [FLT 1.8.2](#), and monitored and considered when assigning flight crew members to duty in accordance with [FLT 3.4.1](#).

- (i) Licenses/certification, including eligibility to exercise privileges of pilot license/certificate in international operations in accordance with [FLT 3.3.5](#);
- (ii) Specific qualifications (LVP, RVSM, EDT0);
- (iii) Equipment qualifications (TCAS/ACAS, GPWS/EGPWS, HGS, HUD/EVS, HUD/EVS, PBN, PBCS);
- (iv) Recency-of-experience;
- (v) Medical status, including Medical Certificate;
- (vi) Initial training and checking/line check/proficiency check/recurrent training and checking results;
- (vii) Right seat qualification;
- (viii) Type(s) qualification;
- (ix) Airport and route competence (including special airports);
- (x) Instructor/evaluator/line check airman qualification;
- (xi) CRM/Human Factors training;
- (xii) Dangerous goods training;
- (xiii) Security training;
- (xiv) Accrued flight time, duty time, duty periods and completed rest periods for the purposes of fatigue risk management and compliance with operator or State flight and/or duty time limitations.

Table 2.4—(Intentionally open)

Table 2.5—Route and Airport Knowledge Requirements

Each pilot crew member, in order to conform to the specifications of [FLT 2.3.1](#), and/or the PIC, in order to conform to the specifications of [FLT 2.4.1](#), shall have adequate knowledge of the following elements related to areas, routes or route segments, and airports to be used in operations:

- (i) Terrain and minimum safe altitudes;
- (ii) Seasonal meteorological conditions;
- (iii) Meteorological, communication and air traffic facilities, services and procedures;
- (iv) Search and rescue services for the areas over which the aircraft will be flown;
- (v) Navigational facilities and procedures, including any long-range navigation procedures associated with the route along which the flight is to take place;
- (vi) Procedures applicable to flight paths over heavily populated areas and areas of high air traffic density;
- (vii) Airport obstructions, physical layout, lighting, approach aids and arrival, departure, holding and instrument approach procedures and applicable operating minima.

Note: That portion of an evaluation relating to arrival, departure, holding and instrument approach procedures may be accomplished in an appropriate training device that is adequate for this purpose.

Table 2.6—Elements Common to an Advanced Qualification Program (AQP), an Alternative Training and Qualification Program (ATQP) or an Evidence-based Training (EBT) Program

The following elements shall be included as part of an AQP, ATQP or EBT program as specified in [FLT 2.1.1B](#).

- (i) Training program and curricula approved or accepted by the State.
- (ii) Training and evaluation which is conducted to the maximum extent possible in a full flight deck crew environment (e.g. Captain and First Officer). Qualification and continuing qualification curricula must include a line operational evaluation (LOE), which consists of a full flight scenario systematically designed to target specific technical and crew resource management (CRM) skills.
- (iii) Mandatory evaluation of CRM proficiency and substandard performance on CRM factors shall be corrected by additional training. A demonstration of proficiency in maneuver oriented technical skills is a necessary but insufficient condition for pilot qualification. For pass/fail purposes, pilots must also demonstrate proficiency in LOE's, which test both technical and CRM skills together.
- (iv) Specific training for instructors and evaluators, together with explicit training and evaluation strategies to verify the proficiency and standardization of such personnel for crew oriented, scenario-based training and evaluation tasks.
- (v) Integrated use of advanced flight training equipment, including full flight simulators. Operators are encouraged to utilize a suite of equipment matched on the basis of analysis to the training requirements at any given stage of a curriculum.
- (vi) Curriculum elements that are:
 - (a) Defined;
 - (b) Crew member-specific or personnel-specific;
 - (c) Aircraft-specific. (See Note 1)

Note 1: Each curriculum must specify the make, model and series aircraft (or variant) and each crew member position or other positions to be covered by that curriculum. Positions to be covered by the program must include all flight crew member positions, instructors and evaluators and could include other positions, such as flight attendants, aircraft dispatchers and other operations personnel.

- (vii) Separate curricula for indoctrination, qualification and continuing qualification.
- (viii) CRM Training/Evaluation and Data Collection (feedback) to determine program effectiveness to include:
 - (a) State-approved or -accepted Crew Resource Management (CRM) Training applicable to each position for which training is provided under the program;
 - (b) State-approved or -accepted training on and evaluation of skills and proficiency of each person being trained under the program to use their crew resource management (CRM) skills and their technical (piloting or other) skills in an actual or simulated operations scenario. For flight crew members, this training and evaluation must be conducted in an approved flight training device or flight simulator;
 - (c) Data collection procedures that will ensure the certificate holder provides information from its crew members, instructors and evaluators that will enable the State to determine whether the training and evaluations are working to accomplish the overall objectives of the curriculum;
 - (d) Performance proficiency data collection on students, instructors, and evaluators and the conduct of airline internal analyzes of such information for the purpose of curriculum refinement and validation.
- (ix) Defined airman certification and licensing requirements.
- (x) Training devices and simulators used under the program evaluated against published standards and be approved or accepted by the State to ensure adequacy for training/qualification performed.

Table 2.6—Elements Common to an Advanced Qualification Program (AQP), an Alternative Training and Qualification Program (ATQP) or an Evidence-based Training (EBT) Program

- (xi) Program approval to include:
 - (a) A demonstration to the Authority of how the program will provide an equivalent or superior level of safety for each curriculum item that differs from traditional training programs approved or accepted by the State.
 - (b) A demonstration to the Authority for every requirement that is replaced by the program curriculum, of how the new curriculum provides an equivalent or superior level of safety for each requirement that is replaced. Each traditional training program requirement that is not specifically addressed in the program curriculum continues to apply to the Operator.
 - (c) A requirement that training, qualification, or evaluation by a person who provides training by arrangement: "Training Centers" must be approved or accepted by the State.
- (xii) Records in sufficient detail to establish the training, qualification and certification of each person qualified under the program in accordance with the approved training, qualification and certification requirements.

Table 2.7—Requirements Specific to an Advanced Qualification Program (AQP) or an Alternative Training and Qualification Program (ATQP)

The specifications in this table apply to an AQP/ATQP as specified in [FLT 2.1.1B](#) and are in addition to those delineated in [Table 2.6](#):

(i) Proficiency Objectives

The Operator shall conduct an aircraft-specific job task analysis beginning with the development of a comprehensive task listing for each duty position. The task listing covers the full range of conditions and contingencies - internal to the aircraft, external to the aircraft, normal, abnormal, and emergency - to which the pilot could be exposed within the Operator's sphere of operations. Proficiency objectives are then extracted from the task and subtask analysis, respectively, for each duty position, and include identification of applicable performance, standards, and conditions. The documentation of proficiency objectives also identifies the references used, respectively, in defining performance, standards, and conditions for each.

An operator may elect to categorize certain proficiency objectives as currency items. Currency items refer to flight activities on which proficiency is maintained by virtue of frequent exercise during routine operations. Such items do not need to be addressed for training or proficiency evaluation purposes in periodic training sessions. However, verification is required that proficiency on such items is being maintained. Such verification might be obtained during line checks.

An operator could also elect to categorize proficiency objectives, including currency items, as critical or non-critical, based on operational significance and the consequences of error. This categorization is employed to determine the time interval within which training and evaluation on such items must occur for continuing qualification curricula. Critical proficiency objectives are trained and evaluated during an evaluation period the initial duration of which cannot exceed thirteen months. Each such evaluation period includes at least one training session. Non-critical terminal proficiency objectives may be distributed over a continuing qualification cycle the initial duration of which cannot exceed twenty-six months.

(ii) First Look Evaluations

Performance on selected proficiency items will be evaluated prior to each formal training session and prior to any pre-briefing or practice. Such pre-evaluation data is used to determine the extent to which safety-critical skills might have decayed since previous training and/or checking, and provides a baseline for assessing degree of improvement attributable to subsequent training. Consistently poor pre-evaluation results occurring within the pilot group might indicate that curriculum modifications, including potentially the frequency and content of training, are warranted.

(iii) Continuing Qualification Cycles and Evaluation Periods

After initial qualification, which incorporates training and evaluation on all proficiency objectives, follow-on training will occur within a scheduling interval called a continuing qualification cycle. This is the time period during which all proficiency objectives are trained, validated, or evaluated for all crewmembers. The initial approval for a continuing qualification cycle is no more than 26 months in duration, divided into two 13-month evaluation periods. All critical proficiency objectives are accomplished during each evaluation period, and all currency proficiency objectives are accomplished during each continuing qualification cycle.

The initial duration of a continuing qualification cycle is 26 months, but it may be subsequently and incrementally extended by the Authority to a maximum of 39 months, contingent upon the results of performance proficiency data from each such cycle.

(iv) Training Sessions

Each evaluation period shall include a minimum of one training session but may include more. Initially, training sessions cannot be more than 13 months apart.

Table 2.7—Requirements Specific to an Advanced Qualification Program (AQP) or an Alternative Training and Qualification Program (ATQP)

(v) Proficiency Evaluations

For PICs, SICs, flight engineers, and other persons covered by an AQP/ATQP, a proficiency evaluation shall be completed during each evaluation period. Typically, the proficiency evaluation will occur during a required training session; however, if more than one training session is completed during an evaluation period, the proficiency evaluation may be divided among training sessions or otherwise allocated to one or more such sessions.

Table 2.8—Requirements Specific to an Evidence-based Training (EBT) Program

The specifications in this table apply to EBT as specified in [FLT 2.1.1B](#), and are in addition to those delineated in [Table 2.6](#).

(i) **EBT Framework**

The operator shall establish as a minimum:

- (a) A core competency framework using behavioral indicators approved or accepted by the authority;
- (b) The means to develop, train and assess competencies utilizing scenarios that are relevant to the operator's environment;
- (c) A malfunction clustering system.

(ii) **Baseline EBT**

The operator shall ensure the following requirements, as a minimum, are met prior to the implementation of EBT:

- (a) A set of core competencies is developed;
- (b) A competency-based assessment and grading system is developed;
- (c) Instructors are trained to ensure a standardized approach to EBT. Such instructor training programs also ensure each instructor's capability to conduct the training and assessment of the core competencies;
- (d) Flight crew members are provided with background knowledge of EBT principles, methodology and the set of competencies;
- (e) A system to measure the effectiveness of EBT is developed;
- (f) Training scenarios are developed as provided in the IATA Data Report for Evidence-based Training or as required by the State.

(iii) **Additional Program Requirements (applicable to any EBT)**

An EBT program shall be approved or accepted by the Authority and include as a minimum:

- (a) The definition of an implementation and operations plan;
- (b) Programs as defined in ICAO Doc 9995, Appendices 2 to 7 to Part II, and as required by the types of operations of the Operator;
- (c) Implementation with a limited trial phase;
- (d) The review of training effectiveness upon receipt of sufficient training system data;
- (e) Adjustment and continuous improvement of the training program according to the training system feedback;
- (f) A risk assessment of any implementation and/or proof of concept trial in accordance with SMS principles.

(iv) **Enhanced EBT Requirements**

The difference between the baseline EBT and an enhanced EBT is optimization that, as a minimum, is based on the following activities:

- (a) Collection and analysis of operations data;
- (b) Collection and analysis of training data;
- (c) Integration of analysis;
- (d) Program development;
- (e) Risk assessment of enhanced EBT implementation and/or proof-of-concept trial in accordance with SMS principles.

Table 2.8—Requirements Specific to an Evidence-based Training (EBT) Program

(v) Enhanced EBT Scenarios

Enhanced EBT scenarios shall be based on one or more of the following:

- (a) IATA Data Report for evidence-based training;
- (b) Flight Data Analysis (FDA) program;
- (c) Safety reporting system;
- (d) Flight deck observation program;
- (e) Training data;
- (f) The Operator's specific operational challenges that relate to route network, airports used, weather, etc.;
- (g) World fleet data with an analysis of available safety data from operations with similar aircraft types and similar operations (e.g. OEM/OSD data).

(vi) Continuing Qualification Cycles and Evaluation Periods

After initial qualification, which incorporates training and evaluation on all proficiency objectives, follow-on training will occur within a scheduling interval called a continuing qualification cycle. This is the time period during which all proficiency objectives are trained, validated, or evaluated for all flight crewmembers. The initial approval is for a continuing qualification cycle that is no more than 26 months in duration and is divided into two 13-month evaluation periods. All critical proficiency objectives are accomplished during each evaluation period, and all currency proficiency objectives are accomplished during each continuing qualification cycle.

The initial duration of a continuing qualification cycle is 26 months but it may be subsequently and incrementally extended by the Authority to a maximum of 39 months, contingent upon the results of performance proficiency data from each such cycle.

(vii) Training Sessions

Each evaluation period shall include a minimum of one training session but may include more. Initially, training sessions cannot be more than 13 months apart.

(viii) Proficiency Evaluations

For PICs, SICs, flight engineers, and other persons covered by EBT, a proficiency evaluation shall be completed during each evaluation period. Typically, the proficiency evaluation will occur during a required training session. However, if more than one training session is completed during an evaluation period, the proficiency evaluation may be divided among training sessions or otherwise allocated to one or more such sessions.

Note: The requirements specified in this table are applicable to an operator that is currently authorized for AQP/ATQP and is transitioning to EBT. For an operator that is initially implementing EBT, and is not currently authorized for AQP/ATQP, requirements as specified in items vi), vii) and viii) might vary in accordance with requirements of the State.

INTENTIONALLY LEFT BLANK

Section 3 — Operational Control and Flight Dispatch (DSP)

Applicability

[Section 3](#) addresses the requirements for operational control of flights conducted by multi-engine aircraft and is applicable to an operator that conducts such flights, whether operational control functions are conducted by the operator or conducted for the operator by an external organization (outsourced). Specific provisions of this section are applicable to an operator based on the operational system in use, the manner in which authority is delegated by the operator, and the responsibilities, functions, duties or tasks assigned to the personnel involved.

The IOSA standards and recommended practices (ISARPs) in [Section 3](#) are applicable only to those aircraft that are of the type authorized in the Air Operator Certificate (AOC) and utilized in commercial passenger and/or cargo operations, unless applicability is extended to encompass non-commercial operations as stated in a note immediately under the body of the provision.

[Subsection 4.6](#) contains provisions that address (optional) performance-based methods for achieving conformity with eligible alternate airport, fuel planning and EDTO provisions contained in other subsections. General guidance related to the practical application of performance-based methods and related provisions prefaces [subsection 4.6](#).

[Table 3.1](#) categorizes the personnel that are delegated the authority to exercise operational control, assigned the overall responsibility for the overall operational control of a flight, assigned the individual responsibility to carry out one or more functions, duties or tasks related to the operational control of a flight, or assigned the duty to provide administrative support to others with responsibilities related to operational control.

[Table 3.5](#) defines the competencies of operational control personnel appropriate to the assignment of overall responsibility for operational control and/or to carry out one or more operational control functions, duties or tasks according to their specific competencies.

All personnel utilized to perform operational control functions as defined in [Table 3.1](#), or that act in a manner consistent with the functional categories specified in [Table 3.1](#) and the competencies specified in [Table 3.5](#), irrespective of management or post holder title, are subject to specified training and qualification provisions in this section relevant to the operational control function performed.

Individual DSP provisions, and/or individual sub-specifications within a DSP provision, that:

- Do not begin with a conditional phrase are applicable to all operators unless determined otherwise by the Auditor.
- Begin with a conditional phrase (“If the Operator...”) are applicable if the operator meets the condition(s) stated in the phrase. The conditional phrase serves to define or limit the applicability of the provision (e.g. “If the operator utilizes...” or “If an FOO or FOA is utilized...”).
- Begin with a conditional phrase that specifies the use of a Flight Operations Officer (FOO) by an operator are applicable when the operator assigns the FOO, as defined in the IRM and delegated authority in accordance with [Table 3.1](#), responsibility to carry out operational control functions, duties or tasks related to *all* of the competencies of operational control as specified in [Table 3.5](#).
- Begin with a conditional phrase that specifies the use of a Flight Operations Assistant (FOA) by an operator are applicable when the operator assigns the FOA, as defined in the IRM, responsibility to carry out operational control functions, duties or tasks related to one or more, *but not all*, competencies of operational control as specified in [Table 3.5](#).
- Are applicable to all systems of operational control, but with differences in application to each system, will have those differences explained in the associated Guidance Material (GM).
- Contain the phrase “personnel responsible for operational control” or “personnel with responsibility for operational control” refer to any suitably qualified personnel with responsibility for operational control as designated by the operator, to include the pilot-in-command (PIC) unless otherwise annotated.

- Contain training and qualification requirements are applicable to personnel, other than the PIC, that are assigned responsibilities related to the operational control of flights. PIC training and qualification requirements for all systems of operational control are specified in ISM [Section 2](#) (FLT).
- Are eligible for conformance using performance-based methods contain a note referring to applicable provisions in [subsection 4](#).

Where operational functions, duties or tasks associated with operational control are outsourced to external service providers, an operator retains overall responsibility for ensuring the management of safety in the operational control of flights and must demonstrate processes for monitoring applicable external service providers in accordance with [DSP 1.11.2](#).

General Guidance

Authority and Responsibility

For the purposes of this section *authority* is defined as the delegated power or right to command or direct, to make specific decisions, to grant permission and/or provide approval, or to control or modify a process.

For the purposes of this section *responsibility* is defined as an obligation to perform an assigned function, duty, task or action. An assignment of responsibility typically also requires the delegation of an appropriate level of authority.

Operational Control

Operational control is defined as the exercise of authority to initiate, continue, divert or terminate a flight in the interest of the safety and security of the aircraft and its occupants. An operator may delegate the authority for operational control of a specific flight to qualified individuals, but typically retains overall authority to operate and control the entire operation. An operator may also assign the responsibility to carry out specific operational control functions, duties, or tasks related to the conduct of each flight to identifiable, qualified and knowledgeable individual(s), but would remain responsible (and accountable) for the conduct of the entire operation.

Any individuals delegated the authority to make specific decisions regarding operational control would also be responsible (and accountable) for those decisions. Additionally, individuals assigned the responsibility to carry out specific operational control functions, duties, or tasks related to the conduct of each flight are also responsible (and accountable) for the proper execution of those functions, duties, or tasks. In all cases, the authority and responsibility attributes of operational control personnel are clearly defined and documented by the operator and communicated throughout the organization.

It is important to note that when an operator assigns the responsibility for functions, duties or tasks related to the initiation, continuation, diversion and termination of a flight to employees or external service providers, such operator retains full responsibility (and accountability) for the proper execution of those functions, duties or tasks by ensuring:

- The training and qualification of such personnel meets any regulatory and operator requirements;
- Personnel are performing their duties diligently;
- The provisions of the Operations Manual are being complied with;
- An effective means of oversight is maintained to monitor the actions of such personnel for the purposes of ensuring operator guidance and policy, as well regulatory requirements, are complied with.

Authority for the Operational Control of Each Flight

In order to practically exercise operational control of flight operations, an operator typically delegates the authority for the initiation, continuation, diversion or termination of each flight to qualified individuals. Such delegation occurs in conjunction with an operator's overall system of operational control as follows:

- Shared systems, wherein operational control authority is shared between the pilot-in-command (PIC) **and** a flight operations officer/flight dispatcher (FOO) **or** designated member of management, such as the Director of Flight Operations (or other designated post holder);

For example: The FOO (or designated member of management, as applicable) has the authority to divert, delay or terminate a flight if in the judgment of the FOO, a designated member of management or the PIC, the flight cannot operate or continue to operate safely as planned or released.

- Non-shared systems, wherein operational control authority is delegated **only** to the PIC.

For example: Only the PIC has the authority to terminate, delay, or divert a flight if in the judgment of the PIC the flight cannot operate or continue to operate safely as planned.

Responsibility for Operational Control of Each Flight

While an operator retains full responsibility (and accountability) for the entire operation, the responsibility for the practical operational control of each flight is typically assigned to qualified individuals. As with the delegation of authority, the assignment of responsibility related to the operational control of each flight occurs in conjunction with a system of operational control as follows:

- Shared systems, wherein operational control responsibility for each flight is shared between the PIC and an FOO, or between the PIC and a designated member of management such as the Director of Flight Operations (or other designated post holder). In either shared system, the PIC, FOO or designated member of management, as applicable, may be assisted by other qualified personnel assigned the individual responsibility (by the operator) to carry out specific operational control functions, duties or tasks. Such personnel, however, typically do not share operational control responsibility with the PIC, FOO or designated member of management, as applicable.

For example: The FOO (or designated member of management) and the PIC are jointly responsible (and accountable) for the functions, duties or tasks associated with the operational control of a flight, such as pre-flight planning, load planning, weight and balance, delay, dispatch release, diversion, termination, etc. In such systems, the FOO (or designated member of management) may carry out such responsibilities unassisted or be assisted by qualified personnel assigned the individual responsibility (by the operator) to carry out specific operational control functions, duties or tasks.

- Non-shared systems, wherein the PIC is solely responsible for all duties, functions, or tasks regarding operational control of each flight, and may carry out such responsibilities unassisted or be assisted by qualified personnel assigned the individual responsibility (by the operator) to carry out specific operational control functions, duties or tasks.

For example: The PIC is solely responsible (and accountable) for the duties, functions, duties or tasks associated with the operational control of a flight, and the PIC either acts unassisted or is assisted by qualified personnel in carrying out functions, duties or tasks such as preflight planning, load planning, weight and balance, delay, dispatch release, diversion, termination, etc.

Responsibility for Individual Operational Control Functions, Duties, or Tasks

It is important to note that, except for purely non-shared (PIC-only) systems, and as illustrated by the examples in the previous paragraph, the assignment of responsibilities related to the operational control of each flight can be further subdivided among a number of qualified and specialized personnel. In such cases, the responsibility for individual or specific operational control functions, duties or tasks is typically assigned to FOA personnel who support, brief and/or assist the PIC, FOO personnel and/or designated member(s) of management, as applicable, in the safe conduct of each flight. Examples of such qualified personnel include Weather Analysts, Navigation Analysts/Flight Planning Specialists, Load Agents/Planners, Operations Coordinators/Planners/Controllers, Maintenance controllers and Air Traffic Specialists.

Note: Some operators might choose to assign the responsibility for specialized operational control functions, such as those described in the example, to fully qualified FOO personnel. In such cases, an FOO, although qualified in all competencies of operational control, would be functionally acting as an FOA. Therefore, for the purpose of an audit, FOO personnel acting in this limited capacity are assessed as FOA personnel.

Note: Load Agents/Planners/Controllers who perform load control functions within the scope of ground handling operations may not be considered FOAs if trained and qualified in accordance with ISM Section 6 (GRH), [Subsection 2.1](#), Training Program.

Administrative Support Personnel

FOA personnel are not to be confused with administrative personnel that lack any operational control authority, have very limited operational control responsibilities, and who simply provide, collect or assemble operational documents or data on behalf of the PIC, the FOO, designated member of management or the operator.

Administrative personnel may be present in any system of operational control, are excluded from the initial and continuing qualification provisions of this section and may be qualified as competent through on-the-job training (OJT), meeting criteria as specified in a job description, or through the mandatory use of written instruments such as task cards, guidelines, or checklists.

Additional Note

For the purposes of this section, continuing qualification includes recurrent or refresher training as well as any training necessary to meet recency-of-experience requirements.

Definitions, Abbreviations, Acronyms

Definitions of technical terms used in this ISM [Section 3](#), as well as the meaning of abbreviations and acronyms, are found in the IATA Reference Manual for Audit Programs (IRM).

1 Management and Control

1.1 Management System Overview

1.2 (Intentionally open)

1.3 Accountability, Authorities and Responsibilities



DSP 1.3.2B

The Operator shall have a process and/or procedures for the delegation of duties within the management system for operational control that ensures managerial and operational control continuity is maintained and responsibility for operational control functions is assumed by qualified personnel when:



(i) Managers directly responsible for the operational control of flights are unable to carry out work duties;



(ii) If utilized in the system of operational control, FOO and/or FOA personnel are unable to carry out work duties. **(GM)**

Auditor Actions



☐ **Identified/Assessed** processes for management system delegation of duties for operational control personnel (focus: operational control managerial continuity is maintained, operational; control responsibilities are assumed by qualified personnel).

☐ **Interviewed** responsible operational control manager(s).



☐ **Examined** example(s) of delegation of duties (focus: responsibilities for operational control are assumed by qualified personnel).

☐ **Other Actions** (Specify)

Guidance



The intent of this provision is to ensure an operator has a process or procedures for succession in cases when operational control personnel directly responsible for the operational control of flights are unable, for any reason, to carry out work duties. Such process or procedures typically also address a handover of responsibilities that ensures no loss of continuity in the operational control of flights.



The operational control personnel subject to the specifications of this provision include, as a minimum:



- Managerial personnel, as defined by the operator, with responsibility for ensuring the operational control of flights;



- If applicable, FOO or FOA personnel who are delegated authority and/or responsibility in accordance with [DSP 1.3.4](#) and [1.3.5](#) respectively.

1.4 Communication and Coordination

1.5 Provision of Resources

1.6 Documentation System

1.7 Operations Manual

1.8 Records System

1.9 (Intentionally open)

1.10 Quality Assurance Program

1.11 Quality Control of Outsourced Operations and Products

1.12 Safety Management

Risk Management

DSP 1.12.1

The Operator shall have a hazard identification program in the organization responsible for the operational control of flights that includes:

- (i) A combination of reactive and proactive methods for hazard identification;
- (ii) Processes for safety data analysis that identify existing hazards, and may predict future hazards, to aircraft operations. **[SMS] (GM) ◀**

Auditor Actions

- ☐ **Identified/Assessed** safety hazard identification program in operational control system (focus: program identifies hazards to aircraft operations; describes/defines method(s) of safety data collection/analysis).
- ☐ **Identified/Assessed** role of operational control in cross-discipline safety hazard identification program (focus: participation with other operational disciplines).
- ☐ **Interviewed** responsible operational control manager(s).
- ☐ **Interviewed** person(s) that perform operational control data collection/analysis to identify hazards to aircraft operations.
- ☐ **Examined** selected examples of hazards identified through operational control data collection/analysis.
- ☐ **Other Actions** (Specify)

Guidance

Refer to the IRM for the definitions of [Hazard \(Aircraft Operations\)](#) and [Safety Risk](#).

Hazard identification is an element of the Safety Risk Management component of the SMS framework.

The specifications of this provision may be satisfied by the hazard identification program in the flight operations organization if such program includes the operational control system.

Hazard identification specific to an operational activity (e.g. alternate airport selection, fuel planning and/or EDTO) is a risk management process that is central to the performance-based methods used for development of operational variations in accordance with applicable provisions in [subsection 4.6](#).

Refer to Guidance associated with [ORG 3.1.1](#) located in ISM Section 1.



DSP 1.12.2

The Operator shall have a safety risk assessment and mitigation program in the organization responsible for the operational control of flights that specifies processes to ensure:

- (i) Hazards are analyzed to determine the corresponding safety risks to aircraft operations;
- (ii) Safety risks are assessed to determine the requirement for risk mitigation action(s);
- (iii) When required, risk mitigation actions are developed and implemented in operational control. **[SMS] [Eff] (GM) ◀**

Assessment Tool

Desired Outcome

The Operator maintains an overview of its operational control risks and through implementation of mitigation actions, as applicable, ensures risks are at an acceptable level.

Suitability Criteria (Suitable to the size, complexity and nature of operations)

Number and type of analyzed hazards and corresponding risks.

Means used for recording risks and mitigation (control) actions.

Safety data used for the identification of hazards.

Effectiveness Criteria

- (i) All relevant operational control hazards are analyzed for corresponding safety risks.
- (ii) Safety risks are expressed in at least the following components:
 - Likelihood of an occurrence.
 - Severity of the consequence of an occurrence.
 - Likelihood and severity have clear criteria assigned.
- (iii) A matrix quantifies safety risk tolerability to ensure standardization and consistency in the risk assessment process which is based on clear criteria.
- (iv) Risk register(s) within the operational control organization capture risk assessment information, risk mitigation (control) and monitoring actions.
- (v) The risk mitigation (control) actions include time lines, allocation of responsibilities and risk control strategies such as hazard elimination, risk avoidance, risk acceptance, risk mitigation.
- (vi) Mitigation (control) actions are implemented to reduce the risk to a level of - as low as reasonably practical.
- (vii) Identified risks and mitigation actions are regularly reviewed for accuracy and relevance.
- (viii) Effectiveness of risk mitigation (control) actions are monitored at least yearly to include auditing in accordance with [ORG 3.4.1](#).
- (ix) Personnel performing risk assessments are appropriately trained in accordance with [ORG 1.6.5](#).

Auditor Actions

- ☐ **Identified/Assessed** safety risk assessment/mitigation program in operational control system (focus: hazards analyzed to identify/define risk; risk assessed to determine appropriate action; action implemented/monitored to mitigate risk).
- ☐ **Identified/Assessed** role of operational control in cross-discipline safety risk assessment/mitigation program (focus: participation with other operational disciplines).
- ☐ **Interviewed** responsible operational control manager(s).
- ☐ **Interviewed** person(s) that perform operational control risk assessment/mitigation.
- ☐ **Examined** selected records/documents that illustrate risk assessment/mitigation actions.
- ☐ **Other Actions** (Specify)

Guidance

Refer to the IRM for the definitions of [EDTO \(Extended Diversion Time Operations\)](#) and [Rescue and Fire Fighting Services \(RFFS\)](#).

Risk assessment and mitigation is an element of the Safety Risk Management component of the SMS framework.

Hazards relevant to the conduct of aircraft operations are potentially associated with:

- Weather (e.g. adverse, extreme and space);
- Geophysical events (e.g. volcanic ash, earthquakes, tsunamis);
- Operations in airspace affected by armed conflict;
- ATM congestion;
- Mechanical failure;
- Geography (e.g. adverse terrain, large bodies of water, polar);
- Airport constraints (e.g. isolated, runway closure, rescue and RFFS capability);
- Alternate airport selection, specification and availability at the estimated time of use;
- Preflight fuel planning and in-flight fuel management;
- Critical fuel scenarios;
- EDTO;
- Performance-based compliance to prescriptive regulations;
- The capabilities of an individual aircraft (e.g. cargo smoke detection, fire suppression systems, open MEL items);
- Criminal and/or unauthorized activities directed at manned aircraft or in the vicinity of manned aircraft operations (e.g. laser pointing, unauthorized UAS/RPAS operations);
- Any other condition(s) that would pose a safety risk to aircraft operations (e.g. radiation).

The specifications of this provision may be satisfied by the safety risk assessment and mitigation program in the flight operations organization if such program includes the operational control system.

Risk assessment and mitigation specific to an operational activity (e.g. alternate airport selection, fuel planning and/or EDTO) is a risk management process that is central to the performance-based methods used for development of operational variations in accordance with applicable provisions in [subsection 4.6](#).

Refer to Guidance associated with [ORG 3.1.2](#) located in ISM Section 1.

Operational Reporting

DSP 1.12.3

The Operator shall have an operational safety reporting system in the organization responsible for the operational control of flights that:

- (i) Encourages and facilitates operational control personnel to submit reports that identify safety hazards, expose safety deficiencies and raise safety concerns;
- (ii) Ensures mandatory reporting in accordance with applicable regulations;
- (iii) Includes analysis and operational control management action as necessary to address safety issues identified through the reporting system. **[SMS] (GM) ◀**

Auditor Actions

- ☐ **Identified/Assessed** operational safety reporting system in operational control (focus: system urges/facilitates reporting of hazards/safety concerns; includes analysis/action to validate/address reported hazards/safety concerns).
- ☐ **Interviewed** responsible operational control manager(s).
- ☐ **Interviewed** person(s) that perform operational safety report review/analysis/follow-up in operational control.
- ☐ **Examined** data that indicates robustness of operational control safety reporting system (focus: quantity of reports submitted/hazards identified).
- ☐ **Examined** records of selected operational control safety reports (focus: analysis/follow-up to identify/address reported hazards/safety concerns).
- ☐ **Other Actions** (Specify)

Guidance

Safety reporting is a key aspect of SMS hazard identification and risk management.

Safety reporting specific to an operational activity (e.g. alternate airport selection, fuel planning and/or EDTO) is a risk management process that is central to the performance-based methods used for development of operational variations in accordance with applicable provisions in [subsection 4.6](#).

The specifications of this provision may be satisfied by the operational reporting system in the flight operations organization if such system includes the operational control system.

Refer to Guidance associated with [ORG 3.1.3](#) located in ISM Section 1.

Safety Performance Monitoring and Management

2 Training and Qualification

General Guidance

Many of the provisions of this subsection contain specifications related to the recurring frequency of training and evaluation events for operational control personnel. Such provisions, with a few exceptions, define cycles or intervals for the completion of recurrent training and/or evaluation expressed in months since training was first completed or qualification was first established. It is important to note, however, that for the purpose of conformity with these provisions, such intervals are nominal and that the actual interval may vary slightly. For example, an Operator may adjust the frequency of evaluations to minimize overlap, provide scheduling flexibility, preserve the original qualification date, and/or to ensure evaluations are consistently completed in accordance with the nominal cycle set forth by the State and/or applicable authorities. Accommodations of this nature are commonplace and vary widely by regulatory jurisdiction. In all cases, however, the auditor will make the determination of whether or not such accommodations fit within the nominal cycles established in each provision.

2.1 Training and Evaluation Program

General

DSP 2.1.1

The Operator shall have a training program, approved or accepted by the Authority, to ensure the operational control personnel as specified in [Table 3.1](#), as applicable to the Operator, are competent to perform any assigned duties relevant to operational control in accordance with the applicable specifications of [Table 3.5](#) prior to being assigned to operational control duties. Such program shall, as a minimum, address:

- (i) Initial qualification;
- (ii) Continuing qualification. **(GM)**

Auditor Actions

- ❑ **Identified/Assessed** training program for operational control personnel (focus: program addresses initial/continuing qualification for functions specified in [Table 3.1](#)).
- ❑ **Interviewed** responsible operational control manager(s).
- ❑ **Examined** training/qualification course curricula for operational control personnel (focus: course content as specified in [Table 3.5](#)).
- ❑ **Examined** training/qualification records of selected operational control personnel (focus: completion of initial/recurrent training).
- ❑ **Other Actions** (Specify)

Guidance

Refer to the IRM for the definitions of [Continuing Qualification](#), [State Acceptance](#) and [State Approval](#). Not all states require the approval or acceptance of a training program for operational control personnel. In such cases, state acceptance is considered implicit.

A training program for operational control personnel typically addresses:

- For FOO and FOA personnel, initial and continuing qualification in accordance with the specifications of [Table 3.1](#) and [Table 3.5](#);
- For FOO and FOA personnel, a method of qualification through written, oral and/or practical evaluation;
- For administrative support personnel as defined in [Table 3.1](#), on-the-job training (OJT), job descriptions, task cards, guidelines, checklists, training materials or other written means to establish competence.

The specifications of this provision apply to FOO or FOA personnel who are delegated authority and/or assigned responsibilities in accordance with [DSP 1.3.4](#) and/or [DSP 1.3.5](#), respectively.

FOO personnel who have completed training programs conducted in accordance with ICAO Doc 7192-AN/857, Part D, Training Manual—Flight Operations Officers/Flight Dispatchers, meet the specifications of this provision.

FOO initial training programs contain all of the competencies in [Table 3.5](#) that are relevant to the operations of the operator.

FOA initial training programs contain the competencies in [Table 3.5](#) that are relevant to their job function as determined by the operator.

Instructors and Evaluators

2.2 Training Elements

2.3 Line Qualification

2.4 Special Qualification

2.5 SMS Training

3 Line Operations

3.1 General

3.2 Flight Preparation and Planning

DSP 3.2.9B

The Operator shall have guidance and procedures to ensure a flight to be conducted in accordance with IFR *does not*:

- (i) Take off from the departure airport unless the meteorological conditions, at the time of use, are at or above the operator's established airport takeoff operating minima for that operation; **and**
- (ii) Take off, or continue beyond the point of in-flight re-planning, unless at the airport of intended landing or at each required alternate airport, current meteorological reports or a combination of current reports and forecasts indicate that the meteorological conditions will be, at the estimated time of use, at or above the operator's established airport operating minima for that operation. **(GM)**

Auditor Actions

- ☐ **Identified/Assessed** guidance/procedures for the assessment of airport meteorological conditions prior to departure of IFR flights (focus: flight planning determines that conditions at departure/destination/alternate airports meet all applicable requirements).
- ☐ **Interviewed** responsible operational control manager(s).
- ☐ **Observed** operational control/flight dispatch operations office (focus: procedures for monitoring/assessing meteorological conditions for operational airports).
- ☐ **Coordinated** with FLT auditor (focus: flight crew assessment of meteorological conditions for operational airports).
- ☐ **Other Actions** (Specify)

Guidance

Refer to the IRM for the definitions of [Alternate Airport](#) and [In-flight Re-planning Point](#).

The intent of this provision is to ensure flights do not takeoff or continue beyond the point of in-flight re-planning unless the meteorological conditions at each airport specified in i) or ii), are or will be, at or above the operator's established airport operating minima for the operation at the estimated time of use.

The specification in item ii) would require the definition and application of alternate airport planning minima in accordance with [DSP 3.2.9C](#).

3.3 Aircraft Performance and Load Planning

DSP 3.3.1

The Operator shall have guidance and procedures to ensure a planned flight does not exceed:

- (i) The maximum performance takeoff and landing weight limits, based upon environmental conditions expected at the times of departure and arrival;
- (ii) The aircraft structural takeoff, en route and landing weight limits. **(GM)**

Auditor Actions

- **Identified/Assessed** guidance/procedures for application of aircraft performance data for planned flights (focus: flight planning accounts for aircraft takeoff/en route/landing performance weight limitations).
- **Interviewed** responsible operational control manager(s).
- **Observed** operational control/flight dispatch operations (focus: guidance/procedures/restrictions that ensure flights do not exceed aircraft performance weight limitations).
- **Coordinated** with FLT auditor (focus: preflight consideration of aircraft performance limitations).
- **Other Actions** (Specify)

Guidance

The intent of this provision is to ensure the presence of guidance and procedures for the calculation of maximum takeoff and landing weights, based on takeoff, en route, landing performance, structural limitations as well as any applicable MEL restrictions. Additionally, such guidance and procedures address the means used to prevent an aircraft from being loaded in a manner that precludes a flight from being operated overweight (e.g. notification of weight restrictions to a Load Control Center/office or equivalent).

DSP 3.3.3

The Operator shall ensure qualified personnel perform weight and balance calculations. **(GM)**

Auditor Actions

- **Identified** specific personnel that perform weight/balance calculations.
- **Identified/Assessed** weight/balance training/qualification program for operational control personnel (if applicable) (focus: applicable to personnel that perform weight/balance calculations; program includes demonstration of competence in weight/balance calculation).
- **Interviewed** responsible operational control manager(s).
- **Examined** training/qualification records of selected operational control personnel (if applicable) (focus: completion of weight/balance training program by operational control personnel that perform weight/balance calculations).
- **Coordinated** with FLT auditor (if applicable) (focus: flight crew members are qualified to perform weight/balance calculations).
- **Coordinated** with ground handling operations (if applicable) (focus: load control personnel are qualified to perform weight/balance calculations).
- **Other Actions** (Specify)

Guidance

Weight and balance calculations may be delegated to a FOO or an appropriately qualified FOA.

The PIC may complete weight and balance calculations, if qualified in accordance with ISM Section 2 (FLT), [Subsection 2.1](#), Training and Evaluation Program.

Load control personnel that perform functions within the scope of ground handling operations may complete weight and balance calculations if qualified in accordance with ISM Section 6 (GRH), [Subsection 2.1](#), Training Program.

3.4 Icing Conditions

3.5 Aircraft Tracking

3.6 Flight Monitoring and In-Flight Management

DSP 3.6.5A

The Operator shall have guidance and procedures to ensure a flight is not continued toward the airport of intended landing unless the latest available information indicates, at the expected time of use, a landing can be made either at that airport or at least one destination alternate airport. **(GM)**

Auditor Actions

- ❑ **Identified/Assessed** guidance/procedures for monitoring/assessing conditions at flight destination/alternate airports (focus: flight continuation permitted only if information indicates landing can be made at destination/alternate airport).
- ❑ **Interviewed** responsible operational control manager(s).
- ❑ **Observed** operational control/flight dispatch operations (focus: monitoring of destination/alternate airport conditions/information during flight).
- ❑ **Other Actions** (Specify)

Guidance

The intent of this provision is to ensure personnel with operational control responsibilities have access to the most current and accurate information available in order to support informed decision-making related to safe flight completion. This is especially important when the conditions under which a flight was originally planned have changed after takeoff (e.g. unplanned re-release) or because the flight was planned with a re-release point (a pre-planned re-release). In either case, the overriding intent is to ensure operational control personnel, including flight crews, have access to the most current and accurate information available. Access to such information is typically necessary to ensure flights do not proceed beyond the last possible point of diversion to an en route alternate airport (appropriate for the aircraft type) and continue to the destination when, in the opinion of either the PIC or, in a shared system of operational control, the PIC and FOO it is unsafe to do so.

Information that would be useful in determining whether a landing can be made at the destination or any required alternate is typically related to:

- Meteorological conditions, both en route and at the airport of intended landing, to include hazardous phenomena such as thunderstorms, turbulence, icing and restrictions to visibility.
- Field conditions, such as runway condition and availability and status of navigation aids.
- En route navigation systems and facilities status, where possible failures could affect the safe continuation or completion of the flight.
- En route fuel supply, including actual en route consumption compared to planned consumption, as well as the impact of any changes of alternate airport or additional en route delays.
- Aircraft equipment that becomes inoperative, which results in an increased fuel consumption or a performance or operational decrement that could affect the flight crew's ability to make a safe landing at an approved airport.
- Air traffic management concerns, such as re-routes, altitude or speed restrictions and facilities or system failures or delays.
- Security concerns that could affect the routing of the flight or its airport of intended landing.

Refer to [Table 2.2](#) found in ISM Section 2 (FLT) for OM documentation requirements.

DSP 3.6.5B

If the Operator selects and specifies en route alternate airports on the OFP, the Operator shall have guidance and procedures to ensure en route alternate airports selected and specified on the OFP are available for approach and landing, and the forecast at those airports is for conditions to be at or above the operating minima approved for the operation. **(GM)**

Auditor Actions

- ☐ **Identified** requirement for selection of en route alternate airports.
- ☐ **Identified/Assessed** guidance/procedures for selection/designation of en route alternate airports (focus: flight planning includes assessment/selection/designation on OFP of en route alternate airports with conditions that will permit approach/landing at estimated time of use).
- ☐ **Interviewed** responsible operational control manager(s).
- ☐ **Examined** selected OFPs (focus: specification of en route alternate airports).
- ☐ **Observed** operational control/flight dispatch operations (focus: monitoring of en route airports conditions/information during flight).
- ☐ **Other Actions** (Specify)

Guidance

The intent of this provision is for the operator to have a methodology to protect a diversion *should* a situation occur that may require an aircraft to divert while en route. For example, such a methodology typically includes ensuring that operational control personnel and pilots are knowledgeable about diversion airport alternates, applicable meteorological conditions, and have the means to obtain information related to the availability of en route alternates.

One way to ensure a reasonable certainty that the weather conditions at a required en route alternate will be at or above operating minima approved for the operation is through the application and use of planning minima (at the planning stage) as specified in [DSP 3.2.9C](#). This is done to increase the probability that a flight will land safely after a diversion to an en route alternate airport.

Refer to [Subsection 4.5](#) for provisions that specify the additional steps necessary to protect an en route alternate airport when aircraft are engaged in operations beyond 60 minutes (from a point on a route to an en route alternate airport) or extended diversion time operations (EDTO).

3.7 Emergency Response

4 Operational Control Requirements and Specifications

General Guidance

Operators and Authorities alike are placing increased emphasis on performance-based methods and performance-based compliance to regulation. Such mechanisms allow for greater operational flexibility without degrading the safety performance of an operational activity. This presumption is primarily dependent on the presence of specific organizational and operational capabilities, the results of safety risk management activities and the determination of acceptable standards of safety performance.

Many of the provisions in the following sub-section contain an option applicable only to those operators that use performance-based methods in order to conform to selected alternate airport selection, fuel planning and/or EDTO ISARPs. These options are typically presented as alternatives to one or more “prescriptive” specifications that are independent of other systems, policies, processes or procedures. That is to say, the parent provision and related specifications completely describe “what” must be accomplished and “how” it is to be accomplished.

In order to take advantage of the shift in emphasis from “how” an operational activity is to be accomplished to “what” the activity is to accomplish, operators would typically have the resources necessary to analyze very specific operational hazards, manage the associated safety risks and achieve target levels of safety performance. The determination that operators will be able to reach a target level of safety performance necessary to ensure safety is dependent on numerous

organizational and operational capabilities that typically include, but are not limited to, those that are compiled in the following table:

Organizational and Operational Capabilities	Description
<p>Organizational and Operational Process Management and Control</p> <p>Practically speaking, operators must possess the requisite knowledge, skills, experience, resources and technologies necessary to implement and oversee the many systems and processes required to support performance-based compliance.</p>	<p>This is demonstrable organizational and operational process management and control that is dependent on robust subordinate or related processes including:</p> <ul style="list-style-type: none"> • The development of policy and procedure; • The staffing of positions with an appropriate number of qualified personnel; • Training to the operator's policy and procedure and to ensure personnel remain competent and qualified; • Implementation or the demonstration of performance in accordance with policy and procedure; • Data reporting, measurement and analysis for the purpose of monitoring the effectiveness and efficiency of systems, processes, policies and/or procedures; • An adjustment component or subsystem to respond to any underperformance or deviation and for the purpose of continuous improvement.
<p>Specific Operational Capabilities (operational control, aircraft, airport, infrastructure and meteorological)</p>	<p>These are the key operator capabilities necessary to support operational activities related to alternate selection, fuel planning and/or EDTO including:</p> <ul style="list-style-type: none"> • Operational control systems and standard operating procedures that provide the direction for the conduct of flight operations; • Ground-based and airborne tools and technologies to improve situational awareness and operational capability; • Flight monitoring that encompasses the activities necessary to effectively exercise operational control; • Field condition monitoring at the destination, en route, en route alternate and destination alternate airports (as applicable) nominated for use by the flight up until the flight is no longer dependent on the use of the applicable airports • Rapid and reliable communication capabilities; • Weather reporting and monitoring capability.



Organizational and Operational Capabilities	Description
A (Tactical) Safety Risk Management Sub-system (specific to operational systems or processes that support performance-based compliance)	This is the subsystem that interfaces with the internal system of production (related to a specific system or process) for data reporting, measurement and analysis, as well as appropriate organizational SRM components. This includes the interfaces with SMS and Quality systems to ensure operational systems and processes are subjected to the organization's overarching safety and quality assurance processes, and: <ul style="list-style-type: none"> • Appropriate data from many sources are isolated and extracted; • Reports from operational personnel are collated and analyzed; • Feedback and control references are provided against which hazard analysis and consequence management can be measured; • Material is provided for root cause and safety trend analysis; • Data are collected relevant to the mitigation of safety risks; • Identification and analysis of applicable hazards; • Assessment, control and of resultant safety risks.
An Oversight Component (performance monitoring and measurement)	This is the monitoring and measurement of safety performance through appropriate safety performance measures that continuously track system safety performance as necessary to determine whether an operator's system is truly operating in accordance with design expectations.

Keeping the aforementioned capabilities in mind, the performance-based options in the following sub-sections allow for operational flexibility based on conformance with the provisions in [sub-section 4.6](#). The specifications in those provisions define the related and interdependent systems, policies, processes or procedures designed to support the achievement of operational outcomes equivalent to that of prescriptive compliance. In other words, they allow for variations in "how" something is achieved as long as "what" is achieved is substantially equal to or better than prescriptive compliance.

It is important to note that the majority of operators will follow a well-defined and prescriptive approach to alternate selection, fuel planning and EDTO. There will be cases, however, where operators that have made significant investments in organizational and operational systems, advanced technologies and modern aircraft seek to derive greater efficiencies from the inherent flexibility of performance-based compliance. In such cases, the specifications of [sub-section 4.6](#) are designed to ensure the operator possesses the capabilities to sustain demonstrable levels of safety performance that are acceptable to the State and the operator.

Refer to the IRM for the definition of Performance-Based Compliance.

4.1 Alternate and Isolated Airports

DSP 4.1.1

The Operator shall have a system, process and/or procedures for alternate airport selection to ensure an appropriate takeoff alternate airport is selected and specified on the OFP whenever:

- (i) The meteorological conditions at the airport of departure are below the applicable airport operating landing minima, *and/or*
- (ii) Other operational conditions exist that would preclude a return to the departure airport. **(GM)**

Note: *The Operator has the option of achieving conformity with the specifications of this provision using performance-based methods in accordance with applicable provisions in [subsection 4.6](#). Such conformance is achievable irrespective of the specifications of this provision.*

Auditor Actions

- ☐ **Identified/Assessed** system/process/procedures for takeoff alternate airport selection (focus: flight planning includes assessment/selection/designation on OFP of takeoff alternate airport when meteorological/other conditions preclude flight return to departure airport).
- ☐ **Interviewed** responsible operational control manager(s).
- ☐ **Examined** selected OFPs (focus: designation of takeoff alternate airport).
- ☐ **Observed** operational control/flight dispatch operations (focus: process for selection of takeoff alternate airports).
- ☐ **Coordinated** with flight operations (focus: complementary process for selection/designation of takeoff alternate airport).
- ☐ **Other Actions** (Specify)

Guidance

The intent of this provision is to ensure a methodology exists for the selection and specification of takeoff alternate airports when required. The selection of such airports is typically intended to address an operational condition (e.g. an emergency during or immediately after takeoff) that would require the flight crew to land the aircraft as soon as practicable. Accordingly, the applicable operating landing minima specified in the provision would typically refer to the minimum ceiling and/or visibility/runway visual range for landing with an engine inoperative as established by the operator.

Takeoff alternates are typically selected during the planning stage but may be selected after flight commencement when necessary via radio, ACARS, or any other communication means acceptable to the operator and the State.

The appropriateness of an airport for selection as a takeoff alternate is dependent on many factors including, but not limited to, the operational conditions specified in [DSP 3.2.8](#).

An operator may use a system, a process or procedures alone or in any combination in order to fulfill operational requirements related to the selection of takeoff alternate airports. In all cases, however, the robustness of any methodologies used for takeoff alternate airport selection is commensurate with the breadth and complexity of the operation.

DSP 4.1.4

The Operator shall have a system, process and/or procedures for alternate airport selection that takes into account meteorological conditions and relevant operational information to ensure a minimum of one destination alternate airport is specified on the OFP and the ATS flight plan, except under one or more of the following conditions (as approved or accepted by the Authority based on the operations of the Operator):

- (i) When, based on the duration of the flight (from the departure airport, or from the point of in-flight re-planning to the destination), there is reasonable certainty that, at the estimated time of use of the destination airport:
 - (a) The approach and landing may be made under visual meteorological conditions (VMC), as defined by the State;

- (b) Separate runways are usable with at least one runway having an operational instrument approach procedure.
- (ii) When, based on the duration of the flight (from the departure airport, or from the point of in-flight re-planning to the destination airport), there is reasonable certainty that, at the estimated time of use of the destination airport, the visibility will be at least 3 miles (5 km) **and** the ceiling will be at or above one or more of the following prescribed heights, (as approved or accepted by the Authority based on the operations of the Operator):
 - (a) The ceiling height for VMC, as defined by the State, or
 - (b) 1,500 feet above the lowest (*TERPS*) circling MDA, if a circling approach is required and authorized for that airport, or
 - (c) 2,000 feet or 500 feet above the (*PANS-OPS*) circling height, whichever is greater, or
 - (d) 2,000 feet or 1,500 feet above the lowest applicable HAT/HAA, whichever is greater. **(GM)**

Note: The specifications of this provision are not applicable for flights conducted under isolated airport operations as specified in [DSP 4.1.7](#).

Note: Conformity with item ii) requires the definition of the ceiling and visibility expected at the estimated time of use of the destination airport. Other determinants such as flight time (e.g. 6 hours) or the availability of separate runways may also be used to further limit the instances when a flight may depart without nominating a destination alternate but are not required to achieve conformity with item ii).

Note: Conformity with the specifications of this provision can be achieved using performance-based methods in accordance with applicable provisions in [subsection 4.6](#). Such conformance is achievable irrespective of the specifications of this provision.

Auditor Actions

- ☐ **Identified** regulatory requirements/exceptions for designation of a minimum of one destination alternate airport.
- ☐ **Identified/Assessed** system/process/procedures for selection of a minimum of one destination alternate airport (focus: flight planning takes into account regulatory/operational conditions/requirements/factors applicable to the operator/flight; such conditions/requirements/factors that are considered/assessed in the destination alternate airport selection process are defined).
- ☐ **Interviewed** responsible operational control manager(s).
- ☐ **Examined** selected OFPs/ATS flight plans (focus: designation of destination takeoff alternate airport in accordance with relevant factors).
- ☐ **Identified/Assessed** method(s) of performance-based compliance used for destination takeoff alternate airport selection (if applicable) (focus: method conforms to the specifications of [DSP 4.6.2](#) and [DSP 4.6.4](#)).
- ☐ **Observed** operational control/flight dispatch operations (focus: process for selection/designation of destination alternate airport).
- ☐ **Coordinated** with FLT auditor (focus: complementary distance criteria for selection/designation of a minimum of one destination alternate airport).
- ☐ **Other Actions** (Specify)

Guidance

Refer to the IRM for the definitions of [Domestic Flight](#), [Isolated Airport](#), [PANS-OPS](#) and [TERPS](#), and for the abbreviations [HAT](#) and [HAA](#).

The principal intent of this provision is to address the safety risks associated with unavailability of the destination airport. As a practical matter this is typically accomplished by the selection and specification of alternate airports in accordance with the technical specifications of the provision and/or to otherwise ensure, to the extent reasonably practicable, that an airport of intended landing will be available to a flight at the estimated time of use.



Item i) identifies the basic operational specifications for alternate airport selection, although an operator may conform to a minimum of one of the numbered specifications of the provision and be in overall conformance with the intent of the entire provision. Individual conformity with items i) and ii) is “as approved or accepted by the Authority based on the operations of the Operator” and dependent on many factors including the regulatory environment and the type of operations conducted.

Isolated airport operations, by definition, preclude the designation of a destination alternate airport and are conducted in accordance with the planning specifications of [DSP 4.1.7](#) and the fuel specifications of [DSP 4.3.11](#).

For the purposes of item ii), separate runways are two or more runways at the same airport configured such that if one runway is closed, operations to the other runway(s) can be conducted.

Applicable authorities typically include those authorities that have jurisdiction over international operations conducted by an operator over the high seas or the territory of a state that is other than the State of the Operator.

The operator may use a system, process and/or procedures alone or in any combination in order to fulfill operational requirements related to the selection of alternate airports. In all cases, however, the robustness of any methodologies used for destination alternate airport selection is commensurate with the breadth and complexity of the operation.

DSP 4.1.7

If the Operator conducts isolated airport operations that preclude the selection of any destination alternate airport in accordance with [DSP 4.1.4](#) or [4.1.5](#), the Operator shall have a process to ensure, for each flight into an isolated destination airport:

- (i) The designation of a point of safe return (PSR);
- (ii) The flight does not continue past the PSR unless a current assessment of meteorological conditions, traffic, and other operational conditions indicate that a safe landing can be made at the estimated time of use. **(GM) ▲**

▲ An operator may conform to [DSP 4.1.7](#) through Active Implementation as long as the implementation Action Plan (IAP) projects conformance on or before 31 August 2021.

Auditor Actions

- **Identified** operations to isolated airport that preclude selection/designation of destination alternate airports.
- **Identified/Assessed** process/procedures for designation/use of PSR in the conduct of isolated airport flights (focus: flight planning includes computing/designating PSR for each isolated airport flight; procedures for monitoring/assessing conditions during flight to allow/disallow flight continuation past PSR to destination airport).
- **Interviewed** responsible operational control manager(s).
- **Examined** selected flight records (focus: designation/use of PSR for isolated airport flights).
- **Observed** operational control/flight dispatch operations (focus: process for designation of PSR for isolated airport flights; ensuring safe destination conditions for flight continuation past PSR).
- **Coordinated** with FLT auditor (focus: complementary PSR procedures for isolated airport flights).
- **Other Actions** (Specify)

Guidance

Refer to the IRM for the definitions of [Isolated Airport](#) and [Point of Safe Return \(PSR\)](#).

The intent of this provision, in combination with the fuel carriage requirements specified in [DSP 4.3.11](#), is the mitigation of some risks associated with operations to those airports that preclude the selection of a destination alternate and, in addition, the creation of awareness among operational control personnel and the PIC as to the actual position of the PSR and the conditions necessary to continue beyond the PSR to the isolated airport.

For the purposes of this provision, an airport is considered isolated when there is no destination alternate appropriate for a given aircraft type within a prescribed flight time from the destination.



A destination airport is typically considered isolated by the Authority when the fuel required to go-around from Decision Altitude/Height (DA/H) or the Missed Approach Point (MAP) at the destination airport and then divert to the nearest alternate exceeds, for a turbine engine aircraft, the fuel required to hold at the destination airport for two hours including final reserve fuel.

In the context of isolated airport operations, a PSR is the point of last possible diversion to an en route alternate. The specification in item i) requires that a PSR is to be determined for each flight to an isolated airport. While this point can be calculated and specified on the OFP at the planning stage, such a calculation does not typically take into account any discretionary fuel, or the real-time changes in fuel consumption that will occur after departure.

Therefore, since the PSR will typically be reached later in the flight than the point originally calculated in the OFP, an operator would normally provide practical instructions so that operational control personnel and the flight crew can calculate or determine the actual position of the PSR.

The Final Decision Point used in Decision Point Planning or the Pre-determined Point used in Pre-determined Point planning may be used to meet the intent of this specification in lieu of a specific PSR.

Guidance for planning operations to isolated airports, including the determination of a PSR, may be found in the ICAO Flight Planning and Fuel Management Manual (Doc 9976).

4.2 Minimum Flight Altitudes and En Route Performance

4.3 Fuel Planning

DSP 4.3.1

The Operator shall have a system, process and/or procedures to ensure an aircraft carries a sufficient amount of usable fuel to complete each planned flight safely and allow for deviations from the planned operation. (GM)

Auditor Actions

- ☐ **Identified/Assessed** system/process/procedures for fuel planning for all flights (focus: flight planning takes into account possible deviations from planned operation in calculating usable fuel for safe completion of flight).
- ☐ **Interviewed** responsible operational control manager(s).
- ☐ **Examined** selected OFPs (focus: fuel load meets/exceeds minimum required departure/dispatch fuel).
- ☐ **Observed** operational control/flight dispatch operations (focus: process or procedures that ensure sufficient usable fuel for safe flight completion taking into account unplanned deviations).
- ☐ **Coordinated** with FLT auditor (focus: complementary procedures for assessing minimum required fuel).
- ☐ **Other Actions** (Specify)

Guidance

The intent of this provision is to define the foundation necessary to support the practical implementation of an operator's fuel policy. It also addresses the baseline criteria to be considered in any methodology used in the determination of total usable fuel required to complete each planned flight safely. Simply put, it requires an operator to use system, process and/or procedures alone or in any combination in order to fulfill operational requirements related to the implementation of its fuel policy. In all cases the robustness of any such methodologies is commensurate with the breadth and complexity of the operation and takes into account:

- The aircraft-specific data and operating conditions for the planned operation (see [DSP 4.3.2](#));

- The following components of usable fuel required in accordance with the respective provisions of this sub-section:
 - Taxi fuel (see [DSP 4.3.5](#));
 - Trip fuel in (see [DSP 4.3.6](#));
 - Contingency fuel (see [DSP 4.3.7](#));
- If required (as applicable to each flight):
 - Destination alternate fuel (see [DSP 4.3.8](#) or [DSP 4.3.9](#)), or
 - No-alternate fuel (see [DSP 4.3.10](#)), or
 - Isolated airport fuel (see [DSP 4.3.11](#)).
- Final reserve fuel (see [DSP 4.3.12](#));
- If required, additional fuel (see [DSP 4.3.13](#));
- If requested by the PIC, or the PIC and FOO in a shared system of operational control, discretionary fuel (see [DSP 4.3.14](#)).

Some regulatory authorities or operators may classify destination alternate fuel, no alternate fuel and Isolated airport fuel under the common heading of “Alternate Fuel” in regulations and/or flight planning systems.

It is important for operational control personnel and the flight crew to have a clear and common understanding of the terms used in the operator's fuel policy, as such understanding is the key to successful flight planning and completion. Equally important is the notion that differences in terminology may exist from operator to operator. Regardless of the terms used, however, an operator can conform to the provisions of this sub-section if the pre-flight computation of usable fuel is substantially equivalent, allocates fuel in a similar fashion, and has the components that, when combined, result in an equivalent or greater amount of fuel.

Fuel calculations are typically made by a flight crew member, a Flight Operations Officer/Flight Dispatcher (FOO), or both.

Guidance on the organizational and operational systems and processes related to the implementation of fuel policy is contained in the ICAO Flight Planning and Fuel Management Manual (Doc 9976).

DSP 4.3.5

The Operator shall have a process and/or procedures to ensure the taxi fuel required in accordance with its fuel policy is the amount of fuel estimated to be consumed before takeoff, taking into account local conditions at the departure airport and auxiliary power unit (APU) fuel consumption. **(GM)**

Note: *The Operator has the option of achieving conformity with the specifications of this provision using performance-based methods in accordance with applicable provisions in [subsection 4.6](#). Such conformance is achievable irrespective of the specifications of this provision.*

Auditor Actions

- ☐ **Identified/Assessed** process/procedures for calculation of taxi fuel for all flights (focus: flight planning takes into account operating data/conditions that might cause/lead to increased taxi fuel consumption; such operating data/conditions that are considered/assessed in taxi fuel calculation process are defined).
- ☐ **Interviewed** responsible operational control manager(s).
- ☐ **Examined** selected OFPs (focus: operating data/conditions used as basis for taxi fuel).
- ☐ **Identified/Assessed** method(s) of performance-based compliance used for calculation of taxi fuel (if applicable) (focus: method conforms to specifications of [DSP 4.6.2](#) and [4.6.5](#)).
- ☐ **Observed** operational control/flight dispatch operations (focus: process or procedures for calculating planned taxi fuel).
- ☐ **Coordinated** with FLT auditor (focus: complementary procedures for assessing taxi fuel in accordance with fuel policy).
- ☐ **Other Actions** (Specify)



Guidance

The intent of this provision is to ensure the accurate computation of taxi fuel in order, to the extent reasonably practicable, protect the remaining elements in the useable fuel equation. To achieve this aim, the computation of taxi fuel would take into account foreseeable taxi conditions and delays in order to result in an amount of fuel generally equal to or greater than the actual taxi fuel consumed before takeoff.

It is important to note that every usable fuel calculation typically takes into account unforeseen as well as foreseen deviations from the planned operation. Unforeseen taxi delays, for example, may be addressed by the use of Statistical Taxi Fuel, the uplift of discretionary fuel when deemed necessary by the PIC, or the partial consumption of contingency fuel. Consuming contingency fuel during taxi, however, would be carefully considered as its use on the ground may leave the flight crew with fewer options, once airborne, to compensate for other unforeseen factor(s).

Guidance on fuel planning, including pre-flight fuel calculation examples, is contained in the ICAO Flight Planning and Fuel Management Manual (Doc 9976).

DSP 4.3.6

The Operator shall have a process and/or procedures to ensure the trip fuel required in accordance with its fuel policy is the amount of fuel required to enable the aircraft to fly from takeoff, or from the point of in-flight re-planning, until landing at the destination airport taking into account the operating conditions specified in [DSP 4.3.2. \(GM\)](#)

Note: *Conformity with the specifications of this provision can be achieved using performance-based methods in accordance with applicable provisions in [subsection 4.6](#). Such conformance is achievable irrespective of the specifications of this provision.*

Auditor Actions

- ☐ **Identified/Assessed** process/procedures for calculation of trip fuel for all flights (focus: flight planning takes into account operating data/conditions that might cause/lead to increased trip fuel consumption; such operating data/conditions that are considered/assessed in trip fuel calculation process are defined).
- ☐ **Interviewed** responsible operational control manager(s).
- ☐ **Examined** selected OFPs (focus: operating data/conditions used as basis for trip fuel).
- ☐ **Identified/Assessed** method(s) of performance-based compliance used for calculation of trip fuel (if applicable) (focus: method conforms to specifications of [DSP 4.6.2](#) and [DSP 4.6.5](#)).
- ☐ **Observed** operational control/flight dispatch operations (focus: process or procedures for calculating planned trip fuel).
- ☐ **Coordinated** with FLT auditor (focus: complementary procedures for assessing trip fuel in accordance with fuel policy).
- ☐ **Other Actions** (Specify)

Guidance

The intent of this provision is to ensure the accurate computation of trip fuel in order, to the extent reasonably practicable, ensure that the total planned trip fuel burn is greater than or equal to the actual trip fuel burn.

The specifications of this provision define trip fuel for preflight planning and in-flight re-planning purposes, as well as to form the basis for the computation of other fuel amounts (e.g., contingency fuel, additional fuel). In this context, trip fuel is typically computed from either the departure airport or the point of in-flight re-planning until landing at the destination airport taking into account the operating conditions of [DSP 4.3.2](#). In the case of in-flight re-planning (planned or unplanned), the intent of this provision is for the operator to reconsider (re-compute) the trip fuel required from the re-planning point to the commercial (actual) destination.

Guidance on fuel planning, including pre-flight fuel calculation examples, is contained in the ICAO Flight Planning and Fuel Management Manual (Doc 9976).



DSP 4.3.7

The Operator shall have a process and/or procedures to ensure the contingency fuel required in accordance with its fuel policy is the amount of fuel required to compensate for unforeseen factors that could have an influence on the fuel consumption to the destination airport. Contingency fuel shall *not be lower than any one or more* of the following (as approved or accepted by the Authority based on the operations of the Operator):

- (i) Five (5) percent of the planned trip fuel or of the fuel required from the point of in-flight re-planning based on the consumption rate used to plan the trip fuel, but never lower than the amount required to fly for five (5) minutes at holding speed at 450 m (1,500 ft) above the destination airport in standard conditions.
- (ii) If approved or accepted by the Authority for domestic operations; an amount of fuel to fly for 45 minutes at normal cruising fuel consumption, including 30 minutes final reserve. **[PCO]**
- (iii) If approved or accepted by the Authority for international operations, an amount of fuel to fly for 10 percent of the total time required to fly from the airport of departure or the point of in-flight re-planning to, and then land at, the airport to which it was released or re-released. **[PCO]**
- (iv) If approved or accepted by the Authority for the purpose of reducing contingency fuel, not less than three (3) percent of the planned trip fuel or, in the event of in-flight re-planning, three (3) percent of the trip fuel for the remainder of the flight, provided that an en route alternate airport is available in accordance with the requirements of the Authority. **[PCO]**
- (v) If approved or accepted by the Authority based on actual fuel consumption data, an amount of fuel sufficient for 20 minutes flying time based upon the planned trip fuel consumption provided that the operator has established a fuel consumption monitoring program for individual aircraft and uses valid data determined by means of such a program for fuel calculation. **[PCO] (GM)**

Note: Items ii), iii), iv) and v) are Parallel Conformity Options (PCOs) for item i); in effect until 31 August 2021.

Note: The specifications in item ii) and iii) are only applicable to an operator if the State and/or the Operator differentiate between domestic and international flights for the purpose of contingency fuel calculations.

Note: Conformity with the specifications of this provision can be achieved using performance-based methods in accordance with applicable provisions in [subsection 4.6](#). Such conformance is achievable irrespective of the specifications of this provision.

Auditor Actions

- ☐ **Identified/Assessed** process/procedures for calculation of contingency fuel for all flights (focus: flight planning takes into account unforeseen operating factors that might cause/lead to increased fuel consumption to the destination airport; such operating factors that are considered/assessed in contingency fuel calculation process are defined; minimum contingency fuel amount in accordance with regulatory requirements is defined).
- ☐ **Interviewed** responsible operational control manager(s).
- ☐ **Examined** selected OFPs (focus: operating factors used as basis for contingency fuel).
- ☐ **Identified/Assessed** method(s) of performance-based compliance used for calculation of contingency fuel (if applicable) (focus: method conforms to specifications of [DSP 4.6.5](#)).
- ☐ **Observed** operational control/flight dispatch operations (focus: process or procedures for calculating planned contingency fuel).
- ☐ **Coordinated** with FLT auditor (focus: complementary procedures for assessing contingency fuel in accordance with fuel policy).
- ☐ **Other Actions** (Specify)

Guidance

The intent of this provision is to ensure fuel is allocated to compensate for unforeseen factors that could influence fuel burn to the destination airport. Such factors include, for example, deviations of an individual aircraft from expected fuel consumption data, forecast meteorological conditions expected taxi times before takeoff or planned routings and cruising altitudes/levels.

From a safety risk management perspective, contingency fuel is used to mitigate the risks associated with operational factors or hazards that cannot be planned, anticipated, or controlled. The risk associated with the improper calculation or complete consumption of contingency fuel is that of creating a low fuel state or a diversion that could subsequently affect Air Traffic Management (ATM) and other aircraft.

It is important to note that differences in fuel computation terminology may exist from operator to operator. For example, required contingency fuel may be a component of other fuel reserves mandated by the Authority. Regardless of the terms used, however, an operator can conform to items i) through iii) of the provision if the pre-flight computation of usable fuel allocates an equivalent or greater amount of fuel as specified in items i) through v) and as applicable to the operator in order to compensate for unforeseen factors that could influence fuel burn to the destination airport.

An operator may conform to a minimum of one of the numbered specifications of the provision and be in overall conformity with the intent of the entire provision. Individual conformity with items i) through v), however, is “as approved or accepted by the Authority based on the operations of the Operator” and dependent on many factors including the regulatory environment and the type of operations conducted.

The specification in item ii) protects 15 minutes of contingency fuel plus 30 minutes of final reserve fuel for a combined domestic reserve of 45 minutes.

Examples related to the computation of contingency fuel are contained in the ICAO Flight Planning and Fuel Management Manual (Doc 9976).

DSP 4.3.8

The Operator shall have a process and/or procedures to ensure, *for flights that require a single destination alternate airport*, the destination alternate fuel required in accordance with its fuel policy is *not lower* than amount of fuel that will enable the aircraft to complete all of the following:

- (i) Perform a missed approach at the destination airport;
- (ii) Climb to the expected cruising altitude;
- (iii) Fly the expected routing to the destination alternate airport;
- (iv) Descend to the point where the expected approach is initiated;
- (v) Conduct the approach and landing at the destination alternate airport. **(GM)**

Note: *The specifications of this provision are not applicable for flights conducted under isolated airport operations as specified in [DSP 4.1.7](#).*

Note: *The Operator has the option of achieving conformity with the specifications of this provision using performance-based methods in accordance with applicable provisions in [subsection 4.6](#). Such conformance is achievable irrespective of the specifications of this provision.*

Auditor Actions

- ☐ **Identified/Assessed** process/procedures for calculation of destination alternate fuel for flights that require a single destination alternate airport (focus: flight planning takes into account fuel consumption required to divert from destination airport and proceed to/hold/land at alternate airport; diversion flight phases that are considered/assessed in single destination alternate fuel calculation process are defined).
- ☐ **Interviewed** responsible operational control manager(s).
- ☐ **Examined** selected OFPs (focus: factors used as basis for single destination alternate fuel).
- ☐ **Identified/Assessed** method(s) of performance-based compliance used for calculation of single destination alternate fuel (if applicable) (focus: method conforms to specifications of [DSP 4.6.2](#) and [4.6.5](#)).

- **Observed** operational control/flight dispatch operations (focus: process or procedures for calculating destination alternate fuel for flights that require a single destination alternate airport).
- **Coordinated** with FLT auditor (focus: complementary procedures for assessing single destination alternate fuel in accordance with fuel policy).
- **Other Actions** (Specify)

Guidance

The intent of this provision is to ensure the accurate computation of destination alternate fuel when one destination alternate airport is required. Such computation ensures, to the extent reasonably practicable, that the planned fuel burn will be greater than or equal to the actual fuel burn.

From a safety risk management perspective, “destination alternate fuel” is used to mitigate the risks associated with the unavailability of the destination airport. The risk associated with the improper calculation or complete consumption of such fuel is that of creating a low fuel state or a diversion that could subsequently affect Air Traffic Management (ATM) and other aircraft.

Examples of the computation of destination alternate fuel are contained in the ICAO Flight Planning and Fuel Management Manual (Doc 9976).

DSP 4.3.10

If the Operator conducts flights that do not require a destination alternate airport, the Operator shall have a process and/or procedures to ensure a supplemental amount of fuel is carried on such flights to provide for increased fuel consumption during the flight to the destination airport due to unforeseen operational occurrences. **(GM)**

Note: The specifications of this provision are not applicable if the contingency fuel calculated in accordance with [DSP 4.3.7](#) is sufficient to enable the aircraft to hold at an altitude of 450 m (1,500 ft) above the destination airport for 15 minutes at the holding speed based on standard conditions.

Note: The specifications of this provision are not applicable for flights conducted under isolated airport operations as specified in [DSP 4.1.7](#) and [DSP 4.3.11](#).

Note: The Operator has the option of achieving conformity with the specifications of this provision using performance-based methods in accordance with applicable provisions in [subsection 4.6](#). Such conformance is achievable irrespective of the specifications of this provision.

Auditor Actions

- **Identified/Assessed** process/procedures for addition of supplemental fuel to provide for potential increased fuel consumption for flights that do not require a destination alternate airport (focus: planned supplemental fuel required when contingency fuel is not sufficient to fly at holding speed for 15 minutes at 450 m/1500 ft above destination airport).
- **Interviewed** responsible operational control manager(s).
- **Examined** selected OFPs (focus: basis for addition of supplemental fuel).
- **Identified/Assessed** method(s) of performance-based compliance used for supplemental fuel (if applicable) (focus: method conforms to specifications of [DSP 4.6.2](#) and [4.6.5](#)).
- **Observed** operational control/flight dispatch operations (focus: process or procedures for calculating planned supplemental fuel for flights that require no destination alternate airport).
- **Coordinated** with FLT auditor (focus: complementary procedures for assessing second destination alternate fuel in accordance with fuel policy).
- **Other Actions** (Specify)

Guidance

From a safety risk management perspective “no-alternate” fuel is intended to mitigate the safety risks associated with the occurrence of unforeseen operational contingencies associated with no-alternate operations. The risk associated with the improper calculation or complete consumption of such fuel is that of creating a low fuel state.

Examples of the computation of alternate and contingency fuel are contained in the ICAO Flight Planning and Fuel Management Manual (Doc 9976).

DSP 4.3.11

If the Operator conducts isolated airport operations, the Operator shall have a process and/or procedures to ensure the isolated airport fuel calculated in accordance with its fuel policy is *not less* than the amount of fuel required to fly for two (2) hours at normal cruise consumption above the isolated destination airport, including the final reserve fuel calculated in accordance with [DSP 4.3.12](#). **(GM)**

Note: The Operator has the option of achieving conformity with the specifications of this provision using performance-based methods in accordance with applicable provisions in [subsection 4.6](#). Such conformance is achievable irrespective of the specifications of this provision.

Auditor Actions

- ☐ **Identified** conduct of isolated airport operations that preclude selection/designation of destination alternate airports.
- ☐ **Identified/Assessed** process/procedures for calculation of isolated airport fuel for flights to isolated airports (focus: planned isolated airport fuel is the amount of fuel sufficient to fly for two hours at normal cruise consumption above destination isolated airport, but not less than the greater of final reserve fuel).
- ☐ **Interviewed** responsible operational control manager(s).
- ☐ **Examined** selected OFPs (focus: factors used as basis for isolated airport fuel).
- ☐ **Identified/Assessed** method(s) of performance-based compliance used for calculation of isolated airport fuel (if applicable) (focus: method conforms to specifications of [DSP 4.6.2](#) and [4.6.5](#)).
- ☐ **Observed** operational control/flight dispatch operations (focus: process or procedures for calculating planned isolated airport fuel).
- ☐ **Coordinated** with FLT auditor (focus: complementary procedures for assessing isolated airport fuel in accordance with fuel policy).
- ☐ **Other Actions** (Specify)

Guidance

The intent of this provision is to ensure sufficient fuel is uplifted to mitigate the safety risks associated with isolated airport operations conducted in accordance with [DSP 4.1.7](#), and to protect final reserve fuel. As such, final reserve fuel must be computed and protected in accordance with [DSP 4.3.12](#) regardless of the method used to compute “isolated airport fuel”

As a practical matter destination airports are typically considered isolated by an authority when the fuel required to go-around from Decision Altitude/Height (DA/H) or the Missed Approach Point (MAP) at the destination airport and then divert to the nearest alternate exceeds, for a turbine engine aircraft, the fuel required to hold at the destination airport for two hours including final reserve fuel (e.g. 90 minutes hold + 30 minutes Final Reserve).

Examples of the computation of isolated airport fuel are contained in the ICAO Flight Planning and Fuel Management Manual (Doc 9976).

DSP 4.3.12

The Operator shall have a process and/or procedures to ensure the final reserve fuel calculated in accordance with its fuel policy is not less than either (as applicable to the Operator):

- (i) The amount of fuel required to fly for 30 minutes at holding speed at 450 m (1,500 ft) above airport elevation in standard conditions, *or*
- (ii) The amount of fuel required to fly for 30 minutes under speed and altitude conditions specified by the Operator and as approved or accepted by the Authority. **[PCO] (GM)**

Note: Item ii) is a Parallel Conformity Option [PCO] for item i); in effect until 31 August 2021.

Auditor Actions

- **Identified/Assessed** process/procedures for calculation of final reserve fuel for all flights (focus: planned final reserve fuel is an amount that is not less than fuel to fly for 30 minutes at holding speed at 450 m/1500 ft or fuel to fly 30 minutes under speed/altitude conditions approved/accepted by authority).
- **Interviewed** responsible operational control manager(s).
- **Examined** selected OFPs (focus: factors used as basis for final reserve fuel).
- **Observed** operational control/flight dispatch operations (focus: process or procedures for calculating planned final reserve fuel).
- **Coordinated** with FLT auditor (focus: complementary procedures for assessing final reserve fuel in accordance with fuel policy).
- **Other Actions** (Specify)

Guidance

The intent of this provision is to ensure the allocation of an amount of fuel to be protected in flight and preserved upon landing at any airport. As such, it represents the last line of defense in a multi-layered strategy to ensure safe flight completion. It also serves as the demarcation line between normal and emergency fuel states for the purposes of the fuel state declarations in accordance with [FLT 3.14.17](#).

An operator may satisfy the final fuel reserve requirements specified in the provision by defining time, speed, altitude, and/or engine power conditions in accordance with requirements of the Authority that yield an equivalent or greater amount of fuel.

DSP 4.3.13

The Operator shall have a process and/or procedures to ensure the additional fuel calculated in accordance with its fuel policy is a supplementary amount of fuel required to be carried when the sum of the trip fuel, contingency fuel, alternate fuel and final reserve fuel is *insufficient* to meet *any one* of the following conditions (as applicable to the Operator):

- (i) Allow the aircraft engaged in ETOPS/EDTO to comply with critical fuel scenario as established by the State.
- (ii) Allow the aircraft flying greater than 90 minutes from an alternate airport to:
 - (a) Descend as necessary and proceed to an alternate airport in the event of engine failure or loss of pressurization, whichever requires the greater amount of fuel based on the assumption that such a failure occurs at the most critical point along the route;
 - (b) Fly for 15 minutes at holding speed at 450 m (1,500 ft) above the alternate airport elevation in standard conditions;
 - (c) Make an approach and landing at the alternate airport.
- (iii) Allow for any additional operational requirements not covered by items i) and ii). **(GM)**

Note: The Operator has the option of achieving conformity with the specifications of this provision using performance-based methods in accordance with applicable provisions in [subsection 4.6](#). Such conformance is achievable irrespective of the specifications of this provision.

▲ An operator may conform to [DSP 4.3.13 \(ii\)](#) through Active Implementation as long as the implementation Action Plan (IAP) projects conformance on or before 31 August 2021.

Auditor Actions

- **Identified/Assessed** process/procedures for calculation of additional fuel for all flights (focus: planned additional fuel is required when the calculated sum of trip fuel/contingency fuel/alternate fuel/final reserve fuel is insufficient to meet defined operational conditions or, if applicable, when calculated using performance-based compliance; operational conditions that are considered/assessed to determine requirement for additional fuel are defined).
- **Interviewed** responsible operational control manager(s).
- **Examined** selected OFPs (focus: factors used as basis for additional fuel).

- ☐ **Identified/Assessed** method(s) of performance-based compliance used for calculation of additional fuel (if applicable) (focus: method conforms to specifications of [DSP 4.6.2](#) and [4.6.5](#)).
- ☐ **Observed** operational control/flight dispatch operations (focus: process or procedures for calculating planned additional fuel when required.).
- ☐ **Other Actions** (Specify)

Guidance

Basic fuel planning, represented by the sum of the trip fuel, contingency fuel, alternate fuel and final reserve is predicated on the termination of a flight at the destination or destination alternate. As such, it only takes into account foreseen and unforeseen factors (excluding system failures) that could influence fuel consumption to the planned destination or destination alternate. The intent of this provision is to define the “additional fuel” required to protect against the very unlikely event of an engine failure or de-pressurization at the most critical point in the flight and presumes that the majority of the fuel used in basic fuel planning will still be available for use in proceeding to an en route alternate in the event of such an occurrence.

The specification in item i) applies to aircraft engaged in ETOPS/EDTO. It addresses the fuel necessary to comply with the ETOPS/EDTO critical fuel scenario as established by the State of the Operator. Such scenarios typically include additional controls to ensure sufficient fuel is uplifted for conditions that would contribute to increased fuel burn (e.g. to account for icing, errors in wind forecasting, deterioration in cruise fuel burn performance, and APU use).

The specification in item (ii) is subject to Active Implementation and is applicable to an operator based on the type of operations conducted.

Examples of additional fuel calculations and critical fuel scenarios are contained in the ICAO Flight Planning and Fuel Management Manual (Doc 9976).

4.4 Oxygen

4.5 Operations Beyond 60 Minutes from an En Route Alternate Airport and Extended Diversion Time Operations (EDTO)

DSP 4.5.1

If the Operator conducts flight operations beyond 60 minutes from a point on a route to an en route alternate airport, including ETOPS/EDTO, the Operator shall have a system, process and/or procedures to ensure such operations are planned and conducted in accordance with operational requirements and applicable regulations. **(GM)**

Auditor Actions

- ☐ **Identified** conduct of flight operations, including ETOPS/EDTO, over routes beyond 60 minutes from alternate airport.
- ☐ **Identified/Assessed** system/process/procedures for planning flights conducted over routes beyond 60 minutes to an alternate airport (focus: flight planning for ETOPS/EDTO takes into account all applicable regulations/requirements).
- ☐ **Interviewed** responsible operational control manager(s).
- ☐ **Observed** operational control/flight dispatch operations (focus: process or procedures to ensure flights operated beyond 60 minutes from an alternate airport are conducted in accordance with applicable requirements).
- ☐ **Other Actions** (Specify)

Guidance

An operator may use a system, process or procedures alone or in combination in order to fulfill operational requirements related to the conduct of operations beyond 60 minutes. In all cases, however, the robustness of any methodologies is commensurate with the breadth and complexity of the operation.

An operator, in accordance with the requirements of the Authority, typically uses technical guidance for the conduct of operations beyond 60 minutes, from a point on a route to an en route alternate airport. Such guidance might be derived from one or more of the following source references, as applicable:

- △ ☐ • ICAO Annex 6, Part 1, Attachment C: Guidance for Operations by Turbine Engine Aeroplanes Beyond 60 minutes to an En route Alternate Aerodrome Including Extended Diversion Time Operations (EDTO).
- ☐ • ICAO Flight Planning and Fuel Management Manual (Doc 9976).
- △ ☐ • ICAO Extended Diversion Time Operations (EDTO) Manual (Doc 10085).
- △ ☐ • FAA Advisory Circular - AC No: 120-42B: Extended Operations (ETOPS and Polar Operations).
- ☐ • EU-OPS AMC 20-6: Extended Range Operation with Two-Engine Aeroplanes, ETOPS Certification and Operation.
- ☐ • Commission Regulation EC No. 965/2012 Annex V SPA.ETOPS.
- Any equivalent reference document approved or accepted by the Authority for the purpose of providing guidance for the conduct of flight operations by turbine engine aircraft beyond 60 minutes to an en route alternate airport.

DSP 4.5.2

If the Operator conducts flight operations beyond 60 minutes from a point on a route to an en route alternate airport, the Operator shall have guidance and procedures to ensure (as applicable to the Operator):

- (i) For all aircraft, en route alternate airports are identified and the most up-to-date information relative to such airports is available to the flight crew, including airport status and meteorological conditions;
- (ii) For aircraft with two engines engaged in ETOPS/EDTO, the most up-to-date information available to the flight crew indicates that conditions at identified en route alternate airports will be at or above the Operator's established airport operating minima for the operation at the estimated time of use. **(GM)**

Auditor Actions

- ☐ **Identified** conduct of flight operations, including ETOPS/EDTO, over routes beyond 60 minutes from alternate airport.
- ☐ **Identified/Assessed** guidance/procedures for planning flights conducted over routes beyond 60 minutes from alternate airport (focus: flight planning includes provision of information for flight crew that identifies en route alternate airports, indicates conditions at en route alternate airports will be at/above established airport operating minima for operation at estimated time of use).
- ☐ **Interviewed** responsible operational control manager(s).
- ☐ **Examined** selected ETOPS/EDTO OFPs (focus: identification of en route alternate airports; information indicates conditions at/above operating minima).
- ☐ **Observed** operational control/flight dispatch operations (focus: guidance/procedures that ensure flight crew has up-to-date information relative to planned en route alternate airports for flight operations beyond 60 minutes from an en route alternate airport).
- ☐ **Other Actions** (Specify)

Guidance

The intent of item i) of this provision is to ensure operational control personnel and the flight crew are knowledgeable about diversion airport options and prevailing weather conditions appropriate for the type of operation conducted.

The intent of item ii) is to ensure a larger strategy exists for two-engine aircraft engaged in ETOPS/EDTO to protect a diversion regardless of the reason for the diversion (i.e. technical or non-technical reasons).

△ Guidance related to the identification and/or protection of en route alternate airports is contained in ICAO Annex 6, Part 1, Attachment C and the ICAO Extended Diversion Time Operations (EDTO) Manual (Doc 10085).

DSP 4.5.3

If the Operator utilizes aircraft with two engines in EDTO, the Operator shall have guidance and procedures to select en route alternate airports for such operations, and ensure en route alternate airports are specified on:

- (i) The OFP or other equivalent operational document available to the PIC in flight;
- (ii) The ATS flight plan where required by the State or the ATS system in use. **(GM)**

Auditor Actions

- **Identified** the conduct of ETOPS/EDTO utilizing aircraft with two engines.
- **Identified/Assessed** guidance/procedures for en route alternate selection/designation for ETOPS/EDTO conducted with two-engine aircraft (focus: flight planning includes selection/designation of en route alternate airports; en route alternate airports shown on OFP; shown on ATS flight plan in accordance with applicable regulatory requirements).
- **Interviewed** responsible operational control manager(s).
- **Examined** selected ETOPS/EDTO OFPs (focus: designation of en route alternate airports).
- **Observed** operational control/flight dispatch operations (focus: guidance/procedures for selecting en route alternate airports and specifying on OFP and ATS flight plan for two-engine aircraft ETOPS/EDTO).
- **Other Actions** (Specify)

Guidance

The intent of the specification in item i) is to ensure en route alternates, when required, are selected and subsequently specified on the OFP or other equivalent operational document available to the PIC in flight.

The intent of the specification in item ii) is to ensure en route alternates, when required for ETOPS/EDTO, are specified on the ATS flight when required by the State or other applicable authority.

DSP 4.5.4

If the Operator conducts ETOPS/EDTO, the Operator shall have guidance and procedures to ensure, for aircraft engaged in such operations:

- (i) A flight will not proceed beyond the threshold time unless the identified en route alternate airports are re-evaluated for availability and the most up-to-date information indicates that, during the estimated time of use, conditions at those airports will be at or above the Operator's established airport operating minima for the operation;
- (ii) If any conditions are identified that would preclude a safe approach and landing at an identified en route alternate airport during the estimated time of use, an alternative course of action has been determined. **(GM)**

Auditor Actions

- **Identified** that ETOPS/EDTO is in use.
- **Identified/Assessed** guidance/procedures for the monitoring/assessment of en route alternate airport conditions during the conduct of ETOPS/EDTO (focus: designated en route alternate airports monitored/assessed during ETOPS/EDTO to verify continuation of planned flight; when conditions make designated en route alternate unusable, planned flight evaluated for change).
- **Interviewed** responsible operational control manager(s).
- **Examined** selected ETOPS/EDTO OFPs (focus: designation of en route alternate airports).
- **Observed** operational control/flight dispatch operations (focus: guidance/procedures for monitoring/assessing en route alternate airports during ETOPS/EDTO).

- △
- **Coordinated** with FLT auditor (focus: complementary procedures for monitoring/assessing conditions at en route alternates; coordination to re-evaluate planned flight in event en route alternate becomes unavailable).
 - **Other Actions** (Specify)

Guidance

The intent of this provision is to ensure a larger strategy exists to preclude a diversion and to protect a diversion should one occur regardless of whether the diversion is for technical (aircraft system or engine) or non-technical reasons.

4.6 Performance-based Methods of Compliance/Conformance

General Guidance

Operators and authorities are placing increased emphasis on the use of performance-based methods to comply with prescriptive regulations. Such methods allow for greater operational flexibility without degrading the safety performance of an operational activity. This presumption is largely dependent on an operator's organizational and operational capabilities, the results of safety risk management activities and the safety performance of a specific operational activity with respect to specified measurable targets.

To account for this potential shift in emphasis, the provisions in this subsection represent options available to operators that wish to use performance-based methods to conform to selected DSP provisions that address alternate airport selection, fuel planning, and/or EDTO. The provisions in this subsection provide the specifications for a performance-based and alternative means of conforming to selected provisions identified in other subsections (3.5, 4.1 and 4.3) that contain "prescriptive" specifications to address the above-mentioned operational areas. A note in each applicable provision in other subsections will indicate their eligibility for conformance using the performance-based methods addressed in this subsection.

It is important to note that the provisions and specifications set forth in this subsection are entirely independent of the operational specifications set forth in the prescriptive counterparts in other subsections. Additionally, it should also be understood that whereas prescriptive provisions typically detail "how" an operational activity is to be accomplished, performance-based provisions (in this subsection) focus on "what" must be accomplished by an operator to ensure the operational activity produces an equivalent safety outcome.

This shift in emphasis from "how" (prescriptive) to "what" (performance-based) would require an operator to have the capabilities and resources typically attributed to the implementation of a safety management system (SMS). A fully implemented SMS could, in fact, be readily tailored to identify the operational hazards associated with a specific operational activity and provide the necessary risk assessment and mitigation capabilities to ensure an equivalent safety outcome.

It follows then that the determination of whether operators will be able to reach a target level of safety performance with respect to a specific operational activity is dependent on numerous, and in many cases, pre-existing organizational, operational and safety risk management capabilities. The following table provides the context for the use of performance-based methods (i.e. alternative means) of conformance for selected IOSA standards that address alternate airport selection, fuel planning, and/or EDTO.

Note: The following table is provided as guidance material and does not introduce new requirements or specifications. It should be used as an aid in evaluating an operator's ability to achieve conformity with the provisions contained in this subsection.

Organizational and Operational Capabilities	Description
<p>Organizational and Operational Process Management and Control</p> <p>Practically speaking, operators would possess the requisite knowledge, skills, experience, resources and technologies necessary implement and oversee performance-based compliance/conformance.</p>	<p>This is a demonstrable organizational and operational process that is dependent on robust subordinate or related processes that typically address:</p> <ul style="list-style-type: none"> • The development of policy and procedure; • The staffing of positions with an appropriate number of qualified personnel. • Training to the operator's policy and procedure and to ensure personnel remain competent and qualified. • The Implementation or the demonstration of performance in accordance with policy and procedure. • Data reporting, measurement and analysis for monitoring the effectiveness and efficiency of systems, processes, policies and/or procedures. • An adjustment component or subsystem to respond to any underperformance or deviation, and to ensure continual improvement.
<p>Specific Operational Capabilities (operational control, aircraft, airport, infrastructure and meteorological)</p>	<p>Specific operator capabilities necessary to support operational activities related to aircraft tracking, alternate airport selection, fuel planning and/or EDTO typically include (as applicable to the operational activity):</p> <ul style="list-style-type: none"> • Operational control systems and standard operating procedures that provide the direction for the conduct of flight operations. • Ground-based and airborne tools and technologies to improve situational awareness and operational capability. • Flight monitoring that encompasses the activities necessary to effectively exercise operational control. • Field condition monitoring at the destination, en route alternate and destination alternate airports (as applicable) nominated for use by the flight up until the flight is no longer dependent on the use of any of the applicable airports. • Rapid and reliable communication capabilities. • Weather reporting and monitoring capability.

Organizational and Operational Capabilities	Description
<p>A (Tactical) Safety Risk Management (SRM) Sub-system or Process (specific to operational systems or processes that support performance-based compliance/conformance)</p> <p><i>Note: An operationally specific SRM sub-system or process may be standalone, or more typically, integrated as a sub-component of an existing SMS.</i></p>	<p>This is the subsystem that interfaces with the internal system of production (related to a specific system or process) for data reporting measurement and analysis, as well as appropriate organizational SRM components. This also would typically include the interfaces with SMS and quality systems to ensure operational systems and processes are subjected to the organization's overarching safety and quality assurance processes, and ensure:</p> <ul style="list-style-type: none"> • Appropriate data from many sources are isolated and extracted. • Reports from operational personnel are collated and analyzed. • Applicable safety hazards are identified. • Safety risks are assessed and controlled. • Data are collected relevant to the mitigation of safety risks. • Feedback and control references are provided against which the effectiveness of risk management can be measured. • Material is provided for root cause and safety trend analysis.
<p>An Oversight Component (performance monitoring and measurement)</p> <p><i>Note: Safety performance monitoring and measurement of an operational activity is typically an operator responsibility, although such responsibility may also be assumed by an authority. In some cases, the development of risk mitigation actions may also be accomplished by a relevant authority in conjunction with issuance of an operational variation (e.g. via OPSPEC, special authorization or other similar regulatory instrument). Where an operator implements this type of variation, the operator would still retain the overall responsibility for safety performance monitoring and measurement of the associated operational activity. This is done to ensure the desired level of safety is being achieved when an operational variation is in use.</i></p>	<p>This is the monitoring and measurement of safety performance through appropriate safety performance measures that continuously track system safety performance as necessary to determine whether an operator's system is truly operating in accordance with design expectations.</p>

Table 3.1—Operational Control Personnel

This table categorizes operational control personnel, defines the scope of their authority, identifies their responsibilities and illustrates the relationship of such responsibilities to the operation as a whole. It shall be used for the purposes of applying relevant [Section 3](#) provisions and is provided to ensure suitably qualified persons are designated, where applicable, to support, brief and/or assist the pilot-in-command (PIC) or FOO or designated member of management in the safe conduct of each flight. The terms used in the table to identify operational control personnel are generic and might vary. Personnel, however, employed in operational control functions that are delegated the authority and/or assigned the responsibility to carry out functions, duties or tasks, as outlined in the table, are subject to the training and qualification requirements commensurate with their position.

Operational Control ➡ ↓	Authority (DSP 1.3.4)	Responsibilities, Including the Assignment of Functions, Duties or Tasks. (DSP 1.3.5 and 1.3.6)	Training and Qualification <i>Operator shall designate responsibilities and ensure personnel are competent to perform the job function.</i>
Administrative Support Personnel¹ (e.g. gate agent)	None Do not make recommendations or decisions regarding the operational control of a flight.	Provide, collect or assemble operational documents or data only.	Not subject to initial and recurrent training in the competencies of operational control in Table 3.5 and are qualified via On the Job Training (OJT), job descriptions, task cards, guidelines, checklists, training materials or other written means to establish competence.
Flight Operations Assistant (FOA)⁴ (e.g. Weather Analysts, Navigation Analysts/Flight Planning Specialists, Operations Coordinators/Planners, Maintenance controllers, Air Traffic Specialists), and Load Agents/Planners/Controllers unless qualified in accordance with GRH)	None or limited to area(s) of expertise May be authorized to make decisions or recommendations in area(s) of expertise. ⁵ (e.g., maintenance controller grounds aircraft.)	Support, brief and/or assist the PIC or FOO. Specializes in one or more of the elements of operational control. ³ Collects, provides filters, evaluates and applies operational documents or data relevant to specific elements of operational control. Makes recommendations or decisions in area(s) of expertise.	For each area of expertise or specialization.³ Subject to initial and continuing qualification in accordance with DSP 2.2.2 and specific competencies of Table 3.5 relevant to the job function and operations of the Operator.

Table 3.1—Operational Control Personnel

Flight Dispatcher or Flight Operations Officer (FOO)⁴ or Designated Member of Management (e.g. Director of Operations or other post holder)	None or limited or shared² May share operational control authority with the PIC. ² May be authorized to make recommendations or decisions.	May share operational control responsibility with the PIC. ² Support, brief, and/or assist the PIC. Collects, provides, filters, evaluates and applies operational documents or data relevant to all elements of operational control. ³ Makes recommendations or decisions.	Subject to initial and continuing qualification in accordance with DSP 2.2.2 and all competencies of Table 3.5 relevant to the operations of the Operator.
Pilot in Command (PIC)	Full/shared² Has final authority to ensure the safe operation of the aircraft. May share authority and responsibility for operational control.	Full/shared² Responsible for safe conduct of the flight. Collect, provide, filter, evaluate and applies operational documents or data relevant to all competencies of operational control. ³	Subject to training and qualification requirements specified in ISM Section 2 .
Legend	<p>1 - Personnel lacking any authority or responsibility for operational control are identified in the table for the purposes of excluding them from the initial and continuing qualification provisions of this section.</p> <p>2 - FOO personnel used in conjunction with a shared system of operational share authority and responsibility with the PIC.</p> <p>3 - The competencies of operational control are contained in Table 3.5. FOA personnel that specialize in one competency of operation control may be referred to as Weather Analysts, Navigation Analysts/Flight Planners, Operations Coordinators/Planners, Maintenance controllers, Air Traffic Specialists and Load Agents/Planners/Controllers unless qualified in accordance with GRH.</p> <p>4 - The terms used in this table to identify operational personnel are generic and may vary. Personnel utilized in operational control functions and assigned the responsibilities delineated in the table are subject to the relevant qualification and training provisions in this section.</p> <p>5 - Authority limited in scope to decision making in area of expertise.</p>		

Table 3.2—Operations Manual (OM) Content Specifications

This table contains the fundamental OM content specifications required to achieve conformity with [DSP 1.7.1](#). It also specifies [Section 2](#) (FLT) provisions that must be addressed in the sections of the OM relevant to personnel with responsibilities related to the operational control of flights.

Note: Specific policies, guidance, data and/or procedures that must be addressed in the sections of the OM relevant to operational control personnel can be found in individual [Section 3](#) provisions and are not duplicated in the table.

General Information		FLT ISARP
(i)	General Operations Manual (GOM), to include:	None
	(a) Non-aircraft type related and/or standard operating procedures for each phase of flight, policies, procedures, checklists, descriptions, guidelines, emergency procedures and other relevant information;	None
	(b) Authorities, duties and responsibilities associated with the operational control of flights;	None
	(c) The requirement for commercial flights to be conducted under an IFR flight plan and in accordance with an IFR flight plan.	FLT 3.10.1
Aircraft Operating Information		FLT ISARP
(ii)	Aircraft Operating Manual (AOM), to include:	None
	(a) Normal, abnormal/non-normal and emergency procedures, instructions and checklists;	None
	(b) Aircraft systems descriptions, limitations and performance data.	None
(iii)	MEL and CDL, to include applicability and a description of the relationship between the Minimum Equipment List (MEL) and the Master Minimum Equipment List (MMEL);	None
(iv)	Aircraft specific weight and balance instructions/data;	None
(v)	Instructions for the conduct and control of ground de/anti-icing operations.	FLT 3.9.6 , 3.9.7
Areas, Routes and Airport Information		FLT ISARP
(vi)	Route and airport instructions and information (departure, destination, en route and destination alternates, to include:	None
	(a) Airway manuals and charts, including information regarding communication facilities and navigation aids;	None
	(b) Airport charts, including the method for determining airport operating minima, operating minima values for destination and alternate airports and the increase of airport operating minima in case of degradation of approach or airport facilities;	None
	(c) Airport and runway analysis manual or documents:	None
	(d) If applicable, flight monitoring requirements and instructions to ensure the PIC notifies the operator of en route flight movement or deviations from the OFP including procedures for loss of communication between the aircraft and the FOO;	None
	(e) Instructions for the conduct of precision and non-precision approaches, including approach minima;	FLT 3.11.65 , 3.11.67
	(f) If applicable, procedures for the conduct of long-range navigation;	FLT 3.11.8 , 3.11.9 , 3.11.11
	(g) Supplemental oxygen requirements and escape routes in case of decompression in an area of high terrain, if applicable;	4.3.5
	(h) Regional guidance necessary to comply with local regulations.	None

Table 3.2—Operations Manual (OM) Content Specifications

Training Information		FLT ISARP
(vii) Training Manual, to include:		None
(a) Details of all relevant training programs, policies, directives and requirements, including curricula and syllabi, as applicable, for initial qualification, continuing qualification and other specialized training;		None
(b) Curricula for ground training, evaluation and certification;		None
(c) Comprehensive syllabi to include lesson plans, procedures for training and conduct of evaluations;		None
(d) The training program for the development of knowledge and skills related to human performance (Crew Resource Management/Dispatch Resource Management, CRM/DRM).		None
Other Information		FLT ISARP
(viii) Cabin safety and emergency procedures relevant to operational control personnel.		None
(ix) Dangerous Goods manual or parts relevant to operational control personnel, to include information and instructions on the carriage of dangerous goods and action to be taken in the event of an emergency.		None
(x) Security Manual or parts relevant to operational control personnel, including bomb search procedures.		None

Table 3.3—Operational Flight Plan (OFP) Specifications

The OM contains a description and specifications for the content and use of the OFP or equivalent document. The content of the OFP shall consist of, as a minimum, the following elements:

- (i) Aircraft registration;
- (ii) Aircraft type and variant;
- (iii) Date of flight and flight identification;
- (iv) Departure airport, STD, STA, destination airport;
- (v) Route and route segments with check points/waypoints, distances and time;
- (vi) Assigned oceanic track and associated information, as applicable;
- (vii) Types of operation (e.g. EDTO, IFR, ferry-flight);
- (viii) Planned cruising speed and flight times between waypoints/check points;
- (ix) Planned altitude and flight levels;
- (x) Fuel calculations;
- (xi) Fuel on board when starting engines;
- (xii) Alternate(s) for destination and, when applicable, takeoff and en route;
- (xiii) Relevant meteorological information.

Table 3.4–Flight Information

The Operator shall record and retain the following information for each flight:

- (i) Aircraft registration;
- (ii) Date;
- (iii) Flight number;
- (iv) Flight crew names and duty assignment;
- (v) Fuel on board at departure, en route and arrival;
- (vi) Departure and arrival point;
- (vii) Actual time of departure;
- (viii) Actual time of arrival;
- (ix) Flight time;
- (x) Incidents and observations, if any;
- (xi) Flight weather briefings;
- (xii) Dispatch or flight releases;
- (xiii) Load Sheet;
- (xiv) NOTOC;
- (xv) OFP;
- (xvi) ATS flight plan;
- (xvii) Communications records;
- (xviii) Fuel and oil records (obtained in accordance with [MNT 3.1.1](#));
- (xix) Aircraft tracking data to assist SAR in determining the last known position of the aircraft.

Note: After an aircraft has landed safely, an operator may discard tracking data.

△

□

Table 3.5—Competencies of Operational Control

The Operator shall ensure FOO or FOA personnel demonstrate knowledge and/or proficiency in the competencies of operational control appropriate to the assignment of responsibility to carry out operational control functions, duties, or tasks, to include, as applicable:

Competency	FOO	FOA	FOA Relevancy Examples
(i) Contents of the Operations Manual relevant to the operational control of flights;	3	3B	Relevant contents
(ii) Radio equipment in the aircraft used;	3	3B	As relevant to function
(iii) Aviation indoctrination;	3	3B	Subjects relevant to function
(iv) Navigation equipment in the aircraft used, including peculiarities and limitations of that equipment;	3	3B	Navigation Analysts, Flight Planners
(v) Seasonal meteorological conditions and hazards;	3	3B	Weather Analysts/Meteorologists
(vi) Source of meteorological information;	3	3B	Weather Analysts/Meteorologists
(vii) Effects of meteorological conditions on radio reception on the aircraft used;	3	3B	Weather Analyst/Meteorologists
(viii) Aircraft mass (weight) balance and control;	3	3B	Load Planners
(ix) Human performance relevant to operations or dispatch duties (CRM/DRM);	3	Not Applicable	Not Applicable
(x) Operational procedures for the carriage dangerous goods;	2	2B	As relevant to function
(xi) Operational procedures for the carriage of cargo;	3B	3B	As relevant to function
(xii) Operational emergency and abnormal procedures;	2B	2B	As relevant to function
(xiii) Security procedures (emergency and abnormal situations);	3	3B	As relevant to function
(xiv) Civil Air Law and regulations;	3	3B	Air Traffic Managers
(xv) Aircraft mass (weight) and performance;	3	3B	Load Planners
(xvi) Navigation, special navigation;	3	3B	Navigation Analysts
(xvii) Special airports;	3A	3AB	Flight Planners
(xviii) Air traffic management;	3	3B	Air Traffic Managers
(xix) Aircraft systems and MEL/CDL;	3	3B	MX Controllers
(xx) Flight planning;	3	3B	Flight Planners
(xxi) Flight monitoring;	3	3B	Flight Followers
(xxii) Communication;	3	3B	Flight Followers
(xxiii) Fuel supply (aircraft and fuel type requirements);	3	3B	Flight Planners
(xxiv) De-icing/anti-icing procedures;	3A	3AB	As relevant to function
(xxv) Procedures for operations beyond 60 minutes including, if applicable, EDTO.	3A	3AB	Flight Planners

Table 3.5—Competencies of Operational Control

Legend	
1:	Shall be satisfactorily completed during initial training and once every calendar year plus or minus one calendar month from the original qualification anniversary date or base month.
2:	Shall be satisfactorily completed during initial training and once every 24 months.
3:	Shall be satisfactorily completed during initial training and once every 36 months plus or minus one month from the original qualification tri-annual anniversary date or base month.
A:	If relevant to the operations of the Operator.
B:	If relevant to area of expertise or job function (e.g. Flight Planning, Maintenance Control, Load Planning, Air Traffic Management).
Notes	
<p>FOO personnel that are assigned overall operational control responsibility for specific flights, assigned responsibilities in all competencies of operational control or utilized in shared systems of operational control demonstrate knowledge and/or proficiency in all applicable competencies in this table. FOO or FOA personnel assigned the individual responsibility to carry out specific operational control functions, duties or tasks demonstrate knowledge and/or proficiency in competencies relevant to area of expertise or function as determined by the operator or State.</p> <p>It is important to note that some operators might choose to assign the responsibility for specific operational control functions to fully qualified FOO personnel. In such cases an FOO is acting in a limited capacity and although qualified in all competencies of operational control, would be functionally acting as an FOA.</p>	

Section 4 — Aircraft Engineering and Maintenance (MNT)

Applicability

Section 4 is applicable to all operators, and addresses aircraft engineering and maintenance functions relevant to the airworthiness of the aircraft, engines and components.

Individual MNT provisions or sub-specifications within a MNT provision that:

- Do not begin with a conditional phrase are applicable unless determined otherwise by the Auditor.
- Begin with a conditional phrase “If the Operator...” are applicable if the Operator meets the condition(s) stated in the phrase.

An operator may choose to have certain functions within the scope of ground handling operations (e.g. aircraft loading, aircraft ground handling) performed by maintenance operations personnel. If this situation exists, the operator must be in conformity with the ISARPs contained in Section 6, Ground Handling Operations (GRH), that are applicable to the ground handling functions performed by maintenance operations personnel.

Where an operator outsources the performance of aircraft engineering and maintenance operational functions to external organizations, the operator retains overall responsibility for ensuring aircraft airworthiness, and must demonstrate processes for monitoring the applicable external organization(s) in accordance with MNT 1.11.7.

General Guidance

Definitions of technical terms used in this ISM Section 4, as well as the meaning of abbreviations and acronyms, are found in the IATA Reference Manual for Audit Programs (IRM).

1 Management and Control

1.1 Management System Overview

1.2 Accountability, Authorities and Responsibilities

1.3 Maintenance Program

MNT 1.3.1

The Operator shall provide, for the use and guidance of relevant maintenance and operational personnel, a Maintenance Program that is approved by the relevant Authority and contains information and data for each aircraft type/model and configuration in the Operator's fleet in accordance with specifications in Table 4.1. The Maintenance Program shall satisfy:

- (i) Requirements of the State of Registry;
- (ii) Requirements of the State of Design;
- (iii) Requirements of the Operator;
- (iv) Maintenance specifications provided by the aircraft, engine and component OEMs. **(GM)**

Auditor Actions

- ☐ **Identified** an approved maintenance program for each aircraft type.
- ☐ **Interviewed** responsible manager(s).
- ☐ **Examined** selected maintenance program(s) (content in accordance with specifications in Table 4.1).
- ☐ **Other Actions** (Specify)

Guidance

Refer to the IRM for the definitions of [Approved Maintenance Organization \(AMO\)](#), [State of Design](#) and [State of Registry](#).

An aircraft maintenance program is usually approved by the authority of the State of the Operator. However, when an operator utilizes an aircraft registered in a different state, it is possible that the maintenance program could be approved by the authority of the State of Registry.

An operator's authority typically holds the operator responsible for the definition, the control and the provision of Maintenance Data, and an Approved Maintenance Program for use by the operator and its maintenance organization.

The aircraft is maintained under one approved operator's aircraft maintenance program. When an operator wishes to change from one approved aircraft maintenance program to another approved program, a transfer/bridging check/inspection may need to be performed, as agreed with the Authority, in order to implement the change.

The operator's aircraft maintenance program typically contains a preface that defines the maintenance program contents, the inspection standards to be applied, permitted variations to task frequencies and, where applicable, any procedure to escalate established check/inspection intervals.

A reliability program provides an appropriate means of monitoring the effectiveness of the maintenance program. Maintenance program optimization relies on implementation of the reliability program.

Some operator's approved aircraft maintenance programs, not developed from the MRB Process, use reliability programs as the basis of the approval. The purpose of a reliability program is to ensure the aircraft maintenance program tasks are effective and carried out at appropriate time intervals. Actions resulting from the reliability program may result in the escalation or de-escalation, or addition or deletion, of maintenance tasks, as deemed necessary.

The maintenance program typically contains the following:

- The type/model and registration number of the aircraft, engines and, where applicable, auxiliary power units (APUs) and propellers;
- The name and address of the operator;
- The operator's reference identification of the program document, the date of issue and issue number;
- A statement signed by the operator to the effect the specified aircraft is maintained in accordance with the program and that the program is reviewed and updated as required;
- Contents/list of effective pages of the document;
- Check periods that reflect the anticipated utilization of the aircraft and where utilization cannot be anticipated, calendar time limits are included;
- Procedures for the escalation of established check periods, where applicable, and acceptable to the Authority;
- Provision to record date and reference to approved amendments incorporated in the program;
- Details of preflight maintenance tasks accomplished by maintenance personnel and not included in the Operations Manual for action by flight crew;
- The tasks and the periods (intervals/frequencies) at which each part of the aircraft, engines, APUs, propellers, components, accessories, equipment, instruments, electrical and radio apparatus and associated systems and installations are to be inspected, together with the type and degree of inspection;
- The periods when items are checked, cleaned, lubricated, replenished, adjusted and tested;
- Details of specific structural inspections or sampling programs;
- Details of the corrosion control program, when applicable;
- The periods and procedures for the collection of engine health monitoring data;
- The periods when overhauls and/or replacements by new or overhauled parts are to be made;

- A cross-reference to other documents approved by the Authority that contain the details of maintenance tasks related to mandatory life-limitations, Certification Maintenance Requirements (CMRs) and Airworthiness Directives (ADs);
***Note:** To prevent inadvertent variations to such tasks or intervals, these items would not be included in the main portion of the maintenance program document, or any planning control system, without specific identification of their mandatory status.*
- Details of, or cross-reference to, any required Reliability Program or statistical methods of continuous surveillance;
- A statement that practices and procedures to satisfy the program are to the standards specified in the Type Certificate Holder's Maintenance Instructions. When practices and procedures are included in a customized operator's maintenance manual approved by the Authority, the statement refers to this manual;
- Each maintenance task quoted is defined in the definitions section of the program.

⊗

⊗

An operator's approved aircraft maintenance programs are subject to periodic review to ensure they reflect current Type Certificate Holder's recommendations, revisions to the Maintenance Review Board Report and the mandatory requirements and maintenance needs of the aircraft. The operator reviews the detailed requirements at least annually for continued validity in light of the operating experience.

1.4 Provision of Resources

1.5 Communication

1.6 Documentation System

1.7 Maintenance Management Manual (MMM)

1.8 Maintenance Records System

1.9 Aircraft Systems/Equipment

MNT 1.9.1

The Operator shall ensure all aircraft in its fleet are equipped with, in accordance with conditions of applicability, the aircraft systems and equipment specified in [Table 4.11](#). (GM)

Auditor Actions

- ☐ **Identified/Assessed** fleet aircraft systems/equipment (focus: systems/equipment in accordance with [Table 4.11](#) for aircraft types in operator's fleet).
- ☐ **Interviewed** responsible manager(s).
- ☐ **Examined** records of installation, inspection and/or maintenance of selected systems/equipment.
- ☐ **Observed** line flight operations (FLT/CAB auditors) or inspected static aircraft (focus: sampled aircraft have applicable systems/equipment installed).
- ☐ **Other Actions** (Specify)

Guidance

The intent of this provision is that, in accordance with conditions of applicability, the systems and equipment specified in [Table 4.11](#) are installed on each aircraft type in the operator's fleet.

The condition of applicability of some system or equipment requirements is predicated on the use of an aircraft type in a certain type of operation (e.g. long-range over-water flights). Where an operator has a fleet of an aircraft type of which some are not used in the conditional operation, then the

operator would typically have to demonstrate a segregation system that prevents such aircraft from being used in the conditional operation.

The operator or the Authority may prescribe additional requirements for aircraft systems or equipment installation.

1.10 Quality Assurance Program

1.11 Quality Control of Outsourced Operations and Products

MNT 1.11.7

The Operator shall have monitoring processes to ensure each approved maintenance organization that performs maintenance for the Operator:

- (i) Complies with applicable regulations and safety and quality requirements;
- (ii) Has procedures that are acceptable to the Authority granting the approval;
- (iii) Performs all maintenance in accordance with requirements of the Operator. **(GM) ◀**

Auditor Actions

- ☐ **Identified/Assessed** (focus: monitoring process ensures provider fulfils applicable safety/security requirements).
- ☐ **Interviewed** responsible manager(s) in MNT operations.
- ☐ **Examined** selected records/reports resulting from monitoring of maintenance operations service providers (focus: monitoring process ensures provider fulfils applicable safety/security requirements).
- ☐ **Observed** maintenance outsourcing management (focus: processes for monitoring all AMO service providers)
- ☐ **Other Actions** (Specify)

Guidance

Refer to Guidance associated with [ORG 3.5.2](#) located in ISM Section 1.

MNT 1.11.9

The Operator shall have processes that ensure:

- (i) Aircraft parts and materials are only obtained from approved sources;
- (ii) Certification documentation requirements are specified;
- (iii) Traceability to the last certifying organization for used or surplus parts;
- (iv) A statement of conformity or certification test results is retained for hardware and raw materials (e.g. extrusions, sheet or bar stock);
- (v) Inventory storage of consumable material is managed to ensure traceability of manufacturer batch/lot control. **(GM)**

Auditor Actions

- ☐ **Identified/Assessed** the process(es) for the management and control of parts and materials.
- ☐ **Interviewed** responsible manager(s).
- ☐ **Examined** selected incoming parts documentation.
- ☐ **Examined** traceability of selected parts.
- ☐ **Observed** aircraft parts/components management/handling (focus: processes for management of acquisition/certification/traceability/inventory for aircraft parts/components).
- ☐ **Other Actions** (Specify)

Guidance

An external maintenance organization that performs contracted maintenance functions for the operator may perform the tasks specified in i) through v).

An aircraft part fabricated or manufactured for an operator by a non-approved maintenance organization is produced under the quality system of either the operator or the external maintenance organization. Such an arrangement must be approved by the Authority.

An operator is not required to keep records of traceability that would track the use of batch-controlled consumables.

1.12 Safety Management

Risk Management

MNT 1.12.1

The Operator shall have a hazard identification program for maintenance operations that includes:

- (i) A combination of reactive and proactive methods for hazard identification;
- (ii) Processes for safety data analysis that identify existing hazards, and may predict future hazards, to aircraft operations. **[SMS] (GM) ◀**

Auditor Actions

- ☐ **Identified/Assessed** safety hazard identification program in MNT operations (focus: program identifies hazards to aircraft operations; describes/defines method(s) of safety data collection/analysis).
- ☐ **Identified/Assessed** role of MNT operations in the organization-wide, cross-discipline safety hazard identification program (focus: participation with other operational disciplines).
- ☐ **Interviewed** responsible manager(s) in MNT operations.
- ☐ **Interviewed** person(s) that perform analysis of MNT operational data for the purpose of identifying hazards to aircraft operations.
- ☐ **Examined** examples of hazards to aircraft operations that have been identified through data collection and analysis in MNT operations.
- ☐ **Other Actions** (Specify)

Guidance

Refer to the IRM for the definitions of [Hazard \(Aircraft Operations\)](#), [Base Maintenance](#), [Line Maintenance](#), [Risk Management](#) and [Safety Risk](#).

Hazard identification is an element of the Safety Risk Management component of the SMS framework.

The operator typically applies its safety hazard identification program to the full scope of maintenance operations associated with maintaining its aircraft, which includes line and base maintenance.

Refer to Guidance associated with [ORG 3.1.1](#) located in ISM Section 1.

MNT 1.12.2

The Operator shall have a safety risk assessment and mitigation program in maintenance operations that specifies processes to ensure:

- (i) Hazards are analyzed to determine corresponding safety risk(s) to aircraft operations;
- (ii) Safety risks are assessed to determine the requirement for risk mitigation action(s);
- (iii) When required, risk mitigation actions are developed and implemented in maintenance operations. **[SMS] [Eff] (GM) ◀**

Assessment Tool

Desired Outcome

The Operator maintains an overview of its maintenance risks and through implementation of mitigation actions, as applicable, ensures risks are at an acceptable level.



Suitability Criteria (Suitable to the size, complexity and nature of operations)

Number and type of analyzed hazards and corresponding risks.

Means used for recording risks and mitigation (control) actions.

Safety data used for the identification of hazards.

Effectiveness Criteria

(i) All relevant maintenance hazards are analyzed for corresponding safety risks.

(ii) Safety risks are expressed in at least the following components:

- Likelihood of an occurrence.
- Severity of the consequence of an occurrence.
- Likelihood and severity have clear criteria assigned.

(iii) A matrix quantifies safety risk tolerability to ensure standardization and consistency in the risk assessment process which is based on clear criteria.

(iv) Risk register(s) within the maintenance organization capture risk assessment information, risk mitigation (control) and monitoring actions.

(v) The risk mitigation (control) actions include time lines, allocation of responsibilities and risk control strategies such as hazard elimination, risk avoidance, risk acceptance, risk mitigation.

(vi) Mitigation (control) actions are implemented to reduce the risk to a level of - as low as reasonably practical.

(vii) Identified risks and mitigation actions are regularly reviewed for accuracy and relevance.

(viii) Effectiveness of risk mitigation (control) actions are monitored at least yearly to include auditing in accordance with [ORG 3.4.1](#).

(ix) Personnel performing risk assessments are appropriately trained in accordance with [ORG 1.6.5](#).

Auditor Actions

- ☐ **Identified/Assessed** safety risk assessment and mitigation program in MNT operations (focus: hazards analyzed to identify/define risk; risk assessed to determine appropriate action; action implemented/monitored to mitigate risk).
- ☐ **Identified/Assessed** role of maintenance operations in cross-discipline safety risk assessment/mitigation program (focus: participation with other operational disciplines).
- ☐ **Interviewed** responsible manager(s) in MNT operations.
- ☐ **Interviewed** person(s) that perform safety risk assessments in MNT operations.
- ☐ **Examined** selected records/documents that illustrate risk assessment and resulting risk mitigation action(s) in MNT operations.
- ☐ **Other Actions** (Specify)

Guidance

Refer to the IRM for the definition of [Safety Risk Assessment \(SRA\)](#).

Risk assessment and mitigation is an element of the Safety Risk Management component of the SMS framework.

The operator typically applies its safety risk assessment and mitigation program to the full scope of maintenance operations associated with maintaining its aircraft, which includes line and base maintenance.

Hazards relevant to the conduct of maintenance operations are potentially associated with:

- Weather (e.g. temperature, precipitation);
- Work environment (e.g. lighting, temperature, noise/vibration, ventilation, hazardous/toxic substances, cleanliness, floor condition, body position, physical facility layout changes);
- Infrastructure (e.g. inadequate, uncontrolled or lack of equipment/tools);
- Automation limitations (e.g. poor assumptions based on misunderstanding of automation functionality);

- Foreign Object Debris (FOD);
- Personnel (e.g. not enough, lack or ineffective training, lack of skills, shift work, inadequate shift patterns);
- Aircraft and parts (e.g. different configurations, lack or difficulty of access);
- Technical data (e.g. uncontrolled, not up to date, inadequate layout of Task Cards, lack of understanding or difficulty in using electronic documentation or IT system);
- Inadequate communication (e.g. language differences, comprehension);
- Changes in processes, procedures, IT platforms, organizational, tooling and equipment.

Refer to Guidance associated with [ORG 3.1.2](#) located in ISM Section 1.

Operational Reporting

MNT 1.12.3

The Operator shall have an operational safety reporting system in maintenance operations that:

- Encourages and facilitates feedback from personnel to report safety hazards, expose safety deficiencies and raise safety concerns;
- Includes analysis and management action as necessary to address safety issues identified through the reporting system. **[SMS] (GM) ◀**

Auditor Actions

- ☐ **Identified/Assessed** operational safety reporting system in MNT operations (focus: system urges/facilitates reporting of hazards/safety concerns; includes analysis/action to validate/address reported hazards/safety concerns).
- ☐ **Interviewed** responsible manager(s) in MNT operations.
- ☐ **Interviewed** person(s) that perform operational safety report review/analysis/follow-up in maintenance operations.
- ☐ **Examined** data that confirm an effective maintenance operations safety reporting system (focus: quantity of reports submitted/hazards identified).
- ☐ **Examined** records of selected maintenance operations safety reports (focus: analysis/follow-up to identify and address reported hazards/safety concerns).
- ☐ **Other Actions** (Specify)

Guidance

Safety reporting is a key aspect of SMS hazard identification and risk management.

Safety issues are generally associated with the various operations (internal and outsourced) that are conducted for the purpose of ensuring aircraft are maintained in an airworthy condition.

Refer to Guidance associated with [ORG 3.1.3](#) located in ISM Section 1.

Safety Assurance

SMS Training

2 Maintenance Control

2.1 Control System

MNT 2.1.1

The Operator shall have a maintenance control system that is in accordance with procedures acceptable to the Authority and ensures:

- Each aircraft is maintained in an airworthy condition;
- Operational and emergency equipment necessary for flight is serviceable;
- The Certificate of Airworthiness of each aircraft remains valid.

Auditor Actions

- ☐ **Identified/Assessed** the system for control of aircraft maintenance.
- ☐ **Identified** the procedures for renewal of certificate of airworthiness (CoA).
- ☐ **Interviewed** responsible manager(s).
- ☐ **Examined** selected individual aircraft records for CoA.
- ☐ **Other Actions** (Specify)

2.2 Maintenance Planning**MNT 2.2.2**

The Operator shall have a system for tracking hours, cycles and calendar time for aircraft, engines and life-limited components.

Auditor Actions

- ☐ **Identified/Assessed** the system for tracking hours, cycles and calendar time for aircraft, engines and life-limited components.
- ☐ **Interviewed** responsible manager(s).
- ☐ **Examined** one aircraft, engine and life-limited component.
- ☐ **Other Actions** (Specify)

2.3 Parts Installation**MNT 2.3.1**

The Operator shall have a process to ensure that no new part is installed on an aeronautical product unless such part meets the standards of airworthiness applicable to the installation of new parts and, in addition, meets a minimum of one of the following:

- (i) The new part has marking identifying it as a part specified in the type design conforming to a recognized national or international standard, or
- (ii) The new part has been approved for use on an aeronautical product, in accordance with the type certificate/STC, if the part was originally designed and manufactured for non-aeronautical use, or
- (iii) The new part was manufactured under a Parts Manufacturer Approval (PMA), or
- (iv) The new part was produced by the Operator using approved procedures for the purpose of maintaining or altering its own aeronautical product. **(GM)**

Auditor Actions

- ☐ **Identified/Assessed** the process for managing and controlling new parts and parts installation.
- ☐ **Interviewed** responsible manager(s).
- ☐ **Observed** inspection of incoming parts.
- ☐ **Examined** selected parts installed on aircraft as new parts.
- ☐ **Observed** aircraft part/component installation/replacement (if applicable) (focus: new part/component being installed meets applicable standards of airworthiness).
- ☐ **Observed** aircraft parts/components management/handling (focus: control process for ensuring new parts meet applicable standards of airworthiness).
- ☐ **Other Actions** (Specify)

Guidance

The operator is responsible for providing an external AMO with approved documentation that contains information about parts allowed to be installed on its aircraft. Such documentation enables the external AMO to validate the airworthy condition of the part and its certification for installation on the aeronautical product being maintained. The “approved documentation” category typically

includes as necessary, without being limited to, any of the following: MMM, IPC (including Supplements), AD, SB, Work Order, Repair Order, Form 8130-3/EASA Form 1/or equivalent.

The production of parts by an operator for its own use, as specified in item iv), is acceptable provided there are approved procedures identified in the MMM.

MNT 2.3.2

The Operator shall have a process to ensure that no used part is installed on an aeronautical product unless such part meets the standards of airworthiness applicable to the installation of used parts and any of the following:

- (i) An airworthy part that has been removed from an aircraft for immediate installation on another aircraft, **or**
- (ii) An airworthy part that has undergone maintenance for which a maintenance release has been signed by an appropriately rated Approved Maintenance Organization (AMO), **or**
- (iii) An airworthy part that has undergone an approved repair or alteration that restored the certificated level of airworthiness to a used part. **(GM)**

Auditor Actions

- ☐ **Identified/Assessed** the process for managing and controlling used parts and parts installation.
- ☐ **Interviewed** responsible manager(s).
- ☐ **Examined** selected parts installed on aircraft for certificates.
- ☐ **Observed** aircraft part/component installation/replacement (if applicable) (focus: used part/component being installed meets applicable standards of airworthiness).
- ☐ **Observed** aircraft parts/components management/handling (focus: control process for ensuring used parts meet applicable standards of airworthiness).
- ☐ **Other Actions** (Specify)

Guidance

The operator is responsible for providing an external AMO with approved documentation that contains information about parts allowed to be installed on its aircraft. Such documentation enables the external AMO to validate the airworthy condition of the part and its certification for installation on the aeronautical product being maintained. The "approved documentation" category typically includes as necessary, without being limited to, any of the following: MMM, IPC (including Supplements), AD, SB, Work Order, Repair Order, Form 8130-3/EASA Form 1/or equivalent.

MNT 2.3.3

The Operator shall have a process to ensure that no used life-limited part is installed on an aeronautical product unless such part meets the standards of airworthiness applicable to the installation of life-limited parts and:

- (i) The technical history of the part is available to demonstrate the time in service, as authorized for that part in the type certificate governing the installation, has not been exceeded;
- (ii) The technical history referred to in sub-paragraph i) is incorporated into the technical record for the aeronautical product on which the part is installed. **(GM)**

Auditor Actions

- ☐ **Identified/Assessed** the process for managing and controlling used life-limited parts and parts installation.
- ☐ **Interviewed** responsible manager(s).
- ☐ **Interviewed** personnel that execute procedures for tracking life-limited parts.
- ☐ **Traced** the technical history of selected life-limited parts.
- ☐ **Observed** aircraft part/component installation/replacement (if applicable) (focus: used life-limited part/component being installed meets applicable standards of airworthiness).

- ☐ **Observed** aircraft parts/components management/handling (focus: control process for ensuring used life-limited parts meet applicable standards of airworthiness).
- ☐ **Other Actions** (Specify)

Guidance

The operator is responsible for providing an external AMO with approved documentation that contains information about parts allowed to be installed on its aircraft.

In general, it is best for an operator to have a fully traceable history for all life-limited parts. Not all parts have a fixed life. The life of some parts might be variable depending on the way the part has been used in the past. For example, load-bearing parts (e.g. landing gear components) that can be installed on different aircraft types (e.g. A319, A320, A321) will have a shorter life if installed on the heavier aircraft (as opposed to the same part installed on a lighter aircraft). Therefore, a complete history of these types of components is critical in knowing exactly when the life of the part will expire. For parts that have a fixed life (e.g. batteries, slides), traceability to birth is not a requirement. However, in such cases, it is very important that the operator has documentation that shows clearly that the used part has not exceeded its airworthiness life limit.

2.4 Deferred Maintenance

MNT 2.4.1

The Operator shall have a maintenance control function that is responsible for approving, controlling, monitoring and scheduling non-routine and deferred maintenance activities, including MEL/CDL requirements.

Auditor Actions

- ☐ **Identified** the description of the maintenance control center (MCC) (or equivalent).
- ☐ **Interviewed** responsible manager(s).
- ☐ **Interviewed** personnel responsible for selected maintenance control functions.
- ☐ **Examined** maintenance control processes/procedures.
- ☐ **Other Actions** (Specify)

MNT 2.4.2

The Operator shall have a process to ensure MEL/CDL restricted items are tracked and corrected within the required time intervals. **(GM)**

Auditor Actions

- ☐ **Identified/Assessed** the process(es) for managing the MEL/CDL.
- ☐ **Interviewed** responsible manager(s).
- ☐ **Interviewed** MCC personnel.
- ☐ **Examined** selected records of MEL/CDL restricted items.
- ☐ **Traced** the tracking and correction of selected MEL/CDL restricted item(s).
- ☐ **Other Actions** (Specify)

Guidance

The intent of this provision is to ensure an operator has a process to rectify all defects affecting the safe operation of the aircraft within the limits prescribed by the approved MEL or CDL. Postponement of any defect rectification cannot typically be permitted without the operator's agreement and in accordance with a procedure approved by the State of Registry/Authority.

2.5 Continuing Airworthiness Information

MNT 2.5.1

The Operator shall have processes to:

- (i) Obtain and assess continuing airworthiness information, including Airworthiness Directives (ADs), Alert Service Bulletins and recommendations from the organizations responsible for aircraft type design, and
- (ii) Implement the resulting actions that are mandatory or considered necessary in accordance with procedures acceptable to the Authority. **(GM)**

Auditor Actions

- ☐ **Identified/Assessed** the process(es) for obtaining, assessing and implementing ADs and ASBs.
- ☐ **Interviewed** responsible manager(s).
- ☐ **Examined** selected records of AD and SB compliance, including Task Cards.
- ☐ **Traced** selected AD(s) and/or SB(s) from receipt to implementation.
- ☐ **Observed** AD/SB management (focus: AD/SB process includes identification, planning, accomplishment, certification, recording, follow-up monitoring).
- ☐ **Other Actions** (Specify)

Guidance

Refer to the IAH for the definitions of [Authority](#), [Service Bulletin](#) (which includes the definition of Alert Service Bulletin) and [Design Approval Holder \(DAH\)](#).

Continuing airworthiness information and recommendations typically include:

- Airworthiness Directives that are developed by the Authority;
- Alert Service Bulletins, Airworthiness Limitations, maintenance planning and accomplishment instructions that are developed by the Type Design Organization(s) in accordance with their obligations as Design Approval Holder (DAH) for the respective product.

If improvements identified in the assessment process are considered by the operator as necessary to meet its safety and reliability needs, the current planning, accomplishment instructions, and/or airworthiness limitations may need to be adjusted through the implementation process.

MNT 2.5.3

The Operator shall have a program for the management of the minimum equipment lists (MELs) used in its fleet operations. Such program shall ensure MELs:

- (i) Are approved by the State of the Operator and/or State of Registry if applicable;
- (ii) Include the latest applicable MMEL provisions released by the Type Certificate Holder(s);
- (iii) Are relevant to and customized for the type/model of aircraft in the Operator's fleet;
- (iv) Identify applicable maintenance procedures called upon by the MEL items and such procedures are readily available for implementation by the appropriate maintenance personnel. **(GM)**

Auditor Actions

- ☐ **Identified/Assessed** the procedure(s) for revising the MEL per the MMEL applicable revision.
- ☐ **Interviewed** responsible manager(s).
- ☐ **Examined** selected records of MEL usage requiring an (M) procedure.
- ☐ **Other Actions** (Specify)

Guidance

Refer to the IRM for the definitions of [Minimum Equipment List \(MEL\)](#) and [Master Minimum Equipment List \(MMEL\)](#).

The relevance and customization of the MEL is performed by the operator to reflect the configuration particular to each aircraft type in its fleet (e.g. the long-range or extended-range version, the engine type/model, the optional equipment installed etc.). The MEL typically does not include MMEL provisions that are not relevant to the actual configuration of the operated aircraft.

The timeframe in which the applicable MMEL revisions released by the type certificate holder (TCH) are incorporated into the MEL is acceptable to the Authority.

The maintenance procedures as specified in (iv) are identified by an (M) symbol in the MEL.

The intent is that all maintenance procedures are developed to a sufficient level.

2.6 Repairs and Modifications

MNT 2.6.1

The Operator shall have a process to ensure all modifications and repairs:

- (i) Are carried out using approved data;
- (ii) Comply with airworthiness requirements of the Authority and State of Registry.

Auditor Actions

- ☐ **Identified/Assessed** the process(es) for managing modifications and repairs.
- ☐ **Identified/Assessed** the procedures for maintaining technical records of modifications and repairs.
- ☐ **Interviewed** responsible manager(s).
- ☐ **Examined** selected records of aircraft modification(s) and/or repair(s).
- ☐ **Observed** aircraft part/component installation/replacement (focus: installation/replacement accomplished using approved data/in accordance with regulations).
- ☐ **Observed** AD/SB management (focus: AD/SB process ensures modifications/repairs accomplished using approved data/in accordance with regulations).
- ☐ **Other Actions** (Specify)

2.7 Defect Recording and Control

MNT 2.7.1

The Operator shall have processes for the management of recurring defects, to include:

- (i) Tracking chronic or repetitive unserviceable items;
- (ii) Documenting troubleshooting history;
- (iii) Implementing instructions for corrective action;
- (iv) Ensuring rectification takes into account the methodology used in previous repair attempts.

Auditor Actions

- ☐ **Identified/Assessed** the process(es) for tracking and correcting chronic or repetitive unserviceable items.
- ☐ **Interviewed** responsible manager(s).
- ☐ **Interviewed** personnel that execute procedures that address chronic or repetitive unserviceable items.
- ☐ **Examined** corrective action records for selected chronic unserviceable items.
- ☐ **Traced** the process for developing corrective action for chronic unserviceable item(s).
- ☐ **Other Actions** (Specify)

2.8 Extended Diversion Time Operations (EDTO)

MNT 2.8.2

If the Operator utilizes twin engine aircraft that are approved for ETOPS/EDTO, the Operator shall ensure compliance with maintenance requirements as specified in [Table 4.5](#). **(GM)**

Auditor Actions

- ☐ **Identified** twin engine aircraft types approved for the conduct of ETOPS/EDTO.
- ☐ **Identified/Assessed** maintenance program for twin engine aircraft approved for the conduct of ETOPS/EDTO (focus: satisfaction of requirements specified in [Table 4.5](#)).
- ☐ **Interviewed** responsible manager(s).
- ☐ **Examined** selected ETOPS/EDTO aircraft maintenance records (focus: compliance with maintenance program requirements).
- ☐ **Other Actions** (Specify)

Guidance

In complying with the requirements specified in [Table 4.5](#), an operator would normally be expected to develop, whenever applicable, the following:

- The list of ETOPS/EDTO Significant Systems/Sub-systems (i.e. the list including, for a given aircraft, any system/sub-system whose failure or degradation could adversely affect the safety of an EDTO flight or whose continued functioning is important to the safe flight and landing of an aircraft during an ETOPS/EDTO diversion).
- The list of maintenance tasks with ETOPS/EDTO significance (i.e. the list of maintenance tasks affecting any EDTO Significant System/Sub-system).
- The reliability program supplemented, as applicable, to take into account the ETOPS/EDTO requirements and specific analysis.
- The Engine Condition Monitoring Program (ECMP) including the Oil Consumption Monitoring Program.
- The APU in-flight Start Program.
- The ETOPS/EDTO aircraft Pre-Departure Service Check (PDSC).
- The list of ETOPS/EDTO Qualified Maintenance Personnel as well as the training program and qualification procedures of such personnel.
- The procedure to integrate in the MMM all applicable Configuration, Maintenance and Procedures (CMP) provisions issued by the manufacturer of the aircraft.

2.9 Aircraft Recorders

2.10 Electronic Navigation Data Management

MNT 2.10.1

If the Operator utilizes aircraft with electronic navigation capabilities, the Operator shall have a procedure to ensure the timely insertion of current and unaltered electronic navigation data to all applicable aircraft. **(GM)**

Auditor Actions

- ☐ **Identified/Assessed** the procedure(s) for inserting/loading electronic data into aircraft navigation systems.
- ☐ **Interviewed** responsible manager(s).
- ☐ **Examined** selected records of electronic navigation data insertion/loading.
- ☐ **Coordinated** with FLT auditor (verify currency of aircraft navigation databases).
- ☐ **Other Actions** (Specify)

Guidance

The intent of this provision is to ensure a procedure for the insertion of databases for use in aircraft navigation systems prior to the first flight on the effective date for the new database.

2.11 Reduced Vertical Separation Minima (RVSM)**2.12 Reporting to the Authority****3 Technical Records****3.1 Aircraft Maintenance Records****3.2 Aircraft Technical Log (ATL)****3.3 (Intentionally open)****3.4 Airworthiness Directives****4 Maintenance Organizations****4.1 Approval****MNT 4.1.1**

The Operator shall have a process to ensure an aircraft is not operated unless it is maintained and released to service by an Approved Maintenance Organization (AMO) that:

- (i) Is acceptable to the Authority;
- (ii) Has established procedures acceptable to the Authority to ensure maintenance practices are in compliance with all relevant requirements;
- (iii) Maintains the validity of its approval through compliance with the requirements for an approved maintenance organization acceptable to the Authority. **(GM)**

Auditor Actions

- ☐ **Identified/Assessed** the process(es) for the selection of AMOs.
- ☐ **Interviewed** responsible manager(s).
- ☐ **Examined** selected AMO selection records.
- ☐ **Observed** maintenance outsourcing management (focus: requirement that aircraft maintenance is performed only by an AMO)
- ☐ **Other Actions** (Specify)

Guidance

Refer to the IRM for the definition of [Approved Maintenance Organization \(AMO\)](#).

4.2 Management**4.3 Quality Assurance**

4.4 Personnel

MNT 4.4.1

The Operator shall have a process to ensure each maintenance organization that performs maintenance for the Operator utilizes maintenance personnel:

- (i) That are appropriately licensed and/or authorized to sign the maintenance release;
- (ii) Whose competence has been established in accordance with a procedure and to a level acceptable to the authority granting approval for the maintenance organization. **(GM)**

Auditor Actions

- ☐ **Identified/Assessed** the requirement criteria for qualifications of personnel in the AMO selection process.
- ☐ **Interviewed** responsible manager(s).
- ☐ **Examined** selected AMO selection records.
- ☐ **Examined** selected AMO oversight/monitoring reports.
- ☐ **Observed** maintenance outsourcing management (focus: process for verifying AMO personnel are licensed/authorized to sign maintenance release).
- ☐ **Observed** aircraft part/component installation/replacement (focus: personnel signing maintenance release are appropriately licensed/authorized).
- ☐ **Other Actions** (Specify)

Guidance

Licensing typically ensures maintenance personnel have met the basic requirements of an applicable authority in terms of age, knowledge, experience and, if required, medical fitness and skill, and have demonstrated the required knowledge and skill in a manner specified by the authority.

Planners, mechanics, specialized services personnel, supervisors and certifying personnel are typically assessed for competence by an on-the-job evaluation and/or examination relevant to their particular job or role within the organization before unsupervised work is permitted.

To assist in the assessment of competence, job descriptions are recommended for each job role in the organization. Basically, the assessment establishes that:

- Planners are able to interpret maintenance requirements into maintenance tasks and have an appreciation that they have no authority to deviate from the maintenance data;
- Mechanics are able to carry out maintenance tasks to any standard specified in the maintenance data and notify supervisors of mistakes requiring rectification to meet required maintenance standards;
- Specialized services personnel are able to carry out specialized maintenance tasks to the standard specified in the maintenance data and will both inform and await instructions from their supervisor in any case where it is impossible to complete the specialized maintenance in accordance with the maintenance data;
- Supervisors are able to ensure that all required maintenance tasks are carried out and where not completed or where it is evident that a particular maintenance task cannot be carried out in accordance with the maintenance data, it is to be reported to the responsible person for appropriate action. In addition, for those supervisors who also carry out maintenance tasks, that they understand such tasks are not to be undertaken when incompatible with their management responsibilities;
- Certifying personnel are able to determine when the aircraft is or is not ready to be released to service.

Knowledge of organizational procedures relevant to each individual's particular role in the organization is important, particularly in the case of planners, specialized services personnel, supervisors and certifying personnel.

4.5 Training Program

MNT 4.5.1

The Operator shall have a process to ensure each maintenance organization that performs maintenance for the Operator has a training program that assures all maintenance personnel receive initial and recurrent training that is appropriate to individually assigned tasks and responsibilities, and provides maintenance personnel with:

- (i) The knowledge of regulations, standards and procedures in accordance with requirements in the MMM;
- (ii) The knowledge and skills related to human performance, including coordination with, as applicable, other maintenance personnel and/or flight crew. **(GM)**

Auditor Actions

- ☐ **Identified/Assessed** the requirement criteria for an overall training program in the AMO selection process.
- ☐ **Interviewed** responsible manager(s).
- ☐ **Examined** selected AMO selection records.
- ☐ **Examined** selected AMO oversight/monitoring reports.
- ☐ **Observed** maintenance outsourcing management (focus: process for verifying AMO has initial/recurrent training programs for maintenance personnel).
- ☐ **Other Actions** (Specify)

Guidance

Refer to the IRM for the definitions of [Human Factors Principles](#) and [Human Performance](#).

The intent of this provision is for the operator to ensure appropriate initial and recurrent training for maintenance personnel and to ensure such training takes into account the knowledge and skills specified.

Maintenance personnel receive training in human performance to promote an understanding of the human factors (e.g. human capabilities, limitations, and the interface(s) between human and system components) involved in performing maintenance duties and coordinating with other maintenance personnel and/or flight crew. These human factors are taken into account during training to reduce human error in maintenance activities, including activities performed by an external AMO.

MNT 4.5.7

If the Operator utilizes a maintenance organization that has maintenance personnel taxi the Operator's aircraft on the movement area of an airport, the Operator shall have a process to ensure such maintenance personnel are authorized, competent and qualified to conduct aircraft taxi operations.

Auditor Actions

- ☐ **Identified/Assessed** the requirement criteria for the qualifications of personnel that taxi aircraft in the AMO selection process.
- ☐ **Interviewed** responsible manager(s).
- ☐ **Examined** selected AMO selection records.
- ☐ **Examined** selected AMO oversight/monitoring reports.
- ☐ **Observed** maintenance outsourcing management (if applicable) (focus: process for verifying training/qualification of AMO personnel authorized to taxi aircraft).
- ☐ **Other Actions** (Specify)

4.6 Facilities and Physical Resources

MNT 4.6.2

The Operator shall have a process to ensure each maintenance organization that performs maintenance for the Operator has the necessary technical data, equipment, tools and material to perform the work for which the maintenance organization has been approved, to include:

- (i) Equipment and tools necessary to comply with the work specified in the agreement between the Operator and the maintenance organization;
- (ii) Sufficient supplies and spare parts to ensure timely rectification of defects with regard to the Minimum Equipment List (MEL) provisions as specified in the agreement between the Operator and the maintenance organization. **(GM)**

Auditor Actions

- ☐ **Identified/Assessed** the requirement criteria for technical data, equipment, tools and material in the AMO selection process.
- ☐ **Interviewed** responsible manager(s).
- ☐ **Examined** selected AMO selection records.
- ☐ **Examined** selected AMO oversight/monitoring reports.
- ☐ **Observed** maintenance outsourcing management (focus: process for verifying adequate AMO data/equipment/supplies/parts to perform maintenance).
- ☐ **Observed** aircraft part/component installation/replacement (focus: availability/use of necessary technical data/equipment/tools/material for maintenance activity being performed).
- ☐ **Observed** aircraft parts/components management/handling (focus: availability/use of necessary technical data/equipment/tools/material for management/handling of aircraft parts/components).
- ☐ **Other Actions** (Specify)

Guidance

Tools and equipment, as specified in the Approved Data, can be made available when needed. Tools and equipment, which require to be controlled in terms of servicing or calibration to measure specified dimensions and torque figures, are to be clearly identified and listed in a control register, including any personal tools and equipment that the organization agrees can be used. Where the manufacturer specifies a particular tool or equipment, then that tool or equipment is used, unless the AMO has an approved procedure to determine the equivalency of alternative tooling/equipment and the procedure documented in the MPM.

The availability of equipment and tools indicates permanent availability except in the case of any tool or equipment that is so rarely needed that its permanent availability is not necessary.

A maintenance organization approved for base maintenance has sufficient aircraft access equipment and inspection platforms/docking such that the aircraft may be properly inspected.

The supplies necessary to perform maintenance work refer to readily available raw material and aircraft components, in accordance with the manufacturer's recommendations, unless the organization has an established spares provisioning procedure.

MNT 4.6.3

The Operator shall have a process to ensure each maintenance organization that performs maintenance for the Operator has facilities suitable for the storage of parts, equipment, tools and material under conditions that provide security and prevent deterioration of and damage to stored items. Such processes shall ensure:

- (i) Clean work areas, including management offices;
- (ii) Parts and material properly identified and stored;
- (iii) Oxygen and other high-pressure bottles properly identified and stored;
- (iv) Flammable, toxic or volatile materials properly identified and stored;
- (v) Equipment identified and protected. **(GM)**

Auditor Actions

- ☐ **Identified/Assessed** the requirement criteria for facilities in the AMO selection process.
- ☐ **Interviewed** responsible manager(s).
- ☐ **Examined** selected AMO selection records.
- ☐ **Examined** selected AMO oversight/monitoring reports.
- ☐ **Observed** maintenance outsourcing management (focus: process for verifying adequate AMO storage facilities for parts/tools/equipment/material).
- ☐ **Observed** aircraft parts/components management/handling (focus: adequate storage facilities for aircraft parts/components).
- ☐ **Other Actions** (Specify)

Guidance

Storage facilities for serviceable aircraft components are clean, well-ventilated and maintained at an even dry temperature to minimize the effects of condensation. Storage recommendations from the manufacturers for aircraft components are to be followed.

Storage racks are strong enough to hold aircraft components and provide sufficient support for large aircraft components such that the component is not distorted during storage.

All aircraft components, wherever practicable, remain packaged in protective material to minimize damage and corrosion during storage.

MNT 4.6.4

The Operator shall have a process to ensure each maintenance organization that performs maintenance for the Operator has a shelf-life program for applicable stored items, which includes a requirement for the shelf-life limit to be controlled and displayed.

Auditor Actions

- ☐ **Identified/Assessed** the requirement criteria for a shelf life program in the AMO selection process.
- ☐ **Interviewed** responsible manager(s).
- ☐ **Examined** selected AMO selection records.
- ☐ **Examined** selected AMO oversight/monitoring reports.
- ☐ **Observed** maintenance outsourcing management (focus: process for verifying acceptable AMO shelf-life program for applicable stored items).
- ☐ **Observed** aircraft parts/components management/handling (focus: shelf-life program for applicable stored aircraft parts/components).
- ☐ **Other Actions** (Specify)

MNT 4.6.5

The Operator shall have a process to ensure each maintenance organization that performs maintenance for the Operator has a receiving inspection program that:

- (i) Assures incoming material has the required certification documentation and traceability;
- (ii) Includes a process for verification of incoming part tags to ensure information on the tag (e.g. part name, part number, serial number, modification and/or any other applicable reference information) matches the corresponding information on the part.

Auditor Actions

- ☐ **Identified/Assessed** the receiving inspection process.
- ☐ **Interviewed** responsible manager(s).
- ☐ **Examined** selected records of incoming material (focus: certification documentation and traceability).
- ☐ **Examined** selected records of verification of incoming part tags.

- ☐ **Observed** maintenance outsourcing management (focus: process for verifying acceptable AMO receiving inspection program).
- ☐ **Observed** aircraft parts/components management/handling (focus: program for ensuring receiving inspection of incoming aircraft parts/components).
- ☐ **Other Actions** (Specify)

4.7 Material Handling

MNT 4.7.1

The Operator shall have a process to ensure each maintenance organization that performs maintenance for the Operator has a secure quarantine area for rejected parts and materials awaiting disposition.

Auditor Actions

- ☐ **Identified/Assessed** the requirement criteria for a secure parts/materials quarantine area in the AMO selection process.
- ☐ **Interviewed** responsible manager(s).
- ☐ **Examined** selected AMO selection records.
- ☐ **Examined** selected AMO oversight/monitoring reports.
- ☐ **Observed** maintenance outsourcing management (focus: process for verifying adequate AMO parts/materials quarantine area).
- ☐ **Observed** aircraft parts/components management/handling (focus: secure quarantine area(s) adequate for rejected aircraft parts/components).
- ☐ **Other Actions** (Specify)

MNT 4.7.2

The Operator shall have a process to ensure each maintenance organization that performs maintenance for the Operator has a process for segregating aircraft serviceable parts, aircraft non-serviceable parts, and non-aircraft parts.

Auditor Actions

- ☐ **Identified/Assessed** the requirement criteria for a parts segregation process in the AMO selection process.
- ☐ **Interviewed** responsible manager(s).
- ☐ **Examined** selected AMO selection records.
- ☐ **Examined** selected AMO oversight/monitoring reports.
- ☐ **Observed** segregated parts.
- ☐ **Observed** maintenance outsourcing management (focus: process for verifying acceptable AMO process for segregating parts).
- ☐ **Observed** aircraft parts/components management/handling (focus: process for segregating serviceable/non-serviceable/non-aircraft parts/components).
- ☐ **Other Actions** (Specify)

MNT 4.7.3

The Operator shall have a process to ensure each maintenance organization that performs maintenance on electrostatic sensitive devices (ESD) for the Operator has an ESD Program. Such ESD program shall comply with applicable manufacturer instructions and the specifications contained in [Table 4.8](#). (GM)

Auditor Actions

- ☐ **Identified** the requirement criteria for an ESD program in the AMO selection process.
- ☐ **Interviewed** responsible manager(s).
- ☐ **Examined** selected AMO selection records.

- ☐ **Examined** selected AMO oversight/monitoring reports.
- ☐ **Observed** maintenance outsourcing management (focus: process for verifying acceptable AMO ESD program).
- ☐ **Observed** aircraft parts/components management/handling (focus: ESD program in accordance with [Table 4.8](#)).
- ☐ **Other Actions** (Specify)

Guidance

Consideration is typically given to the scope of work of the maintenance organization in determining the applicability of ESD requirements.

MNT 4.7.4

The Operator shall have a process to ensure each maintenance organization that performs maintenance for the Operator has a method of storage that assures sensitive parts and equipment, such as, but not limited to, oxygen system components (oxygen generators and bottles), O-rings and electrostatic sensitive devices are properly packaged, identified and stored to protect them from damage and contamination. **(GM)**

Auditor Actions

- ☐ **Identified/Assessed** the requirement criteria for the storage of sensitive parts in the AMO selection process.
- ☐ **Interviewed** responsible manager(s).
- ☐ **Examined** selected AMO selection records.
- ☐ **Examined** selected AMO oversight/monitoring reports.
- ☐ **Observed** maintenance outsourcing management (focus: process for verifying acceptable AMO methods for storage of sensitive parts/equipment).
- ☐ **Observed** aircraft parts/components management/handling (focus: methods for ensuring proper identification/storage of sensitive aircraft parts/components).
- ☐ **Other Actions** (Specify)

Guidance

The intent of this provision is to ensure maintenance organizations comply with storage recommendations from the manufacturers, with particular emphasis on recommendations with respect to temperature and humidity.

Consideration is to be given to the scope of work of the AMO in determining applicability of specific handling and/or storage requirements.

4.8 (Intentionally open)

4.9 Procedures Manual

4.10 Maintenance Release

MNT 4.10.1

The Operator shall have a process to ensure each maintenance organization that performs maintenance for the Operator produces a completed and signed maintenance release that certifies all maintenance work performed has been completed satisfactorily and in accordance with the approved data and procedures described in the MPM of the maintenance organization. Such maintenance release shall include:

- (i) Basic details of the maintenance performed;
- (ii) A reference of the approved data used and, if required, the revision status;
- (iii) Maintenance tasks that were not accomplished;
- (iv) The date maintenance was completed;

- (v) When applicable, identity of the approved maintenance organization;
- (vi) Identity of the person(s) that sign the release. **(GM)**

Auditor Actions

- ☐ **Identified** the requirement criteria for the production of the maintenance release in the AMO selection process.
- ☐ **Interviewed** responsible manager(s).
- ☐ **Examined** selected AMO selection records.
- ☐ **Examined** selected AMO oversight/monitoring reports.
- ☐ **Observed** maintenance outsourcing management (focus: process for verifying AMO production of completed/signed maintenance release that certifies maintenance performed in accordance with MPM).
- ☐ **Observed** aircraft part/component installation/replacement (focus: production of complete maintenance release for specific maintenance activity being performed).
- ☐ **Other Actions** (Specify)

Guidance

Refer to the IRM for the definition of [Maintenance Organization Exposition](#).

An operator has the option of defining when the revision status of approved data (that was used during the performance of maintenance) must be included in the maintenance release. The process that defines such requirement is typically documented in the operator's MMM.

A requirement for the documented revision status to be part of the maintenance release might depend on the particular approved data that is referenced. For example, if the Aircraft Maintenance Manual that was used for maintenance is distributed online, there would be an online record of the revision that was available at the time of maintenance, which might obviate the need for that information to be documented in the maintenance release. Conversely, the revision status of certain engineering documents and/or drawings might not be found online or be otherwise available, in which case the operator could opt to require the revision status to be included in the maintenance release for the purpose of ensuring traceability.

Aircraft CRS

A Certificate of Release to Service (CRS) is required before flight:

- At the completion of any maintenance package specified by the aircraft operator;
- At the completion of any defect rectification, while the aircraft operates flight services between scheduled maintenance.

The maintenance package may include any one or a combination of the following elements: a check or inspection from the operator's aircraft maintenance program, Airworthiness Directives, overhauls, repairs, modifications, aircraft component replacements and defect rectification.

New defects or incomplete maintenance work orders identified during maintenance are brought to the attention of the operator for the specific purpose of obtaining agreement to rectify such defects or complete the missing elements of the maintenance work order. In the case where the aircraft operator declines to have such maintenance carried out and provided this missing element/defect does not affect the airworthiness of the aircraft, this fact is entered in the aircraft CRS before issue of such certificate.

Component CRS

A CRS is necessary at the completion of any maintenance on an aircraft component while off the aircraft.

The authorized release certificate/airworthiness approval tag constitutes the aircraft component certificate of release to service when one AMO maintains an aircraft component for another AMO.

When an AMO maintains an aircraft component for use by the organization, an authorized release certificate/airworthiness approval tag may or may not be necessary, depending upon the organization's internal release procedures defined in the maintenance organization exposition and approved by the Authority.

4.11 Tooling and Calibration

MNT 4.11.1

The Operator shall have a process to ensure each maintenance organization that performs maintenance for the Operator has procedures to control and document the calibration and records of all tools, including personnel-owned tools, and preventing out-of-service and due-for-calibration tools and equipment from being used, in accordance with specifications in [Table 4.10](#). (GM)

Auditor Actions

- ☐ **Identified/Assessed** the requirement criteria for the tool calibration in the AMO selection process.
- ☐ **Interviewed** responsible manager(s).
- ☐ **Examined** selected AMO selection records.
- ☐ **Examined** selected AMO oversight/monitoring reports.
- ☐ **Observed** maintenance outsourcing management (focus: process for verifying acceptable AMO tool calibration program).
- ☐ **Observed** aircraft part/component installation/replacement (focus: proper calibration of tools used in maintenance activity being performed).
- ☐ **Other Actions** (Specify)

Guidance

The control of these tools and equipment requires that the organization has a procedure to inspect/service and, where appropriate, calibrate such items on a regular basis and indicate to users that the item is within any inspection or service or calibration time limit. A clear system of labeling of all tooling, equipment and test equipment is therefore necessary, providing information on:

- When the next inspection or service or calibration is due;
- Whether the item is serviceable or unserviceable and the reason for its unserviceability.

A register is maintained for all precision tooling and equipment together with a record of calibrations and standards used.

Inspection, service or calibration of tools and equipment on a regular basis is in accordance with the equipment manufacturer's instructions except where the maintenance organization can justify by means of results that a different time period is appropriate in a particular case.

The procedural approach complies with the applicable standards authority (e.g. US Bureau of Standards or a country's approved standards certificate from the testing facility).

Table 4.1—Maintenance Program Specifications

The Operator's Maintenance Program shall contain the following information for each aircraft:

- (i) Maintenance tasks and the intervals at which these tasks are to be performed, taking into account the anticipated utilization of the aircraft;
- (ii) When applicable, a continuing structural integrity program;
- (iii) A system that identifies mandatory maintenance tasks, and their corresponding intervals, for tasks that have been specified as mandatory in the approval of the type design, (i.e. Certification Maintenance Requirements or CMRs);
- (iv) Procedures for changing or deviating from (i), (ii) and (iii) above;
- (v) The reliability program and descriptions of any required health monitoring for aircraft, engines, propellers and associated parts where the maintenance program was derived using the Maintenance Review Board process;
- (vi) The procedure for periodic review of the Maintenance Program to ensure it considers current Type Certificate Holder's recommendations, revisions to the Maintenance Review Board Report, mandatory requirements and other applicable requirements from the Authority.

Table 4.2–Maintenance Management and Control Functions

The Operator shall provide for facilities, workspace, equipment, personnel and supporting services, as well as work environment, as necessary to ensure the implementation of the following maintenance management and control functions:

- (i) The initial development of the maintenance schedule;
- (ii) Scheduling maintenance, elementary work and servicing to be performed within the time constraints specified in the approved maintenance schedule;
- (iii) Scheduling the accomplishment of Airworthiness Directives (ADs);
- (iv) Operation of an evaluation program to ensure that all required procedures and, in particular the maintenance schedule, continue to be effective and in compliance with the applicable regulations;
- (v) The proper dispatch of aircraft, with regard to:
 - (a) Control of defects;
 - (b) Availability of spare parts;
 - (c) Conformity with the type design;
 - (d) Requirements of other applicable operating rules.
- (vi) Liaison with approved maintenance organizations for the performance of maintenance;
- (vii) The development and update of the Maintenance Management Manual.

Table 4.3—Maintenance Management Manual Content Specifications

The MMM shall contain the following maintenance policies, procedures and information:

- (i) A description of the administrative arrangements between the operator and the approved maintenance organization;
- (ii) Names (or titles) and duties of the person or persons whose responsibilities are to ensure that maintenance is carried out in accordance with the MMM;
- (iii) A description of aircraft types and models to which the manual applies;
- (iv) A description of the maintenance procedures and the procedures for completing and signing a maintenance release when maintenance is based on a system other than that of an approved maintenance organization;
- (v) A reference to the approved maintenance program;
- (vi) A description of the methods used for the completion and retention of maintenance records, and including procedures for retaining backup records;
- (vii) A description of the procedures for monitoring, assessing and reporting maintenance and operational experience;
- (viii) A description of the procedures for complying with the service information reporting requirements;
- (ix) A description of procedures for assessing continuing airworthiness information and implementing any resulting actions;
- (x) A description of the procedures for implementing action resulting from mandatory continuing airworthiness information;
- (xi) A description of establishing and maintaining a system of analysis and continued monitoring of the performance and efficiency of the maintenance program, in order to improve and correct any deficiency in that program;
- (xii) A description of procedures for ensuring that unserviceable items affecting airworthiness are recorded and rectified;
- (xiii) A description of the procedures for advising the Authority of significant in-service occurrences;
- (xiv) The scope, structure and functionality of the management system for maintenance operations, to include a description of departments, positions, authorities, duties, responsibilities and the interrelation of functions and activities within the system;
- (xv) A process to ensure all amendments to the MMM are approved by the Authority and/or Operator, as applicable;
- (xvi) A description of the duties, responsibilities and reporting relationships within the Quality Assurance Program, or a reference to a separate quality assurance manual, if such description is found in that manual.

Table 4.4—Defect Reporting Specifications

The Operator shall have a procedure for reporting, to the Authority and, if applicable to the OEM, the following defects or un-airworthy conditions:

- (i) General
 - (a) Any failure, malfunction or defect where the safety of operation was or could have been endangered or which could have led to an unsafe condition.
- (ii) Aircraft Structure
 - (a) Any failure of aircraft primary structure or a principal structural element;
 - (b) Cracks, permanent deformation or corrosion or defect or damage of aircraft primary structure or principal structural element that a repair scheme is not already provided in the manufacturer's repair manual, or that occur after repair;
 - (c) Any part of the aircraft that would endanger the aircraft or any person by becoming detached in flight or during operations on the ground;
 - (d) Major defect or damage to aircraft structure;
 - (e) Defects or damage to aircraft structures, if more than allowed tolerances.
- (iii) Powerplant
 - (a) Uncommanded loss of thrust/power, shutdown or failure of any engine;
 - (b) Uncontained failure of engine compressor, turbines;
 - (c) Inability to feather or un-feather a propeller.
- (iv) Aircraft Systems or Equipment
 - (a) Fire or explosion;
 - (b) Smoke, toxic or noxious fumes in the aircraft;
 - (c) Fuel leakage that results in substantial loss, or is a fire hazard;
 - (d) Fuel system malfunction that has significant effect on fuel supply and/or distribution;
 - (e) Fire warnings, except those immediately confirmed as false;
 - (f) Unwanted landing gear or gear doors extension/retraction;
 - (g) Significant loss of braking action.
- (v) If applicable, additional requirements of the Authority.

Table 4.5—ETOPS/EDTO Maintenance Requirements for Twin Turbine Engine Aircraft

The Operator shall ensure the following for twin turbine engine aircraft that are utilized for ETOPS/EDTO:

- (i) The titles and numbers of all airworthiness modifications, additions and changes that were made to qualify aircraft systems for ETOPS/EDTO are provided to the Authority;
- (ii) Any changes to maintenance and training procedures, practices or limitations established in the qualification for ETOPS/EDTO are approved by the Authority before being adopted;
- (iii) A reliability monitoring and reporting program is developed and implemented prior to approval and continued after approval (i.e. new aircraft type);
- (iv) Prompt implementation of required modifications and inspections that could affect propulsion system reliability;
- (v) Procedures to prevent an aircraft from being dispatched for ETOPS/EDTO after an engine shutdown or EDTO-significant system failure on a previous flight until the cause of such failure has been positively identified and the necessary corrective action completed. Confirmation that such corrective action has been effective may, in some cases, require the successful completion of a subsequent flight prior to dispatch on an extended range operation;
- (vi) A procedure to ensure the airborne equipment will continue to be maintained at the level of performance and reliability required for ETOPS/EDTO;
- (vii) A process for monitoring in-flight shutdowns;
- (viii) A process to report uncommanded thrust changes or inability to control the engine and set a desired thrust level;
- (ix) A procedure to minimize scheduled or unscheduled maintenance during the same maintenance visit on more than one parallel or similar ETOPS/EDTO-significant system. Minimization can be accomplished by staggering maintenance tasks, performing and/or supervising maintenance by a different technician, or verifying maintenance correction actions prior to the aircraft entering an ETOPS/EDTO threshold.

Table 4.6—Aircraft Technical Log (ATL) Specifications

The Operator shall have a process to ensure all aircraft have an aircraft technical log (ATL) or approved equivalent that comprises the following elements:

- (i) Aircraft nationality and registration;
- (ii) Date;
- (iii) Place of departure;
- (iv) Place of arrival;
- (v) Time of departure;
- (vi) Time of arrival;
- (vii) Hours of flight;
- (viii) Incidents, observations, as applicable;
- (ix) Details of defects and rectifications/actions taken;
- (x) Signature or identity of the person recording the defect;
- (xi) Signature and identity of the person signing the release following maintenance. **

** The signature and identity shall: (1) be traceable to the individual making the entry; and (2) satisfy the requirements specified in the aircraft release to service procedure of the MMM (i.e. be either a handwritten or electronic signature system or company-controlled stamp identity system, as approved by the Authority).

Table 4.7–Quality Assurance Program Specifications and Control Processes

The Operator shall ensure each maintenance organization that performs maintenance for the Operator has an independent Quality Assurance Program that includes the following elements:

- (i) An internal audit/evaluation program;
- (ii) An established audit schedule that ensures all applicable regulations, requirements and technical activities described within the MPM of the AMO are checked on established intervals, as described in the MPM;
- (iii) A record of audit findings and corrective and/or preventive actions;
- (iv) Follow-up procedures to ensure necessary corrective/preventive actions (both immediate and long-term) implemented by the Maintenance Organization are effective;
- (v) A record-keeping system to ensure details of evaluation findings, corrective actions, preventive actions and follow-up are recorded, and that the records are retained for two complete evaluation cycles.

Table 4.8–ESD Program Specifications

The Operator shall ensure each maintenance organization that performs maintenance on electrostatic sensitive devices (ESD) for the Operator has an ESD Program that addresses the following:

- (i) Appropriate warning and caution signs, as well as decals, are placed in areas where ESDs are handled;
- (ii) Devices contained in ESD-approved packaging are sealed and properly labeled;
- (iii) Devices not contained in ESD-approved sealed packaging are handled by personnel using, as applicable, approved earthing (i.e. grounding) straps and/or conductive desk mats, and:
 - (a) For maintenance activities that require floor grids where ESDs are handled, the floor grids are grounded;
 - (b) ESDs are not stored on shelving covered with carpet, foam, vinyl or any other material that can store or produce an electrical charge;
 - (c) Straps and earthing mats are tested to ensure conductivity at regular intervals or prior to use and such test results are recorded.

Table 4.9—Maintenance Procedures Manual Content Specifications

The Operator shall ensure each maintenance organization that performs maintenance for the Operator provides for the use and guidance of relevant maintenance personnel a Maintenance Procedures Manual (MPM), which may be issued in separate parts, that contains the following information:

- (i) A brief description of the organization that includes:
 - (a) A general description of the scope of work authorized under the organization's terms of approval;
 - (b) A general description of the organization's facilities.
- (ii) A description of the organization procedures and quality or inspection system;
- (iii) Names and duties of the responsible personnel;
- (iv) Names and duties of the person or persons whose responsibilities are to ensure that maintenance is carried out in accordance with the MPM;
- (v) A description of the procedures used to establish the competence of maintenance personnel;
- (vi) A description of the methods used for the completion and retention of the Operator's maintenance records, including procedures for retaining backup records;
- (vii) A description of the procedure for preparing the maintenance release and the circumstances under which the release is to be signed;
- (viii) The process for authorizing personnel to sign the maintenance release and the scope of their authorization;
- (ix) A description of any additional procedures for complying with the Operator's maintenance procedures and requirements;
- (x) A description of the procedures for complying with the service information reporting requirements;
- (xi) A description of the procedure for receiving, amending and distributing within the maintenance organization, all necessary airworthiness data from the type certificate holder or aircraft Type Design Organization.

△

Table 4.10—Tooling and Calibration Program Specifications

The Operator shall ensure each maintenance organization that performs maintenance for the Operator has procedures to control and document the calibration and records of all tools, including personnel-owned tools, and preventing out-of-service and due-for-calibration tools and equipment from being used. The procedures shall include the following elements:

- (i) Calibration date;
- (ii) Identity of individual or vendor that performed calibration or check;
- (iii) Calibration due date;
- (iv) A calibration certificate for each item calibrated by an outside agency;
- (v) Details of adjustments and repairs;
- (vi) Repair history of the tool;
- (vii) The part number and serial number of the standard used to perform the calibration.



Table 4.11—Required Aircraft Systems and Equipment

As specified in [MNT 1.9.1](#), aircraft in the Operator's fleet shall be equipped with, in accordance with conditions of applicability, the systems and equipment specified in this table. Where referenced, refer to guidance material in [Table 4.12](#) or [Table 4.13](#).

	Equipment	Applicability	Requirement	Notes
(i)	Quick-donning oxygen mask	Aircraft operated at flight altitudes above 25000 feet.	A quick-donning oxygen mask for each flight crew member.	
(ii)	Dangerous loss of pressurization device	Aircraft intended to be operated at flight altitudes above 25000 feet for which the individual certificate of airworthiness is first issued on or after 1 July 1962.	A device that provides positive warning to the pilot of any dangerous loss of pressurization.	
(iii)	Protective Breathing Equipment (PBE)	All aircraft.	A PBE that: (a) Protects the eyes, nose and mouth of each crew member while on flight duty; provides oxygen for a period of not less than 15 minutes. (b) Allows the flight crew to communicate using the aircraft radio equipment and to communicate by interphone with each other while at their assigned duty stations.	Note: The specifications for PBE shall be satisfied by equipment that protects the eyes, nose and mouth (e.g. smoke hood, full face oxygen mask or combination of smoke goggles and oxygen mask) and has an oxygen supply that is portable or provided by the aircraft supplemental oxygen system. Note: PBE intended for flight crew use shall be conveniently located on the flight deck and be easily accessible for immediate use by each required flight crew at their assigned duty station.
		Passenger aircraft operated with cabin crew	(c) A unit of PBE located in the cabin adjacent to each required cabin crew station.	
		Passenger aircraft operated without cabin crew	(d) A unit of portable PBE located in the cabin adjacent to each hand-held fire extinguisher.	

Table 4.11—Required Aircraft Systems and Equipment

		Cargo aircraft and passenger aircraft operated without cabin crew	(e) An additional unit of portable PBE located adjacent to the flight deck hand-held fire extinguisher.	
		Cargo aircraft with a cargo compartment accessible to crew member in flight.	(f) An additional unit of portable PBE located outside but adjacent to the entrance of the accessible cargo compartment.	
		Cargo aircraft with a hand-held fire extinguisher in a supernumerary compartment.	(g) An additional unit of portable PBE located adjacent to the hand-held fire extinguisher.	
(iv)	Hand-held fire extinguishers	All aircraft.	(a) A minimum of one hand-held fire extinguisher located on the flight deck.	Note: Hand-held fire extinguishers shall be of a type that will minimize the hazard of toxic gas concentration.
		Passenger aircraft	(b) Hand-held fire extinguishers uniformly distributed throughout the cabin of passenger aircraft (when two or more extinguishers are required) to be readily accessible at each galley not located on a main passenger deck and, if applicable, to be available for use in each cargo compartment that is accessible to the crew. (GM) See Table 4.12 (iv)	
(v)	Crash axe or crowbar	All aircraft.	A minimum of one crash axe or crowbar located on the flight deck and/or the passenger cabin. (GM) See Table 4.12 (v)	Note: Unless constrained by certification or security requirements of the Authority and/or State.
(vi)	Flashlight (torch)	All aircraft intended to be operated at night.	A flashlight (torch) at each flight crew station. (GM) See Table 4.12 (vi)	

Table 4.11—Required Aircraft Systems and Equipment

(vii)	Emergency Locator Transmitters (ELTs)	Aircraft with more than 19 passenger seats.	One automatic ELT or two ELTs of any type	
		Aircraft with more than 19 passenger seats for which the individual certificate of airworthiness was first issued on or after 1 July 2008.	At least two ELTs, one of which shall be automatic; Or At least one ELT and a capability for autonomously transmitting position information at least once every minute, when in distress.	
		Aircraft with 19 or less passenger seats	One ELT of any type.	
		Aircraft with 19 or less passenger seats for which the individual certificate of airworthiness was first issued after 1 July 2008.	One automatic ELT	
(viii)	Underwater Locator Beacon (ULB) attached to aircraft fuselage	Aircraft applicability as defined by the State.	ULB installation in accordance with requirements of the State.	
(ix)	Underwater Locator Beacon (ULB) attached to non-deployable FDR container	Aircraft applicability as defined by the State.	ULB installation in accordance with requirements of the State.	
(x)	Airborne Collision Avoidance System II (ACAS II)	All aircraft.	An ACAS II. (GM) See Table 4.12 (x)	Note: Such system shall utilize a software version approved or accepted by the applicable authorities as appropriate for the airspace or area of operation.
(xi)	Airborne weather radar system	All aircraft.	An airborne weather radar system capable of detecting thunderstorms and other potentially hazardous weather conditions when operating in areas where such weather conditions could be expected to exist along the route either at night or under instrument meteorological conditions.	

Table 4.11—Required Aircraft Systems and Equipment

(xii)	Ground Proximity Warning System (GPWS)	All aircraft.	<p>A GPWS that:</p> <ul style="list-style-type: none"> (a) Automatically provides a warning to the flight crew when the aircraft is in close proximity to the earth's surface; and (b) Has a forward-looking terrain-avoidance function. <p>(GM) See Table 4.12 (xii)</p>	
(xiii)	Flight Data Recorder (FDR)	All aircraft.	<p>A digital FDR that</p> <ul style="list-style-type: none"> (a) Utilizes solid state digital recording; (b) Is capable of recording, as a minimum, the last 25 hours of aircraft operation; (c) Records time, altitude, airspeed, normal acceleration and heading; (d) Is of a type that is in accordance with requirements of the Authority. 	
(xiv)	Cockpit Voice Recorder (CVR)	All aircraft for which the individual certificate of airworthiness was first issued on or after 1 January 1987	A CVR capable of retaining the information recorded during at least the last 30 minutes of their operation.	Note: The CVR must not utilize magnetic tape or wire.
		All aircraft for which the individual certificate of airworthiness was first issued on or after 1 January 2003	A CVR capable of retaining the information recorded during at least the last two hours of its operation.	
(xv)	Data Link Recorder (DLR)	Aircraft utilizing datalink communications, for which the individual certificate of airworthiness was first issued after 1 Jan 2016.	A DLR that records all data link messages and is integrated with an FDR, CVR or with a combination FDR/CVR unit.	▲ An operator may conform to Table 4.11 (xv) through Active Implementation as long as the implementation Action Plan (IAP) projects conformance on or before 31 August 2022.

Table 4.11—Required Aircraft Systems and Equipment

(xvi)	First aid kits	All aircraft.	One or more first aid kits located to be readily accessible for use by the flight crew and, if applicable, supernumeraries. (GM) See Table 4.13 .	Note: This specification is applicable to commercial and/or non-commercial operations
		Passenger aircraft	First aid kits distributed as evenly as practicable throughout the cabin to be readily accessible for use by crew members in the cabin. (GM) See Table 4.13	
(xvii)	Seats and associated restraint devices	All aircraft.	Flight crew seats fitted with a safety harness for each flight crew member. (GM) See Table 4.12 (xvii)	Note: This specification is applicable to commercial and/or non-commercial operations
		Passenger aircraft	A seat (or berth) for each person over a specific age as determined by the State, with each seat (or berth) fitted with a safety harness, seat belt or restraining device. (GM) See Table 4.12 (xvii)	
		Aircraft that transport supernumeraries	A seat fitted with a seat belt (or safety harness) for each supernumerary. (GM) See Table 4.12 (xvii)	
(xviii)	Cabin crew seats	Passenger aircraft operated with cabin crew.	Forward or rearward facing seats at each emergency evacuation station for use by cabin crew members. Such seats are located near floor level exits and fitted with a safety harness.	

Table 4.11—Required Aircraft Systems and Equipment

(xix)	Megaphones	Passenger aircraft operated with cabin crew.	<p>(a) Portable battery-operated megaphones, stowed in a manner to be readily accessible for use by crew members.</p> <p>(b) One megaphone for aircraft with 60 to 100 passenger seats;</p> <p>(c) Two megaphones for aircraft with more than 100 passenger seats.</p> <p>(GM) Table 4.12 (xix)</p>	
(xx)	Life jacket or equivalent individual flotation device	Aircraft utilized for over-water flights with or without cabin crew.	<p>A minimum of one life jacket or equivalent individual flotation device for each person on board, with each life jacket or flotation device fitted with a means for electric illumination and stowed for easy accessibility from individual seating positions.</p> <p>(GM) See Table 4.12 (xx)</p>	
(xxi)	Lifesaving rafts	Aircraft utilized for long-range over-water flights.	<p>Lifesaving rafts with sufficient capacity to accommodate all persons on board, with each raft stowed in a manner to facilitate ready use during a ditching emergency. Lifesaving rafts contain:</p> <p>(a) Life-sustaining equipment as appropriate to the flight to be undertaken;</p> <p>(b) Equipment for making pyrotechnical distress signals.</p>	Note: <i>This specification is applicable to all aircraft, except cargo aircraft that have been granted a specific exemption by the Authority.</i>
(xxii)	Signaling devices and lifesaving equipment	Aircraft utilized for flights across land areas that have been designated by the state(s) concerned as areas in which search and rescue would be especially difficult.	Equipped with signaling devices and lifesaving equipment (including, means of sustaining life) in accordance with requirements of the applicable state(s).	

Table 4.11–Required Aircraft Systems and Equipment

(xxiii)	Fire suppression system	Passenger aircraft with a cargo compartment that is accessible to crew member in flight.	Such compartments are equipped with, as applicable, either: (a) A built-in cargo compartment fire suppression system, or (b) A portable fire suppression system is available for use in such compartments by a crew member. (GM) Table 4.12 (xxiii)	
		Aircraft that have a cargo compartment not accessible to a crew member in flight, for which the application for certification was submitted on or after 2 March 2004.	Each cargo compartment is equipped with a built-in fire detection system and a built-in fire starvation or suppression system. (GM) See Table 4.12 (xxiii)	
(xxiv)	Cargo restraint system	All aircraft transporting cargo.	A cargo restraint system, which may include barriers, ULDs, nets, straps, chains, tie-downs and/or floor locks that prevent cargo from shifting and: (a) Blocking or reducing access to emergency exits; (b) Obstructing the flow of required fire retardants; (c) Interfering with design features of the aircraft critical to the safety of flight (e.g. flight controls).	

Table 4.11—Required Aircraft Systems and Equipment

(xxv)	Humane killer device, (if carried on board).	On cargo aircraft utilized in the transport of livestock, if humane killer device is carried on board.	Humane killer device stowed in a secure manner with only controlled access during flight.	
(xxvi)	Flight deck door	<p>Aircraft utilized for passenger flights with:</p> <ul style="list-style-type: none"> • A maximum certificated takeoff mass in excess of 54 500 kg, or • Of a maximum certificated takeoff mass in excess of 45 500 kg and with a passenger seating capacity greater than 19, or • With a passenger seating capacity greater than 60. 	<p>An approved flight deck door that:</p> <p>(a) Is designed to resist penetration by small arms fire, grenade shrapnel or forcible intrusions by unauthorized persons.</p> <p>(b) Is capable of being locked and unlocked from either pilot station</p> <p>(c) Has the means for monitoring, from either pilot's station, the entire door area outside the flight crew compartment to identify persons requesting entry and to detect suspicious behavior or potential threat</p> <p>(d) Has the means by which cabin crew members or other authorized persons can notify the flight crew in the event of suspicious activity or a security breach.</p> <p>(GM) See Table 4.12 (xxvi)</p>	<p>Note: A smoke barrier or curtain is not acceptable for addressing this specification for a flight deck door.</p>
(xxvii)	Cabin emergency escape path marking system	Aircraft utilized for passenger flights with or without cabin crew, and with more than 9 passenger seats for which the individual certificate of airworthiness was first issued after 1 January 1958	<p>A system that enables visual identification of the emergency escape paths and exits in darkness and conditions of reduced visibility.</p> <p>(GM) See Table 4.12 (xxvii)</p>	

Table 4.11—Required Aircraft Systems and Equipment

(xxviii)	Smoke detection system in lavatories	Aircraft utilized for passenger flights with or without cabin crew, and with 10 or more passenger seats.	A smoke detection system in the lavatories. (GM) See Table 4.12 (xxviii)	
(xxix)	Built in fire extinguisher in lavatories	Aircraft utilized for passenger flights with or without cabin crew, with 20 or more passenger seats, and for which the application for certification was submitted on or after 2 March 2004.	A built-in fire extinguisher system for each lavatory receptacle intended for the disposal of towels, paper or waste. (GM) See Table 4.12 (xxix)	



Table 4.12—Guidance Material: Required Aircraft Systems and Equipment

(i)–(iii)	(Intentionally open)			
(iv)	<p>The requirements for hand-held fire extinguishers in this specification are applicable only to areas of the aircraft other than the flight deck. Specific requirements for the flight deck are found in Table 4.11 (iv) (a).</p> <p>The minimum number of hand-held fire extinguishers required for passenger aircraft is determined by the Authority and is typically based on the number of passengers the aircraft is authorized to carry.</p> <p>The following list provides the typical minimum numbers of hand-held fire extinguishers based on aircraft passenger seats:</p>			
	Seats installed	Number of fire extinguishers	Seats installed	Number of fire extinguishers
	7 to 30	One (1)	301 to 400	Five (5)
	31 to 60	Two (2)	401 to 500	Six (6)
	61 to 200	Three (3)	501 to 600	Seven (7)
	201 to 300	Four (4)	601 or more	Eight (8)
(v)	<p>The intent of this specification is to ensure crash axes and/or crowbars are installed in accordance with:</p> <ul style="list-style-type: none"> • Applicable certification requirements (e.g. aircraft type certification or for issuance of the Air Operator Certificate); • Applicable security requirements. 			
(vi)	<p>This specification is normally satisfied by the installation of a fixed light or torch attached to the aircraft structure, such as a “Grimes Light.”</p> <p>Operators wishing to utilize flight crew member flashlights to conform to the specifications of this specification need to demonstrate the means of ensuring the carriage, accessibility and serviceability of such flashlights.</p>			
(vii–ix)	(Intentionally open)			
(x)	<p>It is important to note that this specification does not refer to a specific ACAS II software version and that technical requirements related to the required ACAS software version vary widely and may be based on one or more of the following criteria:</p> <ul style="list-style-type: none"> • Date of issue of an aircraft's individual certificate of airworthiness; • Deadline for initial equipage or retrofit set by an applicable Authority; • Area(s) of operation, including operations over the high seas or under the jurisdiction of an authority other than the Authority of the operator; • Type of airspace (e.g. RVSM). <p>Technical guidance for the operational requirements applicable to ACAS II is contained in one or more of the following documents as relevant to the operations conducted by the operator:</p> <ul style="list-style-type: none"> • ICAO Annex 10, Volume IV; • FAA InFO (Information for Operators) 12010 dated 06/26/12; • FAA Booklet “Introduction to TCAS II Version 7.1” dated 02/28/11; • FAA Advisory Circular AC 120-55C (Air Carrier Operational Approval and Use of TCAS II) dated 03/18/13; <p>Commission Regulation (EU) No 1332/2011 of 16 December 2011 – “Laying down common airspace usage requirements and operating procedures for airborne collision avoidance.”</p>			
(xi)	(Intentionally open)			

Table 4.12—Guidance Material: Required Aircraft Systems and Equipment

(xii)	<p>A GPWS provides a warning when it senses the aircraft is in close proximity to the earth's surface and not in the landing configuration, which typically means the landing gear is not down and locked, and/or the flaps are not in a landing position.</p> <p>Different systems are available and acceptable as a GPWS with a forward-looking terrain avoidance (FLTA) function, as specified in item ii) of this specification. The following guidance is an overview only; it is not to be construed as technical specifications for an acceptable system.</p> <p>A GPWS with a FLTA function could also be known as a predictive terrain awareness and warning system (TAWS), and provides:</p> <ul style="list-style-type: none"> • A forward-looking capability and terrain clearance floor; • The flight crew, by means of visual and aural signals, and a terrain awareness display, with an alerting time necessary to prevent controlled flight into terrain events. <p>An acceptable system provides a forward-looking capability and terrain clearance floor protection in areas of operations and surrounding airports of intended use. Such systems generally have:</p> <ul style="list-style-type: none"> • A navigation system that provides accurate aircraft position (e.g. GPS or equivalent); • A means of displaying aircraft and terrain information; • A means of providing visual and aural signals; • A terrain database(s) for all areas of potential operations and surrounding airports of intended use. <p>If an obstacle database is commercially available and obstacle detection/display functionality is installed, an obstacle database for all areas of potential operations.</p>
(xiii)–(xvi)	(Intentionally open)
(xvii)	The safety harness typically incorporates a device that will automatically restrain the occupant's torso in the event of rapid deceleration.
(xviii)	(Intentionally open)
(xix)	If located in overhead bins or other cabin compartments, megaphones, in order to be readily accessible, would be kept free from and/or not covered by cabin baggage, cabin supplies or other items.
(xx)	<p>Refer to the IRM for the definition of Over-water Flights.</p> <p>Seat cushions that are designed to float may be considered individual flotation devices.</p> <p>State regulations might permit baby survival cots or infant life jackets to be stowed together in one or more common cabin locations (e.g. in a bustle or doghouse) on passenger aircraft.</p> <p>Under such circumstances, an operator would typically have procedures to ensure such items are handed to the parents of infants when required.</p>
(xxi)–(xxii)	(Intentionally open)
(xxiii)	<p>This specification is applicable to passenger aircraft only and is intended to ensure a means of fire suppression in cargo compartments accessible to crew members.</p> <p>For the purposes of this specification, “in flight” is defined as the period that starts the moment the aircraft is ready to move for the purpose of taking off and ends the moment it finally comes to rest at the end of the flight and the engine(s) are shut down.</p> <p>Ideally, the fire detection system and fire starvation or suppression system as specified in this standard would be designed to account for a sudden and extensive fire that could be caused by an explosive or incendiary device, or by dangerous goods.</p> <p>Refer to the guidance associated with FLT 1.12.2 for the hazards relevant to the conduct of aircraft operations that are typically addressed as part of a safety risk assessment and mitigation program.</p>

Table 4.12—Guidance Material: Required Aircraft Systems and Equipment

	For the purposes of this specification, “in flight” is defined as the period that starts the moment the aircraft is ready to move for the purpose of taking off and ends the moment it finally comes to rest at the end of the flight and the engine(s) are shut down.
(xxiv)–(xxv)	(Intentionally open)
(xxvi)	<p>Item (b): The design of the reinforced flight deck door typically takes into account safety requirements, such as decompression panels, emergency exit capability for the flight crew and emergency access for rescuers. Also, a secondary locking device, such as a deadbolt or cross bar, is installed in case the automated locking device is defective.</p> <p>The aircraft MEL would contain any restrictions pertinent to use of the door in line operations, including, if applicable, a secondary locking system.</p> <p>Item (d): This specification requires a system or device(s) for use by the cabin crew or other authorized persons to notify the flight crew of any security compromise in the cabin.</p>
(xxvii)	An escape path marking system typically consists of any type of illumination that is designed to facilitate the evacuation of the aircraft.
(xxviii)	In certain regulatory jurisdictions there is typically a requirement for the lavatory smoke detection system to provide a warning that can be readily detected by the flight and/or cabin crew.
(xxix)	In certain regulatory jurisdictions there is typically a requirement for the fire extinguisher to discharge automatically into each lavatory waste receptacle in the event of a fire.

Table 4.13—Guidance Material: First Aid Kits

The minimum number of first aid kits required for passenger aircraft is determined by the Authority and is typically based on the number of passengers the aircraft is authorized to carry.

The following list provides typical minimum numbers of cabin first aid kits based on passenger seats:

Seats installed	Number of first aid kits	Seats installed	Number of first aid kits
100 or fewer	One (1)	301 to 400	Four (4)
101 to 200	Two (2)	401 to 500	Five (5)
201 to 300	Three (3)	501 or more	Six (6)

The contents of an aircraft first aid kit would typically include:

- List of kit contents;
- Antiseptic swabs (10/packs);
- Bandage, adhesive strips;
- Bandage, gauze 7.5 cm × 4.5 m;
- Bandage, triangular 100 cm folded and safety pins;
- Dressing, burn 10 cm × 10 cm;
- Dressing, compress, sterile 7.5 cm × 12 cm approx.;
- Dressing, gauze, sterile 10.4 cm × 10.4 cm approx.;
- Adhesive tape, 2.5 cm (roll);
- Skin closure strips;
- Hand cleanser or cleansing towelettes;
- Pad with shield or tape for eye;
- Scissors, 10 cm (if permitted by applicable regulations);
- Adhesive tape, surgical 1.2 cm × 4.6 m;
- Tweezers, splinter;
- Disposable gloves (several pairs);
- Thermometers (non-mercury);
- Resuscitation mask with one-way valve;
- First aid manual (an operator may decide to have one manual per aircraft in an easily accessible location);
- Incident record form.

△ **Note:** First aid kit does not normally include ammonia inhalants.

If permitted by applicable regulations, first aid kits could include the following medications:

- Mild to moderate analgesic;
- Antiemetic;
- Nasal decongestant;
- Antacid;
- Antihistaminic;
- Antidiarrheal.

In states where regulations do not allow any medications in the first aid kit, affected operators may carry an extra kit containing the above medications to be used passively (i.e. only given to a passenger on specific request by the passenger).

Table 4.14—Recommended Aircraft Systems and Equipment

Aircraft in the Operator's fleet *should* be equipped with, in accordance with conditions of applicability, the systems and equipment specified in this table. Where referenced, refer to guidance material in [Table 4.15](#).

	Equipment	Applicability	Requirement	Notes
△ (i)	(Intentionally open)			
△ (ii)	Airborne Collision Avoidance System II (ACAS II)	All aircraft.	Equipped with an ACAS II utilizing software version 7.1. (GM) See Table 4.15 (ii)	
(iii)	Forward-looking wind shear warning system	All aircraft.	Equipped with a forward-looking wind shear warning system	
(iv)	Flight deck door	All aircraft utilized for passenger flights.	Equipped, where practicable, with an approved flight deck door that is: (a) Capable of being locked and unlocked from either pilot station; (b) Designed to resist penetration by small arms fire, grenade shrapnel or forcible intrusions by unauthorized persons.	



Table 4.15—Guidance Material: Recommended Aircraft Systems and Equipment

(i)	(Intentionally open)
(ii)	The intent of this specification is to encourage the earliest practicable deployment of ACAS II with software version 7.1. It is recognized, however, that ACAS software version requirements vary widely based on the criteria contained in the Guidance Material found in Table 4.12 (vii).

INTENTIONALLY LEFT BLANK

Section 5 — Cabin Operations (CAB)

Applicability

Section 5 addresses the safety and security requirements associated with the aircraft passenger cabin. All standards and recommended practices (ISARPs) in this section are applicable to an operator that conducts passenger flights with cabin crew.

Individual CAB provisions or sub-specifications within a CAB provision that:

- Do not begin with a conditional phrase are applicable unless determined otherwise by the Auditor.
- Begin with a conditional phrase “If the Operator...” are applicable if the Operator meets the condition(s) stated in the phrase.
- Begin with a conditional phrase “If the Operator conducts passenger flights with or without cabin crew...” are applicable if the Operator conducts passenger flights without cabin crew.

Additional ISARPs applicable to an operator that conducts passenger flights without cabin crew are located in Section 2 (FLT) of this manual.

Specifications applicable to the carriage of supernumeraries are located in Section 2 (FLT) of this manual.

Where an operator outsources the performance of cabin operations functions to external service providers, the operator retains overall responsibility for ensuring the management of safety in such operations and must demonstrate processes for monitoring applicable external service providers in accordance with CAB 1.10.2.

General Guidance

Definitions of technical terms used in this ISM Section 5, as well as the meaning of abbreviations and acronyms, are found in the IATA Reference Manual for Audit Programs (IRM).

Refer to the IATA Cabin Operations Best Practices Guide for practical information and guidance related to cabin safety policies and procedures, (<http://www.iata.org/publications/Pages/cabin-safety-guide.aspx>).

1 Management and Control

1.1 Management System Overview

1.2 Accountability, Authorities and Responsibilities

CAB 1.2.4

The Operator shall ensure the duties and responsibilities of cabin crew members are defined and described in the Operations Manual (OM). (GM)

Auditor Actions

- ☐ **Identified/Assessed** defined cabin crew member duties and responsibilities in the OM.
- ☐ **Interviewed** cabin operations manager/designated management representative(s).
- ☐ **Other Actions** (Specify)

Guidance

Refer to the IRM for the definitions of [Cabin Crew Member](#) and [Operations Manual](#).

The intent of this standard is that OM documentation describes:

- Duties and responsibilities for cabin crew members, including, if applicable, cabin crew leader;
- Chain and succession of command on board the aircraft.

1.3 Communication

CAB 1.3.2

The Operator shall have processes to ensure information relevant to cabin crew policies, procedures and responsibilities is communicated to all cabin crew members, and to ensure essential operational information or guidance is communicated to the cabin crew prior to each flight. **(GM)**

Auditor Actions

- ☐ **Identified/Assessed** process(es) for communication of information relevant policies/procedures/responsibilities to cabin crew members prior to each flight.
- ☐ **Interviewed** cabin operations manager/designated management representative(s).
- ☐ **Examined** examples of information provided to cabin crew members prior to flight.
- ☐ **Observed** line cabin operations (focus: cabin crew has received essential operational information/guidance prior to flight).
- ☐ **Other Actions** (Specify)

Guidance

Processes are in place to ensure information regarding policies, procedures and responsibilities is made available to cabin crew members on a regular and timely basis. Vehicles for communication typically include the cabin crew operations manual, operations bulletins, bulletin board notices, safety bulletins, electronic platforms, electronic computer messages, telephone calls or any other effective means.

Also, a process is in place to ensure essential information necessary for the safe conduct of a flight is communicated to the cabin crew prior to the departure of each flight or series of flights. Such process would include a means for cabin crew members to acknowledge receipt of essential information.

Written or verbal confirmation to a responsible manager that is recorded is considered an acceptable means of acknowledgement.

1.4 Provision of Resources

1.5 Documentation System

1.6 Operations Manual

CAB 1.6.5

The Operator shall ensure a minimum of one complete version of the OM as specified in [CAB 1.6.1](#) is accessible on board the aircraft for passenger flights and located in a manner that provides for:

- (i) If used directly for the conduct of cabin operations, immediate access by each cabin crew member;
- (ii) If used as a reference document only, unobstructed access by the cabin crew. **(GM)**

Auditor Actions

- ☐ **Identified/Assessed** onboard availability/access of OM to cabin crew members.
- ☐ **Interviewed** cabin operations manager/designated management representative(s).
- ☐ **Observed** line cabin operations (focus: onboard accessibility of complete version of OM).
- ☐ **Other Actions** (Specify)

Guidance

The number of complete OM's on board the aircraft would be determined by how the manual is utilized by the cabin crew. If the complete version of the OM is used directly for the conduct of cabin operations, it might be necessary to have more than one copy on board, depending on the size of the aircraft and the number of cabin crew members.



If a practical manual (or QRH) is used by the cabin crew for the conduct of cabin operations, a minimum of one complete version of the OM would typically be on board the aircraft for use as a reference document. The flight deck is an acceptable location for the OM as a reference document if measures are in place that provide for unobstructed access by the cabin crew.

If electronically accessed manuals are provided on board the aircraft, one or more access terminals or devices would be located so the cabin crew has immediate or unobstructed access, as applicable to the way the manual is utilized, the size of the aircraft, and the number of cabin crew members. In addition, it is recommended that operators give consideration to providing applicable backup physical (paper) manuals in case of electronic manual malfunction.

CAB 1.6.7

If the Operator publishes a practical manual for use by the cabin crew in the performance of cabin operations duties, the Operator shall ensure one or more copies of the up-to-date practical manual are on board the aircraft for passenger flights and located in a manner that provides for immediate access by each cabin crew member. **(GM)**

Auditor Actions

- ☐ **Identified/Assessed** onboard availability/access of practical manual to cabin crew members.
- ☐ **Interviewed** cabin operations manager/designated management representative(s).
- ☐ **Examined** practical manual used by cabin crew members.
- ☐ **Observed** line cabin operations (if applicable) (focus: one or more copies of up-to-date practical manual on board; cabin crew has immediate access to practical manual).
- ☐ **Other Actions** (Specify)

Guidance

Refer to the IRM for the definition of [Practical Manual](#).

A practical manual (or QRH) is typically required to be in the possession of each individual cabin crew member, available at each cabin crew station, or otherwise located to ensure immediate access by each cabin crew member.

1.7 Records System

1.8 (Intentionally open)

1.9 Quality Assurance Program

1.10 Quality Control of Outsourced Operations and Products

1.11 Safety Management

Risk Management

CAB 1.11.1

The Operator shall have a hazard identification program in the cabin operations organization that includes:

- (i) A combination of reactive and proactive methods for hazard identification;
- (ii) Processes for safety data analysis that identify existing hazards, and may predict future hazards, to aircraft operations. **[SMS] (GM) ◀**

Auditor Actions

- ☐ **Identified/Assessed** safety hazard identification program in cabin operations (focus: program identifies hazards to aircraft operations; describes/defines method(s) of safety data collection/analysis).
- ☐ **Identified/Assessed** role of cabin operations in the organization-wide, cross-discipline safety hazard identification program (focus: participation with other operational disciplines).

- ☐ **Interviewed** responsible manager(s) in cabin operations.
- ☐ **Interviewed** person(s) that perform analysis of cabin operational data for the purpose of identifying hazards.
- ☐ **Examined** examples of hazards to aircraft operations that have been identified through data collection and analysis in cabin operations.
- ☐ **Other Action** (Specify)

Guidance

Refer to the IRM for the definitions of [Hazard \(Aircraft Operations\)](#), [Risk Management](#) and [Safety Risk](#).

Hazard identification is an element of the Safety Risk Management component of the SMS framework.

Refer to Guidance associated with [ORG 3.1.1](#) located in ISM Section 1.

CAB 1.11.2

The Operator shall have a safety risk assessment and mitigation program in the cabin operations organization that specifies processes to ensure:

- (i) Hazards are analyzed to determine corresponding safety risks to aircraft operations;
- (ii) Safety risks are assessed to determine the requirement for risk mitigation action(s);
- (iii) When required, risk mitigation actions are developed and implemented in cabin operations.

[SMS] [Eff] (GM) ◀

Assessment Tool

Desired Outcome

The Operator maintains an overview of its cabin operations risks and through implementation of mitigation actions, as applicable, ensures risks are at an acceptable level.

Suitability Criteria (Suitable to the size, complexity and nature of operations)

Number and type of analyzed hazards and corresponding risks.

Means used for recording risks and mitigation (control) actions.

Safety data used for the identification of hazards.

Effectiveness Criteria

- (i) All relevant cabin operations hazards are analyzed for corresponding safety risks.
- (ii) Safety risks are expressed in at least the following components:
 - Likelihood of an occurrence.
 - Severity of the consequence of an occurrence.
 - Likelihood and severity have clear criteria assigned.
- (iii) A matrix quantifies safety risk tolerability to ensure standardization and consistency in the risk assessment process which is based on clear criteria.
- (iv) Risk register(s) within the cabin operations organization capture risk assessment information, risk mitigation (control) and monitoring actions.
- (v) The risk mitigation (control) actions include time lines, allocation of responsibilities and risk control strategies such as hazard elimination, risk avoidance, risk acceptance, risk mitigation.
- (vi) Mitigation (control) actions are implemented to reduce the risk to a level of - as low as reasonably practical.
- (vii) Identified risks and mitigation actions are regularly reviewed for accuracy and relevance.
- (viii) Effectiveness of risk mitigation (control) actions are monitored at least yearly to include auditing in accordance with [ORG 3.4.1](#).
- (ix) Personnel performing risk assessments are appropriately trained in accordance with [ORG 1.6.5](#).

Auditor Actions

- ☐ **Identified/Assessed** safety risk assessment and mitigation program in cabin operations (focus: hazards analyzed to identify/define risk; risk assessed to determine appropriate action; action implemented/monitored to mitigate risk).
- ☐ **Identified/Assessed** role of cabin operations in cross-discipline safety risk assessment/mitigation program (focus: participation with other operational disciplines).
- ☐ **Interviewed** responsible manager(s) in cabin operations.
- ☐ **Interviewed** person(s) that perform safety risk assessments in cabin operations.
- ☐ **Examined** selected records/documents that illustrate risk assessment and resulting risk mitigation action(s) in cabin operations.
- ☐ **Other Action** (Specify)

Guidance

Refer to the IRM for the definition of [Safety Risk Assessment \(SRA\)](#).

Risk assessment and mitigation is an element of the Safety Risk Management component of the SMS framework.

Potential hazards typically associated within cabin operations include, but are not limited to:

- Inadvertent slide deployment;
- Smoke/fire/fumes;
- Turbulence;
- Unruly passengers;
- Cabin crew injury/incapacitation;
- Carriage of lithium batteries in the cabin;
- Inflight product and services;
- Service of hot food and beverages.

Refer to Guidance associated with [ORG 3.1.2](#) located in ISM Section 1.

Operational Reporting

CAB 1.11.3

The Operator shall have an operational safety reporting system in the cabin operations organization that:

- (i) Encourages and facilitates cabin operations personnel to submit reports that identify safety hazards, expose safety deficiencies and raise safety concerns;
- (ii) Ensures mandatory reporting in accordance with applicable regulations;
- (iii) Includes analysis and cabin operations management action to address safety issues identified through the reporting system. **[SMS] (GM) ◀**

Auditor Actions

- ☐ **Identified/Assessed** operational safety reporting system in cabin operations (focus: system urges/facilitates reporting of hazards/safety concerns; includes analysis/action to validate/address reported hazards/safety concerns).
- ☐ **Interviewed** responsible manager(s) in cabin operations.
- ☐ **Interviewed** person(s) that perform operational safety report review/analysis/follow-up in cabin operations.
- ☐ **Examined** data that confirm an effective cabin operations safety reporting system (focus: quantity of reports submitted/hazards identified).
- ☐ **Examined** records of selected cabin operations safety reports (focus: analysis/follow-up to identify and address reported hazards/safety concerns).
- ☐ **Other Actions** (Specify)

Guidance

Safety reporting is a key aspect of SMS hazard identification and risk management.

Refer to Guidance associated with [ORG 3.1.3](#) located in ISM Section 1.

Safety Performance Monitoring and Management**2 Training and Qualification****General Guidance**

Many of the provisions of this subsection contain specifications related to the recurring frequency of training and evaluation events for cabin crew members. Such provisions, with a few exceptions, define cycles or intervals for the completion of recurrent training and/or evaluation expressed in months since training was first completed or qualification was first established. It is important to note, however, that for the purpose of conformance with these provisions, such intervals are nominal and that the actual interval may vary slightly. For example, an operator may adjust the frequency of evaluations to minimize overlap, provide scheduling flexibility, preserve the original qualification date, and/or ensure evaluations are consistently completed in accordance with the nominal cycle set forth by the State and/or applicable authorities. Accommodations of this nature are commonplace and vary widely by regulatory jurisdiction. In all cases, however, the auditor will make the determination of whether or not such accommodations fit within the nominal cycles established in each provision.

2.1 Training Program**CAB 2.1.1A**

The Operator shall have a training and evaluation program that is approved or accepted by the Authority, and that ensures cabin crew members understand their responsibilities and are competent to perform the duties and functions associated with cabin operations. The cabin crew training program shall also, as a minimum, address:

- (i) Initial qualification;
- (ii) Continuing qualification;
- (iii) Re-qualification;
- (iv) If applicable, aircraft transition or conversion;
- (v) If applicable, other specialized training requirements;
- (vi) If applicable, each traditional training program requirement that is replaced by a requirement under an Advanced Qualification Program (AQP) as approved or accepted by the Authority. **(GM)**

Auditor Actions

- ☐ **Identified/Assessed** requirement for specified training/qualification courses applicable to each aircraft type in cabin crew training/evaluation program.
- ☐ **Identified/Assessed** program elements under AQP (as applicable); program has regulatory approval.
- ☐ **Interviewed** responsible manager(s) in cabin operations.
- ☐ **Examined** training/qualification course curriculum (focus: inclusion of applicable training/qualification courses).
- ☐ **Examined** training/qualification records of selected cabin crew members (focus: completion of applicable training/qualification courses).
- ☐ **Other Actions** (Specify)

Guidance

Refer to the IRM for the definitions of [Advanced Qualification Program \(AQP\)](#) and [Continuing Qualification](#).

AQP incorporates the elements and specifications contained in [CAB 2.1.1B](#), [Table 5.2](#) and [Table 5.3](#).

2.2 Program Elements

General Guidance

Many of the provisions of this subsection make reference to cabin crew training conducted in accordance with an AQP that is approved or accepted by the Authority as specified in [CAB 2.1.1B](#).

If applicable, AQP allows development of proficiency-based training programs that encourage innovation in the methods and technologies used during instruction and evaluation, as well as in the efficient management of the training systems. Since these innovations may require some deviations from traditional regulations, the approved qualification standards may replace the applicable portions of the existing regulations and/or training guidance. These deviations or variances will be defined in the approved AQP documentation.

Additionally, an approved AQP Entry Level Analysis may be documented to achieve the most effective use of training resources. An Entry Level Analysis may also be utilized to identify where training is not needed or to justify alternative curriculum tracks or modules targeted at expected differences in entry background.

In an AQP, criticality and currency determination guides how and when training objectives are trained, validated or evaluated. A task factor analysis will be documented within the approved training qualification standards.

CAB 2.2.2

The Operator shall ensure cabin crew members receive training that provides knowledge of safety policies and procedures associated with the preflight, in-flight and post-flight phases of cabin operations. Such training shall be included in the cabin crew initial and requalification training courses, and in the recurrent training course on a frequency in accordance with requirements of the Authority, but not less than once every 24 months or, if applicable, in accordance with the Operator's AQP as specified in [CAB 2.1.1B](#). **(GM)**

Auditor Actions

- ☐ **Identified/Assessed** requirement for completion of preflight/in-flight/post-flight safety training for cabin crew initial/requalification/recurrent training courses.
- ☐ **Interviewed** responsible manager(s) in cabin operations.
- ☐ **Examined** curriculum/syllabus of initial/requalification/recurrent training courses for cabin crew members, including regulatory requirement for frequency of recurrent training courses.
- ☐ **Examined** training records of selected cabin crew members.
- ☐ **Other Actions** (Specify)

Guidance

Training in safety policies and procedures typically addresses:

- Crew coordination and communication;
- Sterile flight deck;
- Mandatory briefings;
- Safety checks;
- Passenger acceptance and handling;
- Cabin baggage;
- Personal electronic devices;
- Fueling with passengers on board;
- Turbulence;
- Flight and cabin crew member incapacitation;
- Flight deck access.

CAB 2.2.3

The Operator shall ensure cabin crew members receive training that provides the knowledge required to execute emergency procedures. Such training shall be included in the cabin crew initial and requalification training courses, and in the recurrent training course on a frequency in accordance with requirements of the Authority, but not less than once every 24 months or, if applicable, in accordance with the Operator's AQP as specified in [CAB 2.1.1B](#). As a minimum, training shall address emergency procedures associated with:

- (i) Cabin fires;
- (ii) Smoke and fumes;
- (iii) Emergency landing (land and water);
- (iv) Planned cabin evacuation (land and water);
- (v) Unplanned cabin evacuation (land and water);
- (vi) Medical emergencies.

Auditor Actions

- ☐ **Identified/Assessed** requirement for completion of cabin emergency procedures training in cabin crew initial/requalification/recurrent training courses.
- ☐ **Interviewed** responsible manager(s) in cabin operations.
- ☐ **Examined** curriculum/syllabus of initial/requalification/recurrent emergency procedures training courses for cabin crew members, including regulatory requirement for frequency of recurrent training courses.
- ☐ **Examined** training records of selected cabin crew members.
- ☐ **Other Actions** (Specify)

CAB 2.2.4

The Operator shall ensure cabin crew members receive training that provides the knowledge required to understand the function and operation of cabin emergency equipment and to execute associated preflight checks. Such training shall be included in the cabin crew initial and requalification training courses and in the recurrent training course, on a frequency in accordance with requirements of the Authority, but not less than once every 24 months or, if applicable, in accordance with the Operator's AQP as specified in [CAB 2.1.1B](#). **(GM)**

Auditor Actions

- ☐ **Identified/Assessed** requirement for completion of cabin emergency equipment training in cabin crew initial/requalification/recurrent training courses (focus: function/operation of equipment).
- ☐ **Interviewed** responsible manager(s) in cabin operations.
- ☐ **Examined** curriculum/syllabus of initial/requalification/recurrent emergency equipment training courses for cabin crew members, including regulatory requirement for frequency of recurrent training courses.
- ☐ **Examined** training records of selected cabin crew members.
- ☐ **Other Actions** (Specify)

Guidance

Aircraft type-training courses may include training in the use of specific emergency equipment such as slides, rafts, slide/rafts and ramp slide/rafts.

CAB 2.2.5

The Operator shall ensure cabin crew members complete practical training exercises consisting of cabin drills and hands-on operation of cabin equipment. Practical training exercises shall be included in the cabin crew initial and requalification training courses, and in the recurrent training course on a frequency in accordance with requirements of the Authority. All focus areas within the scope of practical training exercises shall be addressed in recurrent training not less than once every 36 months or, if applicable, in accordance with the Operator's AQP as specified in [CAB 2.1.1B](#). As a minimum, focus areas within the scope of practical training exercises include:

- (i) Cabin exit operations (normal and emergency) for each aircraft and exit type;
- (ii) Cabin emergency evacuation;
- (iii) If the operator utilizes aircraft equipped with cabin doors that have emergency egress slides:
 - (a) Initial training: Use of emergency egress slide(s);
 - (b) Requalification and recurrent training: Use of emergency egress slide(s) in accordance with requirements of the Authority.
- (iv) Firefighting;
- (v) Oxygen administration;
- (vi) If required, ditching. **(GM)**

Note: *If applicable, cabin crew members may complete practical training exercises through participation in event management scenarios in accordance with the Operator's AQP as specified in [CAB 2.1.1B](#).*

Auditor Actions

- ☐ **Identified/Assessed** requirement for completion of practical training exercises (cabin drills and hands-on operation of cabin equipment) in cabin crew initial/requalification/recurrent training courses.
- ☐ **Interviewed** responsible manager(s) in cabin operations.
- ☐ **Examined** curriculum/syllabus of initial/requalification/recurrent training exercises in courses for cabin crew members (focus: frequency of exercises/courses and regulatory requirement for frequency of recurrent training exercises/courses).
- ☐ **Examined** training records of selected cabin crew members.
- ☐ **Other Actions** (Specify)

Guidance

Refer to the IRM for the definition of [Wet Drill](#).

Practical training exercises to satisfy this provision typically include procedures associated with the use of cabin systems and equipment, to include the public address and intercom systems, life-rafts, life preservers, PBE/smoke hoods, as well as operation of the door(s), deployment and use of emergency egress slide(s), fighting an actual or simulated fire, operation of hand fire extinguishers, passenger briefings and in-flight decompression (group drill).

Personal electronic devices powered by rechargeable lithium-ion (LI) batteries are common in the passenger cabin. The batteries in such devices have the potential for overheating (thermal runaway), explosion and fire. An operator might consider a practical training exercise that simulates a LI battery fire in the cabin, thus requiring the cabin crew members to implement firefighting procedures appropriate for this type of fire.

Hands-on practical training exercises might involve the use of actual aircraft emergency and lifesaving equipment or might be conducted using realistic and functional simulators or mock-ups.

A requirement for a practical training exercise for ditching is determined by the State. An operator that conducts over-water and/or long-range over-water flights would typically ensure cabin crew members complete practical training exercises in ditching.





An operator might elect to include a wet drill as part of initial training as a means of providing hands-on familiarization with ditching equipment and procedures. A wet drill would require cabin crew members to go into the water and then climb into a raft, or to board a raft in the water directly from an aircraft exit (with cabin crew members not going into the water).

When utilizing the actual aircraft to conduct training in emergency exit operations, emergency operation can be simulated by disarming the exits and having the trainee accomplish all steps as though the door were armed.

Due to challenges and problems associated with using actual aircraft systems, cabin simulators or training mock-ups are typically utilized to the extent possible. If cabin exit simulators or training mock-ups are not available, practical hands-on drills are performed on board actual aircraft, which, to preclude disruption of training, would necessitate a documented program and aircraft schedule.

CAB 2.2.7

The Operator shall ensure cabin crew members receive training in dangerous goods awareness, recognition and emergency action. Such training shall be included in the cabin crew initial and re-qualification training courses and in the recurrent training course on a frequency in accordance with requirements of the Authority, but all subjects within the scope of dangerous goods training shall be addressed not less than once within the 24-month period from the previous training in dangerous goods. **(GM)**

Auditor Actions

- ☐ **Identified/Assessed** requirement for completion of dangerous goods training (awareness/recognition/emergency action) in cabin crew initial/requalification/recurrent training courses.
- ☐ **Examined** regulatory requirement for frequency of training in dangerous goods in cabin crew recurrent training.
- ☐ **Interviewed** responsible manager(s) in cabin operations.
- ☐ **Examined** curriculum/syllabus of initial/requalification/recurrent training courses for cabin crew members.
- ☐ **Examined** training records of selected cabin crew members.
- ☐ **Other Actions** (Specify)

Guidance

This provision specifies the minimum dangerous goods awareness training required for cabin crew members and is applicable to an operator regardless of whether such operator *transports or does not* transport dangerous goods.

Recurrent training in dangerous goods is completed within a validity period that expires 24 months from the previous training to ensure knowledge is current, unless a shorter period is defined by a competent authority. However, when such recurrent training is completed within the final 3 months of the 24-month validity period, the new validity period may extend from the month on which the recurrent training was completed until 24 months from the expiry month of the current validity period. If such recurrent training is completed *prior* to the final three months of the validity period, the new validity period would extend 24 months from the month the recurrent training was completed.

The curriculum for dangerous goods training for cabin crew members will typically address the following subject areas:

- General philosophy;
- Limitations;
- Labeling and marking;
- Recognition of undeclared dangerous goods;
- Provisions for passengers and crew;
- Emergency procedures.



Refer to [DGR 1.5.2](#) and [Table 1.5.A](#) for guidance that addresses dangerous goods training for crew members.

CAB 2.2.11

The Operator shall ensure cabin crew members receive training that provides knowledge in first aid and inflight medical events. Such training shall be included in the initial and re-qualification training courses and in the recurrent training course, on a frequency in accordance with requirements of the Authority, but all subjects within the scope of first aid training shall be addressed not less than once every 36 months or, if applicable, in accordance with the Operator's AQP as specified in [CAB 2.1.1B](#). As a minimum, subjects within the scope of first aid training include:

- (i) Life-threatening medical emergencies;
- (ii) Cardiopulmonary resuscitation (CPR);
- (iii) Management of injuries;
- (iv) Management of illnesses;
- (v) First-aid equipment and supplies;
- (vi) If applicable, medical equipment and supplies. **(GM)**

Auditor Actions

- ☐ **Identified/Assessed** requirement for completion of first aid training in cabin crew initial/requalification/recurrent training courses.
- ☐ **Interviewed** responsible manager(s) in cabin operations.
- ☐ **Examined** curriculum/syllabus of initial/requalification/recurrent training in first aid for cabin crew members (focus: scope/content/frequency of training, regulatory requirements for frequency of recurrent training).
- ☐ **Examined** training records of selected cabin crew members.
- ☐ **Other Actions** (Specify)

Guidance

Under an AQP, initial training may be referred to as indoctrination and qualification training. Training typically provides knowledge and skill in five subject areas appropriate for cabin crew members. Suggested subject areas are as follows:

1. Altitude physiology (working at altitude):
 - Changes in atmospheric pressure;
 - Relative hypoxia;
 - Trapped gas;
 - Decompression sickness;
 - Cabin depressurization;
 - Hyperventilation;
 - Cabin air quality.
2. Travel health:
 - Immunization;
 - Protection against infectious diseases;
 - Circadian rhythm and jet lag;
 - Fatigue management;
 - Personal safety (e.g. use of alcohol, other drugs, traffic safety).
3. Standards and regulations:
 - First aid training and equipment (ICAO standards and/or CAA regulations);
 - Reporting of communicable diseases (ICAO standards and WHO International Health Regulations);
 - Aircraft disinfection and disinsection (application of insecticide);
 - Biohazard waste disposal.

4. Procedures and resources:
 - Seeking medical advice (ground and/or in flight);
 - Medical equipment (e.g. first aid kit, medical kit, oxygen);
 - Death on board;
 - Birth on board;
 - Documentation to be completed;
 - PIC notification and communication.
5. First aid (problem recognition and management):
 - Assessing a casualty;
 - Lifesaving procedures:
 - Assess ABC (adult, child, infant);
 - Choking;
 - CPR (practical training);
 - Recovery position.
 - Medical problems:
 - The unconscious (underlying causes);
 - Suspected communicable diseases;
 - Respiratory disorders (asthma, hyperventilation, chronic lung diseases, persistent coughing);
 - Cardiovascular disorders (angina, heart attack, shock, DVT);
 - Abdominal problems (vomiting, diarrhea, pain, heartburn, bleeding);
 - Nervous system disorders (headache, seizure, stroke);
 - Ear, nose and throat problems such as barotrauma (body damage caused by pressurization difference) and/or epistaxis (nose bleed);
 - Behavioral/psychological disorders (panic attack, alcohol intoxication, irrational behavior);
 - Other problems (diabetes, allergic reaction, pregnancy related).
 - Trauma:
 - Wounds and bleeding (practical training);
 - Burns;
 - Head and neck injury;
 - Eye injury;
 - Musculoskeletal injury;
 - Chest and abdominal injury.

Initial training would typically address all the subject areas listed above.

Unless there were changes to the altitude physiology, travel health and regulations components, it would not be necessary to review these areas each year. However, in the event of changes, cabin crew members would typically be promptly advised, and such changes may then be addressed during the next recurrent training.

The procedures, resources and first aid subject areas may be addressed in recurrent training, to include testing and evaluation. Selected elements included in these subject areas would be addressed each year in recurrent training such that all elements are addressed during every 36-month period or, if applicable, in accordance with the Operator's AQP.

CPR is a lifesaving procedure that requires practice in order to maintain competence. Therefore, it is recommended that cabin crew members complete recurrent training in the most current CPR procedures on an annual basis.

It is recommended that elements chosen to be reviewed each year be built into practical scenarios. Scenario-based training is advantageous because:

- It requires the crew to function as a team;
- Scenarios might be designed to cover multiple aspects of first aid, as well as subjects from other areas, such as altitude physiology and regulations;
- It stimulates participation and improves retention.

Other training methods would also be acceptable as long as it can be reasonably established that cabin crew members have the knowledge and skills to apply first aid and lifesaving procedures at any given time.

2.3 Line Qualification

2.4 SMS Training

3 Line Operations

3.1 Cabin Crew Requirements



CAB 3.1.1

The Operator shall specify and require a minimum number of cabin crew members for each aircraft type to ensure a safe and expeditious aircraft evacuation and to perform the necessary functions in an emergency. Such minimum cabin crew specification(s) shall:



- (i) Be based on aircraft seating capacity or number of passengers carried;
- (ii) Be in accordance with minimum cabin crew requirements of the Authority;
- (iii) If the Operator has procedures for a temporary reduction of minimum cabin crew complement during a case of incapacitation or unforeseen circumstances at a stopover (layover) point where a replacement cannot be obtained, require such procedures to be approved or accepted by the Authority. **(GM)**

Auditor Actions



- ☐ **Identified/Assessed** minimum cabin crew specification(s) (focus: specifications cover each aircraft type; are based on aircraft seating capacity or number of passengers carried; are in accordance with requirements of the Authority).
- ☐ **Identified** regulatory requirement for minimum cabin crew complement for each aircraft type.
- ☐ **Interviewed** responsible manager(s) in cabin operations.
- ☐ **Examined** onboard documentation specifying minimum cabin crew requirements.
- ☐ **Observed** line cabin operations (focus: cabin crew complement in accordance with minimum cabin crew requirements).
- ☐ **Other Actions** (Specify)

Guidance

Refer to the IRM for the definitions of [State Acceptance](#) and [State Approval](#).

CAB 3.1.2

If the Operator utilizes aircraft that require more than one cabin crew member, the Operator shall ensure, for flights on such aircraft:

- (i) Designation of a suitably qualified cabin crew leader who has overall responsibility for the conduct and coordination of normal and emergency cabin procedures.
- (ii) A defined delegation of leadership duties during inflight rest periods and/or in the event of unexpected incapacitation of the cabin crew leader. **(GM)**

Auditor Actions

- ☐ **Identified/Assessed** means of designating cabin crew leaders for flights with more than one cabin crew member.
- ☐ **Interviewed** responsible manager(s) in cabin operations.
- ☐ **Examined** responsibilities cabin crew leaders.
- ☐ **Observed** line cabin operations (focus: designation of a cabin crew leader).
- ☐ **Other Actions** (Specify)

Guidance

The position of cabin crew leader might have a different title or name according to the operator (e.g. purser, lead flight attendant, senior cabin crew member or onboard leader).

Suitably qualified cabin crew leaders are normally those with a prerequisite amount of experience as an operating cabin crew member, as defined by the operator (e.g. one year of full-time experience) and who have completed cabin crew leadership training as specified in [CAB 2.2.13](#).

New operators could be required to establish alternative minimum experience requirements.

Leadership duties would normally be delegated during incapacitation or inflight rest periods to a cabin crew member who has undergone the operator's cabin crew leadership training course or, if none have had leadership training, the most experienced cabin crew member.

CAB 3.1.4A

The Operator shall have a methodology for the purpose of managing fatigue-related safety risks to ensure fatigue occurring in one flight, successive flights or accumulated over a period of time does not impair a cabin crew member's alertness and ability to perform safety-related cabin duties. Such methodology shall consist of:

- (i) Flight time, flight duty period, duty period and rest period limitations that are in accordance with the applicable prescriptive fatigue management regulations of the State, and/or,
- (ii) If applicable, the Operator's Fatigue Risk Management System (FRMS) approved or accepted by the State and established in accordance with [CAB 3.1.4B](#). **(GM)**

Auditor Actions

- ☐ **Identified/Assessed** requirements/methodology for cabin crew fatigue management and/or FRMS in accordance with regulations of the State.
- ☐ **Identified/Assessed** FRMS (if applicable) (focus: approved/accepted by State, incorporates elements as specified in [CAB 3.1.4B](#)).
- ☐ **Identified/Assessed** tracking/scheduling processes (focus: processes take into account cabin crew time/flight duty period/duty period/rest period limitations in the duty assignment of cabin crew members).
- ☐ **Interviewed** responsible manager(s) in cabin operations.
- ☐ **Interviewed** selected scheduling personnel.
- ☐ **Examined** selected cabin crew duty assignment records/rosters (focus: examples of application of cabin crew fatigue management limitations/mitigations).
- ☐ **Observed** cabin crew scheduling operations (focus: scheduling includes management of fatigue-related safety risk).
- ☐ **Other Actions** (Specify)

Guidance

Refer to the IRM for the definition of [Fatigue Risk Management System \(FRMS\)](#).

The intent of this provision is to ensure an operator establishes a methodology for the management of cabin crew member fatigue in a manner that:

- Is based upon scientific principles and knowledge;
- Is consistent with the prescriptive fatigue management and/or FRMS regulations of the State;
- Precludes fatigue from endangering safety of the flight.

Where authorized by the State, the operator may use a Fatigue Risk Management System (FRMS) in accordance with [CAB 3.1.4B](#) alone or in combination with prescriptive flight time, flight duty period, duty period and rest period limitations as the means for managing fatigue-related risks.

Guidance for the implementation of an FRMS is contained in the IATA Fatigue Management Guide for Airline Operators, and, as applicable, other reference documents approved or accepted by the State for the purpose of FRMS implementation (e.g. FAA, AC 120–103A–Fatigue Risk Management Systems for Aviation Safety).

CAB 3.1.4B

If the Operator utilizes an FRMS to manage cabin crew fatigue-related safety risks, the Operator shall incorporate scientific principles and knowledge within the FRMS, comply with any applicable requirements for managing cabin crew fatigue as established by the State or Authority and, as a minimum:

- (i) Define and document the FRMS policy;
- (ii) Incorporate risk management processes for fatigue hazard identification, risk assessment and risk mitigation;
- (iii) Develop and maintain effective FRMS safety assurance processes;
- (iv) Establish and implement effective FRMS promotion processes. **(GM)**

Auditor Actions

- ☐ **Identified/Assessed** FRMS policy/components/elements, compliance with fatigue risk management requirements of State/Authority.
- ☐ **Identified/Assessed** FRMS processes for cabin crew fatigue-related risk management data collection/analysis/hazard identification, safety risk assessment, safety risk mitigation/control.
- ☐ **Interviewed** responsible manager(s) in cabin operations.
- ☐ **Interviewed** selected personnel that perform cabin crew fatigue safety risk management functions.
- ☐ **Examined** selected examples of fatigue risk management (focus: hazard identified, risk assessed, mitigation action developed and implemented).
- ☐ **Observed** cabin crew scheduling operations (focus: scheduling includes management of fatigue-related safety risk in accordance with an approved FRMS).
- ☐ **Other Action** (Specify)

Guidance

The intent of this provision is to ensure fatigue occurring either in one flight, successive flights or accumulated over a period of time does not impair a cabin crew member's alertness and ability to safely perform safety-related cabin duties.

Where authorized by the State, the operator may use an FRMS as a means to determine that variations from prescriptive fatigue management policies demonstrate an acceptable level of safety. Guidance for the implementation of an FRMS is contained in the IATA Fatigue Management Guide for Airline Operators, and, as applicable, other reference documents approved or accepted by the State for the purpose of FRMS implementation (e.g. FAA, AC 120–103A–Fatigue Risk Management Systems for Aviation Safety).

The applicability of this provision is limited to those operations wherein fatigue is managed in accordance with the FRMS as defined in the operator's FRMS documentation. It is important to note, however, that an FRMS may be used alone or in combination with prescriptive flight time, flight duty period and rest period limitations as the means for managing fatigue related risks.

The components of an effective FRMS as specified in this provision are described in the following table.

FRMS Component	Item	Description
FRMS policy and documentation	(i)	<p>Policy:</p> <ul style="list-style-type: none"> • Defines FRMS Terms of Reference • Defines scope of FRMS operations • Identifies FRMS elements • Reflects shared responsibility • States safety objectives • Declares management commitment • Identifies lines of accountability <p>Documentation:</p> <ul style="list-style-type: none"> • Policy and objectives • Processes and procedures • Accountabilities, responsibilities and authorities • Mechanism for involvement of all stakeholders • FRMS training records • Planned and actual times worked • Outputs (findings, recommendations, actions)
Fatigue risk management processes	(ii)	<ul style="list-style-type: none"> • Fatigue hazard identification (reactive/proactive/predictive processes) • Safety risk assessment • Safety risk mitigation
FRMS safety assurance processes	(iii)	<ul style="list-style-type: none"> • FRMS performance monitoring • Operational and organizational change management • Continual FRMS improvement
FRMS promotion processes	(iv)	<ul style="list-style-type: none"> • Training programs (for management, crew members and all other involved personnel under the FRMS) • Communication plan (explains FRMS policies, procedures and responsibilities to all relevant stakeholders, and also describes communication channels)

CAB 3.1.5

The Operator shall have a process to ensure flight time, flight duty periods and rest periods for cabin crew members are recorded and retained for a minimum period of time in accordance with applicable regulations. **(GM)**

Auditor Actions

- ☐ **Identified** process for retention of duty and rest periods.
- ☐ **Interviewed** responsible manager(s) in cabin operations.
- ☐ **Examined** time limits for retention of duty and rest periods.
- ☐ **Examined** selected records of duty and rest periods.
- ☐ **Other Actions** (Specify)

Guidance

For each cabin crew member, flight/duty time records would typically consist of:

- The start, duration and end of each flight duty period;
- The start, duration and end of each duty period;
- Rest periods;
- Flight time.

If computer software is used for cabin crew planning and scheduling, the operator would ensure the software provides appropriate warnings when individual flight segments or series of flight segments are projected to exceed applicable maximum or minimum limits.

CAB 3.1.6

The Operator shall consider the following as duty time for the purpose of determining required rest periods and calculating duty time limitations for operating cabin crew members:

- (i) Entire duration of the flight;
- (ii) Pre-operating deadhead time;
- (iii) Training period(s) immediately prior to a flight;
- (iv) Administrative or office time immediately prior to a flight (for cabin crew members that serve in a management function). **(GM)**

Auditor Actions

- ☐ **Identified** the means of calculation of duty time limitations for operating cabin crew members.
- ☐ **Interviewed** responsible manager(s) in cabin operations.
- ☐ **Examined** criteria for calculating duty time and rest period limits.
- ☐ **Examined** selected records of duty times and rest periods.
- ☐ **Other Actions** (Specify)

Guidance

Refer to the IRM of the definition of [Deadheading](#).

Training periods and administrative or office time before a flight, without an intermediate rest period before flying duty, is considered continuous duty time.

The intent of this provision is to ensure an operator considers non-flight duty time that is likely to induce fatigue into the calculation of duty time limitations and the determination of required rest periods.

3.2 Cabin Crew Policies and Procedures

CAB 3.2.1

The Operator shall have procedures that specify cabin crew functions, applicable to each aircraft type, and actions to be executed during an emergency or situation requiring an emergency evacuation.

Auditor Actions

- ☐ **Identified/Assessed** procedures for emergencies and emergency evacuations.
- ☐ **Interviewed** responsible manager(s) in cabin operations.
- ☐ **Observed** line cabin operations (focus: procedures that specify cabin crew functions/actions for an emergency/emergency evacuation situation).
- ☐ **Other Actions** (Specify)

CAB 3.2.2

The Operator shall have procedures to ensure a coordinated and expeditious cabin evacuation during aircraft fueling operations with passengers embarking, on board or disembarking. As a minimum, procedures shall require:

- (i) Cabin exits are designated for rapid deplaning or emergency evacuation, and routes to such exits are unobstructed;
- (ii) The area outside designated emergency evacuation exits is unobstructed;
- (iii) One cabin crew member or other qualified person is positioned by the boarding door(s);
- (iv) Means of communication are established among cabin crew members and with passengers;
- (v) A suitable method of communication is established between qualified persons that monitor passenger safety and personnel that have responsibility for fueling operations. **(GM)**

Auditor Actions

- ☐ **Identified** the specified procedures for cabin evacuation during aircraft fueling operations with passengers embarking, on board or disembarking.
- ☐ **Interviewed** responsible manager(s) in cabin operations.
- ☐ **Observed** line cabin operations (focus: cabin crew procedures to ensure coordinate/expeditious cabin evacuation during fueling operations with passengers on board).
- ☐ **Other Actions** (Specify)

Guidance

During fueling operations with passengers on board the aircraft, the designation of exits for rapid deplaning or evacuation takes into account various factors, which would typically include:

- Aircraft type (e.g. some aircraft types might require the designation of over-wing exits for evacuation);
- Number of cabin crew members on board;
- The method being utilized for passenger boarding and/or deplaning (e.g. boarding bridge, air stairs);
- Exterior obstructions (e.g. catering vehicle) that might render an exit unusable for an emergency evacuation;
- Interior obstructions (e.g. catering trolley) that might block the route to one or more emergency evacuation exits.

Cabin crew procedures ensure a method of communication is established.

- Among cabin crew members positioned throughout the cabin for the purpose of coordination should a passenger evacuation be required (when more than one cabin crew member is required to be on board);
- Between the cabin crew and passengers (one way) for the purpose of providing instructions should a passenger evacuation be required;
- Between the cabin crew and the flight crew (when the flight crew is on board) for the purpose of ensuring notification when fueling operations are in progress and when a passenger evacuation is required;
- Between the cabin crew and the flight crew and/or ground handling personnel for the purpose of ensuring notification when fueling operations must be discontinued for any reason.

CAB 3.2.3

The Operator shall have a procedure to ensure the cabin crew verifies that:

- (i) Passenger and crew baggage in the passenger cabin is securely stowed;
- (ii) If applicable, cargo packages and/or passenger items being transported in passenger seats are properly secured. **(GM)**

Auditor Actions

- ☐ **Identified** procedure for cabin crew to verify cabin security (focus: baggage and cargo packages/passenger items are stowed or properly secured).
- ☐ **Interviewed** responsible manager(s) in cabin operations.
- ☐ **Observed** line cabin operations (focus: cabin crew procedure to verify baggage and cargo packages/passenger items are stowed or properly secured).
- ☐ **Other Actions** (Specify)

Guidance

The intent of this provision is for an operator to have a procedure for verification by the cabin crew that all baggage and, if applicable, cargo packages and/or passenger items being transported in passenger seats are stowed or properly secured.

Some operators might transport smaller cargo packages (e.g. mail, COMAT items) secured in cabin passenger seats.

Some operators might transport certain passenger items secured in cabin passenger seats. These types of items are typically large, valuable or fragile articles belonging to passengers that are not conducive to transport as checked baggage or appropriate for stowage in overhead bins/lockers (e.g. large musical instruments, certain electronic equipment, prominent trophies, works of art). Such items might thus be secured and carried in a dedicated cabin passenger seat (which might be purchased by the passenger-owner for the purpose of transporting the item). Of course, an operator would typically accept such items in the cabin only if the safety and comfort of other passengers will not be compromised.

CAB 3.2.12

If the Operator utilizes aircraft with electrical system circuit breakers that are accessible to cabin crew members, the Operator shall have procedures that specify limitations for resetting tripped circuit breakers by cabin crew members during flight. **(GM)**

Auditor Actions

- ☐ **Identified/Assessed** procedures specifying limitations for resetting tripped circuit breakers by cabin crew members during flight.
- ☐ **Interviewed** responsible manager(s) in cabin operations.
- ☐ **Interviewed** cabin crew members to confirm awareness of limitations for resetting tripped circuit breakers.
- ☐ **Other Actions** (Specify)

Guidance

Procedures and limitations with respect to resetting circuit breakers typically include:

- Authority to reset (normally from the PIC);
- Applicable type of equipment;
- Applicable conditions;
- Number of resets permitted.

3.3 Flight Deck Coordination

CAB 3.3.1

The Operator shall have a policy and associated procedures that define a sterile flight deck during critical phases of flight, to include:

- (i) A procedure for communication between the cabin crew and flight crew;
- (ii) A procedure for notification of the flight crew in the event of an emergency. **(GM)**

Auditor Actions

- ☐ **Identified/Assessed** policy and procedures that define a sterile flight deck during critical phases of flight.
- ☐ **Interviewed** responsible manager(s) in cabin operations.
- ☐ **Observed** line cabin operations (focus: policy/procedures that define sterile flight deck, address cabin-flight crew communication).
- ☐ **Other Actions** (Specify)

Guidance

Refer to the IRM for the definitions of [Critical Phase of Flight](#) and [Sterile Flight Deck](#).

The phases of flight when the operational state of the flight deck must be sterile would be defined by the operator or the State.

CAB 3.3.3

The Operator shall have procedures for communication and coordination between the cabin crew and flight crew to ensure a combined and coordinated process in addressing:

- (i) Passenger safety information;
- (ii) Cabin readiness prior to first aircraft movement, takeoff and landing;
- (iii) Arming or disarming of cabin door slides or slide rafts, if applicable;
- (iv) Preparation for and an encounter with turbulence;
- (v) Medical situations;
- (vi) Flight or cabin crew member incapacitation;
- (vii) Emergency evacuation;
- (viii) Abnormal situations;
- (ix) Emergency situations. **(GM)**

Auditor Actions

- ☐ **Identified/Assessed** procedures as specified in the standard for communication and coordination between the cabin crew and flight crew.
- ☐ **Interviewed** responsible manager(s) in cabin operations.
- ☐ **Observed** line cabin operations (focus: procedures for cabin-flight crew communication/coordination to address cabin operational situations).
- ☐ **Other Actions** (Specify)

Guidance

Refer to the IRM for the definition of [Sterile Flight Deck](#).

Communication and coordination between the flight crew and cabin crew might be verbal or non-verbal and could be included as an integral part of specific normal, abnormal and emergency procedures.

Procedures normally include a flight and cabin crew coordination briefing prior to each flight addresses relevant safety subjects (e.g. sterile flight deck, security, aircraft technical issues, flight crew incapacitation, cabin depressurization, onboard fire, emergency evacuation, forced landing or ditching.)

Appropriate communication and coordination between the flight and cabin crews ensures cabin door slides or slide rafts are armed prior to first movement of the aircraft.

CAB 3.3.4

The Operator shall have procedures to ensure the cabin crew provides notification to the flight crew when a safety-related situation has been identified. **(GM)**

Auditor Actions

- ☐ **Identified** procedures to ensure cabin crew notification to the flight crew when a safety-related situation has been identified.
- ☐ **Interviewed** responsible manager(s) in cabin operations.
- ☐ **Observed** line cabin operations (focus: cabin crew procedures for safety notifications to flight crew).
- ☐ **Other Actions** (Specify)

Guidance

Examples of safety-related situations that typically require notification to the flight deck include:

- Unruly behavior by passenger(s);
- Injury to passenger or crew member;
- Medical emergencies, use of first aid or medical equipment;
- Fire, smoke or toxic fumes in the cabin;
- Failure of any emergency system or equipment.

In general, any occurrences that could pose danger to the aircraft or its occupants would be considered reportable to the flight deck.

Procedures typically specify certain critical phases of flight during which the cabin crew is prohibited from initiating any communication to the flight crew (e.g. takeoff and landing).

3.4 Cabin Operations Policies and Procedures



CAB 3.4.2

If the Operator conducts passenger flights with or without cabin crew, the Operator shall have a policy and associated procedures for addressing passengers that exhibit unruly behavior and/or interfere with a crew member prior to or during flight. Such policy and procedures shall be in accordance with local laws and regulations, and also specify reasonable measures for ensuring passengers obey lawful commands from the PIC and/or cabin crew for the purpose of securing the safety of the aircraft, persons on board and their property. As a minimum, the policy and procedures shall address:

- (i) Identification of unruly behavior;
- (ii) Conditions under which passengers may be denied boarding, disembarked or restrained in accordance with the authority of the PIC;
- (iii) Reporting of instances of unruly behavior. **(GM)**

Auditor Actions

- ☐ **Identified/Assessed** the policy and associated procedures for addressing passengers that exhibit unruly behavior and/or interfere with a crew member prior to or during flight.
- ☐ **Interviewed** responsible manager(s) in cabin operations.
- ☐ **Observed** line cabin operations (focus: procedures for handling of unruly passengers, crew member interference).
- ☐ **Other Actions** (Specify)

Guidance

Policy and associated procedures would typically be published to ensure awareness by all applicable ground and flight personnel.

To ensure procedures are effective, guidelines are typically created to address all aspects of managing unruly behavior including prevention. For example, because of the increased effect of alcohol at altitude, guidelines would normally ensure the service of such beverages is carried out in a reasonable and responsible manner. Additionally, passengers would typically not be permitted to drink alcohol unless served by the cabin crew; the cabin crew would be attentive to identifying passengers that might be consuming their own alcohol.

Additional information may be found in the IATA Guidance on Unruly Passenger Prevention and Management (www.iata.org/cabin-safety).

4 Cabin Systems and Equipment

4.1 Preflight Inspection/Non-serviceable Equipment Reporting

CAB 4.1.1

The Operator shall have procedures to ensure the availability, accessibility and serviceability of aircraft cabin emergency systems and equipment for passenger flights. Such procedures shall include a preflight inspection of systems and equipment, which, as a minimum, shall be conducted by the cabin crew or, if applicable, by the flight crew prior to the first flight:

- (i) After a new cabin crew has assumed control of the aircraft cabin unless there is a procedure for an onboard handover briefing (e.g. during transit stops) between a departing/inbound crew and a replacement/outbound crew that includes verification of the status of emergency systems and equipment;
- (ii) After an aircraft has been left unattended by a flight crew or cabin crew for any period of time unless the Operator has a process or procedure that ensures cabin emergency systems and equipment remain undisturbed while crew members are temporarily absent from the cabin. **(GM)**

Auditor Actions

- ☐ **Identified/Assessed** procedures to ensure the availability/accessibility/serviceability of aircraft cabin emergency systems and equipment for passenger flights.
- ☐ **Interviewed** responsible manager(s) in cabin operations.
- ☐ **Observed** line cabin operations (focus: procedures for preflight inspection of cabin emergency systems/equipment).
- ☐ **Other Actions** (Specify)

Guidance

The intent of this provision is to ensure an operator has procedures for a preflight inspection of cabin emergency systems and equipment that is accomplished by either the cabin crew or, as applicable, the flight crew under the circumstances specified.

Cabin preflight inspection procedures normally define the specific conditions of the preflight checks, including:

- The systems and equipment to be checked by the cabin and/or flight crew;
- The extent of such checks required to ensure availability, accessibility and serviceability.

The check of some cabin emergency systems and equipment may be accomplished by other operational disciplines (e.g. engineering and maintenance) as defined by the operator.

In some cases, emergency systems are continually monitored by built-in test equipment that is designed to alert the crew to a fault condition.

An operator typically includes associated guidance to ensure action is taken to address a condition where equipment is discovered as faulty, missing or does not satisfy operational requirements.

Discrepancies involving cabin systems and equipment are typically documented in a cabin log book or equivalent recording medium.

The cabin unattended period as specified in item (ii) is intended to apply to short periods of time during the same continuous crew duty period (e.g. crew temporarily leaving the aircraft while maintenance procedures are performed or for aircraft immigration checks during a turnaround).

4.2 Safety Equipment Requirements

Table 5.1—Operations Manual Content Specifications

The content of the Operations Manual shall address the following areas of cabin operations:

- (i) Compliance or conformity with:
 - (a) Applicable laws, regulations and rules;
 - (b) Standard operating procedures for each phase of flight.
- (ii) Administration of first aid, to include guidelines for:
 - (a) Life threatening medical emergencies;
 - (b) Cardiopulmonary resuscitation (CPR);
 - (c) Injuries and illnesses;
 - (d) Use of medical equipment (e.g. Automatic External Defibrillator, if applicable).
- (iii) Response to emergency, abnormal, suspected security situations:
 - (a) Aircraft emergency evacuation;
 - (b) Cabin decompression, if applicable;
 - (c) Onboard fires, smoke and fumes;
 - (d) Emergency landing, ditching;
 - (e) Leakage or spillage of suspected dangerous goods;
 - (f) Suspected bomb or explosives, least risk bomb locations (specific to aircraft type);
 - (g) Cabin search;
 - (h) Hijacking or unlawful intervention.
- (iv) Use of cabin systems and equipment, to include malfunctions:
 - (a) Oxygen systems, if applicable;
 - (b) Communication systems;
 - (c) Entry and exit doors;
 - (d) Lifesaving equipment.
- (v) Dangerous goods manual or parts relevant to the cabin crew, to include:
 - (a) Dangerous goods prohibited in passenger and crew baggage;
 - (b) Information/instructions for dangerous goods permitted in passenger and crew baggage;
 - (c) Action to be taken in the event of an emergency.
- (vi) Use of emergency, survival equipment.
- (vii) Cabin crew training program:
 - (a) Abnormal and emergency situations, emergency evacuation;
 - (b) Use of emergency and lifesaving equipment;
 - (c) Lack of oxygen, loss of pressurization (as applicable);
 - (d) Other cabin crew member assignments and functions;
 - (e) Dangerous goods;
 - (f) Human performance, crew resource management (CRM).
- (viii) Limitations pertaining to flight time, flight duty periods and rest periods.

Table 5.2—Elements of an Advanced Qualification Program (AQP)

The following elements shall be included as part of an AQP as specified in [CAB 2.1.1B](#):

- (i) Training program and curricula approved or accepted by the State.
- (ii) Training and/or evaluation which is conducted to the maximum extent possible in a cabin crew environment. Qualification and continuing qualification curricula must include an event management evaluation (EME), which consists of a partial or full phase of flight scenario systematically designed to target specific technical and crew resource management (CRM) skills.
- (iii) Mandatory evaluation of CRM proficiency and substandard performance on CRM factors must be corrected by additional training. For pass/fail purposes, flight attendants must also demonstrate proficiency in an EME, which tests both technical and CRM skills together.
- (iv) Specific training for instructors and/or evaluators, together with explicit training and evaluation strategies to verify the proficiency and standardization of such personnel for crew oriented, scenario-based training and evaluation tasks.
- (v) Integrated use of cabin training equipment, including cabin procedures trainers. Operators are encouraged to utilize a suite of equipment matched on the basis of analysis to the training requirements at any given stage of a curriculum.
- (vi) Curriculum elements that are:
 - (a) Defined;
 - (b) Crew member-specific or personnel-specific;
 - (c) As applicable, aircraft-specific. (see Note 1)

Note 1: Applicable curricula must specify the make, model and series aircraft (or variant) and each crew member position or other positions to be covered by that curriculum. Positions to be covered by the program must include all flight attendant positions, instructors and evaluators and could include other positions, such as flight crew, aircraft dispatchers and other operations personnel.

- (vii) Separate curricula for indoctrination, qualification and continuing qualification.
- (viii) CRM Training/Evaluation and Data Collection (feedback) to determine program effectiveness to include:
 - (a) State-approved or -accepted Crew Resource Management (CRM) Training applicable to positions for which training is provided under the program;
 - (b) State-approved or -accepted training on and evaluation of skills and proficiency of each person being trained under the program to use their crew resource management (CRM) skills and their technical skills in an actual or simulated operations scenario. As applicable, training and evaluation is conducted via CBT and/or in an approved training device;
 - (c) Data collection procedures that will ensure the certificate holder provides information from its crew members, instructors and evaluators that will enable the State to determine whether the training and evaluations are working to accomplish the overall objectives of the curriculum;
 - (d) Performance proficiency data collection on students, instructors, and evaluators and the conduct of airline internal analysis of such information for the purpose of curriculum refinement and validation.
- (ix) Training devices and simulators used under the program are evaluated against applicable published standards and approved or accepted by the State to ensure adequacy for training/qualification performed.
- (x) Program approval to include:
 - (a) A demonstration to the Authority of how the program will provide an equivalent or superior level of safety for each curriculum item that differs from traditional training programs approved or accepted by the State.

Table 5.2—Elements of an Advanced Qualification Program (AQP)

- (b) For every requirement that is replaced by the program curriculum, a demonstration to the Authority of how the new curriculum provides an equivalent or superior level of safety for each requirement that is replaced. Each traditional training program requirement that is not specifically addressed in the program curriculum continues to apply to the Operator.
- (c) A requirement that training, qualification, or evaluation by a person who provides training by arrangement: "Training Centers" must be approved or accepted by the State.
- (xi) Records in sufficient detail to establish the training, qualification and certification of each person qualified under the program in accordance with the approved training, qualification and certification requirements.

Table 5.3—Requirements of an Advanced Qualification Program (AQP)

AQP allows development of proficiency-based training programs that encourage innovation in the methods and technologies used during instruction and evaluation, as well as efficient management of the training systems. Since these innovations may require some deviations from traditional regulations, the approved qualification standards may replace the applicable portions of the existing regulations and/or training guidance. These deviations or variances will be documented in the approved AQP documentation.

Additionally, an approved AQP Entry Level Analysis may be documented to achieve the most effective use of training resources. An Entry Level Analysis may also be utilized to identify where training is not needed or to justify alternative curriculum tracks or modules targeted at expected differences in entry background.

In an AQP, criticality and currency determination guides how and when training objectives are trained, validated or evaluated. A task factor analysis will be documented within the approved training qualification standards.

The specifications in this table apply to an AQP as specified in [CAB 2.1.1B](#), and are in addition to those delineated in [Table 5.2](#):

(i) Proficiency Objectives

The Operator shall conduct a job task analysis beginning with the development of a comprehensive task listing for each duty position. The task listing covers the full range of conditions and contingencies - internal to the aircraft, external to the aircraft, normal, abnormal, and emergency - to which the cabin crew could be exposed within the Operator's sphere of operations. Proficiency objectives are then extracted from the task and subtask analysis, respectively, for each duty position, and include identification of applicable performance, standards, and conditions. The documentation of proficiency objectives also identifies the references used, respectively, in defining performance, standards, and conditions for each.

An operator may elect to categorize certain proficiency objectives as currency items. Currency items refer to activities on which proficiency is maintained by virtue of frequent exercise during routine operations. Such items do not need to be addressed for training or proficiency evaluation purposes in periodic training sessions. However, verification is required that proficiency on such items is being maintained. Such verification might be obtained during line checks.

An operator could also elect to categorize proficiency objectives, including currency items, as critical or non-critical, based on operational significance and the consequences of error. This categorization is employed to determine the time interval within which training and evaluation on such items must occur for continuing qualification curricula. Critical proficiency objectives are trained and evaluated during an evaluation period the initial duration of which cannot exceed thirteen months. Each such evaluation period includes at least one training session. Non-critical terminal proficiency objectives may be distributed over a continuing qualification cycle the initial duration of which cannot exceed twenty-six months.

(ii) Continuing Qualification Cycles and Evaluation Periods

After initial qualification, which incorporates training and evaluation on all proficiency objectives, follow-on training will occur within a scheduling interval called a continuing qualification cycle. This is the time period during which all terminal and supporting proficiency objectives are trained, validated, or evaluated. The initial approval for a continuing qualification cycle is no more than 26 months in duration, divided into two 13-month evaluation periods. All critical proficiency objectives are accomplished during each evaluation period, and all currency proficiency objectives are accomplished during each continuing qualification cycle.

The initial duration of a continuing qualification cycle is 26 months, which may be subsequently and incrementally extended by the Authority to a maximum of 39 months, contingent upon the results of performance proficiency data from each such cycle.

(iii) Training Sessions

Each evaluation period must include a minimum of one training session but may include more. Initially, training sessions cannot be more than 13 months apart.

Table 5.3—Requirements of an Advanced Qualification Program (AQP)**(iv) Proficiency Evaluations**

A proficiency evaluation must be completed during each evaluation period. Typically, the proficiency evaluation will occur during a required training session; however, if more than one training session is completed during an evaluation period, the proficiency evaluation may be divided among training sessions or otherwise allocated to one or more such sessions.

Tables 5.4–5.7 (Intentionally open)

Table 5.8—Guidance Material: Medical Kit Contents

The equipment contents of a medical kit on passenger aircraft would typically include:

- List of contents;
- Stethoscope;
- Sphygmomanometer (electronic preferred);
- Airways, oropharyngeal (appropriate range of sizes);
- Syringes (appropriate range of sizes);
- Needles (appropriate range of sizes);
- Intravenous catheters (appropriate range of sizes);
- System for delivering intravenous fluids;
- Antiseptic wipes, gloves (disposable);
- Sharps disposal box;
- Urinary catheter with sterile lubricating gel;
- Venous tourniquet;
- Sponge gauze;
- Tape adhesive;
- Surgical mask;
- Emergency tracheal catheter (or large gauge intravenous cannula);
- Umbilical cord clamp;
- Thermometers (non-mercury);
- Basic life support cards;
- Bag-valve mask;
- Torch (flashlight) and batteries (operator may choose to have one per aircraft in an easily accessible location).

The carriage of AEDs would be determined by an operator on the basis of a risk assessment, taking into account the particular nature of the operation.

The drug contents of a medical kit would typically include:

- Epinephrine 1:1000;
- Epinephrine 1:10,000 (can be a dilution of epinephrine 1:1,000);
- Antihistaminic (injectable);
- Anti-psychotic drug (e.g. haloperidol);
- Dextrose (50% injectable), 50 ml (single dose ampule or equivalent);
- Nitroglycerine (tablets or spray);
- Major analgesic (injectable or oral);
- Sedative anticonvulsant (injectable);
- Antiemetic injectable, or oral dissolvable (e.g. Ondansetron);
- Bronchial dilator inhaler with disposable collapsible spacer;
- Atropine (injectable);
- Adrenocortical steroid (injectable or similar oral absorption equivalent);
- Diuretic (injectable);
- Sodium chloride 0.9% (1000 ml recommended);
- Acetyl salicylic acid (aspirin) for oral use;
- Oral beta blocker.

Table 5.8—Guidance Material: Medical Kit Contents

Note: Auto-injectors are easier to use and, when available and cost effective, could be used by the cabin crew under orders from the operator's ground medical advisor (if there are no health professional on board).

Note: Where legally and economically possible and where technically available and as effective, new methods of administration (e.g. nasal spray, sub-lingual spray, oral dissolving) should be considered as a replacement for injections (e.g. intra-nasal rather than injectable sedative anticonvulsant). Such new methods would facilitate treatment by an assisting volunteer that might not have been trained to administer injections (this could include a cabin crew member under direction from ground based medical services).

Table 5.9—Guidance Material: Universal Precaution Kit Contents

One or two universal precaution kits per aircraft would typically be adequate for normal operations; additional kits would be carried at times of increased public health risk (e.g. an outbreak of a serious communicable disease with pandemic potential).

The contents of an aircraft universal precaution kit would typically include:

- Dry powder that can convert small liquid spill into a granulated gel;
- Germicidal disinfectant for surface cleaning;
- Skin wipes;
- Face/eye mask (separate or combined);
- Gloves (disposable);
- Impermeable full-length long-sleeved gown that fastens at the back;
- Large absorbent towel;
- Pick-up scoop with scraper;
- Bio-hazard disposal waste bag;
- Instructions.

Section 6 — Ground Handling Operations (GRH)

Applicability

[Section 6](#) addresses functions within the scope of ground handling operations and is applicable to an operator that conducts passenger, cargo and/or combi (combined cargo and passenger) aircraft operations.

Individual GRH provisions or sub-specifications within a GRH provision that:

- Do not begin with a conditional phrase are applicable unless determined otherwise by the Auditor.
- Begin with a conditional phrase (“If the Operator...”) are applicable if the Operator meets the condition(s) stated in the phrase.

Functions within the scope of ground handling operations include:

- Passenger handling;
- Baggage handling;
- Aircraft ground handling and loading;
- Load control;
- Aircraft fueling;
- Aircraft de-/anti-icing.

In this section, non-revenue cargo is addressed in the same way as revenue cargo for the purposes of handling loading, securing and transporting. COMAT is non-revenue cargo.

For the purpose of addressing cargo in this section, mail is considered to be an item of cargo. Therefore, any reference to cargo also includes mail.

Where an operator outsources the performance of ground handling operational functions to external service providers, the operator retains overall responsibility for ensuring the management of safety in the conduct of such operations and must demonstrate processes for monitoring applicable external service providers in accordance with [GRH 1.10.2](#).

General Guidance

Definitions of technical terms used in this ISM [Section 6](#), as well as the meaning of abbreviations and acronyms, are found in the IATA Reference Manual for Audit Programs (IRM).

Processes and procedures for use in ground handling operations are defined in the IATA Ground Operations Manual (IGOM), the IATA Airport Handling Manual (AHM), the IATA Dangerous Goods Regulations (DGR) and in other relevant IATA publications.

Due to revision cycle differences, the IATA documents cited above are typically revised at various times during the effective period of an ISM edition. Accordingly, when an IATA document is revised, it could render an existing reference to specific information in an IATA document to be in error. In such case, the revised IATA document would have to be searched to find the specific information referenced.

1 Management and Control

1.1 Management System Overview

1.2 Accountability, Authorities and Responsibilities

1.3 Communication

1.4 Provision of Resources

1.5 Documentation System

1.6 Operational Manuals

GRH 1.6.4

If the Operator transports dangerous goods as cargo, the Operator shall ensure the OM or an equivalent operational manual contains information that will permit ground handling personnel to carry out duties and responsibilities with respect to dangerous goods. Such information shall include, as a minimum:

- (i) Action to be taken in the event of emergencies involving dangerous goods;
- (ii) Details of the location and identification of cargo holds;
- (iii) The maximum quantity of dry ice permitted in each compartment;
- (iv) If radioactive material is transported, instructions for the loading of such dangerous goods in accordance with applicable requirements. **(GM)**

Auditor Actions

- ☐ **Identified/Assessed** information in the OM or equivalent document that permits personnel to carry out duties and responsibilities relevant to dangerous goods handling.
- ☐ **Interviewed** responsible management representative(s).
- ☐ **Interviewed** personnel that perform operational functions in ground handling operations.
- ☐ **Observed** accessibility of DG information on key cargo (dry ice and radioactive material) in selected areas of operations where personnel carry out dangerous goods handling.
- ☐ **Other Actions** (Specify)

Guidance

Refer to [IGOM 6.4](#) for guidance that addresses response to dangerous goods events.

Guidance may be found in [DGR 9.5](#) and [10.9](#).

GRH 1.6.5

If the Operator does *not* transport dangerous goods, the Operator shall ensure the OM contains the policies and associated guidance necessary to prevent dangerous goods from being inadvertently carried or loaded onto the aircraft. **(GM)**

Auditor Actions

- ☐ **Identified/Assessed** policies and guidance in the ground handling OM or equivalent manual necessary to ensure personnel do not inadvertently permit acceptance or transport of dangerous goods.
- ☐ **Interviewed** responsible management representative(s).
- ☐ **Interviewed** personnel that perform operational functions in ground handling operations.
- ☐ **Observed** availability of policies and guidance that ensures personnel do not inadvertently permit dangerous goods to be carried or loaded onto the aircraft.
- ☐ **Other Actions** (Specify)

Guidance

For a dangerous goods “no-carry” operator, guidance in the OM typically addresses vigilance with respect to hidden or inconspicuous dangerous goods, and includes an indicative list of items that could contain dangerous goods. Such guidance also typically addresses dangerous goods permitted in passenger baggage in accordance with operator policy and procedures.

1.7 Records System

1.8 (Intentionally open)

1.9 Quality Assurance Program

1.10 Quality Control of Outsourced Operations and Products

1.11 Safety Management

Risk Management

GRH 1.11.1

The Operator shall have a hazard identification program for ground handling operations that includes:

- (i) A combination of reactive and proactive methods for hazard identification;
- (ii) Processes for safety data analysis that identify existing hazards, and may predict future hazards, to aircraft operations. **[SMS] (GM) ◀**

Auditor Actions

- ❑ **Identified/Assessed** safety hazard identification program in GRH operations (focus: program identifies hazards to aircraft operations; describes/defines method(s) of safety data collection/analysis).
- ❑ **Identified/Assessed** role of GRH operations in cross-discipline safety hazard identification program (focus: participation with other operational disciplines).
- ❑ **Interviewed** responsible manager(s) in ground handling operations.
- ❑ **Interviewed** person(s) that perform GRH operations data collection/analysis to identify hazards to aircraft operations.
- ❑ **Examined** selected examples of hazards identified through GRH operations data collection/analysis.
- ❑ **Other Actions** (Specify)

Guidance

Refer to the IRM for the definitions of [Hazard \(Aircraft Operations\)](#) and [Safety Risk](#).

Hazard identification is an element of the Safety Risk Management component of the SMS framework.

Refer to Guidance associated with [ORG 3.1.1](#) located in ISM Section 1.



GRH 1.11.2

The Operator shall have a safety risk assessment and mitigation program for ground handling operations that specifies processes to ensure:

- (i) Hazards are analyzed to determine the existing and potential safety risks to aircraft operations;
- (ii) Safety risks are assessed to determine the requirement for risk control action(s);
- (iii) When required, risk mitigation actions are developed and implemented in ground handling operations. **[SMS] [Eff] (GM) ◀**

Assessment Tool

Desired Outcome

The Operator maintains an overview of its ground handling operations risks and through implementation of mitigation actions, as applicable, ensures risks are at an acceptable level.

Suitability Criteria (Suitable to the size, complexity and nature of operations)

Number and type of analyzed hazards and corresponding risks.

Means used for recording risks and mitigation (control) actions.

Safety data used for the identification of hazards.

Effectiveness Criteria

- (i) All relevant ground handling operations hazards are analyzed for corresponding safety risks.
- (ii) Safety risks are expressed in at least the following components:
 - Likelihood of an occurrence.
 - Severity of the consequence of an occurrence.
 - Likelihood and severity have clear criteria assigned.
- (iii) A matrix quantifies safety risk tolerability to ensure standardization and consistency in the risk assessment process which is based on clear criteria.
- (iv) Risk register(s) within the ground handling operations organization capture risk assessment information, risk mitigation (control) and monitoring actions.
- (v) The risk mitigation (control) actions include time lines, allocation of responsibilities and risk control strategies such as hazard elimination, risk avoidance, risk acceptance, risk mitigation.
- (vi) Mitigation (control) actions are implemented to reduce the risk to a level of - as low as reasonably practical.
- (vii) Identified risks and mitigation actions are regularly reviewed for accuracy and relevance.
- (viii) Effectiveness of risk mitigation (control) actions are monitored at least yearly to include auditing in accordance with [ORG 3.4.1](#).
- (ix) Personnel performing risk assessments are appropriately trained in accordance with [ORG 1.6.5](#).

Auditor Actions

- ☐ **Identified/Assessed** safety risk assessment and mitigation program in ground handling operations (focus: hazards analyzed to identify/define risk; risk assessed to determine appropriate action; action implemented/monitored to mitigate risk).
- ☐ **Identified/Assessed** role of ground handling operations in cross-discipline safety risk assessment/mitigation program (focus: participation with other operational disciplines).
- ☐ **Interviewed** responsible manager(s) in ground handling operations.
- ☐ **Interviewed** person(s) that perform ground handling operations risk assessment/mitigation.
- ☐ **Examined** selected records/documents that illustrate risk assessment/mitigation action.
- ☐ **Other Actions** (Specify)

Guidance

Refer to the IRM for the definitions of [Ground Support Equipment \(GSE\)](#) and [Safety Risk Assessment \(SRA\)](#).

Risk assessment and mitigation is an element of the Safety Risk Management component of the SMS framework.

Hazards relevant to the conduct of ground operations are potentially associated with:

- Aircraft loading/unloading operations (e.g. unsafe airside driving, unsupervised ground operations activities at the airside, lack of PPE, ineffective baggage reconciliation process).



- Aircraft special loads (e.g. for dangerous goods, live animals, perishables, valuables, time/temperature-sensitive products: lack of or incomplete NOTOC, lack of or inadequate security controls).
- Aircraft servicing (e.g. for water/toilet service, catering: lack of guide man, lack of proper periodic water testing, lack of proper inspection before/after service).
- Passenger embarkation/disembarkation (e.g. Passengers walking on the ramp).
- Fueling operations (e.g. fueling with passengers on board the aircraft).
- De-/anti-icing operations (e.g. lack of effective pre-departure checks, glycol/water mixture not effectively checked or tested, incorrect de-/anti-icing procedures).
- Aircraft towing and pushback (e.g. lack of wing walkers, improper connection/disconnection of tow-bars, improper ground-to-cockpit communication).
- Adverse weather conditions (e.g. low visibility, high wind, extreme temperatures, volcanic ash).
- ULD Management. (e.g. unsafe ULD loading/buildup/storage).
- Management of Ground Support Equipment (GSE) (e.g. lack of daily equipment checks, lack of proper identification of out-of-service GSE).

Refer to Guidance associated with [ORG 3.1.2](#) located in ISM Section 1.

Operational Reporting

GRH 1.11.3

The Operator shall have an operational safety reporting system for ground handling operations that:

- Encourages and facilitates ground handling operations personnel to submit reports that identify safety hazards, expose safety deficiencies and raise safety concerns;
- Requires reporting of events that result in aircraft ground damage;
- Includes analysis and ground handling operations management action to address operational deficiencies, hazards, incidents and concerns identified through the reporting system. **[SMS] (GM) ◀**

Auditor Actions

- ☐ **Identified/Assessed** operational safety reporting system in ground handling operations (focus: system urges/facilitates reporting of hazards/safety concerns; includes analysis/action to validate/address reported hazards/safety concerns).
- ☐ **Interviewed** responsible manager(s) in ground handling operations.
- ☐ **Interviewed** person(s) that perform operational safety report review/analysis/follow-up in ground handling operations.
- ☐ **Examined** data that confirm an effective ground handling operations safety reporting system (focus: quantity of reports submitted/hazards identified).
- ☐ **Examined** records of selected ground handling operations safety reports (focus: analysis/follow-up to identify and address reported hazards/safety concerns).
- ☐ **Other Actions** (Specify).

Guidance

Safety reporting is a key aspect of SMS hazard identification and risk management.

To enhance industry data usability, it is recommended that ground damage events are reported in accordance with a formal reporting structure (see [GRH 1.11.6](#)).

Refer to [IGOM 6.4](#) for guidance that addresses aircraft damage reporting.

Refer to Guidance associated with [ORG 3.1.3](#) located in ISM Section 1.

Safety Performance Monitoring and Management**2 Training and Qualification****2.1 Training Program****GRH 2.1.2**

The Operator shall have a process to ensure the training programs completed by ground handling operations personnel in accordance with [GRH 2.1.1](#) provide the knowledge necessary to perform duties, execute procedures and operate the equipment associated with specific ground handling functions and responsibilities. Such programs shall include:

- (i) Familiarization training on applicable regulations;
- (ii) In-depth training on requirements, including policies, procedures and operating practices;
- (iii) Training in human factors principles;
- (iv) Safety training on associated operational hazards. **(GM)**

Auditor Actions

- ☐ **Identified/Assessed** training programs for ground handling operations personnel (focus: includes programs for personnel in all ground handling operations functions).
- ☐ **Interviewed** responsible manager(s) in ground handling operations.
- ☐ **Examined** selected training program records/documents (focus: programs include all specified training areas as applicable to ground handling operations functions).
- ☐ **Other Actions** (Specify).

Guidance

△ Refer to the IRM for the definition of [FOD \(Foreign Object Debris/Damage\)](#) and [Human Factors Principles](#).

□ Safety and human factors training typically includes the following subject areas as appropriate to the individual's assigned operational function(s):

- Safety philosophy;
- Safety regulations;
- Hazards;
- Human factors;
- Airside markings and signage;
- Emergency situations;
- FOD prevention;
- Personal protection;
- Accidents, incidents, near misses;
- Airside safety supervision.

[AHM 1110 Item 11](#) contains detailed guidance for safety and human factors training.

2.2 Program Elements

2.3 SMS Training

3 Ground Handling Operations

3.1 Passenger and Baggage Handling

GRH 3.1.3

If the Operator conducts passenger flights and accepts battery-operated mobility aids for transport on the aircraft, the Operator shall have procedures for acceptance and handling of such mobility aids to ensure they meet following requirements:

- (i) The battery is a type that is permitted;
- (ii) Battery terminals are protected and electrical circuits are isolated;
- (iii) Loading is in a manner that prevents movement and damage from other cargo;
- (iv) If applicable, batteries are removed, protected and transported as per specifications applicable to the type of batteries;
- (v) The pilot in command is informed of the location of the mobility aids and/or the batteries. **(GM)**

Auditor Actions

- ☐ **Identified/Assessed** procedures for acceptance/handling of battery-operated mobility aids.
- ☐ **Interviewed** responsible manager(s) in ground handling operations.
- ☐ **Observed** acceptance/handling of battery-operated mobility (focus: acceptance/handling procedures are implemented).
- ☐ **Other Actions** (Specify)

Guidance

Refer to the IRM for the definition of [Passenger Mobility Aid](#).

Refer to [DGR 2.3.2](#) and ICAO Technical Instructions Part 7;2.13 for additional guidance.

GRH 3.1.5

If the Operator transports passengers that require special handling, the Operator shall have a policy and associated procedures for the preflight acceptance and handling of such passengers by ground passenger handling personnel. Such policy and procedures shall be in accordance with applicable regulations and, as a minimum, address:

- (i) Unruly passengers;
- (ii) Passengers with disabilities or reduced mobility;
- (iii) Passengers with injuries or illness;
- (iv) Infants and unaccompanied children;
- (v) Inadmissible passengers;
- (vi) Deportees;
- (vii) Passengers in custody. **(GM)**

Auditor Actions

- ☐ **Identified/Assessed** policy and procedures for passengers requiring the listed categories of special handling.
- ☐ **Interviewed** responsible manager(s) in ground handling operations
- ☐ **Sampled** records of specific cases of handling special needs passengers.

- ☐ **Observed** passenger/baggage handling operations (focus: policy/procedures for preflight acceptance of passengers that require special handling).
- ☐ **Other Actions** (Specify)

Guidance

A policy and associated procedures typically address the acceptance and pre-boarding handling of passengers that require special handling, or perhaps the refusal to accept certain categories of passengers. For example, such policy and procedures might include or address the following:

- For intoxicated and/or abusive passengers: Refusal to accept at check-in and, upon discovery after check-in, refusal to board the aircraft.
- For passengers with disabilities: Acceptance and/or limitations for such acceptance in accordance with applicable regulations, ground handling and, as applicable, specialized equipment considerations.
- If unaccompanied children are accepted: Maximum number, minimum age, any special arrangements once on board, specific seat allocation, ground handling considerations.
- If stretchers are accepted: Maximum number, escort requirement, associated equipment that would need to be available, ground handling considerations.
- If passengers in custody are accepted: Maximum number, number of escort officers, specific seat allocation, ground handling considerations.

Refer to [IGOM 1.4](#).

3.2 Airside Operations



GRH 3.2.9

If the Operator conducts aircraft pushback or towing operations, the Operator shall ensure procedures are in place for such operations. Such procedures shall ensure:

- (i) Equipment used is suitable for the aircraft type;
- (ii) Maximum aircraft nose gear turn limits are not exceeded;
- (iii) Standardized verbal communication is used between the ground crew and the flight crew;
- (iv) A safe connection, operation and disconnection of the pushback or towing equipment. **(GM)**

Auditor Actions

- ☐ **Identified/Assessed** aircraft departure procedures in the OM (focus: published procedure for aircraft pre-departure check is in accordance with specifications in this standard).
- ☐ **Interviewed** responsible manager(s) in ground handling operations.
- ☐ **Observed** aircraft departure operations (focus: procedure for aircraft departure walkaround check is implemented as published in the OM).
- ☐ **Other Actions** (Specify)

Guidance

Documented procedures in accordance with [IGOM 4.6](#) (Aircraft Departure), [IGOM 4.7](#) (Power Push Unit) and [IGOM 4.9](#) (Aircraft Towing) will typically demonstrate documental conformity with the specifications in this provision.

3.3 Load Control

GRH 3.3.4

If the Operator transports dangerous goods as cargo, the Operator shall ensure a process is in place to provide the pilot-in-command (PIC), as soon as practicable prior to departure of the aircraft, with accurate and legible written information pertaining to dangerous goods on board the aircraft to be transported as cargo. Such notification shall include the following:

- (i) If applicable, Air Waybill number;
- (ii) Proper shipping name and/or UN/ID number;

- (iii) Class or division, and subsidiary risk(s) corresponding to the label(s) applied, and for Class 1, the compatibility group;
- (iv) If applicable, packing group;
- (v) For non-radioactive material, number of packages, exact loading location and, as required, net quantity or, if applicable, gross weight of each package, except:
 - (a) For *UN 1845: carbon dioxide, solid (dry ice)*, UN number, proper shipping name, classification, total quantity in each aircraft hold and offload airport;
 - (b) For UN 3480 (Lithium ion batteries) and UN 3090 (lithium metal batteries), only the UN number, proper shipping name, class, total quantity at each loading location, and whether the package must be carried on a cargo only aircraft need be provided. UN 3480 (Lithium ion batteries) and UN 3090 (lithium metal batteries) carried under a State exemption must meet all of the requirements of iv) and v).
- (vi) For radioactive material, number and category of packages, overpacks or freight containers, exact loading location and, as applicable, transport index for each package;
- (vii) Any restriction for transport on cargo aircraft only;
- (viii) Offload airport;
- (ix) If applicable, dangerous goods transported under a state exemption;
- (x) An indication that aircraft loading personnel observed no evidence of damage to or leakage from packages, or leakage from ULDs, loaded onto the aircraft. **(GM)**

Auditor Actions

- ☐ **Identified/Assessed** load control process to provide PIC with information pertaining to onboard dangerous goods as cargo.
- ☐ **Interviewed** responsible manager(s) in load control operations.
- ☐ **Examined** documents that confirm dangerous goods information was provided to PIC (e.g. NOTOC).
- ☐ **Observed** load control operations (focus: load control system includes process/method for providing applicable dangerous goods information to PIC).
- ☐ **Other Actions** (Specify)

Guidance

Refer to the IRM for the definitions of [NOTOC \(Notification to Captain\)](#) and [State](#).

Such information is typically presented to the PIC in a notification called the NOTOC (notification to the captain). The NOTOC contains the detailed information (as specified in this provision) relative to all dangerous goods loaded on the aircraft as cargo.

Information contained in the NOTOC may also be used:

- For emergency response to an accident or incident involving dangerous goods on board;
- To provide to air traffic services in the event of an in-flight emergency.

In the event the NOTOC is of such a size as to make in-flight radiotelephony transmission impracticable in an emergency situation, a summary of the information is typically provided to the PIC (NOTOC Summary), which contains at least the quantities and classes or division of dangerous goods in each cargo compartment.

Guidance may be found in [DGR 9.5](#) and [Table 9.5.A](#).

3.4 Aircraft Loading

GRH 3.4.1

The Operator shall have procedures that ensure aircraft are loaded:

- (i) In accordance with written loading instructions;
- (ii) In a manner that satisfies weight and balance requirements. **(GM)**

Auditor Actions

- ☐ **Identified/Assessed** aircraft loading procedures.
- ☐ **Interviewed** responsible manager(s) in ground handling operations.
- ☐ **Examined** examples of documented aircraft loading instructions.
- ☐ **Observed** aircraft loading operations (focus: aircraft loaded in accordance with loading instructions/weight/balance requirements).
- ☐ **Interviewed** personnel that perform aircraft loading.
- ☐ **Other Actions** (Specify)

Guidance

Refer to [IGOM 4.5.9](#) and [5](#) (all), as well as [AHM 514](#) and [590](#) for additional guidance.

GRH 3.4.2

If the Operator transports dangerous goods as cargo, the Operator shall ensure a qualified individual is designated to be responsible for the correct loading and securing of dangerous goods on board the aircraft.

Auditor Actions

- ☐ **Identified/Assessed** process for designating qualified individual to be responsible for loading/securing dangerous goods.
- ☐ **Interviewed** responsible manager(s) in ground handling operations.
- ☐ **Observed** aircraft loading operations (focus: qualified individual is responsible for loading/securing dangerous goods on board the aircraft).
- ☐ **Other Actions** (Specify)

GRH 3.4.3

If the Operator transports dangerous goods as cargo, the Operator shall ensure procedures are in place for the transportation of dangerous goods to/from an aircraft and the loading and securing of dangerous goods on an aircraft in a manner that:

- (i) Prevents damage to packages and containers;
- (ii) Provides for separation and segregation in accordance with applicable requirements;
- (iii) Prevents any movement in the aircraft. **(GM)**

Auditor Actions

- ☐ **Identified/Assessed** procedures for loading/securing dangerous goods on aircraft.
- ☐ **Interviewed** responsible manager(s) in ground handling operations.
- ☐ **Observed** transportation of cargo to/from aircraft (focus: handling of dangerous goods to prevent damage and maintain separation).
- ☐ **Interviewed** personnel that perform transport of and/or aircraft loading of cargo shipments.
- ☐ **Other Actions** (Specify)

Guidance

Refer to [IGOM 4.5.1](#) and [DGR 9.3](#) for guidance that addresses the transportation, loading and securing of dangerous goods.

GRH 3.4.4

If the Operator transports dangerous goods as cargo, the Operator shall ensure procedures are in place that assure, when a dangerous goods package or shipment appears to be damaged or leaking:

- (i) The package or shipment is prevented from being loaded into an aircraft;
- (ii) If already loaded, the package or shipment is removed from an aircraft;
- (iii) In the case of leakage, an evaluation is conducted to identify and prevent from transport any baggage, cargo, transport devices or other items that may have become contaminated. **(GM)**

Auditor Actions

- ☐ **Identified/Assessed** procedures for handling/addressing leaking/damaged dangerous goods shipments.
- ☐ **Interviewed** responsible manager(s) in ground handling operations.
- ☐ **Examined** records/documents that illustrate handling of leaking/damaged dangerous goods shipments.
- ☐ **Observed** aircraft loading operations (focus: procedures for addressing dangerous goods packages/shipments that appear to be leaking or damaged).
- ☐ **Interviewed** personnel that perform aircraft loading.
- ☐ **Other Actions** (Specify)

Guidance

Refer to [DGR 9.3](#), [9.4](#) and [10.9](#), which contain guidance that addresses apparent damage to dangerous goods shipments.

GRH 3.4.5

If the Operator transports dangerous goods as cargo, the Operator shall ensure procedures are in place that require, when an aircraft has been contaminated by dangerous goods leakage:

- (i) Hazardous contamination is removed from the aircraft without delay;
- (ii) In the case of radioactive contamination, arrangements are made to take the aircraft out of service for evaluation by appropriately qualified personnel.

Auditor Actions

- ☐ **Identified/Assessed** procedures for addressing aircraft contaminated by leakage of dangerous goods.
- ☐ **Interviewed** responsible manager(s) in ground handling operations.
- ☐ **Examined** guidance/checklists used for dealing with an aircraft contaminated by leakage of dangerous goods.
- ☐ **Other Actions** (Specify)

GRH 3.4.8

If the Operator conducts passenger flights, the Operator shall ensure procedures are in place that prevent shipments labeled "Cargo Aircraft Only" from being loaded onto an aircraft for a passenger flight.

Auditor Actions

- ☐ **Identified/Assessed** procedure(s) for preventing shipments with "Cargo Aircraft Only" labels from being loaded onto aircraft for passenger flight.
- ☐ **Interviewed** responsible manager(s) in ground handling operations.
- ☐ **Examined** guidance/checklists used to ensure personnel do not load shipments with "Cargo Aircraft Only" labels onto aircraft for passenger flight.
- ☐ **Interviewed** personnel that perform aircraft loading.
- ☐ **Other Actions** (Specify)

GRH 3.4.12

If the Operator conducts passenger flights and permits cargo or passenger items to be transported in the passenger seats of the aircraft cabin, the Operator shall ensure aircraft loading procedures are in place that require such cargo packages or passenger items:

- (i) To be secured by a safety belt or restraint device having enough strength to eliminate the possibility of shifting under all normal anticipated flight and ground conditions;
- (ii) To be packaged or covered in a manner to avoid possible injury to passengers and cabin crew members;
- (iii) To not impose any load on the seats that exceeds the load limitation for the seats;
- (iv) To not restrict access to or use of any required emergency or regular exit, or aisle(s) in the cabin;
- (v) To not obscure any passenger's view of the seat belt sign, no smoking sign or required exit sign. **(GM)**

Auditor Actions

- ☐ **Identified/Assessed** procedure(s) for loading and securing cargo/passenger items in cabin passenger seats.
- ☐ **Interviewed** responsible manager(s) in ground handling operations.
- ☐ **Examined** guidance/checklists used for loading cargo/passenger items in cabin passenger seats.
- ☐ **Other Actions** (Specify)

Guidance

The intent of this provision is for an operator that permits the transport of cargo packages or passenger items in cabin passenger seats to have procedures that ensure such packages or items are properly loaded and secured.

Some operators might permit the transport of smaller cargo packages (e.g. mail pouches, COMAT items) secured in cabin passenger seats.

In some regulatory jurisdictions, cargo transported in the passenger cabin is required to be put inside an approved bin or container that is certified to withstand certain loads. Such bin or container is then attached or secured to a seat or seat/floor structure in a manner that ensures maximum load limits are observed.

An operator might also use approved restraining nets to cover and secure cargo in passenger seats.

Also, some operators might permit the transport of certain passenger items secured in cabin passenger seats. These types of items are typically large, valuable or fragile articles belonging to passengers that are not conducive to transport as checked baggage or appropriate for stowage in overhead bins/lockers (e.g. large musical instruments, certain electronic equipment, prominent trophies, works of art). Such items might thus be secured and carried in a dedicated cabin passenger seat (which might be purchased by the passenger-owner for this purpose).

Loading procedures for any of the above items would typically include access to technical data that ensures seat load limitations are not exceeded.

A verification that cargo packages or passenger items being transported in passenger seats are properly secured is accomplished by the cabin crew in accordance with [CAB 3.2.3](#).

3.5 Ground Support Equipment

3.6 Airside Event Response and Reporting

3.7 Security

4 Special Aircraft Ground Handling Operations

4.1 Aircraft Fueling

4.2 Aircraft De-/Anti-icing

GRH 4.2.2

If the Operator has a De-/Anti-icing Program, the Operator shall ensure policies and procedures are in place that result in:

- (i) Standardized methods of fluid application;
- (ii) Compliance with specific aircraft limitations;
- (iii) A clean aircraft through proper treatment of applicable surfaces. **(GM)**

Auditor Actions

- ☐ **Identified/Assessed** policies and procedures for aircraft de-/anti-icing.
- ☐ **Interviewed** responsible manager(s) in ground handling operations.
- ☐ **Examined** checklist(s) used for de-/anti-icing operations.
- ☐ **Interviewed** personnel that perform operational functions in aircraft de-/anti-icing operations.
- ☐ **Examined** selected quality control inspection reports (focus: aircraft de-/anti-icing operations).
- ☐ **Interviewed** supervisory personnel for aircraft de-/anti icing operations.
- ☐ **Other Actions** (Specify)

Guidance

To ensure desired results, an operator's de-/anti-icing program would typically include policies and procedures that:

- Define equipment for and methods of applying de-icing and anti-icing fluid to produce an aircraft free of contamination (clean aircraft);
- Specify a sequence for fluid application to the applicable aircraft surfaces and define specific methods and techniques for applying fluid to each individual surface;
- Provide limitations that are to be observed to successfully complete the process, including correct fluid mixtures, fluid temperatures and nozzle pressure.

Additional guidance may be found in ICAO Doc 9640-AN/940, Manual of Aircraft Ground De-icing/Anti-icing Operations, Chapter 11, and in SAE AS6285, Aircraft Ground Deicing/Anti-Icing Processes.



Table 6.1—Passenger Services, Ramp Services, Load Control Training Elements

As specified in [GRH 2.2.4](#), the Operator *should* have processes to ensure training for ground handling personnel assigned to perform passenger services, ramp services and load control includes the following training elements:

(I) Passenger Services:

- (a) Aviation Basics;
- (b) Arrivals/Departures;
- (c) Baggage Services;
- (d) Check-in;
- (e) Passenger Assistance and PRM (passengers with reduced mobility);
- (f) Post-Flight Requirements;
- (g) Special Category Passengers;
- (h) Transfer of Load Information;
- (i) Transfer, Transit and Connection;
- (j) Boarding Bridge Operations;
- (k) Aircraft Cabin Access Doors.

(II) Ramp Services:

- (a) Basic Ramp;
- (b) Airside Driving;
- (c) Basic Hand Signals;
- (d) Aircraft Marshalling;
- (e) Boarding Bridge Operations;
- (f) Aircraft Cargo Access Doors;
- (g) Aircraft Cabin Access Doors;
- (h) Aircraft Loading;
- (i) Aircraft Arrival;
- (j) Aircraft Departure;
- (k) Aircraft Pushback;
- (l) Aircraft Towing;
- (m) GSE Operations;
- (n) Ground-to-Flight Deck Headset Communication and Engine Start;
- (o) Ramp Baggage Handling;
- (p) Aircraft Loading Supervision;
- (q) Airside Safety Supervision.

(III) Load Control:

- (a) Aviation Basics;
- (b) Aircraft Weight & Balance Principles;
- (c) Load Planning and Load Sheet;
- (d) Documentation and Messaging.



- ⊗
- ⊗
- ⊗
- ⊗
- ⊗
- ⊗
- ⊗

INTENTIONALLY LEFT BLANK

Section 7 — Cargo Operations (CGO)

Applicability

[Section 7](#) addresses functions within the scope of cargo operations, and is applicable to an operator that transports revenue and/or non-revenue cargo. COMAT (Company Material) is non-revenue cargo.

In this section, non-revenue cargo is addressed in the same way as revenue cargo for the purposes of handling, loading, securing and transporting.

For the purpose of addressing cargo in this section, mail is considered to be an item of cargo. Therefore, any reference to cargo also includes mail.

Individual CGO provisions or sub-specifications within a CGO provision that:

- Do not begin with a conditional phrase are applicable unless determined otherwise by the Auditor.
- Begin with a conditional phrase (“If the Operator...”) are applicable if the Operator meets the condition(s) stated in the phrase.

Functions within the scope of cargo operations include:

- Cargo acceptance;
- Cargo handling;
- ULD loading/build-up;
- Application of required security measures.

Certain operators, particularly all-cargo operators, might have ground handling operations functions performed by cargo operations personnel (e.g. aircraft loading, airside operations, load control). Where this situation exists, the operator must be in conformity with the ISARPs contained in [Section 6](#), Ground Handling Operations (GRH), that are applicable to the ground handling operations functions performed by cargo operations personnel.

Where an operator outsources the performance of cargo operations functions to external service providers, the operator retains overall responsibility for ensuring the management of safety in the conduct of such operations and must demonstrate processes for monitoring applicable external service providers in accordance with [CGO 1.10.2](#).

General Guidance

Definitions of technical terms used in this ISM [Section 7](#), as well as the meaning of abbreviations and acronyms, are found in the IATA Reference Manual for Audit Programs (IRM).

1 Management and Control

1.1 Management System Overview

1.2 Accountability, Authorities and Responsibilities

1.3 Communication

1.4 Provision of Resources

1.5 Documentation System

1.6 Operational Manuals

1.7 Records System

1.8 (Intentionally open)

1.9 Quality Assurance Program

1.10 Quality Control of Outsourced Operations and Products

1.11 Safety Management

Risk Management

CGO 1.11.1

If the Operator transports revenue cargo, the Operator shall have a hazard identification program implemented in the cargo operations organization that includes:

- (i) A combination of reactive and proactive methods for hazard identification;
- (ii) Processes for safety data analysis that identify existing hazards, and may predict future hazards, to aircraft operations. **[SMS] (GM) ◀**

Auditor Actions

- ☐ **Identified/Assessed** safety hazard identification program in cargo operations (focus: program identifies hazards to aircraft operations; describes/defines method(s) of safety data collection/analysis).
- ☐ **Identified/Assessed** role of cargo operations in cross-discipline safety hazard identification program (focus: participation with other operational disciplines).
- ☐ **Interviewed** responsible manager(s) in cargo operations.
- ☐ **Interviewed** person(s) that perform cargo operations data collection/analysis to identify hazards to aircraft operations.
- ☐ **Examined** selected examples of hazards identified through cargo operations data collection/analysis.
- ☐ **Other Actions** (Specify)

Guidance

Refer to the IRM for the definitions of [Hazard \(Aircraft Operations\)](#) and [Safety Risk](#).

Hazard identification is an element of the Safety Risk Management component of the SMS framework.

Refer to Guidance associated with [ORG 3.1.1](#) located in ISM Section 1.



CGO 1.11.2

If the Operator transports revenue cargo, the Operator shall have a safety risk assessment and mitigation program implemented in the cargo operations organization that specifies processes to ensure:

- (i) Hazards are analyzed to determine the corresponding safety risks to aircraft operations;
- (ii) Safety risks are assessed to determine the requirement for risk mitigation action(s);
- (iii) When required, risk mitigation actions are developed and implemented in cargo operations.

[SMS] [Eff] (GM) ◀

Assessment Tool

Desired Outcome

The Operator maintains an overview of its cargo operations risks and through implementation of mitigation actions, as applicable, ensures risks are at an acceptable level.

Suitability Criteria (Suitable to the size, complexity and nature of operations)

Number and type of analyzed hazards and corresponding risks.

Means used for recording risks and mitigation (control) actions.

Safety data used for the identification of hazards.

Effectiveness Criteria

- (i) All relevant cargo operations hazards are analyzed for corresponding safety risks.
- (ii) Safety risks are expressed in at least the following components:
 - Likelihood of an occurrence.
 - Severity of the consequence of an occurrence.
 - Likelihood and severity have clear criteria assigned.
- (iii) A matrix quantifies safety risk tolerability to ensure standardization and consistency in the risk assessment process which is based on clear criteria.
- (iv) Risk register(s) within the cargo operations organization capture risk assessment information, risk mitigation (control) and monitoring actions.
- (v) The risk mitigation (control) actions include time lines, allocation of responsibilities and risk control strategies such as hazard elimination, risk avoidance, risk acceptance, risk mitigation.
- (vi) Mitigation (control) actions are implemented to reduce the risk to a level of - as low as reasonably practical.
- (vii) Identified risks and mitigation actions are regularly reviewed for accuracy and relevance.
- (viii) Effectiveness of risk mitigation (control) actions are monitored at least yearly to include auditing in accordance with [ORG 3.4.1](#).
- (ix) Personnel performing risk assessments are appropriately trained in accordance with [ORG 1.6.5](#).

Auditor Actions

- ☐ **Identified/Assessed** safety risk assessment and mitigation program in cargo operations (focus: hazards analyzed to identify/define risk; risk assessed to determine appropriate action; action implemented/monitored to mitigate risk).
- ☐ **Identified/Assessed** role of cargo operations in cross-discipline safety risk assessment/mitigation program (focus: participation with other operational disciplines).
- ☐ **Interviewed** responsible manager(s) in cargo operations.
- ☐ **Interviewed** person(s) that perform cargo operations risk assessment/mitigation.
- ☐ **Examined** selected records/documents that illustrate risk assessment/mitigation action.
- ☐ **Other Actions** (Specify)

Guidance

Refer to the IRM for the definition of [Safety Risk Assessment \(SRA\)](#).

Risk assessment and mitigation is an element of the Safety Risk Management component of the SMS framework.

The potential for hazards is typically associated with the following aspects of cargo handling operations:

- Acceptance and handling of dangerous goods and other special cargo shipments (e.g. lithium batteries);
- Application of security controls;
- Protection from acts of unlawful interference;
- Build-up, handling and serviceability of ULDs;
- Operation and serviceability of cargo handling equipment;
- Adequacy of facilities.

Refer to Guidance associated with [ORG 3.1.2](#) located in ISM Section 1.

Operational Reporting

CGO 1.11.3

If the Operator transports revenue cargo, the Operator shall have an operational safety reporting system in the cargo operations organization that:

- (i) Encourages and facilitates cargo operations personnel to submit reports that identify safety hazards, expose safety deficiencies and raise safety concerns;
- (ii) Includes analysis and cargo operations management action to address operational deficiencies, hazards, incidents and concerns identified through the reporting system.

[SMS] (GM) ◀

Auditor Actions

- ☐ **Identified/Assessed** documented operational safety reporting system in cargo operations (focus: system urges/facilitates reporting of hazards/safety concerns; includes analysis/action to validate/address reported hazards/safety concerns).
- ☐ **Interviewed** responsible manager(s) in cargo operations.
- ☐ **Interviewed** person(s) that perform operational safety report review/analysis/follow-up in cargo operations.
- ☐ **Interviewed** personnel that perform operational functions in cargo operations.
- ☐ **Examined** data that confirm an effective cargo operations safety reporting system (focus: quantity of reports submitted/hazards identified).
- ☐ **Examined** records of selected cargo operations safety reports (focus: analysis/follow-up to identify and address reported hazards/safety concerns).
- ☐ **Other Actions** (Specify)

Guidance

Safety reporting is a key aspect of SMS hazard identification and risk management.

Refer to Guidance associated with [ORG 3.1.3](#) located in ISM Section 1.

Safety Performance Monitoring and Management

2 Training and Qualification

2.1 Training Program

2.2 Program Elements

CGO 2.2.1

△ If the Operator transports dangerous goods as revenue or non-revenue cargo, the Operator shall have a process to ensure cargo operations personnel assigned the responsibility for accepting dangerous goods complete dangerous goods training, to include initial training and recurrent training within 24 months of previous training in dangerous goods. **(GM)**

Auditor Actions

- ❑ **Identified/Assessed** dangerous goods training program: (focus: defines DG training requirements for all cargo handling personnel based on specific assigned responsibilities/duty functions).
- ❑ **Interviewed** responsible manager(s) in cargo operations.
- ❑ **Examined** applicable initial/recurrent dangerous goods training curricula and syllabi (focus: subject areas appropriate for personnel based on specific responsibilities/duty functions).
- ❑ **Examined** initial/recurrent dangerous goods training records of selected personnel (focus: completion of required training as appropriate for assigned responsibilities/duty functions).
- ❑ **Other Actions** (Specify)

Guidance

Recurrent training in dangerous goods is completed within a validity period that expires 24 months from the previous training to ensure knowledge is current, unless a shorter period is defined by a competent authority. However, when such recurrent training is completed within the final 3 months of the 24-month validity period, the new validity period may extend from the month on which the recurrent training was completed until 24 months from the expiry month of the current validity period. If such recurrent training is completed *prior* to the final three months of the validity period, the new validity period would extend 24 months from the month the recurrent training was completed.

The curriculum for dangerous goods training for cargo operations personnel will vary depending on specific responsibilities and duty function(s), but will typically address the following subject areas:

- General philosophy;
- Limitations;
- General requirements for shippers;
- Classification;
- List of dangerous goods;
- General packing requirements;
- Packing instructions;
- Labeling and marking;
- Shipper's declaration and other relevant documentation;
- Acceptance procedures;
- Recognition of undeclared dangerous goods;
- Storage and loading procedures;
- Flight crew notification;
- Provisions for passengers and/or crew;
- Emergency procedures.

- △ Refer to [DGR 1.5.2](#) and [Table 1.5.A](#), Minimum Requirements for Training Curricula, for guidance that addresses dangerous goods training subjects applicable to specific cargo operations functions.

CGO 2.2.2

- △ If the Operator transports revenue or non-revenue cargo, but does not transport dangerous goods, the Operator shall have a process to ensure cargo operations personnel assigned the responsibility for accepting cargo complete dangerous goods training, to include initial training and recurrent training within 24 months of previous training in dangerous goods. **(GM)**

Auditor Actions

- **Identified/Assessed** dangerous goods training program: (focus: defines DG training requirements for personnel with cargo acceptance/handling responsibilities).
- **Interviewed** responsible manager(s) in cargo operations.
- **Examined** selected initial/recurrent dangerous goods training curricula/syllabi (focus: subject areas appropriate for personnel with cargo acceptance/handling responsibilities).
- **Examined** initial/recurrent training records of selected cargo operations personnel (focus: completion of required training as appropriate for assigned responsibilities/duty functions).
- **Other Actions** (Specify)

Guidance

When an operator does not transport dangerous goods (i.e. a “no-carry” operator), dangerous goods training is still required for cargo operations personnel to ensure declared and undeclared dangerous goods are recognized and prohibited from being carried or loaded onto an aircraft.

Dangerous goods training is structured to provide the requisite knowledge to permit cargo operations personnel to recognize dangerous goods, whether labeled or not labeled, and to prevent such dangerous goods from being inadvertently accepted and/or planned for loading into an aircraft.

The curriculum for dangerous goods training for cargo handling personnel will vary depending on specific responsibilities and duty function(s), but will typically address the following subject areas:

- General philosophy;
- Limitations;
- Labeling and marking;
- For personnel that accept cargo, shipper's declarations and other relevant documentation;
- Recognition of undeclared dangerous goods;
- Provisions for passengers and/or crew;
- Emergency procedures.

- △ Refer to [DGR 1.5.2](#) and [Table 1.5.B](#), Minimum Requirements for Training Curricula for “No-carry” Operators, for guidance that addresses dangerous goods training subjects applicable to specific cargo operations functions.

CGO 2.2.3

- △ If the Operator transports dangerous goods as revenue or non-revenue cargo, the Operator shall have a process to ensure cargo operations personnel assigned the responsibility for handling or storing such cargo, as well as, where applicable, the loading of ULDs, receive dangerous goods training, to include initial training and recurrent training within 24 months of previous training in dangerous goods. **(GM)**

Auditor Actions

- **Identified/Assessed** process for dangerous goods training for cargo operations personnel that handle/store cargo; where applicable, load cargo on/into ULDs.
- **Interviewed** responsible manager(s) in cargo operations.
- **Examined** selected initial/recurrent dangerous goods training curricula/syllabi applicable to cargo operations personnel that handle/store cargo; where applicable, load cargo on/into ULDs.

- ☐ **Examined** initial/recurrent training records of selected cargo operations personnel that handle/store cargo; where applicable, load cargo on/into ULDs.
- ☐ **Other Actions** (Specify)

Guidance

Refer to the IRM for the definition of [Unit Load Device \(ULD\)](#), which addresses certified and non-certified units.

The curriculum for dangerous goods training for cargo personnel with responsibilities for handling or storing dangerous goods cargo as well as, where applicable, the loading of such cargo onto/into ULDs, will vary depending on specific responsibilities and duty function(s), but will typically address the following subject areas:

- General philosophy;
- Limitations;
- Labeling and marking;
- Recognition of undeclared dangerous goods;
- Storage and loading procedures;
- Flight crew notification;
- Provisions for passengers and/or crew;
- Emergency procedures.

△ Refer to [DGR 1.5.2](#) and [Table 1.5.A](#) for guidance that addresses dangerous goods training subjects applicable to personnel with responsibilities for handling, storing and loading cargo onto/into ULDs.

2.3 SMS Training

3 Acceptance and Handling

3.1 General Cargo

CGO 3.1.1

If the Operator transports revenue or non-revenue cargo, the Operator shall have a process to ensure such shipments accepted for transport:

- (i) If revenue cargo, are in compliance with standards in the OM as specified in [CGO 1.6.1](#);
- (ii) If interline cargo, are in compliance with IATA interline cargo requirements;
- (iii) If non-revenue cargo, are in compliance with the OM or equivalent document as specified in [CGO 1.6.1. \(GM\)](#)

Auditor Actions

- ☐ **Identified/Assessed** process that ensures cargo shipments accepted for transport are in compliance with applicable requirements.
- ☐ **Interviewed** responsible manager(s) in cargo operations.
- ☐ **Examined** selected quality control inspection reports.
- ☐ **Observed** cargo acceptance operations (focus: process for ensuring cargo shipments comply with applicable requirements).
- ☐ **Other Actions** (Specify)

Guidance

Cargo is accepted under the terms of the OM, which typically specifies procedures to ensure acceptance personnel verify the cargo (revenue or non-revenue) has been packed in a manner:

- For safe transport with ordinary care in handling;
- To preclude injury or damage to any person, cargo or property.

Also, interline cargo typically complies with the applicable requirements of the receiving operator(s).

Refer to the IATA Cargo Services Conference Resolution 660 for guidance pertaining to interline cargo.

3.2 Dangerous Goods

CGO 3.2.1

If the Operator transports dangerous goods as revenue or non-revenue cargo, the Operator shall have a Dangerous Goods Acceptance Checklist that:

- (i) Reflects applicable requirements contained in the current DGR;
- (ii) Once completed, contains information that identifies the person(s) that performed the acceptance check. **(GM)**

Auditor Actions

- ☐ **Identified/Assessed** dangerous goods acceptance checklist (focus: contains DGR requirements, information that identifies person that performed acceptance check).
- ☐ **Interviewed** responsible manager(s) in cargo operations.
- ☐ **Examined** process(es) for development/maintenance of dangerous goods acceptance checklist.
- ☐ **Observed** cargo acceptance operations (focus: dangerous goods acceptance in accordance with DGR requirements).
- ☐ **Other Actions** (Specify)

Guidance

Sample checklists for non-radioactive shipments, radioactive shipments and dry ice (carbon dioxide, solid) are found in the back of the DGR.

Refer to [DGR 9.1.3](#) for guidance that addresses the Dangerous Goods Acceptance Checklist.

CGO 3.2.2

If the Operator transports dangerous goods as revenue or non-revenue cargo, the Operator shall have procedures to ensure the use of a Dangerous Goods Acceptance Checklist as specified in [CGO 3.2.1](#) to verify:

- (i) Package(s), overpack(s) or freight containers, as applicable, are correctly marked and labeled;
- (ii) The Shipper's Declaration for Dangerous Goods, if required, or other documentation complies with the requirements of the current edition of the DGR. **(GM)**

Auditor Actions

- ☐ **Identified/Assessed** procedures for use of dangerous goods acceptance checklist (focus: checklist is used to verify package marking/labeling, documentation compliance).
- ☐ **Interviewed** responsible manager(s) in cargo operations.
- ☐ **Observed** cargo acceptance operations (focus: use of dangerous goods acceptance checklist to verify package marking/labeling, documentation compliance).
- ☐ **Other Actions** (Specify)

Guidance

Refer to [DGR 9.1.3](#) for guidance that addresses use of the Dangerous Goods Acceptance Checklist.

CGO 3.2.4

If the Operator transports dangerous goods as revenue or non-revenue cargo, the Operator shall have procedures to ensure any package, overpack, freight container, or ULD containing dangerous goods is inspected and is not accepted, unless:

- (i) Properly marked and labeled;
- (ii) There is no leakage;
- (iii) Its integrity has not been compromised. **(GM)**

Auditor Actions

- ☐ **Identified/Assessed** procedures for inspection dangerous goods shipments prior to acceptance for transport.
- ☐ **Interviewed** responsible manager(s) in cargo operations.
- ☐ **Observed** cargo acceptance operations (focus: procedures for inspection of dangerous goods shipments prior to acceptance).
- ☐ **Other Actions** (Specify)

Guidance

Detailed instructions for acceptance and handling of dangerous goods are contained in [DGR Section 9](#). This information is not to be interpreted as requiring an operator to accept or transport a particular article or substance, or as preventing an operator from imposing special requirements on the transport of a particular article or substance.

CGO 3.2.5

If the Operator transports dangerous goods as revenue or non-revenue cargo on or in ULDs, the Operator shall have procedures to ensure ULDs containing dangerous goods, which require a hazard label, have a dangerous goods tag that:

- (i) Contains information that is visible and legible and, if placed in a protective tag holder, such information remains visible and legible;
- (ii) Is marked with the class or division number(s) of such dangerous goods;
- (iii) If a ULD contains packages bearing a “Cargo Aircraft Only” label, indicates the ULD can only be loaded onto a cargo aircraft. **(GM)**

Auditor Actions

- ☐ **Identified/Assessed** procedures for ensuring ULD containing dangerous goods have a tag in accordance with applicable requirements.
- ☐ **Interviewed** responsible manager(s) in cargo operations.
- ☐ **Observed** cargo acceptance and cargo handling operations (focus: procedures for ensuring ULDs containing dangerous goods are tagged in accordance with applicable requirements).
- ☐ **Other Actions** (Specify)

Guidance

The need for procedures would normally apply to any operator that accepts dangerous goods for transport on or in ULDs to ensure:

- The types of dangerous goods contained in ULDs, as well as any associated restrictions, are accurately displayed on a ULD tag, which may be placed inside a protective tag holder on the exterior of the ULD;
- ULDs are only loaded onto aircraft that are compatible with the load and associated restrictions.

Refer to [DGR 9.3.8](#) for guidance that addresses ULD dangerous goods tags.

CGO 3.2.10

If the Operator transports dangerous goods as revenue or non-revenue cargo, the Operator shall have procedures that ensure dangerous goods are separated from other cargo or incompatible materials in accordance with published category restrictions. **(GM)**

⊗

Auditor Actions

- ☐ **Identified/Assessed** dangerous goods handling procedures (focus: dangerous goods are separated from other cargo or incompatible materials in accordance with published category restrictions).
- ☐ **Interviewed** responsible manager(s) in cargo operations.

- ❑ **Observed** cargo handling operations (focus: procedures that ensure dangerous goods separation from other cargo in accordance with published restrictions).
- ❑ **Other Actions** (Specify)

Guidance

Loading requirements contained in [DGR 9.3.2](#) and [Table 9.3.A](#), primarily address dangerous goods compatibility restrictions on an aircraft. Similar separation requirements are applicable for stowage of these materials in a cargo facility.

Specifications for the segregation of dangerous goods during transportation and aircraft loading/unloading are found in GRH 3.4.3.

CGO 3.2.12

If the Operator transports dangerous goods as revenue or non-revenue cargo, the Operator shall have procedures to ensure any dangerous goods shipment that appears to be damaged or leaking:

- (i) Is not to be loaded on or into a ULD or delivered to an aircraft;
- (ii) Is safely removed from the ULD (or other transport device) by the Provider or other relevant authority, and safe disposal arranged;
- (iii) In the case of leakage, an evaluation is conducted to ensure the remainder of the shipment is in proper condition for transport by air and that no other package, cargo, ULD, other transport device has been contaminated or damaged.

Auditor Actions

- ❑ **Identified/Assessed** procedures for handling/addressing ULDs and leaking/damaged dangerous goods shipments.
- ❑ **Interviewed** responsible manager(s) in cargo operations.
- ❑ **Examined** selected records/documents (focus: handling of leaking/damaged ULDs containing dangerous goods).
- ❑ **Observed** cargo handling operations (focus: procedures that address damaged/leaking ULDs that contain dangerous goods).
- ❑ **Other Actions** (Specify)

3.3 Live Animals and Perishables

CGO 3.3.1

If the Operator transports live animal and/or perishable cargo shipments, the Operator shall have procedures that ensure live animal and/or perishable cargo shipments are accepted and handled in accordance with requirements specified in the OM. **(GM)**

Auditor Actions

- ❑ **Identified/Assessed** procedure(s) for acceptance/handling of live animal and/or perishable cargo shipments.
- ❑ **Interviewed** responsible manager(s) in cargo operations.
- ❑ **Observed** cargo acceptance and cargo handling operations (focus: live animal/perishable cargo acceptance/handling in accordance with OM).
- ❑ **Other Actions** (Specify)

Guidance

Refer to the IRM for the definition of [CITES \(The Convention on International Trade in Endangered Species of Wild Fauna and Flora\)](#).

Live animal handling procedures and specific responsibilities of an operator with regard to required documentation, acceptance, containers, animal welfare, compliance with all regulations, storage and loading and liability are addressed in the LAR and PCR. Additional requirements may be mandated by the State of Flight Departure, the State of Flight Arrival and/or the Convention on International Trade in Endangered Species of Wild Fauna and Flora (CITES).

3.4 Other Special Cargo

CGO 3.4.1

If the Operator transports special cargo shipments such as human remains, valuable cargo, fragile goods, outsized cargo and heavy cargo, the Operator shall have procedures that ensure such special cargo shipments are accepted and handled in accordance with standards specified in the OM. **(GM)**

Auditor Actions

- ☐ **Identified/Assessed** procedure(s) for acceptance/handling of special cargo shipments.
- ☐ **Interviewed** responsible manager(s) in cargo operations.
- ☐ **Observed** cargo acceptance and cargo handling operations (focus: procedures that ensure other special cargo acceptance/handling in accordance with OM).
- ☐ **Interviewed** cargo operations personnel that accept/handle special cargo.
- ☐ **Other Actions** (Specify)

Guidance

Refer to the IRM for the definition of the [Air Cargo Tariff and Rules \(TACT\)](#).

Guidance for the handling of human remains can be found in the TACT Rules and the Airport Handling Manual (AHM).

Outsized and heavy cargo refers to items that are larger or heavier than can be accommodated on or in a ULD. Standards for handling these items are found in the OM as well as in the Weight and Balance Manual for each aircraft type.

Prior arrangements and specific handling requirements generally apply to all types of special cargo and are incorporated into the OM, including those items identified in this provision, but also emergency medical supplies, live human organs and diplomatic shipments.

3.5 Unit Load Device (ULD)

3.6 Combi Aircraft Operations

CGO 3.6.1

If the Operator conducts combi aircraft operations, the Operator shall ensure procedures are in place for loading such aircraft, and such procedures shall be in accordance with, as applicable, requirements of the aircraft manufacturer, Supplemental Type Certificate (STC) holder and/or data approved by the Authority. **(GM)**

Auditor Actions

- ☐ **Identified/Assessed** procedure(s) for loading cargo onto combi aircraft in accordance with all requirements.
- ☐ **Interviewed** responsible manager(s) in cargo operations.
- ☐ **Interviewed** cargo operations personnel that load cargo onto combi aircraft.
- ☐ **Other Actions** (Specify)

Guidance

Refer to the IRM for the definitions of [Cargo Restraint System](#), [Combi \(Combined Passenger and Cargo\) Aircraft Operations](#) and [Supplemental Type Certificate \(STC\) Holder](#).

Procedures would typically ensure passengers seated on the same deck and forward of the cargo are protected through provision of an adequate buffer and/or cargo restraint system.

3.7 Security

CGO 3.7.3

If the Operator transports revenue or non-revenue cargo, the Operator shall have processes to ensure cargo is not accepted for transport on an aircraft unless the application of screening or other security controls is confirmed and accounted for by a regulated agent or another entity that is approved by the relevant authority. **(GM)**

Auditor Actions

- ☐ **Identified/Assessed** process(es) for ensuring application of screening/security controls for all cargo.
- ☐ **Interviewed** responsible manager(s).
- ☐ **Examined** selected records from regulated agent database.
- ☐ **Other Actions** (Specify)

Guidance

Refer to the IRM for the definitions of [Known Consignor](#) and [Regulated Agent](#).

The term “entity that is approved by the relevant authority” as used in this provision is non-specific, but could include, for example, a cargo service provider for the operator or, in certain cases, the operator itself. As stated, any such entity must be approved by the relevant authority.

For cargo destined to an EU country, the application of screening or other security controls by a Regulated Agent that holds a current RA3 validation issued by an EU Independent Validator is evidence the agent has approval by the relevant authority.

Additional guidance may be found in the IATA Security Manual.

CGO 3.7.4

If the Operator transports revenue or non-revenue cargo, the Operator shall have processes for the acceptance of cargo as follows:

- (i) For cargo that can be identified as having the application of screening or other security controls confirmed or accounted for by a regulated agent or an entity approved by the relevant authority (known cargo), a process to ensure such cargo is:
 - (a) Delivered by a regulated agent, a nominated representative of an entity approved by the relevant authority, or a known representative of the operator;
 - (b) Free from any signs of tampering;
 - (c) Accompanied by all required information (paper or electronic) corresponding to the cargo being delivered, including documentation that details the security status (e.g. consignment security declaration);
 - (d) Subjected to additional security controls as required by risk assessment.
- (ii) For cargo that *cannot* be identified as having the application of screening or other security controls confirmed or accounted for by a regulated agent or an entity approved by the relevant authority (unknown cargo), a process to ensure such cargo is subjected to screening or other security controls as accepted by the applicable state. **(GM)**

Auditor Actions

- ☐ **Identified/Assessed** process(es) for acceptance of cargo (focus: processes address both known and unknown cargo).
- ☐ **Interviewed** responsible manager(s).
- ☐ **Examined** selected cargo shipment acceptance documents.
- ☐ **Observed** cargo acceptance operations (focus: acceptance processes for verifying the security status of known cargo, ensuring application of screening/security control for unknown cargo).
- ☐ **Other Actions** (Specify)

Guidance

Refer to the IRM for the definitions of [Known Cargo](#) and [Unknown Cargo](#).

The IATA Security Manual outlines specific provisions covering the basic acceptance of all known cargo to be carried on commercial passenger flights.

Known cargo, when presented to an operator for transport on an aircraft, has by definition been subjected to screening or appropriate security controls by a regulated agent, an approved entity or the operator. An operator, as a minimum, implements the steps specified in this provision to maintain or protect the “known” status of the shipment from the time the shipment is accepted until it is finally loaded into an aircraft.

All cargo shipments on which the application of screening or security controls has been confirmed and accounted for by a regulated agent or approved entity are required to be accompanied by documentation that states the security status (e.g. consignment security declaration), either in electronic or paper form.

When cargo has been screened or subjected to other security controls as required by a regulated agent or an approved entity prior to acceptance by the operator, the operator, among other protective actions, would typically examine the documentation (e.g. consignment security declaration) and check the shipment for evidence of tampering prior to loading onto the aircraft.

If for some reason a shipment is not properly maintained or protected in its known status, the shipment then reverts to unknown cargo. In such case, the operator, in order to return the shipment to known cargo status, would have to ensure the shipment is again subjected to the application of screening or other security controls.

Table 7.1—Operations Manual Content Specifications

The content of the Operations Manual shall contain standards and guidance that address the acceptance and handling of revenue cargo, to include, as applicable to type(s) of shipments transported by the Operator:

- (i) Compliance or conformity with:
 - (a) Applicable laws, regulations and rules, including civil aviation cargo security programs;
 - (b) Industry standard operating procedures for each aspect of cargo acceptance and handling.
- (ii) Response to abnormal or emergency situations:
 - (a) Leakage or spillage of suspected dangerous goods;
 - (b) Suspected bomb or explosives;
 - (c) Damaged or leaking cargo;
 - (d) Other emergencies.
- (iii) Cargo acceptance and handling, including conditions of carriage:
 - (a) General cargo;
 - (b) Security requirements, to include “high risk” cargo;
 - (c) Dangerous goods;
 - (d) Live animals;
 - (e) Other special cargo:
 - Perishable cargo;
 - Human remains;
 - Outsized and heavy cargo;
 - Fragile goods.
 - (f) Mail;
 - (g) Valuable cargo;
- (iv) Requirements associated with the transport of ULDs.

Section 8 — Security Management (SEC)

Applicability

[Section 8](#) addresses the management of operational security in accordance with requirements of an Air Operator Security Program (AOSP). This section is applicable to all operators.

Individual SEC provisions or sub-specifications within a SEC provision that:

- Do not begin with a conditional phrase are applicable to all operators unless determined otherwise by the Auditor.
- Begin with a conditional phrase (“If the Operator...”) are applicable if the operator meets the condition(s) stated in the phrase.

Where operational security functions are outsourced to contracted external service providers, an operator retains responsibility for the conduct of such functions and will have processes to monitor applicable external service providers in accordance with [SEC 1.11.2](#) to ensure requirements that affect the security of operations are being fulfilled.

General Guidance

Definitions of technical terms used in this ISM [Section 8](#), as well as the meaning of abbreviations and acronyms, are found in the IATA Reference Manual for Audit Programs (IRM).

1 Management and Control

1.1 Management System Overview

1.2 Air Operator Security Program (AOSP)

SEC 1.2.1

The Operator shall have a formal Air Operator Security Program (AOSP) that includes:

- (i) The requirements of the civil aviation security program of the State of the Operator (hereinafter, the State);
- (ii) Applicable requirements of other states where operations are conducted;
- (iii) The security standards of the Operator. **(GM)**

Auditor Actions

- ☐ **Identified/Assessed** the AOSP.
- ☐ **Examined** operator-specific security requirements and standards.
- ☐ **Interviewed** responsible manager(s).
- ☐ **Other Actions** (Specify)

Guidance

Refer to the IRM for the definitions of [Acts of Unlawful Interference](#), [State](#), [State Acceptance](#) and [State Approval](#).

An operator is required to have a AOSP in order to:

- Protect customers, personnel and assets from any act of unlawful interference;
- Comply with regulatory requirements.

The name of an operator's security program may vary based on the regulatory jurisdiction. Examples of typical alternative names to AOSP include ACSP (Air Carrier Security Program) and ASP (Airline Security Program).

The Security Program may be structured in accordance with the template provided by the State or other relevant states (where operations are conducted).

The State may issue a standard security program with which all operators must comply (operators may apply for exemptions or amendments, as applicable). In such cases, the standard security program of the State is typically recognized as the AOSP of the operator. The AOSP typically also includes other company manuals and procedures that provide carrier-specific details.

A standard security program may be acceptable in meeting security requirements of other states, or the operator may be required to submit individual security programs tailored to meet requirements of other states. An operator must satisfy the security requirements of all applicable states for the purpose of meeting the intent of this standard.

The AOSP may be approved or accepted (i.e. no notice of deficiency or equivalent is issued) by the relevant state.

1.3 Authorities and Responsibilities

SEC 1.3.1

The Operator shall ensure the security management system defines the authorities and responsibilities of management personnel, as well as a general description of security responsibilities for categories of non-management personnel as defined under the AOSP. The security management system shall specify:

- (i) The levels of management with the authority to make decisions that affect the operational security;
- (ii) Responsibilities for ensuring security functions are performed and procedures are implemented in accordance with applicable regulations and standards of the Operator;
- (iii) Lines of accountability throughout the organization, including direct accountability for security on the part of senior management;
- (iv) Responsibilities of members of management, irrespective of other functions, as well as of non-management personnel, with respect to the security performance of the organization.

(GM)

Auditor Actions

- ☐ **Identified/Assessed** defined management/non-management authorities and responsibilities throughout the security management system.
- ☐ **Interviewed** designated management representative(s).
- ☐ **Examined** job descriptions of selected management/non-management personnel in security management.
- ☐ **Other Actions** (Specify)

Guidance

Refer to Guidance associated with [ORG 1.3.1](#) located in ISM Section 1.

1.4 Communication

1.5 Provision of Resources

1.6 Documentation System

SEC 1.6.4

If the Operator has external service providers conduct outsourced operational security functions, the Operator shall have a process to ensure such external service providers receive information regarding security directives and instructions in a timely manner that meets requirements of the AOSP. **(GM)**

Auditor Actions

- ☐ **Identified/Assessed** process(es) to circulate relevant security information to external service providers.

- ☐ **Interviewed** responsible manager(s).
- ☐ **Examined** selected examples of information provided to external service providers.
- ☐ **Other Actions** (Specify)

Guidance

Refer to the IRM for the definition of [Outsourcing](#).

1.7 (Intentionally open)

1.8 Records System

1.9 Management Review

1.10 Quality Assurance/Quality Control Programs

Quality Assurance

Quality Control

1.11 Quality Control of Outsourced Operations and Products

1.12 Operational Reporting

SEC 1.12.1

The Operator shall have an operational reporting system that is implemented throughout the organization in a manner that:

- (i) Encourages and facilitates personnel to report security incidents and threats, identify security deficiencies, and raise security concerns pertaining to the Operator;
- (ii) Includes analysis and management action as necessary to address security issues identified through the reporting system. **(GM)**

Auditor Actions

- ☐ **Identified/Assessed** system for operational personnel to report security incidents, threats, deficiencies and concerns (focus: system urges/facilitates reporting of hazards/safety concerns; includes analysis/action to validate/address reported hazards/safety concerns).
- ☐ **Interviewed** responsible manager(s).
- ☐ **Examined** selected reports submitted by operational personnel.
- ☐ **Other Actions** (Specify)

Guidance

Refer to the IRM for the definition of [Security Threat](#).

Frontline personnel, such as flight or cabin crew members, maintenance technicians and ground handling personnel, are in the best position to note abnormalities that could indicate real or potential security threats, or any other security concerns, so they may be brought to the attention of the head of security and other relevant managers.

The effectiveness of a reporting system is determined by a basic requirement for safeguarding information. Typically, individuals will continue to provide information only when there is confidence that such information will be used only for the purpose of improving operational security and will never be compromised or used against them.

A system that encourages and promotes reporting from personnel might include:

- A process that protects the confidentiality of the report;
- A process that provides for review by corporate security personnel;

- An articulated policy that encourages reporting of security incidents or events, even if resulting from human error;
- A shared responsibility between personnel (or, if applicable, respective professional associations) and management to promote the confidentiality of the reporting system;
- A process for secure de-identification of reports;
- A tracking process of action taken in response to reports;
- A process to provide feedback to the reporter, when appropriate;
- A communication process for ensuring frontline operational personnel, as well as other relevant personnel, are apprised of potential security issues through dissemination of de-identified report information.

An operational reporting system is implemented as permitted by law or as restricted by other specified obligations placed on an operator.

- ☐ A security reporting system, regardless if developed separately or in conjunction with other operational reporting system(s), is normally designed in a way that enables analysis and the undertaking of necessary actions.
 - ☐ Typically, an operator's reporting system includes its own staff and, as applicable, that of service providers as reporting is a service provider's obligation under the IATA Standard Ground Handling Agreement provisions.
 - ☐ Qualitative and quantitative analysis of security data would be facilitated if the operator uses a harmonized taxonomy for the classification of reports. Expanding this harmonized taxonomy to service providers would benefit security threat, vulnerability and event analysis by allowing for more consistency, benchmarking and security performance measurement
 - ☐ In late 2019 IATA is expected to bring online a new database system called the Incident Data Exchange (IDX). IDX will permit operators to report security threats, vulnerabilities and incidents for uploading into the IDX safety management database for analysis by users. Once IDX becomes operational, an operator can facilitate the submission of security threat, vulnerability and incident reports into the IDX system by ensuring its reporting system has a taxonomy that is aligned with the IDX security taxonomy. See SEC 4.3.3, which addresses the reporting of acts of unlawful interference and/or preparatory acts against the Operator to IATA for inclusion in the IDX
- Refer to [ORG 3.1.3](#) and [ORG 3.1.4](#) located in ISM Section 1, which address operational safety reporting systems.

2 Training and Qualification

2.1 Training Program

SEC 2.1.1

The Operator shall have a security training program that is approved or accepted by the State and meets applicable requirements of other states. Such program shall consist of initial and recurrent training, and include, as appropriate, theoretical and practical training to ensure:

- (i) Personnel, employed by or under the control of the Operator who implement security controls, have the competence to perform their duties;
- (ii) Flight and cabin crew members, as well as frontline aircraft ground handling and cargo handling personnel, are able to act in the most appropriate manner to minimize the consequences of acts of unlawful interference and disruptive passenger behavior. **(GM)**

Note: Applicable personnel shall complete initial security training prior to being assigned to operational duties.

Auditor Actions

- ☐ **Identified/Assessed** security training program (focus: approval/acceptance by State; meets applicable requirements of other states).
- ☐ **Interviewed** responsible manager(s).

- ☐ **Examined** selected security training program curricula (focus: contain theoretical and practical training elements).
- ☐ **Examined** selected ground/cargo handling personnel training records (focus: completion of initial/recurrent security training).
- ☐ **Other Actions** (Specify)

Guidance

Training may be sub-divided for line managers/supervisors, aircrew, ramp workers, cargo personnel and other personnel who are directly involved in the implementation of security measures and thereby require an awareness of obligations to the AOSP.

The security training program is typically integrated into the normal training curriculum for operational personnel and need not be stand-alone training.

The proportion of theoretical and practical training is typically based on requirements of the State. For certain functions or duties there may not be a practical component.

The scope of recurrent security training, as well as the specific subject matter included, may vary in accordance with requirements of the applicable authorities and the security policy of the operator.

3 Security Operations

3.1 Access Control

SEC 3.1.2

The Operator shall ensure measures are in place to control and supervise personnel and vehicles moving to and from the aircraft in security restricted areas to prevent unauthorized access to the aircraft. **(GM)**

Auditor Actions

- ☐ **Identified/Assessed** measure(s) to control and supervise the movement of personnel and vehicle to and from the aircraft in the security restricted area(s)
- ☐ **Interviewed** responsible manager(s).
- ☐ **Other Actions** (Specify)

Guidance

Procedures are in place to ensure airline personnel intercept any person identified as having no need to be on board or near the aircraft.

In some environments, it would be prudent not to leave an in-service aircraft unattended. Precautions may be taken to prevent unauthorized access to aircraft that are not in service and are parked and unattended. For example, all external doors may be locked, all stairs and loading bridges are removed (or locked) and any steps left near the aircraft are immobilized.

Passengers boarding or disembarking from flights using the apron are to be supervised when passing from the terminal building to the aircraft. Such measures are applied whether the passengers are walking or are being transported in vehicles.

Particular care is taken to ensure only crew members, authorized representatives and officials, and bona fide passengers are permitted access to the aircraft.

SEC 3.1.3

The Operator shall ensure access control measures are in place to prevent the introduction of unauthorized weapons, explosives or other dangerous devices or items on board an aircraft by persons other than passengers. **(GM)**

Auditor Actions

- ☐ **Identified/Assessed** process(es) to prevent the introduction of unauthorized weapons, explosives or other dangerous devices on board an aircraft.

- ☐ **Examined** records of the capture and prevention of unauthorized weapons, explosives or other dangerous devices on board an aircraft.
- ☐ **Interviewed** responsible manager(s).
- ☐ **Other Actions** (Specify)

Guidance

An effective method to deter or detect illegal access to aircraft is the implementation of frequent but irregularly timed patrols by security personnel. This is particularly important when operations are at their lowest levels and aprons and hangar areas are least frequented. Such patrols are normally conducted by airport personnel.

Additional measures to prevent unauthorized access to passenger aircraft may include:

- Parking aircraft in a well-lit area; adding security lighting, if necessary;
- When possible, parking aircraft in an observable area;
- Parking aircraft away from fences or buildings that might provide easier access;
- For aircraft parked overnight, depending on the assessed risk at the location, applying a tamper-evident seal to all exterior doors or verifying the identity of all persons who access the aircraft to ensure a legitimate reason for accessing the aircraft;
- For aircraft parked remotely from a loading bridge:
 - Closing all exterior doors and exterior hatches of the aircraft;
 - Removing all stairs;
 - Ensuring no portable stairs, lift devices or passenger transfer vehicles are in the immediate vicinity of the aircraft.
- For aircraft parked with access to a loading bridge:
 - Closing all exterior hatches of the aircraft;
 - Closing all exterior doors of the aircraft not served by a bridge;
 - Locking the door between the terminal and the bridge;
 - Ensuring no portable stairs, lift devices or passenger transfer vehicles are in the immediate vicinity of the aircraft;
 - Locking or keeping under constant surveillance doors that provide access to the bridge from the apron or retracting the bridgehead from the aircraft and deactivating the bridgehead positioning controls.

3.2 (Intentionally open)

3.3 Carriage of Weapons

3.4 Passengers, Supernumeraries and Cabin Baggage

SEC 3.4.1

If the Operator conducts passenger flights, the Operator shall have a process to ensure originating passengers and their cabin baggage are subjected to screening prior to boarding a passenger aircraft for;

- (i) An international flight;
- (ii) As required by the applicable aviation security authority, a domestic flight. **(GM)**

Auditor Actions

- ☐ **Identified/Assessed** process(es) to ensure all passengers and their cabin baggage are screened prior to boarding a passenger aircraft for international flights.
- ☐ **Identified/Assessed** process(es) for the screening of originating passengers and their cabin baggage for domestic flights (if required by the applicable aviation security authority).
- ☐ **Interviewed** responsible manager(s).

- ❑ **Observed** passenger/baggage handling operations (focus: originating passengers/cabin baggage are subjected to screening prior to aircraft boarding).
- ❑ **Other Actions** (Specify)

Guidance

Refer to the IRM for the definition of [Domestic Flight](#).

The effective screening of all passengers and their cabin baggage is recognized as an essential element in achieving a safe and secure operation, and forms part of the passenger handling procedures contained in the AOSP.

Technical equipment used for the screening of persons and baggage has certain limitations. Archway metal detectors and hand-held metal detectors, for example, cannot detect non-metallic weapons and explosives. Even conventional X-ray equipment does not always image or define explosive material effectively. To compensate for such limitations, or to introduce a random element into the selection process, it may be advisable to conduct an additional search of passengers and cabin baggage after they have been screened. The additional screening can be performed by hand or by technical means, such as explosive trace detection (ETD), full-body X-ray, explosive particle or vapor detection portals and/or other approved advanced technological methods.

It is recommended that screening equipment used to assist screening personnel is capable of detecting explosive materials and/or explosive devices that might be carried by passengers either on their person or in cabin baggage.

- ❑ If the use of explosive detection screening equipment is not continuous, then it is recommended that such equipment be used on a random basis to ensure non-predictability by passengers and others.

- △ Specific guidelines and procedures are developed and training is given to personnel for addressing persons with special needs.

SEC 3.4.3

If the Operator conducts passenger flights, the Operator shall have a process to ensure transfer and transit passengers and their cabin baggage *either*:

- (i) Are subjected to screening prior to boarding a passenger aircraft, *or*
- (ii) Have been screened to an appropriate level at the point of origin and subsequently protected from unauthorized interference from the point of screening at the originating airport to the departing aircraft at the transfer or transit airport. **(GM)**

Auditor Actions

- ❑ **Identified** process(es), when required, to ensure all passengers and their cabin baggage are screened prior to boarding a passenger aircraft.
- ❑ **Identified/Assessed** criteria used to determine whether passengers and cabin baggage are re-screened at the transit/transfer airport or if one-stop-security is applied.
- ❑ **Observed** screening measures being implemented for transfer and transit passenger and their cabin baggage, as applicable.
- ❑ **Interviewed** responsible manager(s).
- ❑ **Other Actions** (Specify)

Guidance

Refer to the IRM for the definition of [Unauthorized Interference](#).

Transit and transfer passengers and their cabin baggage may not require screening prior to admission to an airport sterile area if, in the judgment of the appropriate authority for security, the standard of screening en route and at the airport of embarkation is equal or comparable to that of the admitting state. However, measures ought to be established to ensure transit or transfer passengers do not take unauthorized articles on board an aircraft.

3.5 Special Category Passengers

SEC 3.5.1

If the Operator conducts passenger flights, the Operator shall have a policy and a process that incorporates risk assessment measures to ensure procedures are in place for the transport of potentially disruptive passengers who are obliged to travel because they have been the subject of judicial or administrative proceedings. Such procedures shall be designed to take into consideration the assurance of the safety of the aircraft during the flight. **(GM)**

Auditor Actions

- ☐ **Identified/Assessed** policy and process(es) in place for the transport of potentially disruptive passengers.
- ☐ **Identified/Assessed** process(es) used to assess the risk posed by any potentially disruptive passenger.
- ☐ **Interviewed** responsible manager(s).
- ☐ **Other Actions** (Specify)

Guidance

Refer to the IRM for the definitions of [Deportee](#) and [Inadmissible Passenger](#).

Airlines that have transported people who have been refused entry to a state can be called upon to return such person(s) to the port of embarkation. Such removal is accompanied by a judicial order of removal.

Those responsible within the organization of an operator for compliance with judicial orders (e.g., station managers) inform the PIC and cabin crew at the point of embarkation. Transit and destination airports also need to be advised that such a person is being carried. The original operator advises all other operators involved in the transport of the inadmissible passenger to their final destination.

The following information is provided to the originating operator, as well as subsequent operators:

- Name and sex of the person identified as the deportee; reason for deportation (nature of crime);
- Willingness or unwillingness to travel by air;
- Whether the person has attempted to escape custody;
- Whether the person has any history of violence;
- Whether the person has a history of self-harm;
- Whether members of the person's family are booked on the same flight;
- Whether the person is likely to be the target of harm during the transportation;
- Identity of escorts (if required);
- The mental and/or physical state of the person;
- Wanted status of the person (by any other authority);
- Other information that would allow an operator to assess the risk of endangering the security of the flight;
- Special conditions and precautions for transport of the person, if any.

To ensure the safety of the aircraft during a flight, an operator typically has a process to assess the information (see above) associated with the transport of passengers that require special attention. For example, a decision might be needed as to whether a passenger will be denied boarding, or whether a passenger might require an escort.

Accordingly, there is usually a well-defined escort policy that is provided to the appropriate immigration authorities. Females travelling under the provisions of a judicial order may require a female escorting officer as a member of the escort team.

Special provisions may exist for flights where transportation of multiple inadmissible passengers is required.

Although a person is involved in travel in response to a judicial or custodial order, while in flight, such passenger is always under the control of the PIC and crew of the aircraft.

3.6 Hold Baggage

SEC 3.6.1

If the Operator conducts international passenger flights, the Operator shall have a process to ensure originating hold baggage, including courier baggage, is subjected to screening prior to being loaded into an aircraft for an international passenger flight. **(GM)**

Auditor Actions

- ☐ **Identified/Assessed** process(es) for ensuring all originating checked baggage is subjected to screening prior to being loaded onto an aircraft.
- ☐ **Interviewed** responsible manager(s).
- ☐ **Observed** passenger/baggage handling operations (focus: originating hold baggage is subjected to screening prior to being loaded onto an aircraft for an international flight).
- ☐ **Other Actions** (Specify)

Guidance

All checked baggage loaded on international flights is examined by authorized screeners using approved screening methods. Each state will have varying regulations and requirements, but typically approved screening methods include:

- Explosive detection systems (EDS);
- Explosive trace detection (ETD);
- X-ray;
- Physical search;
- Canine.

Where the State delegates screening to the operator, or where the foreign host government does not perform screening to the standard required, the operator is responsible for ensuring all checked baggage is screened to the appropriate level and meets the requirements of the Operator.

In the event of an increased threat, the operator, based on risk assessment, may direct supplementary screening procedures as appropriate to counter the threat.

Courier service is an operation whereby shipments tendered by one or more shippers are transported as the baggage of a courier passenger on board a scheduled airline flight under normal passenger hold baggage documentation.

This provision also refers to a person who is employed by a courier service operator and travels as a passenger or crew member, and who checks a courier shipment in as hold baggage. Such baggage is then screened under the same requirements that apply to all hold baggage.

SEC 3.6.10

If the Operator conducts International passenger flights, the Operator shall have a process to ensure transfer hold baggage for such flights *either*:

- (i) Is subjected to screening prior being loaded onto the aircraft, *or*
- (ii) Has been screened at the point of origin and subsequently protected from unauthorized interference from the point of screening at the originating airport to the departing flight at the transfer airport.

Auditor Actions

- ☐ **Identified/Assessed** the process(es) to ensure transfer hold baggage for international flights is subjected to screening prior to being loaded, where applicable.
- ☐ **Identified** the process(es) to determine that hold baggage does not need to be rescreened at a point of transfer, where applicable.
- ☐ **Interviewed** responsible manager(s).

- ☐ **Observed** passenger/baggage handling operations (focus: processes for ensuring international transfer hold baggage has been screened and protected from unauthorized interference prior to being loaded onto an aircraft).
- ☐ **Other Actions** (Specify)

3.7 Cargo Shipments

SEC 3.7.1

If the Operator transports revenue or non-revenue cargo, the Operator shall have a process to ensure cargo shipments for transport on all flights have been subjected to the appropriate security controls, including screening where required, as established by the applicable state(s) prior to being loaded onto an aircraft.

Auditor Actions

- ☐ **Identified/Assessed** process(es) to ensure cargo has been subjected to the appropriate security controls.
- ☐ **Identified/Assessed** process(es) to ensure security controls performed on cargo meet the requirement of the applicable state(s).
- ☐ **Examined** selected records that reflect implementation of cargo security controls.
- ☐ **Interviewed** responsible manager(s).
- ☐ **Other Actions** (Specify)

3.8 In-Flight, Catering and Other Supplies

3.9 General Protection

4 Security Threat and Contingency Management

4.1 Threat Management

SEC 4.1.1

The Operator shall have processes for maintaining a constant review of the level and nature of security threats to civil aviation, and for identifying direct or potential threats against the Operator. For threats that have been identified, such processes shall include:

- (i) an assessment of associated risks and vulnerabilities;
- (ii) Development of appropriate response measures. **(GM)**

Auditor Actions

- ☐ **Identified/Assessed** process(es) for monitoring level and nature of security threats to civil aviation (focus: identification of threats to operator, assessment of associated risks, development of response measures).
- ☐ **Interviewed** responsible manager(s).
- ☐ **Examined** methods used to monitor security threats to civil aviation.
- ☐ **Examined** selected records of threats identified, risk assessments and appropriate response measures.
- ☐ **Other Actions** (Specify)

Guidance

To ensure threat assessment remains up to date and relevant to the changing environment, an operator will have mechanisms in place that allow it to collect real-time (or close to real-time) security threat information from both open and, if possible, restricted sources. Included would be relevant information shared or provided by applicable states for the purpose of assisting the operator in

(1) identifying direct or potential threats to its operations and (2) conducting effective security risk assessments.

Processes would include, based on threat information received, periodic security risk assessment(s), with the focus on airports it operates to, usual flight routes and any locations where it may have assets.

Furthermore, significant security or geo-political events would also be monitored to indicate the possible need for unscheduled security risk assessments and, if applicable, development of appropriate response measures.

Procedures might also include instructions for communicating security threats to persons responsible for making decisions and taking action, as well as providing advice to the flight crew. Means of communication and details of telephone numbers, emergency radio channels and contact persons would be readily available to ensure a response to threats without delay.

4.2 Contingency Planning

4.3 Investigation and Notification

INTENTIONALLY LEFT BLANK

International Air Transport Association
ISBN 978-92-9264-172-6
Customer service: www.iata.org/cs
+1 800 716 6326

iata.org/publishing

